

AIR CONDITIONER

**Multi: 5 rooms type**

# DESIGN & TECHNICAL MANUAL

---



AUU7RLF  
AUU9RLF  
AUU12RLF  
AUU18RLF



ARU7RLF  
ARU9RLF  
ARU12RLF



ARU18RLF



ARU24RLF

INDOOR

---



ASU7RLF1  
ASU9RLF1  
ASU12RLF1  
ASU15RLF1



ASU18RLF  
ASU24RLF



AGU9RLF  
AGU12RLF  
AGU15RLF

OUTDOOR

---



AOU45RLXFZ

---

FUJITSU GENERAL LIMITED

DR\_MU002EF\_09  
2018.06.14

**Notices:**

- Product specifications and design are subject to change without notice for future improvement.
- For further details, please check with our authorized dealer.

# CONTENTS

---

<b>Part 1. INDOOR UNIT .....</b>	<b>1</b>
<b>1. Model lineup .....</b>	<b>2</b>
1-1. Indoor unit connection patterns .....	3
<b>2. Specifications .....</b>	<b>6</b>
2-1. Compact cassette type .....	6
2-2. Slim duct type .....	7
2-3. Wall mounted type .....	9
2-4. Floor type .....	11
<b>3. Dimensions .....</b>	<b>12</b>
3-1. Compact cassette type .....	12
3-2. Slim duct type .....	15
3-3. Wall mounted type .....	20
3-4. Floor type .....	24
<b>4. Wiring diagrams .....</b>	<b>25</b>
4-1. Compact cassette type .....	25
4-2. Slim duct type .....	26
4-3. Wall mounted type .....	27
4-4. Floor type .....	29
<b>5. Air velocity and temperature distributions .....</b>	<b>30</b>
5-1. Compact cassette type .....	30
5-2. Slim duct type .....	36
5-3. Wall mounted type .....	46
5-4. Floor type .....	52
<b>6. Fan performance .....</b>	<b>53</b>
6-1. Slim duct type .....	53
<b>7. Airflow .....</b>	<b>63</b>
7-1. Compact cassette type .....	63
7-2. Slim duct type .....	64
7-3. Wall mounted type .....	65
7-4. Floor type .....	66
<b>8. Noise level curve .....</b>	<b>67</b>
8-1. Compact cassette type .....	67
8-2. Slim duct type .....	69
8-3. Wall mounted type .....	72
8-4. Floor type .....	75
8-5. Sound level check point .....	77
<b>9. Electrical characteristics .....</b>	<b>79</b>
<b>10. Safety devices .....</b>	<b>80</b>
<b>11. External input and output .....</b>	<b>81</b>
11-1.External input .....	81

# **CONTENTS (continued)**

11-2.External output.....	84
<b>12. Group connection .....</b>	<b>91</b>
12-1.Precautions on creating a group connection .....	92
12-2.Remote controller address setting procedure for wireless remote controllers .....	94
<b>13. Remote controller .....</b>	<b>95</b>
13-1.Wireless remote controller (UTY-LNHUM).....	95
13-2.Wireless remote controller (AR-REG1U).....	97
13-3.Wired remote controller (UTY-RNNUM).....	99
13-4.Simple remote controller (UTY-RSNUM: Optional part).....	104
13-5.Central remote controller (UTY-DMMUM: Optional part) .....	109
<b>14. Function settings .....</b>	<b>113</b>
14-1.Indoor unit (setting by jumper wire).....	113
14-2.Indoor unit (setting by wireless remote controller).....	114
14-3.Indoor unit (setting by wired remote controller) .....	127
14-4.Indoor unit (setting by simple remote controller) .....	130
14-5.Function details .....	134
14-6.Wired remote controller.....	139
14-7.Simple remote controller .....	141
14-8.Central remote controller.....	142
<b>15. Accessories .....</b>	<b>143</b>
15-1.Compact cassette type .....	143
15-2.Slim duct type .....	143
15-3.Wall mounted type .....	145
15-4.Floor type .....	147
<b>16. Optional parts .....</b>	<b>148</b>
16-1.Controllers .....	148
16-2.Cassette grille .....	150
16-3.Others .....	151
<b>17. Indoor unit installation precautions .....</b>	<b>153</b>
17-1.Places where prohibited for use .....	153
17-2.Points to remember when installing .....	154

# **CONTENTS (continued)**

---

<b>Part 2. OUTDOOR UNIT.....</b>	<b>157</b>
<b>1. Specifications.....</b>	<b>158</b>
<b>2. Dimensions.....</b>	<b>159</b>
2-1. Model: AOU45RLXFZ.....	159
<b>3. Installation space .....</b>	<b>160</b>
3-1. Model: AOU45RLXFZ.....	160
<b>4. Refrigerant circuit .....</b>	<b>163</b>
4-1. Model: AOU45RLXFZ.....	163
<b>5. Wiring diagram .....</b>	<b>164</b>
5-1. Model: AOU45RLXFZ.....	164
<b>6. Capacity table.....</b>	<b>165</b>
6-1. Combinations.....	165
6-2. Cooling capacity.....	171
6-3. Heating capacity .....	193
<b>7. Capacity compensation rate for pipe length and height difference.....</b>	<b>211</b>
7-1. Model: AOU45RLXFZ.....	211
<b>8. Additional charge calculation .....</b>	<b>215</b>
8-1. Model: AOU45RLXFZ.....	215
<b>9. Airflow .....</b>	<b>216</b>
9-1. Model: AOU45RLXFZ.....	216
<b>10. Operation noise (sound pressure).....</b>	<b>217</b>
10-1.Noise level curve.....	217
10-2.Sound level check point.....	217
<b>11. Electrical characteristics .....</b>	<b>218</b>
<b>12. Safety devices .....</b>	<b>219</b>
<b>13. Function settings .....</b>	<b>220</b>
13-1.Setting methods .....	220
13-2.Outdoor unit low noise operation function (option) .....	223
<b>14. Check and test.....</b>	<b>224</b>
14-1.Check run .....	224
14-2.Test run.....	230
14-3.Error code .....	232
14-4.Pump down .....	235
<b>15. Accessories .....</b>	<b>237</b>
<b>16. Optional parts .....</b>	<b>238</b>
<b>17. Outdoor unit installation precautions .....</b>	<b>239</b>
17-1.Places where prohibited for use .....	239
17-2.Points to remember when installing .....	239



# **Part 1. INDOOR UNIT**

---

**COMPACT CASSETTE TYPE:**  
**AUU7/9/12/18RLF**

**SLIM DUCT TYPE:**  
**ARU7/9/12/18/24RLF**

**WALL MOUNTED TYPE:**  
**ASU7/9/12/15RLF1**  
**ASU18/24RLF**

**FLOOR TYPE:**  
**AGU9/12/15RLF**

# 1. Model lineup

Indoor unit		
		
AUU7RLF AUU9RLF AUU12RLF AUU18RLF	ARU7RLF ARU9RLF ARU12RLF	ARU18RLF
		
ARU24RLF	ASU7RLF1 ASU9RLF1 ASU12RLF1 ASU15RLF1	ASU18RLF ASU24RLF
		
AGU9RLF AGU12RLF AGU15RLF		
Outdoor unit		
		
AOU45RLXFZ		

# 1-1. Indoor unit connection patterns

## ● 5 rooms

Outdoor unit: AOU45RLXFZ						
No.	room 1	room 2	room 3	room 4	room 5	total
1	12	24	—	—	—	36
2	15	24	—	—	—	39
3	18	18	—	—	—	36
4	18	24	—	—	—	42
5	24	24	—	—	—	48
6	7	7	24	—	—	38
7	7	9	18	—	—	34
8	7	9	24	—	—	40
9	7	12	18	—	—	37
10	7	12	24	—	—	43
11	7	15	15	—	—	37
12	7	15	18	—	—	40
13	7	15	24	—	—	46
14	7	18	18	—	—	43
15	7	18	24	—	—	49
16	9	9	18	—	—	36
17	9	9	24	—	—	42
18	9	12	15	—	—	36
19	9	12	18	—	—	39
20	9	12	24	—	—	45
21	9	15	15	—	—	39
22	9	15	18	—	—	42
23	9	15	24	—	—	48
24	9	18	18	—	—	45
25	9	18	24	—	—	51
26	12	12	12	—	—	36
27	12	12	15	—	—	39
28	12	12	18	—	—	42
29	12	12	24	—	—	48
30	12	15	15	—	—	42
31	12	15	18	—	—	45
32	12	15	24	—	—	51
33	12	18	18	—	—	48
34	12	18	24	—	—	54
35	15	15	15	—	—	45
36	15	15	18	—	—	48
37	15	15	24	—	—	54
38	15	18	18	—	—	51
39	18	18	18	—	—	54
40	7	7	7	15	—	36
41	7	7	7	18	—	39
42	7	7	7	24	—	45
43	7	7	9	12	—	35
44	7	7	9	15	—	38
45	7	7	9	18	—	41
46	7	7	9	24	—	47
47	7	7	12	12	—	38
48	7	7	12	15	—	41
49	7	7	12	18	—	44
50	7	7	12	24	—	50

**Outdoor unit: AOU45RLXFZ**

No.	room 1	room 2	room 3	room 4	room 5	total
51	7	7	15	15	—	44
52	7	7	15	18	—	47
53	7	7	15	24	—	53
54	7	7	18	18	—	50
55	7	9	9	9	—	34
56	7	9	9	12	—	37
57	7	9	9	15	—	40
58	7	9	9	18	—	43
59	7	9	9	24	—	49
60	7	9	12	12	—	40
61	7	9	12	15	—	43
62	7	9	12	18	—	46
63	7	9	12	24	—	52
64	7	9	15	15	—	46
65	7	9	15	18	—	49
66	7	9	18	18	—	52
67	7	12	12	12	—	43
68	7	12	12	15	—	46
69	7	12	12	18	—	49
70	7	12	15	15	—	49
71	7	12	15	18	—	52
72	7	15	15	15	—	52
73	9	9	9	9	—	36
74	9	9	9	12	—	39
75	9	9	9	15	—	42
76	9	9	9	18	—	45
77	9	9	9	24	—	51
78	9	9	12	12	—	42
79	9	9	12	15	—	45
80	9	9	12	18	—	48
81	9	9	12	24	—	54
82	9	9	15	15	—	48
83	9	9	15	18	—	51
84	9	9	18	18	—	54
85	9	12	12	12	—	45
86	9	12	12	15	—	48
87	9	12	12	18	—	51
88	9	12	15	15	—	51
89	9	12	15	18	—	54
90	12	12	12	12	—	48
91	12	12	12	15	—	51
92	12	12	12	18	—	54
93	12	12	12	18	—	54
94	12	12	15	15	—	54
95	7	7	7	7	7	35
96	7	7	7	7	9	37
97	7	7	7	7	12	40
98	7	7	7	7	15	43
99	7	7	7	7	18	46
100	7	7	7	7	24	52
101	7	7	7	9	9	39
102	7	7	7	9	12	42
103	7	7	7	9	15	45
104	7	7	7	9	18	48
105	7	7	7	9	24	54

**Outdoor unit: AOU45RLXFZ**

No.	room 1	room 2	room 3	room 4	room 5	total
106	7	7	7	12	12	45
107	7	7	7	12	15	48
108	7	7	7	12	18	51
109	7	7	7	15	15	51
110	7	7	7	15	18	54
111	7	7	9	9	9	41
112	7	7	9	9	12	44
113	7	7	9	9	15	47
114	7	7	9	9	18	50
115	7	7	9	12	12	47
116	7	7	9	12	15	50
117	7	7	9	12	18	53
118	7	7	9	15	15	53
119	7	7	12	12	12	50
120	7	7	12	12	15	53
121	7	9	9	9	9	43
122	7	9	9	9	12	46
123	7	9	9	9	15	49
124	7	9	9	9	18	52
125	7	9	9	12	12	49
126	7	9	9	12	15	52
127	7	9	12	12	12	52
128	9	9	9	9	9	45
129	9	9	9	9	12	48
130	9	9	9	9	15	51
131	9	9	9	9	18	54
132	9	9	9	12	12	51
133	9	9	9	12	15	54
134	9	9	12	12	12	54

7: 7,000Btu/h, 9: 9,000Btu/h, 12: 12,000Btu/h, 15: 14,000Btu/h, 18: 18,000Btu/h,  
24: 24,000Btu/h

## 2. Specifications

### 2-1. Compact cassette type

Model name				AUU7RLF	AUU9RLF	AUU12RLF	AUU18RLF			
Power supply				208/230 V ~ 60 Hz						
Available voltage range				187—264 V						
Capacity		Btu/h class		7,000	9,000	12,000	18,000			
Input power		W		18	18	23	39			
Running current		A		0.15	0.15	0.19	0.30			
Fan	Airflow rate	Cooling	HIGH	318 (540)	318 (540)	359 (610)	441 (750)			
			MED	288 (490)	288 (490)	312 (530)	359 (610)			
			LOW	259 (440)	259 (440)	277 (470)	306 (520)			
			QUIET	230 (390)	230 (390)	241 (410)	241 (410)			
		Heating	HIGH	318 (540)	318 (540)	359 (610)	471 (800)			
			MED	288 (490)	288 (490)	312 (530)	418 (710)			
			LOW	259 (440)	259 (440)	277 (470)	353 (600)			
			QUIET	230 (390)	230 (390)	241 (410)	265 (450)			
	Type × Q'ty			Turbo fan × 1						
Motor output				54						
Sound pressure level *	Cooling	HIGH		33	33	37	42			
			MED	31	31	33	37			
			LOW	29	29	31	33			
			QUIET	27	27	28	29			
		Heating	HIGH	34	34	37	44			
			MED	32	32	33	40			
			LOW	29	29	31	37			
			QUIET	27	27	28	30			
				Dimensions (H × W × D)						
Heat exchanger type	in (mm)			8-1/4 × 51-9/16 × 1/2 + 8-1/4 × 49-3/16 × 1/2 (210 × 1,310 × 13.3 + 210 × 1,250 × 13.3)						
	Fin pitch			FPI						
	Rows × Stages			2 × 10						
	Pipe type			Copper tube						
Dimensions (H × W × D)				Fin type						
Dimensions (H × W × D)	Net		in (mm)	Aluminum						
	Gross			9-5/8 × 22-7/16 × 22-7/16 (245 × 570 × 570)						
Weight	Net		lb (kg)	10-7/16 × 28-3/4 × 24-5/8 (265 × 730 × 625)						
	Gross			33 (15)						
Connection pipe	Size	Liquid	in (mm)	40 (18)						
		Gas		Ø1/4 (Ø6.35)						
Method				Ø3/8 (Ø9.52)						
Operation range		Cooling	°F (°C)	Flare						
			%RH	64 to 90 (18 to 32)						
		Heating	°F (°C)	80 or less						
Drain hose	Material			60 to 86 (16 to 30)						
	Size			Hard PVC						
Cassette grille (Standard type: Option)	Model name				Ø 3/4(I.D.), Ø 1-1/16(O.D.) [Ø 20.7 (I.D.), Ø 26.6 (O.D.)]					
	Material				UTG-CCGF					
	Color				PS					
					White					
	Dimensions (H × W × D)				Approximate color of Munsell N 9.25/					
	Net		in (mm)	1-15/16 × 27-9/16 × 27-9/16 (49 × 700 × 700)						
	Gross			4-3/4 × 30-1/8 × 29-3/4 (120 × 765 × 755)						
	Weight	Net	lb (kg)	5.7 (2.6)						
				10 (4.5)						
Cassette grille (Grid type: Option)	Model name				UTG-CCGF					
	Material				PS					
	Color				White					
					Approximate color of Munsell 9PB 9.1/0.2					
	Dimensions (H × W × D)	Net	in (mm)	1-15/16 × 24-7/16 × 24-7/16 (49 × 620 × 620)						
				4-3/4 × 30-1/8 × 29-3/4 (120 × 765 × 755)						
	Weight	Net	lb (kg)	5.1 (2.3)						
				10 (4.5)						
Remote controller type				Wired (Wireless [option])						

**NOTES:**

- The protective function might work when using it outside the operation range.
- \*: Sound pressure level:
  - Measured values in manufacturer's anechoic chamber.
  - Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.

## 2-2. Slim duct type

Model name				ARU7RLF	ARU9RLF	ARU12RLF			
Power supply				208/230 V ~ 60 Hz					
Available voltage range				187—264 V					
Capacity				Btu/h class	7,000	9,000			
Input power				W	33	49			
Running current				A	0.30	0.30			
Fan	Airflow rate	Cooling	HIGH	CFM (m <sup>3</sup> /h)	324 (550)	353 (600)			
			MED		288 (490)	324 (550)			
			LOW		277 (470)	294 (500)			
			QUIET		259 (440)	265 (450)			
		Heating	HIGH		324 (550)	353 (600)			
			MED		288 (490)	324 (550)			
			LOW		277 (470)	294 (500)			
			QUIET		259 (440)	265 (450)			
Type × Q'ty				Sirocco fan × 2					
Motor output				80					
Recommended static pressure				inWG (Pa)	0 to 0.36 (0 to 90)				
Sound pressure level *	Cooling	HIGH	HIGH	dB (A)	28	28			
			MED		26	27			
			LOW		25	26			
			QUIET		24	25			
		Heating	HIGH		28	28			
			MED		26	26			
			LOW		25	27			
			QUIET		24	24			
Heat exchanger type	Dimensions (H × W × D)			in (mm)	11-9/16 × 19-11/16 × 1-1/16 (294 × 500 × 26.6)	11-9/16 × 19-11/16 × 1-9/16 (294 × 500 × 39.9)			
	Fin pitch			FPI	20				
	Rows × Stages			2 × 14					
	Pipe type			Copper tube					
	Fin type			Aluminum					
Enclosure	Material			Galvanized steel sheet					
	Color			-					
Dimensions (H × W × D)	Net			in (mm)	7-13/16 × 27-9/16 × 24-7/16 (198 × 700 × 620)				
	Gross				10-13/16 × 37-3/16 × 30-3/8 (274 × 945 × 772)				
Weight	Net			lb (kg)	37 (17)	40 (18)			
	Gross				49 (22)	51 (23)			
Connection pipe	Size	Liquid	in (mm)	Ø1/4 (Ø6.35)					
		Gas		Ø3/8 (Ø9.52)					
Drain hose	Method			Flare					
	Material			Hard PVC					
	Size			Ø 3/4 (I.D.), Ø 1-1/16 (O.D.) [Ø 20.7 (I.D.), Ø 26.6 (O.D.)]					
Operation range	Cooling			°F (°C)	64 to 90 (18 to 32)				
	Heating				80 or less				
				°F (°C)	60 to 86 (16 to 30)				
Remote controller type				Wired (Wireless [option])					

**NOTES:**

- Specifications are based on the following conditions.
  - Standard static pressure: 0.10 inWG (25 Pa)
- \*: Sound pressure level:
  - Measured values in manufacturer's anechoic chamber.
  - Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.

Model name				ARU18RLF	ARU24RLF				
Power supply				208/230 V ~ 60 Hz					
Available voltage range				187—264 V					
Capacity		Btu/h class		18,000	24,000				
Input power		W		73	111				
Running current		A		0.44	0.66				
Fan	Airflow rate	Cooling	HIGH	CFM (m <sup>3</sup> /h)	554 (940)				
			MED		518 (880)				
			LOW		483 (820)				
			QUIET		441 (750)				
		Heating	HIGH		554 (940)				
			MED		518 (880)				
			LOW		483 (820)				
			QUIET		441 (750)				
Type × Q'ty				Sirocco × 3	Sirocco × 4				
Motor output				81					
Recommended static pressure				inWG (Pa)	0 to 0.36 (0 to 90) 0 to 0.20 (0 to 50)				
Sound pressure level *2	Cooling	HIGH		dB (A)	32				
			MED		31				
			LOW		30				
			QUIET		29				
		Heating	HIGH		33				
			MED		32				
			LOW		31				
			QUIET		29				
Heat exchanger type	Dimensions (H × W × D)			in (mm)	11-9/16 × 27-9/16 × 1-9/16 (294 × 700 × 39.9)				
	Fin pitch			FPI	20				
	Rows × Stages				3 × 14				
	Pipe type				Copper tube				
	Fin type				Aluminum				
Enclosure	Material								
	Color								
Dimensions (H × W × D)	Net		in (mm)	7-13/16 × 35-7/16 × 24-7/16 (198 × 900 × 620)					
	Gross			10-13/16 × 45-1/16 × 30-3/8 (274 × 1,145 × 772)					
Weight	Net		lb (kg)	49 (22)					
	Gross			60 (27)					
Connection pipe	Size	Liquid	mm (in)	Ø1/4 (Ø6.35)					
		Gas		Ø1/2 (Ø12.70)					
Drain hose	Method			Flare					
	Material			Hard PVC					
	Size			Ø 3/4(I.D.), Ø 1-1/16(O.D.) [Ø 20.7 (I.D.), Ø 26.6 (O.D.)]					
Operation range	Cooling			64 to 90 (18 to 32)					
				%RH 80 or less					
Heating				60 to 86 (16 to 30)					
Remote controller type				Wired (Wireless [option])					

**NOTES:**

- Specifications are based on the following conditions.
  - Standard static pressure: 0.10 inWG (25 Pa)
- \*: Sound pressure level:
  - Measured values in manufacturer's anechoic chamber.
  - Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.

## 2-3. Wall mounted type

Model name				ASU7RLF1	ASU9RLF1	ASU12RLF1	ASU15RLF1				
Power supply				208/230 V ~ 60 Hz							
Available voltage range				187–264 V							
Capacity		Btu/h class	7,000	9,000	12,000	14,000					
Input power		W	15	17	22	28					
Running current		A	0.13	0.15	0.19	0.25					
Fan	Airflow rate	Cooling	HIGH	330 (560)	353 (600)	388 (660)	430 (730)				
			MED	294 (500)	306 (520)	330 (560)	353 (600)				
			LOW	253 (430)	253 (430)	265 (450)	312 (530)				
			QUIET	182 (310)	182 (310)	182 (310)	212 (360)				
		Heating	HIGH	330 (560)	353 (600)	388 (660)	430 (730)				
			MED	294 (500)	306 (520)	330 (560)	362 (615)				
			LOW	253 (430)	253 (430)	277 (470)	330 (560)				
			QUIET	194 (330)	194 (330)	194 (330)	221 (375)				
	Type × Q'ty			Cross flow fan × 1							
Motor output				30							
Sound pressure level *	Cooling	HIGH		36	37	40	42				
			MED	32	33	36	38				
			LOW	29	29	30	33				
			QUIET	21	21	21	25				
		Heating	HIGH	36	37	40	42				
			MED	32	33	36	38				
			LOW	29	29	31	35				
			QUIET	22	22	22	27				
	Type × Q'ty			Main: 12-5/8 × 24-13/16 × 13/16 (320 × 630 × 20) Sub: 3-5/16 × 24-13/16 × 1/2 (84 × 630 × 13.3)							
Heat exchanger type				Main: 2 × 20, Sub: 1 × 4							
Dimensions (H × W × D)				Main: 12-5/8 × 24-13/16 × 13/16 (320 × 630 × 20) Sub: 3-5/16 × 24-13/16 × 1/2 (84 × 630 × 13.3)							
Fin pitch				Main: 23, Sub: 18							
Rows × Stages				Main: 2 × 20, Sub: 1 × 4							
Pipe type				Copper tube							
Fin type				Aluminum							
Enclosure	Material			Polystyrene							
	Color			White (Approximate color of Munsell N 9.25/)							
Dimensions (H × W × D)	Net		in (mm)	10-9/16 × 33-1/16 × 8 (268 × 840 × 203)							
	Gross			10-5/8 × 34-13/16 × 14-3/4 (270 × 884 × 336)							
Weight	Net		lb (kg)	19 (8.5)							
	Gross			23 (10.5)							
Connection pipe	Size	Liquid	in (mm)	Ø1/4 (Ø6.35)							
		Gas		Ø3/8 (Ø9.52)   Ø1/2 (Ø12.70)							
Drain hose	Method		in (mm)	Flare							
	Material			PP + LLDPE							
Operation range	Size		in (mm)	Ø 9/16(I.D.), Ø 5/8 to Ø 11/16(O.D.) [Ø 13.8(I.D.), Ø 15.8 to Ø 16.7(O.D.)]							
	Cooling			64 to 90 (18 to 32)							
	Heating			80 or less							
Remote controller type				60 to 86 (16 to 30)							
NOTES:				Wireless (Wired [option])							
<ul style="list-style-type: none"> <li>The protective function might work when using it outside the operation range.</li> <li>*Sound pressure level:       <ul style="list-style-type: none"> <li>Measured values in manufacturer's anechoic chamber.</li> <li>Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.</li> </ul> </li> </ul>											

Model name				ASU18RLF	ASU24RLF		
Power supply				208/230 V ~ 60 Hz			
Available voltage range				187—264 V			
Capacity		Btu/h class		18,000	24,000		
Input power		W		41	69		
Running current		A		0.32	0.53		
Fan	Airflow rate	Cooling	HIGH	CFM (m <sup>3</sup> /h)	542 (920)		
			MED		436 (740)		
			LOW		365 (620)		
			QUIET		324 (550)		
		Heating	HIGH		542 (920)		
			MED		436 (740)		
			LOW		365 (620)		
			QUIET		324 (550)		
Type × Q'ty				Cross flow fan × 1			
Motor output				42			
Sound pressure level *	Cooling	HIGH		dB (A)	43		
			MED		37		
			LOW		33		
			QUIET		31		
		Heating	HIGH		44		
			MED		37		
			LOW		33		
			QUIET		31		
Heat exchanger type	Dimensions (H × W × D)			in (mm)	Main: 15-7/8 × 33-3/4 × 1-1/16 (378 × 832 × 26.6) Sub: 3-5/16 × 33-3/4 × 1/2 (84 × 832 × 13.3)		
	Fin pitch			FPI	Main: 21, Sub: 18		
	Rows × Stages				Main: 2 × 18, Sub: 1 × 4		
	Pipe type				Copper tube		
	Fin type				Aluminum		
Enclosure	Material				Polystyrene		
	Color				White (Approximate color of Munsell N 9.25/)		
Dimensions (H × W × D)	Net		in (mm)	12-5/8 × 39-1/4 × 9 (320 × 998 × 228)			
	Gross			12-9/16 × 42-15/16 × 16-7/8 (319 × 1,090 × 429)			
Weight	Net		lb (kg)	31 (14)			
	Gross			40 (18)			
Connection pipe	Size	Liquid	mm (in)	Ø1/4 (Ø6.35)			
		Gas		Ø1/2 (Ø12.70)			
Drain hose	Method			Flare			
	Material			PVC			
Operation range	Size		in (mm)	Ø 1/2(I.D.), Ø 5/8(O.D.) [Ø 12(I.D.), Ø 16(O.D.)]			
				64 to 90 (18 to 32) 80 or less			
	Cooling			60 to 86 (16 to 30)			
				60 to 86 (16 to 30)			
Remote controller type				Wireless (Wired [option])			

**NOTES:**

- The protective function might work when using it outside the operation range.
- \*Sound pressure level:
  - Measured values in manufacturer's anechoic chamber.
  - Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.

## 2-4. Floor type


Model name				AGU9RLF	AGU12RLF	AGU15RLF		
Power supply				208/230 V ~ 60 Hz				
Available voltage range				187—264 V				
Capacity		Btu/h class		9,000	12,000	14,000		
Input power		W		16	20	23		
Running current		A		0.15	0.18	0.20		
Fan	Airflow rate	Cooling	HIGH	CFM (m <sup>3</sup> /h)	312 (530)	353 (600)		
			MED		259 (440)	288 (490)		
			LOW		212 (360)	224 (380)		
			QUIET		159 (270)	159 (270)		
	Heating	HIGH	312 (530)		353 (600)			
		MED	270 (460)		300 (510)			
		LOW	224 (380)		241 (410)			
		QUIET	159 (270)		159 (270)			
	Type × Q'ty				Cross flow fan × 2			
Motor output				W	16			
Sound pressure level *	Cooling	HIGH	dB (A)	39	42	44		
				34	36	38		
				28	30	31		
				22	22	22		
	Heating	HIGH		39	42	44		
		MED		35	38	39		
		LOW		30	32	33		
		QUIET		22	22	22		
	Type × Q'ty	Dimensions (H × W × D)	in (mm)	14-7/8 × 21-5/8 × 1-1/16 (378 × 550 × 26.6)				
Heat exchanger type	Fin pitch		FPI	21				
	Rows × Stages			2 × 18				
	Pipe type			Copper tube				
	Fin type			Aluminium				
	Enclosure			Polystyrene				
Dimensions (H × W × D)	Material		White					
	Color		(Approximate color of Munsell N 9.25/)					
Weight	Net	lb (kg)	23-5/8 × 29-1/8 × 7-7/8 (600 × 740 × 200)					
	Gross		27-9/16 × 32-5/16 × 12-3/16 (700 × 820 × 310)					
Connection pipe	Size	Liquid	in (mm)	Ø1/4 (Ø 6.35)				
		Gas		Ø3/8 (Ø 9.52)		Ø1/2 (Ø 12.70)		
Drain hose	Method			Flare				
	Material			PVC				
Operation range	Size		in (mm)	Ø 9/16 (I.D.), Ø 11/16 (O.D.) [Ø 13.8 (I.D.), Ø 16.7 (O.D.)]				
	Cooling		°F (°C)	64 to 90 (18 to 32)				
	Heating		%RH	80 or less				
Remote controller type				60 to 86 (16 to 30)				
NOTES:				Wireless (Wired [option])				
<ul style="list-style-type: none"> <li>The protective function might work when using it outside the operation range.</li> <li>*Sound pressure level: <ul style="list-style-type: none"> <li>Measured values in manufacturer's anechoic chamber.</li> <li>Because of the surrounding sound environment, the sound levels measured in actual installation conditions might be higher than the specified values here.</li> </ul> </li> </ul>								

### 3. Dimensions

#### 3-1. Compact cassette type



##### ■ Models: AUU7RLF, AUU9RLF, AUU12RLF, and AUU18RLF

Unit: in (mm)





Standard type grille UTG-CCGF	Grid type grille UTG-CCGFG
22-13/16 to 26 (580 to 660)	22-13/16 to 24 (580 to 610)

- Standard type grille (UTG-CCGF)



Side view


- Grid type grille (UTG-CCGFG)



Side view

## ● Installation space


Unit: in (mm)



	Maximum height from floor to ceiling [Unit: in (mm)]	
Model name	AUU7RLF and AUU9RLF	AUU12RLF and AUU18RLF
Standard mode		107 (2,700)
High ceiling mode	—	119 (3,000)

### • 3-way direction setting

Unit: in (mm)




### NOTES:

- \*: When installing the indoor unit, be careful about the maintenance space.
- To set “3-direction”, optional Air outlet shutter plate (UTR-YDZB) must be installed, and the “outlet-direction” need to be switched to “3-way” by remote controller.
- The ceiling height cannot be set in the 3-way outlet mode. Therefore, ceiling height setting change by function setting 20 is prohibited. For details, refer to "Contents of function setting" on page 134.

## 3-2. Slim duct type


■ Models: ARU7RLF, ARU9RLF, and ARU12RLF

Unit: in (mm)




## ■ Model: ARU18RLF

Unit: in (mm)



## ■ Model: ARU24RLF


Unit: in (mm)




## ■ Installation space requirement

Provide sufficient installation space for product safety.

### In ceiling-concealed installations:




### In wall-concealed installations:



## ■ Maintenance space requirement

For future maintenance and service access, provide sufficient maintenance space.


**NOTE:** Do not place any wiring or illumination in the maintenance space, as they will impede service.




### 3-3. Wall mounted type

■ Models: **ASU7RLF1, ASU9RLF1, ASU12RLF1, and ASU15RLF1**

Unit: in (mm)




## ■ Installation space





## ■ Models: ASU18RLF and ASU24RLF

Unit: in (mm)



## ■ Installation space


Unit: in (mm)



## 3-4. Floor type

### ■ Models: AGU9RLF, AGU12RLF, and AGU15RLF

Unit: in (mm)




Front view

Side view

### ■ Installation space


Unit: in (mm)



## 4. Wiring diagrams


### 4-1. Compact cassette type

■ Models: AUU7RLF, AUU9RLF, AUU12RLF, and AUU18RLF




## 4-2. Slim duct type

■ Models: ARU7RLF, ARU9RLF, ARU12RLF, ARU18RLF, and ARU24RLF




## 4-3. Wall mounted type

■ Models: ASU7RLF1, ASU9RLF1, ASU12RLF1, and ASU15RLF1




## ■ Models: ASU18RLF and ASU24RLF



## 4-4. Floor type

■ Models: AGU9RLF, AGU12RLF, and AGU15RLF




## 5. Air velocity and temperature distributions

### 5-1. Compact cassette type

#### ■ Models: AUU7RLF and AUU9RLF

- Air velocity distribution


Measuring conditions	Fan speed	Operation mode
	HIGH	FAN



Measuring conditions	Fan speed	Operation mode	Outlet directions
NOTE: Reference data	HIGH	HEAT	4-way air outlet


- Air velocity distribution

Side view  
Vertical airflow direction louver: Down



- Air temperature distribution



Side view  
Vertical airflow direction louver: Down



## ■ Model: AUU12RLF

- Air velocity distribution


Measuring conditions	Fan speed	Operation mode
	HIGH	FAN



Measuring conditions	Fan speed	Operation mode	Outlet directions
NOTE: Reference data	HIGH	HEAT	4-way air outlet


- Air velocity distribution

Side view  
Vertical airflow direction louver: Down



- Air temperature distribution



Side view  
Vertical airflow direction louver: Down



## ■ Model: AUU18RLF

- Air velocity distribution


Measuring conditions	Fan speed	Operation mode
	HIGH	FAN



Measuring conditions	Fan speed	Operation mode	Outlet directions
NOTE: Reference data	HIGH	HEAT	4-way air outlet


- Air velocity distribution

Side view  
Vertical airflow direction louver: Down



- Air temperature distribution

Side view  
Vertical airflow direction louver: Down






## 5-2. Slim duct type

### ■ Model: ARU7RLF

**NOTE:** This data is measured after installing optional Auto louver grille kit.

Measuring conditions	Fan speed	Operation mode
	HIGH	FAN


- Air velocity distribution



Measuring conditions	Fan speed HIGH	Operation mode HEAT
----------------------	-------------------	------------------------


- Air velocity distribution

Side view  
Vertical airflow direction louver: Down  
Horizontal airflow direction louver: Center



- Air temperature distribution

Side view  
Vertical airflow direction louver: Down  
Horizontal airflow direction louver: Center




## ■ Model: ARU9RLF

**NOTE:** This data is measured after installing optional Auto louver grille kit.


Measuring conditions	Fan speed	Operation mode
	HIGH	FAN

- Air velocity distribution


Top view  
Vertical airflow direction louver: Up  
Horizontal airflow direction louver: Center



Top view  
Vertical airflow direction louver: Up  
Horizontal airflow direction louver: Left & Right




Side view  
Vertical airflow direction louver: Up  
Horizontal airflow direction louver: Center



Measuring conditions	Fan speed HIGH	Operation mode HEAT
----------------------	-------------------	------------------------


- Air velocity distribution

Side view  
Vertical airflow direction louver: Down  
Horizontal airflow direction louver: Center



- Air temperature distribution

Side view  
Vertical airflow direction louver: Down  
Horizontal airflow direction louver: Center




## ■ Model: ARU12RLF

**NOTE:** This data is measured after installing optional Auto louver grille kit.


Measuring conditions	Fan speed	Operation mode
	HIGH	FAN

- Air velocity distribution


Top view  
Vertical airflow direction louver: Up  
Horizontal airflow direction louver: Center



Top view  
Vertical airflow direction louver: Up  
Horizontal airflow direction louver: Left & Right




Side view  
Vertical airflow direction louver: Up  
Horizontal airflow direction louver: Center



Measuring conditions	Fan speed HIGH	Operation mode HEAT
----------------------	-------------------	------------------------


- Air velocity distribution

Side view  
Vertical airflow direction louver: Down  
Horizontal airflow direction louver: Center



- Air temperature distribution

Side view  
Vertical airflow direction louver: Down  
Horizontal airflow direction louver: Center




## ■ Model: ARU18RLF

**NOTE:** This data is measured after installing optional Auto louver grille kit.


Measuring conditions	Fan speed HIGH	Operation mode FAN
----------------------	-------------------	-----------------------

- Air velocity distribution


Top view  
Vertical airflow direction louver: Up  
Horizontal airflow direction louver: Center



Top view  
Vertical airflow direction louver: Up  
Horizontal airflow direction louver: Left & Right




Side view  
Vertical airflow direction louver: Up  
Horizontal airflow direction louver: Center



Measuring conditions	Fan speed HIGH	Operation mode HEAT
----------------------	-------------------	------------------------


- Air velocity distribution

Side view  
Vertical airflow direction louver: Down  
Horizontal airflow direction louver: Center



- Air temperature distribution

Side view  
Vertical airflow direction louver: Down  
Horizontal airflow direction louver: Center




## ■ Model: ARU24RLF

**NOTE:** This data is measured after installing optional Auto louver grille kit.

Measuring conditions	Fan speed	Operation mode
	HIGH	FAN


- Air velocity distribution



Measuring conditions	Fan speed HIGH	Operation mode HEAT
----------------------	-------------------	------------------------


- Air velocity distribution

Side view  
Vertical airflow direction louver: Down  
Horizontal airflow direction louver: Center



- Air temperature distribution


Side view  
Vertical airflow direction louver: Down  
Horizontal airflow direction louver: Center



## 5-3. Wall mounted type


### ■ Model: ASU7RLF1

Measuring conditions	Fan speed	Operation mode
	HIGH	FAN




# ■ Model: ASU9RLF1

Measuring conditions	Fan speed HIGH	Operation mode FAN
----------------------	-------------------	-----------------------







## ■ Model: ASU12RLF1



## ■ Model: ASU15RLF1


Measuring conditions	Fan speed	Operation mode
	HIGH	FAN




# ■ Model: ASU18RLF

Measuring conditions	Fan speed HIGH	Operation mode FAN
----------------------	-------------------	-----------------------


Top view  
Vertical airflow direction louver: Up  
Horizontal airflow direction louver: Center




Top view  
Vertical airflow direction louver: Up  
Horizontal airflow direction louver: Left & Right



Side view  
Vertical airflow direction louver: Up  
Horizontal airflow direction louver: Center




Side view  
Vertical airflow direction louver: Down  
Horizontal airflow direction louver: Center




## ■ Model: ASU24RLF

Measuring conditions	Fan speed HIGH	Operation mode FAN
----------------------	-------------------	-----------------------


Top view  
Vertical airflow direction louver: Up  
Horizontal airflow direction louver: Center




Top view  
Vertical airflow direction louver: Up  
Horizontal airflow direction louver: Left & Right



Side view  
Vertical airflow direction louver: Up  
Horizontal airflow direction louver: Center




Side view  
Vertical airflow direction louver: Down  
Horizontal airflow direction louver: Center



## 5-4. Floor type

### ■ Models: AGU9RLF, AGU12RLF, and AGU15RLF



Measuring conditions	Fan speed	Operation mode	Fan select
	HIGH	FAN	Upper and lower



## 6. Fan performance

### 6-1. Slim duct type

#### ■ Model: ARU7RLF




\*1: Available airflow rate range when Auto louver grille (option) is installed.

Fan speed : HIGH


Vertical airflow direction louver : Up

## ● Characteristics of air volume and capacity


- Cooling



- Heating




## ■ Model: ARU9RLF




## ● Characteristics of air volume and capacity


- Cooling




- Heating



## ■ Model: ARU12RLF



Available airflow rate range (High level)




\*1: Available airflow rate range when Auto louver grille (option) is installed.

Fan speed : HIGH


Vertical airflow direction louver : Up

## ● Characteristics of air volume and capacity


- Cooling




- Heating



## ■ Model: ARU18RLF



Available airflow rate range (High level)




\*1: Available airflow rate range when Auto louver grille (option) is installed.

Fan speed : HIGH


Vertical airflow direction louver : Up

## ● Characteristics of air volume and capacity


- Cooling



- Heating



## ■ Model: ARU24RLF




\*1: Available airflow rate range when Auto louver grille (option) is installed.

Fan speed : HIGH


Vertical airflow direction louver : Up

## ● Characteristics of air volume and capacity

- Cooling



- Heating



## 7. Airflow

Conversion factor:

- $1 \text{ m}^3/\text{h} = 0.2778 \text{ l/s} = 0.5886 \text{ CFM}$
- $3.6 \text{ m}^3/\text{h} = 1 \text{ l/s}$
- $1.699 \text{ m}^3/\text{h} = 1 \text{ CFM}$

### 7-1. Compact cassette type

Model	Operation mode	Fan speed	Airflow		
			$\text{m}^3/\text{h}$	l/s	CFM
AUU7RLF	Cooling	High	540	150	318
		Med	490	136	288
		Low	440	122	259
		Quiet	390	108	230
	Heating	High	540	150	318
		Med	490	136	288
		Low	440	122	259
		Quiet	390	108	230
AUU9RLF	Cooling	High	540	150	318
		Med	490	136	288
		Low	440	122	259
		Quiet	390	108	230
	Heating	High	540	150	318
		Med	490	136	288
		Low	440	122	259
		Quiet	390	108	230
AUU12RLF	Cooling	High	610	169	359
		Med	530	147	312
		Low	470	131	277
		Quiet	410	114	241
	Heating	High	610	169	359
		Med	530	147	312
		Low	470	131	277
		Quiet	410	114	241
AUU18RLF	Cooling	High	750	208	441
		Med	610	169	359
		Low	520	144	306
		Quiet	410	114	241
	Heating	High	800	222	471
		Med	710	197	418
		Low	600	167	353
		Quiet	450	125	265

## 7-2. Slim duct type

Model	Operation mode	Fan speed	Airflow		
			m <sup>3</sup> /h	l/s	CFM
ARU7RLF	Cooling	High	550	153	324
		Med	490	136	288
		Low	470	131	277
		Quiet	440	122	259
	Heating	High	550	153	324
		Med	490	136	288
		Low	470	131	277
		Quiet	440	122	259
ARU9RLF	Cooling	High	600	167	353
		Med	550	153	324
		Low	500	139	294
		Quiet	450	125	265
	Heating	High	600	167	353
		Med	550	153	324
		Low	500	139	294
		Quiet	450	125	265
ARU12RLF	Cooling	High	650	181	383
		Med	600	167	353
		Low	550	153	324
		Quiet	480	133	283
	Heating	High	650	181	383
		Med	600	167	353
		Low	550	153	324
		Quiet	480	133	283
ARU18RLF	Cooling	High	940	261	554
		Med	880	244	518
		Low	820	227	483
		Quiet	750	208	441
	Heating	High	940	261	554
		Med	880	244	518
		Low	820	227	483
		Quiet	750	208	441
ARU24RLF	Cooling	High	1,330	369	783
		Med	1,240	344	730
		Low	1,100	306	648
		Quiet	1,030	286	607
	Heating	High	1,330	369	783
		Med	1,240	344	730
		Low	1,100	306	648
		Quiet	1,030	286	607

## 7-3. Wall mounted type

Model	Operation mode	Fan speed	Airflow		
			m <sup>3</sup> /h	I/s	CFM
ASU7RLF1	Cooling	High	560	156	330
		Med	500	139	294
		Low	430	119	253
		Quiet	310	86	182
	Heating	High	560	156	330
		Med	500	139	294
		Low	430	119	253
		Quiet	330	92	194
ASU9RLF1	Cooling	High	600	167	353
		Med	520	144	306
		Low	430	119	253
		Quiet	310	86	182
	Heating	High	600	167	353
		Med	520	144	306
		Low	430	119	253
		Quiet	330	92	194
ASU12RLF1	Cooling	High	660	183	388
		Med	560	156	330
		Low	450	125	265
		Quiet	310	86	182
	Heating	High	660	183	388
		Med	560	156	330
		Low	470	131	277
		Quiet	330	92	194
ASU15RLF1	Cooling	High	730	203	430
		Med	600	167	353
		Low	530	147	312
		Quiet	360	100	212
	Heating	High	730	203	430
		Med	615	171	362
		Low	560	156	330
		Quiet	375	104	221
ASU18RLF	Cooling	High	920	256	542
		Med	740	206	436
		Low	620	172	365
		Quiet	550	153	324
	Heating	High	920	256	542
		Med	740	206	436
		Low	620	172	365
		Quiet	550	153	324
ASU24RLF	Cooling	High	1,120	311	659
		Med	900	250	530
		Low	740	206	436
		Quiet	620	172	365
	Heating	High	1,100	306	647
		Med	900	250	530
		Low	740	206	436
		Quiet	620	172	365

## 7-4. Floor type


Model	Operation mode	Fan speed	Airflow		
			m <sup>3</sup> /h	l/s	CFM
AGU9RLF	Cooling	High	530	147	312
		Med	440	122	259
		Low	360	100	212
		Quiet	270	75	159
	Heating	High	530	147	312
		Med	460	128	270
		Low	380	106	224
		Quiet	270	75	159
AGU12RLF	Cooling	High	600	167	353
		Med	490	136	288
		Low	380	106	224
		Quiet	270	75	159
	Heating	High	600	167	353
		Med	510	142	300
		Low	410	114	241
		Quiet	270	75	159
AGU15RLF	Cooling	High	650	181	383
		Med	520	144	306
		Low	400	111	235
		Quiet	270	75	159
	Heating	High	650	181	383
		Med	540	150	318
		Low	430	119	253
		Quiet	270	75	159

## 8. Noise level curve


### 8-1. Compact cassette type

#### ■ Model: AUU7RLF

##### ● Cooling




##### ● Heating








#### ■ Model: AUU9RLF

##### ● Cooling



##### ● Heating




**■ Model: AUU12RLF****● Cooling****● Heating****■ Model: AUU18RLF****● Cooling****● Heating**


## 8-2. Slim duct type

### ■ Model: ARU7RLF

#### ● Cooling




#### ● Heating








### ■ Model: ARU9RLF

#### ● Cooling




#### ● Heating




**■ Model: ARU12RLF****● Cooling****● Heating****■ Model: ARU18RLF****● Cooling****● Heating**

## ■ Model: ARU24RLF

### ● Cooling




### ● Heating




## 8-3. Wall mounted type

### ■ Model: ASU7RLF1

#### ● Cooling




#### ● Heating








### ■ Model: ASU9RLF1





#### ● Cooling



#### ● Heating




**■ Model:ASU12RLF1****● Cooling****● Heating****■ Model: ASU15RLF1****● Cooling****● Heating**

**■ Model: ASU18RLF****● Cooling****● Heating****■ Model: ASU24RLF****● Cooling****● Heating**


## 8-4. Floor type

### ■ Model: AGU9RLF

#### ● Cooling




#### ● Heating




### ■ Model: AGU12RLF

#### ● Cooling




#### ● Heating




## ■ Model: AGU15RLF

### ● Cooling





### ● Heating




## 8-5. Sound level check point


### ■ Compact cassette type



## ■ Slim duct type




## ■ Wall mounted type



**NOTE:** Detailed shape of the actual indoor unit might be slightly different from the one illustrated above.

## ■ Floor type



## 9. Electrical characteristics

		Power supply			Indoor rated	
Type	Model name	Hz	Voltage (V)	MCA (A)	Input power (W)	FLA (A)
Compact cassette	AUU7RLF	60	208 / 230	0.19 / 0.19	17 / 18	0.15 / 0.15
	AUU9RLF			0.19 / 0.19	17 / 18	0.15 / 0.15
	AUU12RLF			0.24 / 0.24	22 / 23	0.19 / 0.19
	AUU18RLF			0.41 / 0.38	38 / 39	0.32 / 0.30
Slim duct	ARU7RLF			0.40 / 0.41	47 / 33	0.32 / 0.30
	ARU9RLF			0.40 / 0.38	47 / 49	0.32 / 0.30
	ARU12RLF			0.47 / 0.44	56 / 58	0.37 / 0.35
	ARU18RLF			0.59 / 0.55	71 / 73	0.47 / 0.44
	ARU24RLF			0.89 / 0.83	109 / 111	0.71 / 0.66
Wall mounted	ASU7RLF1			0.18 / 0.16	15 / 15	0.14 / 0.13
	ASU9RLF1			0.20 / 0.19	17 / 17	0.16 / 0.15
	ASU12RLF1			0.25 / 0.24	22 / 22	0.20 / 0.19
	ASU15RLF1			0.34 / 0.31	28 / 28	0.27 / 0.25
	ASU18RLF			0.42 / 0.40	40 / 41	0.34 / 0.32
	ASU24RLF			0.71 / 0.66	68 / 69	0.57 / 0.53
Floor	AGU9RLF			0.36 / 0.33	35 / 32	0.29 / 0.26
	AGU12RLF			0.36 / 0.33	35 / 32	0.29 / 0.26
	AGU15RLF			0.41 / 0.38	40 / 36	0.33 / 0.30

Wiring spec. (Indoor unit to outdoor unit)	Connection cable	Size	AWG	14
		Limited wiring length	ft (m)	85 (26)

MCA: Minimum Circuit Ampacity = Maximum operating current (Full load)

FLA: Full Load Amperes (Fan motor)

## 10. Safety devices

Indoor unit type	Model name	PCB* fuse	Fan motor thermal protector	Terminal thermal fuse	Float switch
Compact cassette	AUU7RLF AUU9RLF AUU12RLF AUU18RLF	250 V, 3.15 A	Activate: 212 ±27 °F (100 ±15 °C) Fan motor stop Reset: 203 ±18 °F (95 ±10 °C) Fan motor restart	—	○
Slim duct	ARU7RLF ARU9RLF ARU12RLF ARU18RLF ARU24RLF	250 V, 3.15 A	Activate: 275 ±27 °F (135 ±15 °C) Fan motor stop Reset: 239 ±27 °F (115 ±15 °C) Fan motor restart	—	○
Wall mounted	ASU7RLF1 ASU9RLF1 ASU12RLF1 ASU15RLF1	250 V, 3.15 A	Activate: 221 ±18 °F (105 ±10 °C) Fan motor stop Reset: 194 ±18 °F (90 ±10 °C) Fan motor restart	—	—
	ASU18RLF ASU24RLF	250 V, 3.15 A	Activate: 302 ±27 °F (150 ±15 °C) Fan motor stop Reset: 248 ±27 °F (120 ±15 °C) Fan motor restart	Activate: 216 °F (102 °C)	—
Floor	AGU9RLF AGU12RLF AGU15RLF	250 V, 3.15 A	Activate: 302 ±27 °F (150 ±15 °C) Fan motor stop Reset: 248 ±27 °F (120 ±15 °C) Fan motor restart	Activate: 216 °F (102 °C)	—

\*: Printed Circuit Board

## 11. External input and output

Indoor unit type	External input	External output			
	Control input	Operation status output	Fresh air control output	Auxiliary heater output	Error status output
Compact cassette	•	•	•	—	—
Slim duct	•	•	•	•	—
Wall mounted	•	•	—	—	• (ASU7-15RLF1)
Floor	•	•	—	—	•

### 11-1. External input

With using external input function, some functions on this product can be controlled from an external device.

- “Operation/Stop” mode or “Forced stop” mode can be selected with function setting of indoor unit.
- A twisted pair cable (22AWG) should be used. Maximum length of cable is 492 ft (150 m).
- The wire connection should be separate from the power cable line.

### ■ Control input (Operation/Stop or Forced stop)


Indoor unit type		Connector
Compact cassette		CN102
Slim duct		CN102
Wall mounted	ASU7RLF1, ASU9RLF1, ASU12RLF1, ASU15RLF1	CNA01
	ASU18RLF, ASU24RLF	CN14
Floor	AGU9RLF, AGU12RLF, AGU15RLF	CN14

The air conditioner can be remotely operated by means of the following on-site work.

Operation is started at the following contents by adding the contact input of a commercial on/off switch to a connector on the external control PCB and turning it on.

Unit operation	Initial setting after power is on	Starting mode other than initial setting
Operation mode	Auto changeover	Mode at previous operation
Set temperature	76 °F (24 °C)	Temperature at previous operation
Airflow mode	AUTO	Mode at previous operation
Air direction (swing)	Standard air direction (swing: off)	Air direction at previous operation


- Circuit diagram example




- Contact capacity: DC 24 V or more, 10 mA or more.
- \*1: PCB of Communication kit is used for wall mounted (ASU7RLF1, ASU9RLF1, ASU12RLF1, and ASU15RLF1) type.
- \*2: Make the distance from the PCB to the connected unit within 33 ft (10 m).
- Use non-polar relays and switches.

Indoor unit type		1-pin (Polarity)	3-pin (Polarity)
Compact cassette		-	+
Slim duct		-	+
Wall mounted	ASU7RLF1, ASU9RLF1, ASU12RLF1, ASU15RLF1 ASU18RLF, ASU24RLF	-	+
	AGU9RLF, AGU12RLF, AGU15RLF	-	+

- When function setting is "Operation/Stop" mode




- When function setting is "Forced stop" mode




- Optional part


Indoor unit type		Part name	Model name	
Compact cassette		External connect kit	UTY-XWZX	
Slim duct			UTD-ECS5A	
Wall mounted	ASU7RLF1, ASU9RLF1, ASU12RLF1, ASU15RLF1		UTY-XWZXZ5	
	ASU18RLF, ASU24RLF		UTY-XWZX	
Floor	AGU9RLF, AGU12RLF, AGU15RLF		UTY-XWZXZ5	



UTY-XWZX



UTD-ECS5A



UTY-XWZXZ5

Indoor unit type		Part name	Model name
Compact cassette		—	—
Slim duct		—	—
Wall mounted	ASU7RLF1, ASU9RLF1, ASU12RLF1, ASU15RLF1	Communication kit	UTY-XCBXZ2
	ASU18RLF, ASU24RLF		—
Floor	AGU9RLF, AGU12RLF, AGU15RLF	—	—

\*For operating the external input function, the wall mounted type (ASU7RLF1, ASU9RLF1, ASU12RLF1, and ASU15RLF1) requires optional communication kit (UTY-XCBXZ2) in addition to the wire (UTY-XWZXZ5).

## 11-2. External output


Use an external output cable with appropriate external dimension, depending on the number of cables to be installed.

### ■ Operation status output


Indoor unit type		Connector
Compact cassette		CN103
Slim duct		CN103
Wall mounted	ASU7RLF1, ASU9RLF1, ASU12RLF1, ASU15RLF1	CNB01
	ASU18RLF, ASU24RLF	CN16
Floor	AGU9RLF, AGU12RLF, AGU15RLF	CN20

Air conditioner operation status signal can be output.

- **Circuit diagram example**




- \*1: PCB of communication kit is used for wall mounted type (ASU7RLF1, ASU9RLF1, ASU12RLF1, and ASU15RLF1).
- \*2: Make the distance from the PCB to the connected unit within 33 ft (10 m).
- Relay spec: Max. DC 24 V, 10 mA to less than 500 mA.



- Optional part

Indoor unit type		Part name	Model name	
Compact cassette		External connect kit	UTY-XWZX	
Slim duct			UTD-ECS5A	
Wall mounted	ASU7RLF1, ASU9RLF1, ASU12RLF1, ASU15RLF1		UTY-XWZXZ5	
	ASU18RLF, ASU24RLF		UTY-XWZX	
Floor	AGU9RLF, AGU12RLF, AGU15RLF		UTY-XWZXZ5	



Indoor unit type		Part name	Model name	
Compact cassette		Communication kit	—	
Slim duct			—	
Wall mounted	ASU7RLF1, ASU9RLF1, ASU12RLF1, ASU15RLF1		UTY-XCBXZ2	
	ASU18RLF, ASU24RLF		—	
Floor	AGU9RLF, AGU12RLF, AGU15RLF		—	

\*For operating the external output function, the wall mounted type (ASU7RLF1, ASU9RLF1, ASU12RLF1, and ASU15RLF1) requires optional Communication kit (UTY-XCBXZ2) in addition to the wire (UTY-XWZXZ5).


## ■ Fresh air control output

Indoor unit type	Connector
Compact cassette	CN6
Slim duct	—
Wall mounted	—
Floor	—

Signal linked to air conditioner indoor fan on can be output.


\* However, signal becomes off during cold air prevention control operation.

- **Circuit diagram example**



– \*: Make the distance from the PCB to the connected unit within 33 ft (10 m).

– Relay spec.: Rated DC 12 V, 50 mA to less.



- **Optional part**

Indoor unit type	Part name	Model name
Compact cassette	Fresh air intake kit	UTZ-VXAA
Slim duct	External control set	UTD-ECS5A
Wall mounted	—	—
Floor	—	—



## ■ Auxiliary heater output


Indoor unit type	Connector
Compact cassette	—
Slim duct	CN10
Wall mounted	—
Floor	—

Signal is output from connector when indoor fan and compressor turn on under heating operation.

\*Signal output performance specifications are as shown as follows:

**Example:** When Set Temperature (Ts) is 72 °F(22 °C)

- and room temperature (Tr) increase above 52 °F(12 °C), signal output is on.
- and room temperature (Tr) increase above 70 °F(21 °C), signal output is off.
- and room temperature (Tr) decrease below 66 °F(19 °C), signal output is on.
- and room temperature (Tr) decrease below 48 °F(10 °C), signal output is off.




- **Fan delay setting (JM3)**


This is used to continue indoor unit fan operation for 1 minute after thermostat "Off" in heating mode.

1 minute delay control set by cutting jumper wire on PCB.

- Circuit diagram example




- Relay spec.: Rated DC 12 V, 50 mA to less.
- \*: Make the distance from the PCB to the connected unit within 33 ft (10 m).



**⚠ CAUTION**

- Locate an external heater between the indoor unit and the outlet.



- Be sure to use delay control of a fan.

---

- Optional part

Indoor unit type	Part name	Model name
Compact cassette	—	—
Slim duct	External control set	UTD-ECS5A
Wall mounted	—	—
Floor	—	—




## ■ Error status output


Indoor unit type		Connector
Compact cassette		—
Slim duct		—
Wall mounted	ASU7RLF1, ASU9RLF1, ASU12RLF1, ASU15RLF1	CNB02
	ASU18RLF, ASU24RLF	—
Floor	AGU9RLF, AGU12RLF, AGU15RLF	CN21

Air conditioner error status signal can be output.

- **Circuit diagram example**




- \*1: PCB of communication kit is used for wall mounted type (ASU7RLF1, ASU9RLF1, ASU12RLF1, and ASU15RLF1).
- \*2: Make the distance from the PCB to the connected unit within 33 ft (10 m).
- Relay spec.: Max. DC 24 V, 10 mA to less than 500 mA.



- Optional part

Indoor unit type		Part name	Model name
Compact cassette		—	—
Slim duct		—	—
Wall mounted	ASU7RLF1, ASU9RLF1, ASU12RLF1, ASU15RLF1	External connect kit	UTY-XWZXZ5
	ASU18RLF, ASU24RLF	—	—
Floor	AGU9RLF, AGU12RLF, AGU15RLF	External connect kit	UTY-XWZXZ5




Indoor unit type		Part name	Model name
Compact cassette		—	—
Slim duct		—	—
Wall mounted	ASU7RLF1, ASU9RLF1, ASU12RLF1, ASU15RLF1	Communication kit	UTY-XCBXZ2
	ASU18RLF, ASU24RLF	—	—
Floor	AGU9RLF, AGU12RLF, AGU15RLF	—	—

\*For operating the external input function, the wall mounted type (ASU7RLF1, ASU9RLF1, ASU12RLF1, and ASU15RLF1) requires Communication kit (UTY-XCBXZ2) in addition to the wire (UTY-XWZXZ5).

## 12. Group connection

Wiring regulation on the remote controllers in the multi split models are reviewed and allowed for group connection.

**Example of group connection**



\*Exterior of each device shown above might be different from the actual one.

**NOTES:**


- Group connection is applicable for multi system consists of following products that are produced in 2013 or later:
  - ASU7RLF1, ASU9RLF1, ASU12RLF1, ASU15RLF1, ASU18RLF, and ASU24RLF in wall mounted type
  - AGU9RLF, AGU12RLF, and AGU15RLF in floor type
- Maximum number of connectable indoor units is depend on the outdoor unit.

## 12-1. Precautions on creating a group connection


Take precautions on items described in this section when creating a group connection in the multi split models.

### **⚠ CAUTION**

Group connection to other refrigerant system between the multi systems with same communication system as shown below is strictly prohibited.




- Group connection is allowed only in the same refrigerant system. (Maximum number of connectable indoor units is depend on the outdoor unit.).



\*Exterior of each device shown above might be different from the actual one.

- Central remote controller (UTY-DMMUM) cannot be connected simultaneously.



\*Exterior of each device shown above might be different from the actual one.

— : Piping      — : Wired remote controller wiring

- Maximum wiring length of the remote controller cable:** 984 ft (300 m)

Even if the maximum wiring length of the product itself is specified as longer than 984 ft (300 m), the maximum length of the remote controller cable will be 984 ft (300 m) if the system is group-connected.

When total wiring length is longer than 328 ft (100 m), the cable diameter needs to be changed as follows:

Total wiring length of remote controller cable Unit: ft (m)	Cross section of cable Unit: AWG (mm <sup>2</sup> )
328 (100) or less	18—22 (0.3—0.8)
328—656 (100—200)	18—20 (0.5—0.8)
656—984 (200—300)	18 (0.8)

- Required parts for group connection**


- Optional part:

Indoor unit type	Communication kit
Wall mounted	ASU7-15RLF1 UTY-XCBXZ2

As for the optional parts, refer to Chapter 16-3. "Others" on page 151.

- Service part: Wire with connector (Service part no. 9705932012)

#### Wiring example for multiple remote control or group control:



#### NOTES:

- Conceal the wirings of the group connection inside of the wall or by means of trunking at the thickness of 1-mm or more to prevent electrical shocks when getting in touch with the cables under certain circumstances.
- When using the Communication kit for wall mounted type, store the crimping terminals inside the Communication kit.
- In the wireless remote controllers for the group connection, its remote controller address can be set by its own. For the details, refer to following section "Remote controller address setting procedure for wireless remote controllers". An error is displayed immediately just turning on the power to effect the settings of the group connection. However the error will automatically disappear when the subsequent function setting is completed.
- Bundle the wires with a cable tie to prevent external pressures apply on the crimping terminals. (Ensure that the tensile strength for the splicing position is 10 N or above.)


## 12-2. Remote controller address setting procedure for wireless remote controllers

1. Enter the function setting mode of the wireless remote controller. For details, refer to "["Function settings"](#) on page 113.
2. Select the function number "00" (Remote controller address setting), and then select any of the number (Setting value) from 00 to 15. (Factory setting: 00)


## 13. Remote controller

### 13-1. Wireless remote controller (UTY-LNHUM)

#### ■ Overview



Display panel



**NOTE:** Functions may differ by type of the indoor unit. For details, refer to the operation manual.

**1 FAN button**

Selects the fan speed (AUTO, HIGH, MED, LOW, and QUIET).

**2 START/STOP button**

Starts and stops operation.

**3 SET button (vertical)**

Adjusts the vertical airflow direction.

**4 SET button (horizontal)**

Adjusts the horizontal airflow direction.

**5 SWING button**

Sets the automatic swing operation and selects swing mode (Up/down, Left/right, Up/down/left/right, and Stop swing).

**6 RESET button**

Used when replacing batteries.

**7 Timer set (- / +) button**

Sets the current time and on-off time.

**8 TEST RUN button**

Only used for the initial test in the unit installation.

**9 CLOCK ADJUST button**

Used for adjusting the clock.

**10 TIMER MODE button**

Selects the timer mode (off timer, on timer, program timer, and timer reset).

**11 SLEEP button**

Pressed to select sleep timer.

**12 ECONOMY button**

**13 MIN. HEAT button**

**14 SET TEMP. (temperature) (▲ / ▼) button**

- Sets desired temperature.
- Sets remote controller custom code.

**15 MODE button**

- Switches operation mode (AUTO, COOL, DRY, FAN, and HEAT).
- Starts/ends the remote controller custom code (max. 4 types) change.

**16 Signal transmitter**

**17 Signal transmit indicator**

**18 Fan speed indicator**

**19 Swing indicator**

**20 Timer mode indicator**

**21 Clock indicator**

**22 Sleep indicator**


**23 Operating mode indicator**

**24 Temperature indicator**

## ■ Specifications

### ● Controller

Unit: in (mm)




Size (H × W × D)	in (mm)	6-11/16 × 2-3/16 × 3/4 (170 × 56 × 19)
Weight	oz (g)	3 (85) (without batteries)

**NOTE:** Actual number of buttons might be different from the figure above.

### ● Holder

Unit: in (mm)




Size (H × W × D)	in (mm)	6-1/16 × 2-3/8 × 1-1/16 (154.7 × 60.4 × 26.2)
Weight	oz (g)	1 (28)


## 13-2. Wireless remote controller (AR-REG1U)

### ■ Overview

- AR-REG1U



**NOTE:** Functions may differ by type of the indoor unit. For details, refer to the operation manual.  
**Display panel**




To facilitate explanation, the accompanying illustration has been drawn to show all possible indicators; in actual operation, however, the display will only show those indicators appropriate to the current operation.

## ■ Specifications

### ● Controller


Unit: in (mm)



Size (H × W × D)	in (mm)	8-1/16 × 2-3/8 × 11/16 (205 × 61 × 17)
Weight	oz (g)	4.3 (122) (without batteries)

### ● Holder


Unit: in (mm)




Size (H × W × D)	in (mm)	5-7/8 × 2-3/4 × 1-1/16 (150 × 69.3 × 26.2)
Weight	oz (g)	1 (27)

## 13-3. Wired remote controller (UTY-RNNUM)

### ■ Overview



Display panel




**NOTE:** Functions may differ by type of the indoor unit. For details, refer to the operation manual.


- 1 START/STOP button**  
Starts and stops operation.
- 2 SET TEMP. button**  
Selects the setting temperature.
- 3 MODE button**  
Selects the operating mode (AUTO , HEAT , FAN , COOL , and DRY ).
- 4 FAN button**  
Selects the fan speed AUTO , QUIET , LOW , MED , and HIGH .
- 5 ECONOMY (THERMO SENSOR) button**  
Turns the economy-efficient mode on and off.
- 6 TIMER MODE (CLOCK ADJUST) button**  
Selects the timer mode (off timer, on timer, and weekly timer). Sets the current time.
- 7 DAY (DAY OFF) button**  
Temporarily cancels one day timer.
- 8 SET BACK button**  
Selects the set back timer.
- 9 Set time button**  
Pressed to set time.
- 10 TIMER DELETE button**  
Deletes the weekly timer schedule.
- 11 TIMER SET button**  
Sets the date, hour, minute, and on-off time.
- 12 Vertical airflow direction and swing button**  
Push for 2 seconds to change the swing mode.
- 13 Horizontal airflow direction and swing button**  
Push for 2 seconds to change the swing mode.
- 14 FILTER RESET button**
- 15 Operation lamp**  
Lights during operation and when the timer is on.
- 16 Timer and clock indicator**
- 17 Operation mode indicator**
- 18 Fan speed indicator**
- 19 Operation lock indicator**
- 20 Temperature indicator**
- 21 Function indicators**
  - Defrost indicator
  - Thermo sensor indicator
  - Economy indicator
  - Vertical swing indicator
  - Horizontal swing indicator
  - Filter indicator

## ■ System diagram

### 1 remote controller:




### 2 remote controllers:




A, B, C: Remote controller cable  
 $A \leq 1,640 \text{ ft (500 m)}$ ;  $B + C \leq 1,640 \text{ ft (500 m)}$

## ■ Electrical wiring

### 1 remote controller:




### 2 remote controllers:



## ■ Specifications

Dimensions and other specifications on the wired remote controller are as follows.

			Unit: in (mm)
		4-3/4 (120)	
		11/16 (18)	
	Front view		Side view
Size (H × W × D)	in (mm)	$4\frac{3}{4} \times 4\frac{3}{4} \times 11\frac{1}{16}$ (120 × 120 × 18)	
Weight	oz (g)	5.6 (160)	
Cable length (accessory)	ft (m)	33 (10)	
Power	V	12	

### ● Wiring specifications

Use	Cable size	Wire type	Remarks
Remote controller cable	22 AWG ( $0.33 \text{ mm}^2$ )	Polar 3-core	Use sheathed PVC cable.

## ■ Installation


### ● Connection pattern

**NOTE:** Connection pattern is different according to type of Indoor unit.

Indoor unit types		Connection pattern
Compact cassette type		Pattern A
Slim duct type		Pattern A
Wall mounted type	ASU7RLF1, ASU9RLF1, ASU12RLF1, and ASU15RLF1	Pattern B
	ASU18RLF and ASU24RLF	Pattern C
Floor type		

### ● Pattern A

Connect the end of remote controller cable directly to the exclusive terminal block.




**NOTE:** It may be failed if it is connected to the outdoor unit or the terminal block for power supply.


### ● Pattern B

1. Modify the remote controller cable as follows:

- Use a tool to cut off the terminal on the end of the remote controller cable and then remove the insulation from the cut end of the cable as shown in following figure.
- Connect the remote controller cable and connecting cable as shown in following figure.
- Be sure to insulate the connection between the cables.




2. Connect the remote controller cable.
  - Connect the cable made in step 1. to the terminal (\*1) of optional communication kit.
  - Connect the cable from the terminal (\*2) of communication kit to the indoor unit PCB.




## ● Pattern C

1. Modify the remote controller cable as follows:
  - Use a tool to cut off the terminal on the end of the remote controller cable and then remove the insulation from the cut end of the cable as shown in following figure.
  - Connect the remote controller cable and connecting cable as shown in following figure.
  - Be sure to insulate the connection between the cables.



2. Connect the remote controller cable.
  - Connect the cable made in step 1. to the indoor unit PCB.




## ■ Optional parts

Wall mounted	Model name
ASU7/9/12/15RLF1	UTY-XCBXZ2


The communication kit is needed for connecting the wired remote controller to the wall mounted type.

## 13-4. Simple remote controller (UTY-RSNUM: Optional part)

### ■ Overview



Display panel



#### 1 START/STOP button

Starts and stops operation.

#### 2 Display backlight button

Lights during operation.

#### 3 Operation lamp

Lights during operation.

#### 4 FAN button

Selects the fan speed (AUTO $\text{A}^{\circ}$ , HIGH $\text{H}^{\circ}$ , MED $\text{M}^{\circ}$ , LOW $\text{L}^{\circ}$ , and QUIET $\text{Q}^{\circ}$ ).

#### 5 SET TEMP. button

Selects the setting temperature.

#### 6 MODE button

Selects the operating mode (AUTO $\text{A}^{\circ}$ , COOL $\text{C}^{\circ}$ , DRY $\text{D}^{\circ}$ , FAN $\text{F}^{\circ}$ , HEAT $\text{H}^{\circ}$ ).

#### 7 Standby indicator

Indicates during the oil recovery and defrosting operation.

#### 8 Power source indicator

Indicates the main power is on.

#### 9 Central control indicator

Indicates when function is locked.

#### 10 Fan speed indicator

Deletes the weekly timer schedule.

#### 11 Set temperature

- Indicates error history number in error code history display mode.
- Indicates indoor unit address in address display mode.


#### 12 Operating mode indicator

#### 13 Indicator


- Upper:
  - Indicates the error code in error code history display mode and in self diagnosis mode.
  - Indicates the refrigerant system address in address display mode.
- Lower: Indicates the remote controller address in error code history display mode, address display mode, and self diagnosis mode.

## ■ System diagram

### 1 remote controller:




### 2 remote controllers:




A, B, C: Remote controller cable  
 $A \leq 1,640 \text{ ft (500 m)}$ ;  $B + C \leq 1,640 \text{ ft (500 m)}$

## ■ Electrical wiring

### 1 remote controller:




### 2 remote controllers:



## ■ Specifications

Dimensions and other specifications on the wired remote controller are as follows.



**Front View:** Dimensions include width 2-15/16 (75), height 15/16 (23.5), depth 4-3/4 (120), top panel width 1-9/16 (39), left panel width 1-15/16 (49), and right panel width 2-15/16 (75).

**Side View:** Depth 9/16 (14).

**Rear View:** Dimensions include height 1-7/8 (47.5), width 3-5/16 (83.5), depth 3/16 (4), and a central cavity height of 3-1/16 (83.5). There are two holes at the top and bottom labeled "hole x 2".

**Unit:** in (mm)

Size (H × W × D)	in (mm)	4-3/4 × 2-15/16 × 9/16 (120 × 75 × 14)
Weight	oz (g)	3.2 (90)
Cable length (accessory)	ft (m)	33 (10)
Power	V	12

## ● Wiring specifications

Use	Size	Wire type	Remarks
Remote controller cable	22 AWG (0.33 mm <sup>2</sup> )	Polar 3 core	Use sheathed PVC cable.

## ■ Installation


### ● Connection pattern

**NOTE:** Connection pattern is different according to type of Indoor unit.

Indoor unit types		Connection pattern
Compact cassette type		Pattern A
Slim duct type		Pattern A
Wall mounted type	ASU7RLF1, ASU9RLF1, ASU12RLF1, and ASU15RLF1	Pattern B
	ASU18RLF and ASU24RLF	Pattern C
Floor type		

### ● Pattern A

Connect the end of remote controller cable directly to the exclusive terminal block.




**NOTE:** It may be failed if it is connected to the outdoor unit or the terminal block for power supply.


### ● Pattern B

1. Modify the remote controller cable as follows:

- Use a tool to cut off the terminal on the end of the remote controller cable and then remove the insulation from the cut end of the cable as shown in following figure.
- Connect the remote controller cable and connecting cable as shown in following figure.
- Be sure to insulate the connection between the cables.




2. Connect the remote controller cable.
  - Connect the cable made in step 1. to the terminal (\*1) of optional communication kit.
  - Connect the cable from the terminal (\*2) of communication kit to the indoor unit PCB.




## ● Pattern C

1. Modify the remote controller cable as follows:
  - Use a tool to cut off the terminal on the end of the remote controller cable and then remove the insulation from the cut end of the cable as shown in following figure.
  - Connect the remote controller cable and connecting cable as shown in following figure.
  - Be sure to insulate the connection between the cables.



2. Connect the remote controller cable.
  - Connect the cable made in step 1. to the indoor unit PCB.




## ■ Optional parts

Wall mounted	Model name
ASU7/9/12/15RLF1	UTY-XCBXZ2

The communication kit is needed for connecting the wired remote controller to the wall mounted type.

## 13-5. Central remote controller (UTY-DMMUM: Optional part)


### ■ Overview



- 1** Display panel (with backlight)
- 2** Screen switch button (Left)
- 3** Menu button
- 4** Cancel button
- 5** Cursor button
- 6** Screen switch button (Right)
- 7** Power indicator
- 8** On / Off button
- 9** Enter button

### ■ Electrical wiring

Example: Wiring diagram when 3 indoor units are connected.



**NOTE:** Maximum length of remote controller cable is 1,650 ft (500 m).

## ■ Specifications

Dimensions and other specifications on the wired remote controller are as follows.

The technical drawing illustrates the dimensions of the wired remote controller from three perspectives:

- Front View:** Shows the overall width of 4-3/4 (120) mm and the height of 4-3/4 (120) mm. The face features a large rectangular display at the top and a control panel below with buttons for power, volume, and temperature.
- Side View:** Shows the depth of 13/16 (21.3) mm.
- Rear View:** Shows the thickness of 5/8 (15.3) mm and various mounting holes and dimensions: top width 1-3/16 (30), top height 1-5/16 (33.5), top center height 7/8 (23), side height 1-13/16 (45.3), bottom width 3/16 (4.5), bottom height 1/2 (12.5), and bottom center height 3/16 (4.5).

**Table of Specifications:**

Size (H × W × D)	in (mm)	4-3/4 × 4-3/4 × 13/16 (120 × 120 × 21.3)
Weight	oz (g)	7.8 (220)
Cable length (accessory)	ft (m)	33 (10)
Power	V	12


### ● Wiring specifications

Use	Cable size	Wire type	Remarks
Remote controller cable	22AWG (0.33 mm <sup>2</sup> )	Polar 3 core	Use sheathed PVC cable


## ■ Installation

1. Remove the insulation of the remote controller cable.

Unit: in (mm)




2. Insert the flat-blade screwdriver and remove the front case and rear case by twisting it slightly.



3. Install the rear case to the wall, box, etc. with 2 screws (M4 × 16 mm). Fix the 2 screws in either horizontal or vertical position.

### A. When mounting on the box:

Attach the case after leading the cable.




### B. When the cable is along the wall:

- Mount the rear case on the wall.
- Remove knock out hole for cable routing in the front case.

#### **⚠ CAUTION**

When connecting the remote controller cable, take measures to prevent the water or insects coming into the remote controller through the cable, such as to provide the trap or close the hole for cabling with the putty.



4. Configure the DIP switch setting with referring Chapter 14-8. "[Central remote controller](#)" on page 142.

5. Connect the cable to the terminals on the front case. Fix the cable together with the sheath by using the cable tie. Cut off the excess cable tie.



Tightening torque	
Terminal screw	7 to 10 lbf · in (0.8 to 1.2N · m)

### ⚠ CAUTION

- Be careful to avoid breaking the cable by over-tightening the binder.
- When connecting the remote controller cables, do not over-tighten the screws.

6. Attach the front case.

- Adjust the upper part of the front case first, then insert the front case until it clicks.
- When inserting the front case, do not pinch the cable.



### ⚠ CAUTION

Insert the front case firmly. If improperly attached, it will cause the front case to fall off.

## 14. Function settings


To adjust the functions of this product according to the installation environment, various types of function settings are available.

**NOTE:** Incorrect settings can cause a product malfunction.

### 14-1. Indoor unit (setting by jumper wire)

**NOTE:** This setting is necessary only for slim duct type.

#### ■ Component location



#### ■ Jumper wire setting

##### ● Drainage function setting (JM1)

JM1	Function	Factory setting
Connect	Enable	♦
Disconnect	Disable	

##### ● Auto louver grille setting (JM2)

When optional Auto louver grille kit is attached, set this setting to "Valid".

JM2	Function	Factory setting
Connect	Disable	♦
Disconnect	Enable	

##### ● Fan delay setting (JM3)

JM3	Function	Factory setting
Connect	Disable	♦
Disconnect	Enable	


## 14-2. Indoor unit (setting by wireless remote controller)

- The function settings of the control of the indoor unit can be changed by this procedure according to the installation conditions. Incorrect settings can cause the indoor unit malfunction.
- After the power is turned on, perform the “Function setting” according to the installation conditions using the remote controller.
- The settings may be selected between the following two: Function number or Setting number.
- Settings will not be changed if invalid numbers or setting numbers are selected.

### ■ Preparation

Before connecting the power supply of the indoor unit, reconfirm following items:


- Piping air tight test and vacuuming have been performed firmly.
- There is no wiring mistake. Then, connect the power supply of the indoor unit.



## ■ UTY-LNHUM

### ● Button name and function


During address setting mode, indoor unit reject the any operation command from remote controller.




**NOTE:** Actual number of buttons might be different from the figures in following instructions.

### ● Function setting procedure


1. Connect the power supply of the outdoor unit.
2. To enter the function setting mode, while holding down the FAN and the SET TEMP. ▲ buttons, press the RESET button.




3. Press the SET TEMP. ▲ or ▼ buttons to select the custom code that matches the setting with the indoor unit. By selecting the appropriate custom code, the communication between the indoor unit and the wireless remote controller become possible.




4. For confirming the custom code, press the TIMER MODE button to send the code to the indoor unit.




5. Press the MODE button to enter the function setting mode.




6. Select the function number by pressing the ▲ or the ▼ button.  
Each time the MODE button is pressed, it switches between the left digit and the right digit.




7. Proceed to number setting by pressing the FAN button.  
To return to the function number selection, press the FAN button again.




8. Select the setting number by pressing the ▲ or the ▼ button.  
Each time the MODE button is pressed, it switches between the left digit and the right digit.



9. Send the function mode information by pressing the TIMER MODE button once.



10. Send the function setting information by pressing the START/STOP button once.  
2 short beeps will be emitted from the indoor unit when the signal is received correctly. If wrong code is set, no beep sound will be emitted.



**NOTE:** Press START/STOP button within 30 seconds after pressing TIMER MODE button.


Function details: Refer to Chapter 14-5. "[Function details](#)" on page 134.

11. Exit the function setting mode by pressing the RESET button.



To set custom code **b**, **c**, or **d**, perform same procedures for each code.

## ● Setting up each indoor unit



Repeat step from 1. to 11. to set up each indoor unit. If the custom code is other than "R", steps from 1. to 4. and 11. need to be performed.

## ● Resetting the power after setting up all indoor units

### NOTES:

- If the reset is not performed, function cannot be read correctly.
- After all the functions have been set, the circuit breaker needs to be switched off for at least 2 minutes.
  - After the 2 minutes has passed, power can be restored.
  - The set function is stored in the PCB and will remain in memory even when the power of indoor unit is turned off.  
However setting function is effective after disconnecting the power supply and then reconnecting it.
- Record the latest configuration of the indoor unit function setting on a label, and put the label on the unit so it can be used for after-sales service operations.

Once the RESET button is pressed on the remote controller, the operation mode will be set to the AUTO MODE.


Adjust the operation mode to either cooling or heating before starting the operation of the air conditioner.

**NOTE:** If custom code other than "R" is set, the remote control must be set accordingly to the indoor unit setting.


## ● Remote controller custom code setting

Custom code setting of wireless remote controller needs to be same as the setting of the indoor unit. When you change the custom code setting of the wireless remote controller, do as follows:


1. Press the START/STOP button until only the clock is displayed on the remote controller display.




2. Press the MODE button for at least 5 seconds to display the current custom code (initially set to A).



3. Press the SET TEMP. ▲ or the ▼ button to change the custom code between A → b → c → d.



4. Press the MODE button again to return to the clock display. The custom code will be changed.




- If no buttons are pressed within 30 seconds after the custom code is displayed, the system returns to the original clock display. In this case, start again from step 1.
- The air conditioner custom code is set to A prior to shipment.
- The remote controller resets to custom code A when the batteries in the remote controller are replaced. If you use a custom code other than custom code A, reset the custom code after replacing the batteries. If you do not know the air conditioner custom code setting, try each of the custom codes ( $\square \rightarrow \triangle \rightarrow \square \rightarrow \triangle$ ) until you find the code which operates the air conditioner.

## ■ AR-REG1U


### ● Button name and function

During address setting mode, indoor unit reject the any operation command from remote controller.



### ● Function setting procedure

1. Connect the power supply of the outdoor unit.
2. To enter the function setting mode, while holding down the POWERFUL and SET TEMP.  $\wedge$  buttons, press the RESET button.




3. Select the function number by pressing the  $\wedge$  or the  $\vee$  buttons. Each time the MIN. HEAT button is pressed, it switches between the right digit and the left digit.




4. Proceed to the setting number by pressing the POWERFUL button. (To return to the function number selection, press the POWERFUL button again.)




5. Select the function number by pressing the  $\wedge$  or the  $\vee$  button. Each time the MIN. HEAT button is pressed, it switches between the right digit and the left digit.



6. Press the MODE button once to transmit the function mode information.



7. Press the  $\oplus/\ominus$  button once to transmit the function setting information. 2 short beeps will be emitted from the indoor unit when the signal is received correctly. If wrong code is set, no beep sound will be emitted.




**NOTE:** Press  $\oplus/\ominus$  button within 30 seconds after pressing MODE button.

For the function details, refer to Chapter 14-5. "[Function details](#)" on page 134.

8. Exit the function setting mode by pressing the RESET button.



## ● Setting up each indoor unit



Repeat step from 1. to 8. to set up each indoor unit. If the custom code is other than "R", steps from 1. to 2. and 8. need to be performed.

## ● Resetting the power after setting up all indoor units

### NOTES:

- If the reset is not performed, function cannot be read correctly.
- After all the functions have been set, the circuit breaker needs to be switched off for at least 2 minutes.
  - After the 2 minutes has passed, power can be restored.
  - The set function is stored in the PCB and will remain in memory even when the power of indoor unit is turned off.  
However setting function is effective after disconnecting the power supply and then reconnecting it.
- Record the latest configuration of the indoor unit function setting on a label, and put the label on the unit so it can be used for after-sales service operations.

Once the RESET button is pressed on the remote controller, the operation mode will be set to the AUTO MODE.

Adjust the operation mode to either cooling or heating before starting the operation of the air conditioner.

**NOTE:** If custom code other than "R" is set, the remote control must be set accordingly to the indoor unit setting.

## ● Remote controller custom code setting

Custom code setting of wireless remote controller needs to be same as the setting of the indoor unit. When you change the custom code setting of the wireless remote controller, do as follows:

1. Press the START/STOP button until only the clock is displayed on the display.



2. Press the MODE button for at least 5 seconds to display the current custom code (initially set to A).



3. Press the SET TEMP. "↑" or the "↓" button to change the custom code between  $\text{A} \rightarrow \text{b} \rightarrow \text{c} \rightarrow \text{d}$ .




4. Press the MODE button again to return to the clock display. The custom code will be changed.



- If no buttons are pressed within 30 seconds after the custom code is displayed, the system returns to the original clock display. In this case, start again from step 1.
- The air conditioner custom code is set to A prior to shipment.
- If you do not know the air conditioner custom code setting, try each of the custom codes ( $\text{A} \rightarrow \text{b} \rightarrow \text{c} \rightarrow \text{d}$ ) until you find the code which operates the air conditioner.

## ● Remote controller temperature unit

To change the displayed temperature unit, press the "°C/°F" switching button to select the preferred temperature unit. (Factory setting is set to "°F").:




## 14-3. Indoor unit (setting by wired remote controller)

- The function settings of the control of the indoor unit can be changed by this procedure according to the installation conditions. Incorrect settings can cause the indoor unit malfunction.
- After the power is turned on, perform the “Function setting” according to the installation conditions using the remote controller.
- The settings may be selected between the following two: Function number or Setting number.
- Settings will not be changed if invalid numbers or setting numbers are selected.
- This function cannot be used on the secondary units.

### ■ Preparation

Before connecting the power supply of the indoor unit, reconfirm following items:


- Piping air tight test and vacuuming have been performed firmly.
- There is no wiring mistake. Then, connect the power supply of the indoor unit.



## ■ UTY-RNNUM

### ● Button name and function


During address setting mode, indoor unit reject the any operation command from remote controller.




### ● Function setting procedure

1. Connect the power supply of the outdoor unit.
2. Switch to the function setting mode.


To enter the function setting mode, hold down the 3 buttons of SET TEMP. V, SET TEMP. A, and FAN at the same time for 5 seconds or longer.



3. Select the function number by pressing the SET TIME < or the SET TIME > button.




4. Select the setting number by pressing the SET TEMP. A or the SET TEMP. V button.  
The display flashes during setting number selection.




5. Confirm the setting by pressing the TIMER SET button.

The data will be transferred to the indoor unit.



Function details: Refer to Chapter 14-5. "Function details" on page 134.

6. Exit the function setting mode by holding 3 buttons of SET TEMP. ▼, SET TEMP. ▲ and FAN at the same time.



If no button is pressed within 60 seconds after buttons mentioned above are pressed, it will automatically exit the function setting mode.

If you exit the function setting mode unintentionally during setting, enter the mode again according to the procedure in step 2.

## ● Setting up each indoor unit

Repeat the procedures from step 1 to 6, and set up the indoor units requiring function setting.

## ● Resetting the power after setting up function of all indoor units

### NOTES:

- If the reset is not performed, function cannot be read correctly.
- After all the functions have been set, the circuit breaker needs to be switched off for at least 2 minutes.
  - After the 2 minutes has passed, power can be restored.
  - The set function is stored in the PCB and will remain in memory even when the power of indoor unit is turned off.  
However setting function is effective after disconnecting the power supply and then reconnecting it.
- Record the latest configuration of the indoor unit function setting on a label, and put the label on the unit so it can be used for after-sales service operations.


## 14-4. Indoor unit (setting by simple remote controller)

- The function settings of the control of the indoor unit can be changed by this procedure according to the installation conditions. Incorrect settings can cause the indoor unit malfunction.
- After the power is turned on, perform the “Function setting” according to the installation conditions using the remote controller.
- The settings may be selected between the following two: Function number or Setting number.
- Settings will not be changed if invalid numbers or setting numbers are selected.
- This function cannot be used on the secondary units.

### ■ Preparation

Before connecting the power supply of the indoor unit, reconfirm following items:


- Piping air tight test and vacuuming have been performed firmly.
- There is no wiring mistake. Then, connect the power supply of the indoor unit.



## ■ UTY-RSNUM

### ● Button name and function


During address setting mode, indoor unit reject the any operation command from remote controller.



### ● Function setting procedure


1. Connect the power supply of the outdoor unit.
2. Switch to the function setting mode.

To enter the function setting mode, hold down the 3 buttons of SET TEMP. ▲, SET TEMP. ▼ and FAN at the same time for 5 seconds or longer.




3. Press the FAN button.

The Function number indicator flashes. Then, press either the SET TEMP. ▲ button or the SET TEMP. ▼ button to set up the function number.




4. Select the setting number by pressing the SET TEMP. ▲ or SET TEMP. ▼ button.  
The setting number indicator flashes during setting number selection.



Example) Function number : 30, Setting number : 01


5. Confirm the setting by pressing the TIMER SET button.  
The data will be transferred to the indoor unit.



- Data is not set up on the indoor unit correctly (-- is displayed.)
  - Set up the data again according to the procedure in step 3, 4 above.
- Data is correctly set up on the indoor unit.

Function details: Refer to Chapter 14-5. "Function details" on page 134.

6. Exit the function setting mode by pressing the 3 buttons of SET TEMP. ▲, SET TEMP. ▼, and FAN at the same time for 5 seconds or longer.  
After exiting the function setting mode, the display returns to the normal mode.



If no button is pressed within 60 seconds after buttons mentioned above are pressed, it will automatically exit the function setting mode.

If you exit the function setting mode unintentionally during setting, enter the mode again according to the procedure in step 2.

## ● Setting up each indoor unit

Repeat the procedures from step 1 to 6, and set up the indoor units requiring function setting.

## ● Resetting the power after setting up function of all indoor units

### NOTES:

- If the reset is not performed, function cannot be read correctly.
- After all the functions have been set, the circuit breaker needs to be switched off for at least 2 minutes.
  - After the 2 minutes has passed, power can be restored.
  - The set function is stored in the PCB and will remain in memory even when the power of indoor unit is turned off.  
However setting function is effective after disconnecting the power supply and then reconnecting it.
- Record the latest configuration of the indoor unit function setting on a label, and put the label on the unit so it can be used for after-sales service operations.

## 14-5. Function details

### ■ Contents of function setting

Each function setting listed in this section is adjustable in accordance with the installation environment.

**NOTE:** Setting will not be changed if invalid numbers or setting values are selected.

### ● Function setting list

	Functions	Compact cassette	Slim duct	Wall mounted	Floor
1)	Filter sign	●	●	●	●
2)	Ceiling height	●	—	—	—
3)	Outlet directions	●	—	—	—
4)	Vertical airflow direction range control	—	—	—	●
5)	Static pressure	—	●	—	—
6)	Room temperature control for indoor unit sensor	●	●	●	●
7)	Auto restart	●	●	●	●
8)	Room temperature sensor switching	●	●	●	●
9)	Remote controller custom code	●	●	●	●
10)	External input control	●	●	●	●
11)	Room temperature sensor switching (Aux.)	●	●	●	●
12)	Indoor unit fan control for energy saving for cooling	—	—	ASU7-15RL F1	●
13)	Room temperature control for wired remote controller sensor	●	●	●	●
14)	Heat insulation condition (building insulation)	●	●	●	●

#### 1) Filter sign

Select appropriate intervals for displaying the filter sign on the indoor unit according to the estimated amount of dust in the air of the room.

If the indication is not required, select "No indication" (03).

Function number	Setting value	Setting description	Factory setting
11	00	Standard	
	01	Long interval	
	02	Short interval	
	03	No indication	♦

Intervals will differ depending on the indoor unit type as follows.

Setting description	Compact cassette	Slim duct	Wall mounted	Floor
Standard	2,500 hours		400 hours	
Long interval	4,400 hours		1,000 hours	
Short interval	1,250 hours		200 hours	

## 2) Ceiling height

Select the appropriate ceiling height according to the place of installation.

Function number	Setting value	Setting description	Factory setting
20	00	Standard	◆
	01	High ceiling	

For the specific height for each setting value, refer to "Installation space" in Chapter 3. "[Dimensions](#)" on page 12.

### In case of cassette type models:

The ceiling height values are for the 4-way outlet. Do not change this setting in the 3-way outlet mode.

7000, 9000 Btu/h models cannot be installed in high ceilings. Do not change this setting.

## 3) Outlet directions

Select the appropriate number of outlet directions according to the installation conditions.

Function number	Setting value	Setting description	Factory setting
22	00	4-way	◆
	01	3-way	

## 4) Vertical airflow direction range control

In a concealed installation, change the setting to "Fixed" (02) to restrict the movement of the upper air outlet so that the airflow is only towards the horizontal direction.

Function number	Setting value	Setting description	Factory setting
23	00	Standard	◆
	01	(Setting prohibited)	
	02	Fixed (Concealed)	

## 5) Static pressure

Select the appropriate static pressure according to the installation conditions.

Function number	Setting value	Setting description	Factory setting
26	00	0 in.WG (0 Pa)	
	01	0.04 in.WG (10 Pa)	
	02	0.08 in.WG (20 Pa)	
	03	0.12 in.WG (30 Pa)	
	04	0.16 in.WG (40 Pa)	
	05	0.20 in.WG (50 Pa)	
	06	0.24 in.WG (60 Pa)	
	07	0.28 in.WG (70 Pa)	
	08	0.32 in.WG (80 Pa)	
	09	0.36 in.WG (90 Pa)	
	31	Standard (0.10 in.WG [25 Pa])	◆

**NOTE:** Range of static pressure is different by model.

Model name	Range of static pressure
7-18 type	0 to 0.36 in.WG (0 to 90 Pa)
24 type	0 to 0.20 in.WG (0 to 50 Pa)

## 6) Room temperature control for indoor unit sensor

**NOTE:** Before performing this setting, refer to Function 95.

Depending on the installed environment, correction of the room temperature sensor may be required. Select the appropriate control setting according to the installed environment.

The temperature correction values show the difference from the Standard setting "00" (manufacturer's recommended value).

\*When Function 95-01 (High insulation) is set, the Standard setting "00" will be the same as "No correction 0.0 °F (0.0 °C)" (01).

Function number		Setting value	Setting description	Factory setting
30 (For cooling)	31 (For heating)	00	Standard setting*	◆
		01	No correction 0.0 °F (0.0 °C)	
		02	-1 °F (-0.5 °C)	More cooling Less heating
		03	-2 °F (-1.0 °C)	
		04	-3 °F (-1.5 °C)	
		05	-4 °F (-2.0 °C)	
		06	-5 °F (-2.5 °C)	
		07	-6 °F (-3.0 °C)	
		08	-7 °F (-3.5 °C)	
		09	-8 °F (-4.0 °C)	
		10	+1 °F (+0.5 °C)	Less cooling More heating
		11	+2 °F (+1.0 °C)	
		12	+3 °F (+1.5 °C)	
		13	+4 °F (+2.0 °C)	
		14	+5 °F (+2.5 °C)	
		15	+6 °F (+3.0 °C)	
		16	+7 °F (+3.5 °C)	
		17	+8 °F (+4.0 °C)	

### In case of Slim duct type and Floor/Ceiling type models:

In wall-concealed installations or floor installations, select "01".

## 7) Auto restart

Enables or disables automatic restart after a power interruption.

Function number	Setting value	Setting description	Factory setting
40	00	Enable	◆
	01	Disable	

**NOTE:** Auto restart is an emergency function such as for power outage etc. Do not attempt to use this function in normal operation. Be sure to operate the unit by remote controller or external device.

## 8) Room temperature sensor switching

(Only for wired remote controller)

When using the wired remote controller temperature sensor, change the setting to "Both" (01).

Function number	Setting value	Setting description	Factory setting
42	00	Indoor unit	◆
	01	Both	

00: Sensor on the indoor unit is active.

01: Sensors on both indoor unit and wired remote controller are active.

**NOTE:** Remote controller sensor must be turned on by using the remote controller.

**9) Remote controller custom code**

(Only for wireless remote controller)

The indoor unit custom code can be changed. Select the appropriate custom code.

Function number	Setting value	Setting description	Factory setting
44	00	A	◆
	01	B	
	02	C	
	03	D	

**10) External input control**

"Operation/Stop" mode or "Forced stop" mode can be selected.

Function number	Setting value	Setting description	Factory setting
46	00	Operation/Stop mode	◆
	01	(Setting prohibited)	
	02	Forced stop mode	

**11) Room temperature sensor switching (Aux.)**

To use the temperature sensor on the wired remote controller only, change the setting to "Wired remote controller" (01).

This function will only work if the function setting 42 is set at "Both" (01).

When the setting value is set to "Both" (00), more suitable control of the room temperature is possible by setting function setting 30 and 31 too.

Function number	Setting value	Setting description	Factory setting
48	00	Both	◆
	01	Wired remote controller	◆*

\*: For Slim duct only.

**12) Indoor unit fan control for energy saving for cooling**

Enables or disables the power-saving function by controlling the indoor unit fan rotation when the outdoor unit is stopped during cooling operation.

Function number	Setting value	Setting description	Factory setting
49	00	Disable	◆
	01	Enable	

00: When the outdoor unit is stopped, the indoor unit fan operates continuously following the setting on the remote controller.

01: When the outdoor unit is stopped, the indoor unit fan operates intermittently at a very low speed.

### 13) Room temperature control for wired remote controller sensor

**NOTE:** Before performing this setting, refer to Function 95.

Depending on the installed environment, correction of the room temperature sensor may be required. Select the appropriate control setting according to the installed environment.

To change this setting, set Function 42 to "Both" (01).

Ensure that the thermo sensor icon is displayed on the remote controller screen.

Function number	Setting value	Setting description	Factory setting			
92 (For cooling)	93 (For heating)	00	No correction 0.0 °F (0.0 °C)			
		01	No correction 0.0 °F (0.0 °C)			
		02	-1 °F (-0.5 °C)			
		03	-2 °F (-1.0 °C)			
		04	-3 °F (-1.5 °C)			
		05	-4 °F (-2.0 °C)			
		06	-5 °F (-2.5 °C)			
		07	-6 °F (-3.0 °C)			
		08	-7 °F (-3.5 °C)			
		09	-8 °F (-4.0 °C)			
		10	+1 °F (+0.5 °C)			
		11	+2 °F (+1.0 °C)			
		12	+3 °F (+1.5 °C)			
		13	+4 °F (+2.0 °C)			
		14	+5 °F (+2.5 °C)			
		15	+6 °F (+3.0 °C)			
		16	+7 °F (+3.5 °C)			
		17	+8 °F (+4.0 °C)			
		More cooling Less heating	◆			

### 14) Heat insulation condition (building insulation)

Heat insulation conditions differ according to the installed environment.

"Standard insulation" (00) allows system to rapidly respond to the cooling or heating load changes.

"High insulation" (01) is when the heat insulation structure of the building is high and does not require system to rapidly respond to cooling or heating load changes.

When "High insulation" (01) is selected:

- Overheating (overcooling) is prevented at the start-up.
- All room-temperature control settings (Function 30, 31, 92, and 93) will reset to "No correction 0.0 °F (0.0 °C)".

Function number	Setting value	Setting description	Factory setting
95	00	Standard insulation	◆
	01	High insulation	


**NOTE:** When changing Function 95, perform this setting before other room-temperature control settings (Function 30, 31, 92, and 93). If Function 95 is not set first, room-temperature control settings (Function 30, 31, 92, and 93) will be reset and you must re-do them again.

## 14-6. Wired remote controller

DIP switch 1	SW1	Prohibited
	SW2	Dual remote controller setting
	SW3	Prohibited
	SW4	°F/°C switch
	SW5	Prohibited
	SW6	Memory backup setting

\* Do not use DIP switch 2.

### ■ Switch location




### ■ DIP switch 1 setting

#### ● SW2: Dual remote controller setting

Set the remote controller SW2 according to the following table.

Number of remote controller	Primary unit	Secondary unit	Factory setting
	SW2	SW2	
1 (Normal)	OFF	—	♦
2 (Dual)	OFF	ON	



#### ● SW4: Switching temperature unit °F / °C

Displayed temperature unit can be switched between Fahrenheit (°F) and Celsius (°C).

SW4	Fahrenheit (°F) / Celsius (°C)	Factory setting
OFF	°C	
ON	°F	♦

## ● SW6: Memory backup setting

Set to "ON" to use batteries for the memory backup.


When batteries are not used, all of settings stored in memory will be deleted if there is a power failure.

SW6	Memory backup	Factory setting
OFF	Disable	♦
ON	Enable	

## 14-7. Simple remote controller

DIP switch	SW1	Prohibited
	SW2	Dual remote controller setting
	SW3	°F/°C switch
	SW4	Prohibited
	SW5	Prohibited
	SW6	Prohibited

### ■ Switch location




### ■ DIP switch setting

#### ● SW2: Dual remote controller setting

Set the remote controller SW2 according to the following table.

Number of remote controller	Primary unit	Secondary unit	Factory setting
	SW2	SW2	
1 (Normal)	OFF	—	◆
2 (Dual)	OFF	ON	



#### ● SW3: Switching temperature unit °F / °C


Displayed temperature unit can be switched between Fahrenheit (°F) and Celsius (°C).

SW3	Fahrenheit (°F) / Celsius (°C)	Factory setting
OFF	°C	
ON	°F	◆

## 14-8. Central remote controller

DIP switch 1	SW1	Memory backup setting
	SW2	Prohibited
	SW3	Prohibited
	SW4	Prohibited
	SW5	Prohibited
	SW6	Prohibited

### ■ Switch location



### ■ DIP switch setting

#### ● SW1: Memory backup setting

Set to "ON" to use batteries for the memory backup.





When batteries are not used, all of settings stored in memory will be deleted if there is a power failure.

SW1		Factory setting
Off	Invalidity	♦
On	Validity	

## 15. Accessories



### 15-1. Compact cassette type

■ Models: AUU7RLF, AUU9RLF, AUU12RLF, and AUU18RLF

Part name	Exterior	Q'ty	Part name	Exterior	Q'ty
Operating manual		1	Drain hose		1
Installation manual		1	Hose band		1
Coupler heat insulation (Large)		1	Drain hose insulation		1
Coupler heat insulation (Small)		1	Remote controller		1
M10 nut A (with flange)		4	Remote controller cable		1
M10 nut B (with spring lock washer)		4	Tapping screw		2
Template (Carton top)		1			

### 15-2. Slim duct type




■ Models: ARU7RLF, ARU9RLF, ARU12RLF, ARU18RLF, and ARU24RLF

Part name	Exterior	Q'ty	Part name	Exterior	Q'ty
Operating manual		1	Cable tie (large)		4
Installation manual		1	Cable tie (small)		3
Installation template		1	Drain hose		1

Part name	Exterior	Q'ty	Part name	Exterior	Q'ty
Washer		8	Hose band		1
Coupler heat insulation (large)		1	Drain hose insulation B		1
Coupler heat insulation (small)		1	Remote controller		1
Filter (Small) (For 7/9/12/24)		2	Remote controller cable		1
Filter (Big) (For 18/24)		2 (18)	Tapping screw		2
		1 (24)			

## 15-3. Wall mounted type

■ Models: ASU7RLF1, ASU9RLF1, ASU12RLF1, and ASU15RLF1


Part name	Exterior	Q'ty	Part name	Exterior	Q'ty
Operating manual		1	Cloth tape		1
Installation manual		1	Tapping screw (large)		5
Wall hook bracket		1	Tapping screw (small)		2
Remote controller		1	Air cleaning filter		2
Battery		2	Filter holder		2
Remote controller holder		1	Seal A • It is necessary when using 15 model. • It is used when the diameter of gas pipe is Ø1/2 in (12.70 mm) or more.		1

## ■ Models: ASU18RLF and ASU24RLF

Part name	Exterior	Q'ty	Part name	Exterior	Q'ty
Operating manual		1	Drain hose insulation		1
Installation manual		1	Cloth tape		1
Wall hook bracket		1	Tapping screw (large)		8
Remote controller		1	Tapping screw (small)		2
Battery		2	Air cleaning filter		2
Remote controller holder		1	Air cleaning filter frame		2

## 15-4. Floor type

### ■ Models: AGU9RLF, AGU12RLF, and AGU15RLF

Part name	Exterior	Q'ty	Part name	Exterior	Q'ty
Operating manual		1	Cable tie		1
Installation manual		1	Cloth tape		1
Wall hook bracket		1	Tapping screw (large)		9
Remote controller		1	Tapping screw (small)		2
Battery		2	Air cleaning filter		2
Remote controller holder		1			

## 16. Optional parts

### 16-1. Controllers


#### ■ Lineup

Indoor unit type		Type			
		Wired remote controller	Wireless remote controller	IR receiver unit	Simple remote controller
		UTY-RNNUM	UTY-LNHUM	AR-REG1U	UTY-LRHUM
Compact cassette	●	○	—	—	○
Slim duct	●	—	—	○	○
Wall mounted	ASU7RLF1 ASU9RLF1 ASU12RLF1 ASU15RLF1	○*1	—	●	—
	ASU18RLF ASU24RLF	○	●	—	—
Floor		○	—	●	—

●: Accessory, ○: Optional, —: Not applicable

- \*1: Optional Communication kit (UTY-XCBXZ2) is necessary for the installation.
- \*2: Optional Communication kit (UTY-XCBXZ1) is necessary for the installation.
- \*3: Optional Communication kit (UTY-TWBXF) is necessary for the installation.

## ■ Parts


Wired remote controller	Simple remote controller	IR receiver kit with Wireless remote controller
		
UTY-RNNUM	UTY-RSNUM	UTY-LRHUM
<b>Wireless remote controller</b>		
		
UTY-LNHUM	AR-REG1U	

## 16-2. Cassette grille

### ■ Lineup

Indoor unit type	Model	Remarks
Compact cassette	UTG-CCGF	Standard type
	UTG-CCGFG	Grid type

### ■ Parts



## 16-3. Others

### ■ Lineup




Indoor unit type		Type				
		Air outlet shutter plate	Insulation kit for high humidity	Fresh air intake kit	External control set	External connect kit
		UTR-YDZB	UTZ-KXGC	UTZ-VXAA	UTD-ECS5A	UTY-XWZX
Compact cassette	○	○	○	—	○	—
Slim duct	—	—	—	○	—	—
Wall mounted	ASU7RLF1 ASU9RLF1 ASU12RLF1 ASU15RLF1 ASU18RLF ASU24RLF	— — — — — —	— — — — — —	— — — — — —	— — — — ○ —	— — ○*1 —
Floor	—	—	—	—	—	○

Indoor unit type		Type		
		Remote sensor unit	Auto louver grille kit	Communication kit
		UTY-XSZX	UTD-GXSA-W UTD-GXSB-W UTD-GXSC-W UTD-GXTA-W UTD-GXTB-W UTD-GXTC-W	UTY-XCBXZ2
Compact cassette	—	—	—	—
Slim duct	○	○	○	—
Wall mounted	ASU7RLF1 ASU9RLF1 ASU12RLF1 ASU15RLF1 ASU18RLF ASU24RLF	— — — — — —	— — — — — —	○ — —
Floor	—	—	—	—

●: Accessory, ○: Optional, —: Not applicable

\*1: Optional Communication kit (UTY-XCBXZ2) is necessary for the installation.

## ■ Parts

<b>Air outlet shutter plate</b> <b>Model: UTR-YDZB</b>  For compact cassette type	<b>Insulation kit for high humidity</b> <b>Model: UTZ-KXGC</b>  For compact cassette type
<b>Fresh air intake kit</b> <b>Model: UTZ-VXAA</b>  For compact cassette type	<b>External control set</b> <b>Model: UTD-ECS5A</b>  For slim duct type
<b>External connect kit</b> <b>Model: UTY-XWZX</b>  For compact cassette type and wall mounted type (ASU18RLF and ASU24RLF)	<b>External connect kit</b> <b>Model: UTY-XWZXZ5</b>  For wall mounted type (ASU7RLF1, ASU9RLF1, ASU12RLF1, and ASU15RLF1) and floor type
<b>Auto louver grille kit</b> <b>Models:</b> <b>UTD-GXSA-W<sup>*1</sup></b> <b>UTD-GXSB-W<sup>*2</sup></b> <b>UTD-GXSC-W<sup>*3</sup></b> <b>UTD-GXTA-W<sup>*1</sup></b> <b>UTD-GXTB-W<sup>*2</sup></b> <b>UTD-GXTC-W<sup>*3</sup></b>  *1 For slim duct (7-12 models) *2 For slim duct (18 model) *3 For slim duct (24 model)	<b>Remote sensor unit</b> <b>Model: UTY-XSZX</b>  For slim duct type
<b>Communication kit</b> <b>Model: UTY-XCBXZ2</b>  For wall mounted type (ASU7RLF, ASU9RLF, and ASU12RLF)	<b>Communication kit</b> <b>Model: UTY-XCBXZ2</b>  For wall mounted type (ASU7RLF1, ASU9RLF1, ASU12RLF1, and ASU15RLF1)

## 17. Indoor unit installation precautions

**NOTE:** The information listed below are general precautions.

Some models also include items that do not apply.


### 17-1. Places where prohibited for use

- Places where there is a danger of combustible gas leakage.
- Places where sulfur gas, chlorine gas, acid, alkali, or other matter which effects equipment is generated.
- Places where there is a lot of oil splash and steam such as kitchen or machinery room.
- Places where machinery which generates high frequencies is used.
- Ocean beaches and other areas where there is a lot of salt.
- Places where carbon fibers or any kind of powder suspended in the air.
- Inside of vehicles, ships, and other conveyances.
- Places where voltage fluctuations are large such as a factory.

## 17-2. Points to remember when installing

- The product shall be installed at a place which can withstand the weight and vibration of the indoor.
- To allow maintenance after refrigerant piping, drain piping, and electric wiring connection and installation, provide an installation service space and an inspection port, as required.  
\*Installation service space is shown on "Dimensions" on page 12.
- Be careful when installing the unit at the following places.

Condition	Contents	Countermeasures (Reference)
When the ceiling is high.	If the indoor unit is installed where the installation height given in the installation manual is exceeded, the temperature difference between the floor and ceiling of the room will be large and the heating effect will be poor. Moreover, even if the indoor unit is installed within the installation height, a similar phenomena will occur when installed in a room in which the doors are opened and closed frequently and hot air circulation is obstructed by furniture such as desks or chairs.	<ol style="list-style-type: none"> <li>Switch the setting to the high ceiling mode.</li> <li>Install a circulator.</li> <li>Arrange the furniture in the room so that it does not obstruct the hot air.</li> </ol>
When lower level directly contacts the outside air.	When the lower level of the room is a semi-open space such as warehouse or parking lot the surface temperature of the flooring will become low and the radiation of cold from the floor will increase. In this case, even if the room temperature is suitable, you may feel the foot level is cold.	
When the airflow distribution is poor.	When an indoor unit is installed in a position where the outlet airflow will directly contact people, a draft may be felt. In addition, when there are obstructions in the path of the intake and outlet airflow, the air distribution may become extremely bad.	<ol style="list-style-type: none"> <li>Adjust the louver fins or take other measures matched to the site.</li> <li>Change the indoor unit outlet.</li> </ol>
When inside the ceiling is high temperature and high humidity.	When the indoor unit is installed where the inside of the ceiling is 30 °C (86 °F) RH80% or greater, the dew point temperature of the outer perimeter may become higher than the cabinet surface temperature and moisture will condense on the surface of the cabinet and water drops may fall inside the room. →Refer to Fig. A. In addition, the humidity may vary considerably the same as when the inside of the ceiling is close to hermetically sealed and used as the outside air intake path.	<ol style="list-style-type: none"> <li>Add heat insulating material to the outside of the indoor unit cabinet. *Regarding the cassette type, use of optional High humidity correspondence kit is recommended.</li> <li>Strengthen the heat insulating material of the refrigerant piping and drain piping too. →Refer to Fig. B.</li> <li>When the humidity inside the ceiling changes considerably, install a ventilation port.</li> </ol>



Dry bulb temperature 30 °C (86 °F)

Fig. A


**Work method when reinforcing the heat insulation of on-site piping**

Fig. B

Condition	Contents	Countermeasures (Reference)
When using an external duct.	When using an external duct to take in new fresh air, etc., condensation may form on the surface of the duct due to the effect of the outside air temperature and the humidity inside the ceiling.	Always perform heat insulation processing. (Heat insulating material: Glass wool 25-mm [1-in] thick or more.)
When the remote controller installation site is bad.	If the cold or warm air blown out from the air conditioner directly contacts the thermostat section of the remote controller, the outlet temperature of the air conditioner may be sensed and room temperature control will be different from the room temperature, and "not cooled" or "not heated" or other trouble may occur. In addition, there is the possibility that the same kind of trouble may also occur when the remote controller is effected by direct sunlight.	1. Install the remote controller where it will not be directly exposed to the cold or hot air. 2. Install the remote controller where it will not be directly exposed to sunlight or strong lighting.
When installation environment is quiet.	When the wall mounted type was installed in a bedroom, living room, or other quiet place, the sound of the refrigerant flow may be sensed as noise and must be taken into account.	1. Plan installation of a model with external expansion valve. 2. Plan installation of a branch box farther from indoor unit. 3. Plan installation using another air conditioner.
When installing duct type in ceiling chamber system.	In the case of the ceiling chamber system (duct is not installed at indoor unit inlet side and room air is sucked into the indoor unit through the inside of the ceiling), the thermistor inside the indoor unit may not correctly detect the room temperature. <ul style="list-style-type: none"> <li>• Heating operation: Room is not heated because the indoor unit is easily turned off by the thermostat.</li> <li>• Cooling operation: Room is too cold because the indoor unit is difficult to turn off by the thermostat.</li> </ul>	Replace the indoor unit thermistor with optional Remote sensor unit, and install the sensor where the room temperature can be correctly detected.
When the outlet air is sucked in at duct type.	Cooling operation does not cool the room and heating operation does not heat the room because the short circuited indoor unit is not turned on by the thermostat.	1. Reconsider the ventilation port construction. 2. Replace the indoor unit thermistor with optional Remote sensor unit, and install the sensor where the room temperature can be correctly detected.
When using the wireless remote controller.	Signals may not be received when using it in a room illuminated by an inverter fluorescent lamp.	Turn on the fluorescent lamp and check if the indoor unit receives the signals from the remote controller. If the indoor unit does not receive the signals, consult an authorized service personnel.
When installing the inverter type.	It may generate noise in TV sets, stereos and PCs.	The inverter type should be installed at a sufficient distance from these equipments.



## **Part 2. OUTDOOR UNIT**

---

**5 ROOMS TYPE:  
AOU45RLXFZ**

# 1. Specifications


Type	Inverter heat pump				
Model name	AOU45RLXFZ				
Power source	1Ø 208/230 V 60 Hz				
Available voltage range	187—264V				
Connectable indoor unit	Number	2 to 5			
	Total capacity range	34,000 to 54,000 Btu/h			
Combination of indoor unit		Non-Duct ASU9RLF1 x 5	Duct ARU9RLF x 5	Mix	
Capacity	Cooling	Rated Btu/h	45,000		
		Rated kW	13.2		
		Min. - Max. Btu/h	12,000—48,000		
	Heating	Rated kW	3.5—14.0		
		Rated Btu/h	48,000	46,000	47,000
		Min. - Max. kW	12,000—54,000		
Input power	Cooling	Rated kW	3.5—15.8		
		Max.	4.28		
		Rated	4.59		
	Heating	Max.	4.77	4.86	4.82
		Rated	3.88	3.89	3.90
		Max.	4.32	4.41	4.37
Current	Cooling	Rated A	18.8	20.1	19.4
	Heating		17.0	17.0	17.1
EER	Cooling	Rated Btu/W	10.5	9.8	10.2
SEER *1	Cooling		-	19.7	18.7
COP	Heating	Rated W/W	3.60	3.46	3.53
HSPF *1	Heating		-	10.3	9.8
Starting current		A		20.1	
Maximum operating current *2		A		23.8	
Fan	Type x Q'ty		Propeller x 1		
	Airflow rate	Cooling	2,472 (4,200)		
		Heating	2,472 (4,200)		
	Motor	Type x Quantity	DC motor x 1		
		Output W	111		
	Sound pressure level	Cooling	53		
		Heating	55		
Heat exchanger	Dimension (H x W x D)	in (mm)	38-1/16 x 36-5/16 x 2-3/16 (966 x 922 x 55)		
	Fin pitch	FPI	1.45		
	Rows x Stages		2 x 38		
		Pipe type (Material)	Grooved H-pin (Copper)		
		Fin Type (Material)	Corrugate (Aluminum)		
	Compressor	Surface treatment	Corrosion resistance (Blue Fin)		
		Type x Quantity	DC twin rotary x 1		
		Motor output W	2,100		
Refrigerant	Type		R410A		
	Charge	lb (g)	8 lb 13 oz (4,000)		
Refrigerant oil	Type		RB68		
	Amount	in³ (cm³)	70.1(1,150)		
Enclosure	Material		Painted galvanized steel		
	Color		Beige (Approximate color of Munsell 10YR 7.5/1.0 NN)		
Dimensions	Net (H x W x D)	in (mm)	39-5/16 x 38-3/16 x 14-9/16 (998 x 970 x 370)		
	Gross		45-3/4 x 45-1/4 x 18-13/16 (1,162 x 1,150 x 478)		
Weight	Net	lb (kg)	205 (93)		
	Gross		229 (104)		
Connection pipe	Size	Liquid	in (mm)	$\varnothing 1/4$ ( $\varnothing 6.35$ ) x 5	
		Gas		$\varnothing 3/8$ ( $\varnothing 9.52$ ) x 3 + $\varnothing 1/2$ ( $\varnothing 12.70$ ) x 2	
	Method			Flare	
	Pre-charge length (Total)			164 (50)	
	Max. length (Total)			262 (80)	
	Max. length (Each)			82 (25)	
	Min. length (Total)			49 (15)	
	Min. length (Each)			16 (5)	
	Max. height difference between outdoor unit and each Indoor Units.			49 (15)	
	Max. height difference between indoor units.		ft (m)	33 (10)	
Operation range	Cooling	°F (°C)		14 to 115 (-10 to 46)	
	Heating			5 to 75 (-15 to 24)	

## NOTES:

- Specifications are based on the following conditions:
  - Power source of specifications : 230 V
  - Pipe length : 24.6 ft (7.5 m), Height difference : 0 ft (0 m) [Outdoor unit - Indoor unit]
  - Cooling: Indoor temperature of 80 °FDB (26.7 °CDB) / 67 °FWB (19.4 °CWB), and outdoor temperature of 95 °FDB (35°CDB) / 75 °FWB (23.9 °CWB).
  - Heating: Indoor temperature of 70 °FDB (21.1 °CDB) / 60 °FWB (15.6 °CWB), and outdoor temperature of 47 °FDB (8.3 °CDB) / 43 °FWB (6.1 °CWB).
  - \*1: Test conditions are based on AHRI 210 / 240.
  - \*2: The maximum current is the maximum value when the operated within the operation range.
- For other combination, refer to the combination table.
- The protective function might work when using it outside the operation range.

## 2. Dimensions

### 2-1. Model: AOU45RLXFZ



### 3. Installation space

#### 3-1. Model: AOU45RLXFZ

##### ■ Space requirement


Provide sufficient installation space for product safety.

###### ● Single outdoor unit installation


- When the upper space is open:

Unit: in (mm)


When there are obstacles at the rear only.




When there are obstacles at the rear and sides.



When there are obstacles at the front only.




When there are obstacles at the front and rear.




- When there is an obstruction in the upper space:

Unit: in (mm)

When there are obstacles at the rear and above.



When there are obstacles at the rear, sides, and above.




## ● Multiple outdoor unit installation


- When the upper space is open:

Unit: in (mm)


When there are obstacles at the rear only.



When there are obstacles at the front only.




When there are obstacles at the front and rear.



- When there is an obstruction in the upper space:

Unit: in (mm)


When there are obstacles at the rear and above.





## ● Outdoor unit installation in multi-row

Unit: in (mm)

Single parallel unit arrangement




Multiple parallel unit arrangement

**NOTES:**

- If the space is larger than stated above, the condition will be the same as when there is no obstacle.
- Height above the floor level should be 2 in (50 mm) or more.
- When installing the outdoor unit, be sure to open the front and left side to obtain better operation efficiency.


**⚠ CAUTION**

- Do not install the outdoor unit in two-stage where the drain water could freeze. Otherwise the drainage from the upper unit may form ice and cause a malfunction of the lower unit.
- When the outdoor temperature is 32 °F (0 °C) or less, do not use the accessory drain pipe and drain cap. If the drain pipe and drain cap are used, the drain water in the pipe may freeze in extremely cold climate. (For reverse cycle model only.)
- In area with heavy snowfall, if the inlet and outlet of the outdoor unit is blocked with snow, it might become difficult to get warm, and it is likely to cause product malfunction. Construct a canopy and a pedestal, or place the unit on a high stand that is locally installed.



## 4. Refrigerant circuit

### 4-1. Model: AOU45RLXFZ



$T_{He}$  : THERMISTOR (DISCHARGE TEMP.)

$T_{Ho}$  : THERMISTOR (OUTDOOR TEMP.)

$T_{Hpo}$  : THERMISTOR (PIPE TEMP.)


$T_{Hc}$  : THERMISTOR (COMPRESSOR TEMP.)

$T_{Hr}$  : THERMISTOR (ROOM TEMP.)

$T_{Hpi}$  : THERMISTOR (PIPE TEMP.)

## 5. Wiring diagram

### 5-1. Model: AOU45RLXFZ



# 6. Capacity table

## 6-1. Combinations

### ■ Model: AOU45RLXFZ

#### ● Cooling

Combination of indoor unit						Type of indoor unit	Rated capacity for each indoor unit [kBtu/h]					Maximum capacity for each indoor unit [kBtu/h]					Total capacity [kBtu/h]			Input power [kW]		
							room					room					Min.	Rated	Max.	Min.	Rated	Max.
1	2	3	4	5	Total		1	2	3	4	5	1	2	3	4	5	12.0	36.0	38.4	0.80	3.28	3.42
12	24	—	—	—	36	Non-ducted	12.0	24.0	—	—	—	12.8	25.6	—	—	—	12.0	36.0	38.4	0.80	3.28	3.42
15	24	—	—	—	39	Non-ducted	15.0	24.0	—	—	—	16.0	25.6	—	—	—	12.0	39.0	41.6	0.80	3.72	3.89
18	18	—	—	—	36	Non-ducted	18.0	18.0	—	—	—	19.2	19.2	—	—	—	12.0	36.0	38.4	0.80	3.28	3.42
18	24	—	—	—	42	Non-ducted	18.0	24.0	—	—	—	19.2	25.6	—	—	—	12.0	42.0	44.8	0.80	4.17	4.36
24	24	—	—	—	48	Non-ducted	22.5	22.5	—	—	—	24.0	24.0	—	—	—	12.0	45.0	48.0	0.80	4.55	4.77
7	7	24	—	—	38	Non-ducted	7.0	7.0	24.0	—	—	7.5	7.5	25.6	—	—	12.0	38.0	40.5	0.80	3.50	3.73
7	9	18	—	—	34	Non-ducted	7.0	9.0	18.0	—	—	7.5	9.6	19.2	—	—	12.0	34.0	36.3	0.80	2.92	3.10
7	9	24	—	—	40	Non-ducted	7.0	9.0	24.0	—	—	7.5	9.6	25.6	—	—	12.0	40.0	42.7	0.80	3.79	4.05
7	12	18	—	—	37	Non-ducted	7.0	12.0	18.0	—	—	7.5	12.8	19.2	—	—	12.0	37.0	39.5	0.80	3.35	3.58
7	12	24	—	—	43	Non-ducted	7.0	12.0	24.0	—	—	7.5	12.8	25.6	—	—	12.0	43.0	45.9	0.80	4.22	4.52
7	15	15	—	—	37	Non-ducted	7.0	15.0	15.0	—	—	7.5	16.0	16.0	—	—	12.0	37.0	39.5	0.80	3.35	3.58
7	15	18	—	—	40	Non-ducted	7.0	15.0	18.0	—	—	7.5	16.0	19.2	—	—	12.0	40.0	42.7	0.80	3.79	4.05
7	15	24	—	—	46	Non-ducted	6.8	14.7	23.5	—	—	7.3	15.7	25.0	—	—	12.0	45.0	48.0	0.80	4.46	4.77
7	18	18	—	—	43	Non-ducted	7.0	18.0	18.0	—	—	7.5	19.2	19.2	—	—	12.0	43.0	45.9	0.80	4.22	4.52
7	18	24	—	—	49	Non-ducted	6.4	16.5	22.0	—	—	6.9	17.6	23.5	—	—	12.0	45.0	48.0	0.80	4.46	4.77
9	9	18	—	—	36	Non-ducted	9.0	9.0	18.0	—	—	9.6	9.6	19.2	—	—	12.0	36.0	38.4	0.80	3.21	3.42
9	9	24	—	—	42	Non-ducted	9.0	9.0	24.0	—	—	9.6	9.6	25.6	—	—	12.0	42.0	44.8	0.80	4.08	4.36
9	12	15	—	—	36	Non-ducted	9.0	12.0	15.0	—	—	9.6	12.8	16.0	—	—	12.0	36.0	38.4	0.80	3.21	3.42
9	12	18	—	—	39	Non-ducted	9.0	12.0	18.0	—	—	9.6	12.8	19.2	—	—	12.0	39.0	41.6	0.80	3.64	3.89
9	12	24	—	—	45	Non-ducted	9.0	12.0	24.0	—	—	9.6	12.8	25.6	—	—	12.0	45.0	48.0	0.80	4.46	4.77
9	15	15	—	—	39	Non-ducted	9.0	15.0	15.0	—	—	9.6	16.0	16.0	—	—	12.0	39.0	41.6	0.80	3.64	3.89
9	15	18	—	—	42	Non-ducted	9.0	15.0	18.0	—	—	9.6	16.0	19.2	—	—	12.0	42.0	44.8	0.80	3.92	4.36
9	15	24	—	—	48	Non-ducted	8.4	14.1	22.5	—	—	9.0	15.0	24.0	—	—	12.0	45.0	48.0	0.80	4.28	4.77
9	18	18	—	—	45	Non-ducted	9.0	18.0	18.0	—	—	9.6	19.2	19.2	—	—	12.0	45.0	48.0	0.80	4.28	4.77
9	18	24	—	—	51	Non-ducted	7.9	15.9	21.2	—	—	8.5	16.9	22.6	—	—	12.0	45.0	48.0	0.80	4.28	4.77
12	12	12	—	—	36	Non-ducted	12.0	12.0	12.0	—	—	12.8	12.8	12.8	—	—	12.0	36.0	38.4	0.80	3.08	3.42
12	12	15	—	—	39	Non-ducted	12.0	12.0	15.0	—	—	12.8	12.8	16.0	—	—	12.0	39.0	41.6	0.80	3.50	3.89
12	12	18	—	—	42	Non-ducted	12.0	12.0	18.0	—	—	12.8	12.8	19.2	—	—	12.0	42.0	44.8	0.80	3.22	3.46
12	12	24	—	—	48	Non-ducted	11.3	11.3	22.5	—	—	12.0	12.0	24.0	—	—	12.0	45.0	48.0	0.80	4.28	4.77
12	15	15	—	—	42	Non-ducted	12.0	15.0	15.0	—	—	12.8	16.0	16.0	—	—	12.0	42.0	44.8	0.80	3.92	4.36
12	15	18	—	—	45	Non-ducted	12.0	15.0	18.0	—	—	12.8	16.0	19.2	—	—	12.0	45.0	48.0	0.80	4.28	4.77
12	15	24	—	—	51	Non-ducted	10.6	13.2	21.2	—	—	11.3	14.1	22.6	—	—	12.0	45.0	48.0	0.80	4.28	4.77
12	18	18	—	—	48	Non-ducted	11.3	16.9	16.9	—	—	12.0	18.0	18.0	—	—	12.0	45.0	48.0	0.80	4.46	4.77
12	18	24	—	—	54	Non-ducted	10.0	15.0	20.0	—	—	10.7	16.0	21.3	—	—	12.0	45.0	48.0	0.80	4.46	4.77
15	15	15	—	—	45	Non-ducted	15.0	15.0	15.0	—	—	16.0	16.0	16.0	—	—	12.0	45.0	48.0	0.80	4.46	4.77
15	15	18	—	—	48	Non-ducted	14.1	14.1	16.9	—	—	15.0	15.0	18.0	—	—	12.0	45.0	48.0	0.80	4.46	4.77
15	15	24	—	—	54	Non-ducted	12.5	12.5	20.0	—	—	13.3	13.3	21.3	—	—	12.0	45.0	48.0	0.80	4.46	4.77
15	18	18	—	—	51	Non-ducted	13.2	15.9	15.9	—	—	14.1	16.9	16.9	—	—	12.0	45.0	48.0	0.80	4.46	4.77
18	18	18	—	—	54	Non-ducted	15.0	15.0	15.0	—	—	16.0	16.0	16.0	—	—	12.0	45.0	48.0	0.80	4.46	4.77
7	7	15	—	—	36	Non-ducted	7.0	7.0	7.0	15.0	—	7.5	7.5	7.5	16.0	—	12.0	36.0	38.4	0.80	3.14	3.42
7	7	18	—	—	39	Non-ducted	7.0	7.0	7.0	18.0	—	7.5	7.5	7.5	19.2	—	12.0	39.0	41.6	0.80	3.57	3.89
7	7	24	—	—	45	Non-ducted	7.0	7.0	7.0	24.0	—	7.5	7.5	7.5	25.6	—	12.0	45.0	48.0	0.80	4.37	4.77
7	7	9	12	—	35	Non-ducted	7.0	7.0	9.0	12.0	—	7.5	7.5	9.6	12.8	—	12.0	35.0	37.3	0.80	3.00	3.26
7	7	9	15	—	38	Non-ducted	7.0	7.0	9.0	15.0	—	7.5	7.5	9.6	16.0	—	12.0	38.0	40.5	0.80	3.43	3.73
7	7	9	18	—	41	Non-ducted	7.0	7.0	9.0	18.0	—	7.5	7.5	9.6	19.2	—	12.0	41.0	43.7	0.80	3.86	4.20
7	7	9	24	—	47	Non-ducted	6.7	6.7	8.6	23.0	—	7.1	7.1	9.2	24.5	—	12.0	45.0	48.0	0.80	4.37	4.77
7	7	12	12	—	38	Non-ducted	7.0	7.0	12.0	12.0	—	7.5	7.5	12.8	12.8	—	12.0	38.0	40.5	0.80	3.43	3.73
7	7	12	15	—	41	Non-ducted	7.0	7.0	12.0	15.0	—	7.5	7.5	12.8	16.0	—	12.0	41.0	43.7	0.80	3.86	4.20
7	7	12	18	—	44	Non-ducted	7.0	7.0	12.0	18.0	—	7.5	7.5	12.8	19.2	—	12.0	44.0	46.9	0.80	4.28	4.67
7	7	12	24	—	50	Non-ducted	6.3	6.3	10.8	21.6	—	6.7	6.7	11.5	23.0	—	12.0	45.0	48.0	0.80	4.37	4.77
7	7	15	15	—	44	Non-ducted	7.0	7.0	15.0	15.0	—	7.5	7.5	16.0	16.0	—	12.0	44.0	46.9	0.80	4.28	4.67
7	7	15	18	—	47	Non-ducted	6.7	6.7	14.4	17.2	—	7.1	7.1	15.3	18.4	—	12.0	45.0	48.0	0.80	4.28	4.77
7	7	15	24	—	53	Non-ducted	5.9	5.9	12.7	20.4	—	6.3	6.3	13.6	21.7	—	12.0	45.0	48.0	0.80	4.28	4.77
7	7	18	18	—	50	Non-ducted	6.3	6.3	16.2	16.2	—	6.7	6.7	17.3	17.3	—	12.0	45.0	48.0	0.80	4.28	4.7

Combination of indoor unit						Type of indoor unit	Rated capacity for each indoor unit [kBtu/h]					Maximum capacity for each indoor unit [kBtu/h]					Total capacity [kBtu/h]			Input power [kW]			
room					Total		room					room					Min.	Rated	Max.	Min.	Rated	Max.	
1	2	3	4	5			1	2	3	4	5	1	2	3	4	5							
9	9	9	15	—	42	Non-ducted	9.0	9.0	9.0	15.0	—	9.6	9.6	9.6	16.0	—	12.0	42.0	44.8	0.80	4.00	4.36	
9	9	9	18	—	45	Non-ducted	9.0	9.0	9.0	18.0	—	9.6	9.6	9.6	19.2	—	12.0	45.0	48.0	0.80	4.37	4.77	
9	9	9	24	—	51	Non-ducted	7.9	7.9	7.9	21.2	—	8.5	8.5	8.5	22.6	—	12.0	45.0	48.0	0.80	4.37	4.77	
9	9	12	12	—	42	Non-ducted	9.0	9.0	12.0	12.0	—	9.6	9.6	12.8	12.8	—	12.0	42.0	44.8	0.80	4.00	4.36	
9	9	12	15	—	45	Non-ducted	9.0	9.0	12.0	15.0	—	9.6	9.6	12.8	16.0	—	12.0	45.0	48.0	0.80	4.37	4.77	
9	9	12	18	—	48	Non-ducted	8.4	8.4	11.3	16.9	—	9.0	9.0	12.0	18.0	—	12.0	45.0	48.0	0.80	4.37	4.77	
9	9	12	24	—	54	Non-ducted	7.5	7.5	10.0	20.0	—	8.0	8.0	10.7	21.3	—	12.0	45.0	48.0	0.80	4.37	4.77	
9	9	15	15	—	48	Non-ducted	8.4	8.4	14.1	14.1	—	9.0	9.0	15.0	15.0	—	12.0	45.0	48.0	0.80	4.28	4.77	
9	9	15	18	—	51	Non-ducted	7.9	7.9	13.2	15.9	—	8.5	8.5	14.1	16.9	—	12.0	45.0	48.0	0.80	4.28	4.77	
9	9	18	18	—	54	Non-ducted	7.5	7.5	15.0	15.0	—	8.0	8.0	16.0	16.0	—	12.0	45.0	48.0	0.80	4.28	4.77	
9	12	12	12	—	45	Non-ducted	9.0	12.0	12.0	12.0	—	9.6	12.8	12.8	12.8	—	12.0	45.0	48.0	0.80	4.28	4.77	
9	12	12	15	—	48	Non-ducted	8.4	11.3	11.3	14.1	—	9.0	12.0	12.0	15.0	—	12.0	45.0	48.0	0.80	4.28	4.77	
9	12	12	18	—	51	Non-ducted	7.9	10.6	10.6	15.9	—	8.5	11.3	11.3	16.9	—	12.0	45.0	48.0	0.80	4.28	4.77	
9	12	15	15	—	51	Non-ducted	7.9	10.6	13.2	13.2	—	8.5	11.3	14.1	14.1	—	12.0	45.0	48.0	0.80	3.45	4.77	
9	12	15	18	—	54	Non-ducted	7.5	10.0	12.5	15.0	—	8.0	10.7	13.3	16.0	—	12.0	45.0	48.0	0.80	4.28	4.77	
12	12	12	12	—	48	Non-ducted	11.3	11.3	11.3	11.3	—	12.0	12.0	12.0	12.0	—	12.0	45.0	48.0	0.80	4.28	4.77	
12	12	12	15	—	51	Non-ducted	10.6	10.6	10.6	13.2	—	11.3	11.3	11.3	14.1	—	12.0	45.0	48.0	0.80	4.28	4.77	
12	12	12	18	—	54	Non-ducted	10.0	10.0	10.0	15.0	—	10.7	10.7	10.7	16.0	—	12.0	45.0	48.0	0.80	4.28	4.77	
12	12	12	18	—	54	Non-ducted	10.0	10.0	10.0	15.0	—	10.7	10.7	10.7	16.0	—	12.0	45.0	48.0	0.80	4.37	4.77	
7	7	7	7	7	35	Non-ducted	7.0	7.0	7.0	7.0	7.0	7.5	7.5	7.5	7.5	7.5	12.0	35.0	37.3	0.80	2.94	3.26	
7	7	7	7	9	37	Non-ducted	7.0	7.0	7.0	9.0	9.0	7.5	7.5	7.5	7.5	9.6	12.0	37.0	39.5	0.80	3.22	3.58	
7	7	7	7	12	40	Non-ducted	7.0	7.0	7.0	7.0	12.0	7.5	7.5	7.5	7.5	12.8	12.0	40.0	42.7	0.80	3.64	4.05	
7	7	7	7	15	43	Non-ducted	7.0	7.0	7.0	15.0	15.0	7.5	7.5	7.5	7.5	16.0	12.0	43.0	45.9	0.80	4.05	4.52	
7	7	7	7	18	46	Non-ducted	6.8	6.8	6.8	6.8	17.6	7.3	7.3	7.3	7.3	18.8	12.0	45.0	48.0	0.80	4.28	4.77	
7	7	7	7	24	52	Non-ducted	6.1	6.1	6.1	6.1	20.8	6.5	6.5	6.5	6.5	22.2	12.0	45.0	48.0	0.80	4.28	4.77	
7	7	7	9	9	39	Non-ducted	7.0	7.0	9.0	9.0	7.5	7.5	7.5	9.6	9.6	12.0	39.0	41.6	0.80	3.50	3.89		
7	7	7	9	12	42	Non-ducted	7.0	7.0	7.0	9.0	12.0	7.5	7.5	7.5	7.5	12.8	12.0	42.0	44.8	0.80	3.92	4.36	
7	7	7	9	15	45	Non-ducted	7.0	7.0	9.0	15.0	15.0	7.5	7.5	7.5	9.6	16.0	12.0	45.0	48.0	0.80	4.28	4.77	
7	7	7	9	18	48	Non-ducted	6.6	6.6	6.6	8.4	16.9	7.0	7.0	9.0	9.0	18.0	12.0	45.0	48.0	0.80	4.28	4.77	
7	7	7	9	24	54	Non-ducted	5.8	5.8	5.8	7.5	20.0	6.2	6.2	6.2	8.0	21.3	12.0	45.0	48.0	0.80	4.28	4.77	
7	7	7	12	12	45	Non-ducted	7.0	7.0	12.0	12.0	7.5	7.5	7.5	12.8	12.8	12.0	45.0	48.0	0.80	4.28	4.77		
7	7	7	12	15	48	Non-ducted	6.6	6.6	6.6	11.3	14.1	7.0	7.0	7.0	12.0	15.0	12.0	45.0	48.0	0.80	4.28	4.77	
7	7	7	12	18	51	Non-ducted	6.2	6.2	6.2	10.6	15.9	6.6	6.6	6.6	11.3	16.9	12.0	45.0	48.0	0.80	4.28	4.77	
7	7	7	15	15	51	Non-ducted	6.2	6.2	6.2	13.2	13.2	6.6	6.6	6.6	14.1	14.1	12.0	45.0	48.0	0.80	4.28	4.77	
7	7	7	15	18	54	Non-ducted	5.8	5.8	5.8	12.5	15.0	6.2	6.2	6.2	13.3	16.0	12.0	45.0	48.0	0.80	4.28	4.77	
7	7	9	9	41	41	Non-ducted	7.0	7.0	9.0	9.0	9.0	7.5	7.5	9.6	9.6	12.0	41.0	43.7	0.80	3.78	4.20		
7	7	9	9	12	44	Non-ducted	7.0	7.0	9.0	9.0	12.0	7.5	7.5	9.6	9.6	12.8	12.0	44.0	46.9	0.80	4.20	4.67	
7	7	9	9	15	47	Non-ducted	6.7	6.7	8.6	8.6	14.4	7.1	7.1	9.2	9.2	15.3	12.0	45.0	48.0	0.80	4.28	4.77	
7	7	9	9	18	50	Non-ducted	6.3	6.3	8.1	8.1	16.2	6.7	6.7	8.6	8.6	17.3	12.0	45.0	48.0	0.80	4.28	4.77	
7	7	9	12	12	47	Non-ducted	6.7	6.7	8.6	11.5	11.5	7.1	7.1	9.2	12.3	12.3	12.0	45.0	48.0	0.80	4.28	4.77	
7	7	9	12	15	50	Non-ducted	6.3	6.3	8.1	10.8	13.5	6.7	6.7	8.6	11.5	14.4	12.0	45.0	48.0	0.80	4.28	4.77	
7	7	9	12	18	53	Non-ducted	5.9	5.9	7.6	10.2	15.3	6.3	6.3	8.2	10.9	16.3	12.0	45.0	48.0	0.80	4.28	4.77	
7	7	9	15	15	53	Non-ducted	5.9	5.9	7.6	12.7	12.7	6.3	6.3	8.2	13.6	13.6	12.0	45.0	48.0	0.80	3.45	4.77	
7	7	12	12	12	50	Non-ducted	6.3	6.3	10.8	10.8	10.8	6.7	6.7	11.5	11.5	11.5	12.0	45.0	48.0	0.80	4.28	4.77	
7	7	12	12	15	53	Non-ducted	5.9	5.9	10.2	10.2	12.7	6.3	6.3	10.9	10.9	13.6	12.0	45.0	48.0	0.80	4.28	4.77	
7	9	9	9	9	43	Non-ducted	7.0	9.0	9.0	9.0	9.0	7.5	9.6	9.6	9.6	12.0	43.0	45.9	0.80	4.05	4.52		
7	9	9	9	12	46	Non-ducted	6.8	8.8	8.8	8.8	11.7	7.3	9.4	9.4	9.4	12.5	12.0	45.0	48.0	0.80	4.28	4.77	
7	9	9	9	15	49	Non-ducted	6.4	8.3	8.3	8.3	13.8	6.9	8.8	8.8	8.8	14.7	12.0	45.0	48.0	0.80	4.28	4.77	
7	9	9	9	18	52	Non-ducted	6.1	7.8	7.8	7.8	15.6	6.5	8.3	8.3	8.3	16.6	12.0	45.0	48.0	0.80	4.28	4.77	
7	9	9	12	12	49	Non-ducted	6.4	8.3	8.3	11.0	11.0	6.9	8.8	8.8	11.8	11.8	12.0	45.0	48.0	0.80	4.28	4.77	
7	9	9	12	15	52	Non-ducted	6.1	7.8	7.8	10.4	13.0	6.5	8.3	8.3	11.1	13.8	12.0	45.0	48.0	0.80	4.28	4.77	
7	9	12	12	12	52	Non-ducted	6.1	7.8	10.4	10.4	6.5	8.3	11.1	11.1	11.1	12.0	45.0	48.0	0.80	4.28	4.77		
9	9	9	9	9	45	Non-ducted	9.0	9.0	9.0	9.0	9.0	9.6	9.6	9.6	9.6	9.6	12.0	45.0	48.0	0.80	4.28	4.77	

Combination of indoor unit					Type of in-door unit	Rated capacity for each indoor unit [kBtu/h]					Maximum capacity for each indoor unit [kBtu/h]					Total capacity [kBtu/h]			Input power [kW]			
room					Ducted	room					room					Min.	Rated	Max.	Min.	Rated	Max.	
1	2	3	4	5		1	2	3	4	5	1	2	3	4	5							
7	7	12	18	—	44	7.0	7.0	12.0	18.0	—	7.5	7.5	12.8	19.2	—	12.0	44.0	46.9	0.80	4.50	4.76	
7	7	12	24	—	50	6.3	6.3	10.8	21.6	—	6.7	6.7	11.5	23.0	—	12.0	45.0	48.0	0.80	4.59	4.86	
7	7	18	18	—	50	6.3	6.3	16.2	16.2	—	6.7	6.7	17.3	17.3	—	12.0	45.0	48.0	0.80	4.68	4.86	
7	9	9	9	—	34	Ducted	7.0	9.0	9.0	9.0	—	7.5	9.6	9.6	9.6	—	12.0	34.0	36.3	0.80	3.03	3.15
7	9	9	12	—	37	Ducted	7.0	9.0	9.0	12.0	—	7.5	9.6	9.6	12.8	—	12.0	37.0	39.5	0.80	3.50	3.64
7	9	9	18	—	43	Ducted	7.0	9.0	9.0	18.0	—	7.5	9.6	9.6	19.2	—	12.0	43.0	45.9	0.80	4.34	4.60
7	9	9	24	—	49	Ducted	6.4	8.3	8.3	22.0	—	6.9	8.8	8.8	23.5	—	12.0	45.0	48.0	0.80	4.59	4.86
7	9	12	12	—	40	Ducted	7.0	9.0	12.0	12.0	—	7.5	9.6	12.8	12.8	—	12.0	40.0	42.7	0.80	3.89	4.12
7	9	12	18	—	46	Ducted	6.8	8.8	11.7	17.6	—	7.3	9.4	12.5	18.8	—	12.0	45.0	48.0	0.80	4.59	4.86
7	9	12	24	—	52	Ducted	6.1	7.8	10.4	20.8	—	6.5	8.3	11.1	22.2	—	12.0	45.0	48.0	0.80	3.75	4.86
7	9	18	18	—	52	Ducted	6.1	7.8	15.6	15.6	—	6.5	8.3	16.6	16.6	—	12.0	45.0	48.0	0.80	4.59	4.86
7	12	12	12	—	43	Ducted	7.0	12.0	12.0	12.0	—	7.5	12.8	12.8	12.8	—	12.0	43.0	45.9	0.80	4.43	4.60
7	12	12	18	—	49	Ducted	6.4	11.0	11.0	16.5	—	6.9	11.8	11.8	17.6	—	12.0	45.0	48.0	0.80	4.68	4.86
9	9	9	9	—	36	Ducted	9.0	9.0	9.0	9.0	—	9.6	9.6	9.6	9.6	—	12.0	36.0	38.4	0.80	3.35	3.48
9	9	9	12	—	39	Ducted	9.0	9.0	9.0	12.0	—	9.6	9.6	9.6	12.8	—	12.0	39.0	41.6	0.80	3.74	3.96
9	9	9	18	—	45	Ducted	9.0	9.0	9.0	18.0	—	9.6	9.6	9.6	19.2	—	12.0	45.0	48.0	0.80	4.59	4.86
9	9	9	24	—	51	Ducted	7.9	7.9	7.9	21.2	—	8.5	8.5	8.5	22.6	—	12.0	45.0	48.0	0.80	4.59	4.86
9	9	12	12	—	42	Ducted	9.0	9.0	12.0	12.0	—	9.6	9.6	12.8	12.8	—	12.0	42.0	44.8	0.80	4.19	4.44
9	9	12	18	—	48	Ducted	8.4	8.4	11.3	16.9	—	9.0	9.0	12.0	18.0	—	12.0	45.0	48.0	0.80	4.59	4.86
9	9	12	24	—	54	Ducted	7.5	7.5	10.0	20.0	—	8.0	8.0	10.7	21.3	—	12.0	45.0	48.0	0.80	4.59	4.86
9	9	18	18	—	54	Ducted	7.5	7.5	15.0	15.0	—	8.0	8.0	16.0	16.0	—	12.0	45.0	48.0	0.80	4.68	4.86
9	12	12	12	—	45	Ducted	9.0	12.0	12.0	12.0	—	9.6	12.8	12.8	12.8	—	12.0	45.0	48.0	0.80	4.68	4.86
9	12	12	18	—	51	Ducted	7.9	10.6	10.6	15.9	—	8.5	11.3	11.3	16.9	—	12.0	45.0	48.0	0.80	4.68	4.86
12	12	12	12	—	48	Ducted	11.3	11.3	11.3	11.3	—	12.0	12.0	12.0	12.0	—	12.0	45.0	48.0	0.80	4.59	4.86
12	12	12	18	—	54	Ducted	10.0	10.0	10.0	15.0	—	10.7	10.7	10.7	16.0	—	12.0	45.0	48.0	0.80	4.59	4.86
12	12	12	24	—	54	Ducted	10.0	10.0	10.0	15.0	—	10.7	10.7	10.7	16.0	—	12.0	45.0	48.0	0.80	4.59	4.86
7	7	7	7	7	35	Ducted	7.0	7.0	7.0	7.0	7.0	7.5	7.5	7.5	7.5	7.5	12.0	35.0	37.3	0.80	2.91	3.32
7	7	7	7	9	37	Ducted	7.0	7.0	7.0	7.0	9.0	7.5	7.5	7.5	7.5	9.6	12.0	37.0	39.5	0.80	3.43	3.64
7	7	7	7	12	40	Ducted	7.0	7.0	7.0	7.0	12.0	7.5	7.5	7.5	7.5	7.5	12.0	40.0	42.7	0.80	3.89	4.12
7	7	7	7	18	46	Ducted	6.8	6.8	6.8	6.8	17.6	7.3	7.3	7.3	7.3	18.8	12.0	45.0	48.0	0.80	4.59	4.86
7	7	7	7	24	52	Ducted	6.1	6.1	6.1	6.1	20.8	6.5	6.5	6.5	6.5	22.2	12.0	45.0	48.0	0.80	4.59	4.86
7	7	7	9	9	39	Ducted	7.0	7.0	7.0	9.0	9.0	7.5	7.5	7.5	9.6	9.6	12.0	39.0	41.6	0.80	3.74	3.96
7	7	7	9	12	42	Ducted	7.0	7.0	7.0	9.0	12.0	7.5	7.5	7.5	7.5	12.8	12.0	42.0	44.8	0.80	4.19	4.44
7	7	7	9	18	48	Ducted	6.6	6.6	6.6	8.4	16.9	7.0	7.0	7.0	9.0	18.0	12.0	45.0	48.0	0.80	4.59	4.86
7	7	7	9	24	54	Ducted	5.8	5.8	5.8	7.5	20.0	6.2	6.2	6.2	8.0	21.3	12.0	45.0	48.0	0.80	4.59	4.86
7	7	7	12	12	45	Ducted	7.0	7.0	7.0	12.0	12.0	7.5	7.5	7.5	12.8	12.0	45.0	48.0	0.80	4.59	4.86	
7	7	7	12	18	51	Ducted	6.2	6.2	6.2	10.6	15.9	6.6	6.6	6.6	11.3	16.9	12.0	45.0	48.0	0.80	4.59	4.86
7	7	9	9	9	41	Ducted	7.0	7.0	9.0	9.0	9.0	7.5	7.5	9.6	9.6	9.6	12.0	41.0	43.7	0.80	3.41	4.28
7	7	9	9	12	44	Ducted	7.0	7.0	9.0	9.0	12.0	7.5	7.5	9.6	9.6	12.8	12.0	44.0	46.9	0.80	4.50	4.76
7	7	9	9	18	50	Ducted	6.3	6.3	8.1	8.1	16.2	6.7	6.7	8.6	8.6	17.3	12.0	45.0	48.0	0.80	4.59	4.86
7	7	9	12	12	47	Ducted	6.7	6.7	8.6	11.5	11.5	7.1	7.1	9.2	12.3	12.3	12.0	45.0	48.0	0.80	4.59	4.86
7	7	9	12	18	53	Ducted	5.9	5.9	7.6	10.2	15.3	6.3	6.3	8.2	10.9	16.3	12.0	45.0	48.0	0.80	4.59	4.86
7	7	12	12	12	50	Ducted	6.3	6.3	10.8	10.8	10.8	6.7	6.7	11.5	11.5	11.5	12.0	45.0	48.0	0.80	4.59	4.86
7	9	9	9	9	43	Ducted	7.0	9.0	9.0	9.0	9.0	7.5	9.6	9.6	9.6	9.6	12.0	43.0	45.9	0.80	4.34	4.60
7	9	9	9	12	46	Ducted	6.8	8.8	8.8	8.8	11.7	7.3	9.4	9.4	9.4	12.5	12.0	45.0	48.0	0.80	4.59	4.86
7	9	9	9	18	52	Ducted	6.1	7.8	7.8	7.8	15.6	6.5	8.3	8.3	8.3	16.6	12.0	45.0	48.0	0.80	4.59	4.86
7	9	9	12	12	49	Ducted	6.4	8.3	8.3	11.0	11.0	6.9	8.8	8.8	11.8	11.8	12.0	45.0	48.0	0.80	4.59	4.86
7	9	9	12	12	52	Ducted	6.1	7.8	10.4	10.4	10.4	6.5	8.3	11.1	11.1	11.1	12.0	45.0	48.0	0.80	3.75	4.86
9	9	9	9	9	45	Ducted	9.0	9.0	9.0	9.0	9.0	9.6	9.6	9.6	9.6	9.6	12.0	45.0	48.0	0.80	4.59	4.86
9	9	9	9	12	48	Ducted	8.4	8.4	8.4	8.4	11.3	9.0	9.0	9.0	9.0	12.0	12.0	45.0	48.0	0.80	4.59	4.86
9	9	9	9	18	54	Ducted	7.5	7.5	7.5	7.5	15.0	8.0	8.0	8.0	8.0	16.0	12.0	45.0	48.0	0.80	4.59	4.86
9	9	9	12	12	51	Ducted	7.9	7.9	7.9	10.6	10.6	8.5	8.5	8.5	11.3	11.3	12.0	45.0	48.0	0.80	4.59	4.86
9	9	12	12	12	54	Ducted	7.5	7.5	10.0	10.0	10.0	8.0	8.0	10.7	10.7	12.0	45.0	48.0	0.80	4.59	4.86	

**NOTES:**

- Specifications are based on the following conditions.
  - Power source of specifications: 230 V
  - 7: 7,000 Btu/h, 9: 9,00

## ■ Model: AOU45RLXFZ

## ● Heating

**OUTDOOR UNIT**  
AOU45RLXFZ

**OUTDOOR UNIT**  
AOU45RLXFZ

Combination of indoor unit						Type of indoor unit	Rated capacity for each indoor unit [kBtu/h]					Maximum capacity for each indoor unit [kBtu/h]					Total capacity [kBtu/h]			Input power [kW]			
							room					room					Min.			Rated			
1	2	3	4	5	Total		1	2	3	4	5	1	2	3	4	5	Min.	Max.	Min.	Rated	Max.	Min.	Rated
12	24	—	—	—	36	Non-ducted	12.8	25.6	—	—	—	14.4	28.8	—	—	—	12.0	38.4	43.2	0.70	3.24	3.39	
15	24	—	—	—	39	Non-ducted	16.0	25.6	—	—	—	18.0	28.8	—	—	—	12.0	41.6	46.8	0.70	3.53	3.70	
18	18	—	—	—	36	Non-ducted	19.2	19.2	—	—	—	21.6	21.6	—	—	—	12.0	38.4	43.2	0.70	3.24	3.39	
18	24	—	—	—	42	Non-ducted	19.2	25.6	—	—	—	21.6	28.8	—	—	—	12.0	44.8	50.4	0.70	3.83	4.01	
24	24	—	—	—	48	Non-ducted	24.0	24.0	—	—	—	27.0	27.0	—	—	—	12.0	48.0	54.0	0.70	4.13	4.32	
7	7	24	—	—	38	Non-ducted	7.5	7.5	25.6	—	—	8.4	8.4	28.8	—	—	12.0	40.5	45.6	0.70	3.36	3.60	
7	9	18	—	—	34	Non-ducted	7.5	9.6	19.2	—	—	8.4	10.8	21.6	—	—	12.0	36.3	40.8	0.70	2.98	3.19	
7	9	24	—	—	40	Non-ducted	7.5	9.6	25.6	—	—	8.4	10.8	28.8	—	—	12.0	42.7	48.0	0.70	3.56	3.80	
7	12	18	—	—	37	Non-ducted	7.5	12.8	19.2	—	—	8.4	14.4	21.6	—	—	12.0	39.5	44.4	0.70	3.27	3.49	
7	12	24	—	—	43	Non-ducted	7.5	12.8	25.6	—	—	8.4	14.4	28.8	—	—	12.0	45.9	51.6	0.70	3.85	4.12	
7	15	15	—	—	37	Non-ducted	7.5	16.0	16.0	—	—	8.4	18.0	18.0	—	—	12.0	39.5	44.4	0.70	3.27	3.49	
7	15	18	—	—	40	Non-ducted	7.5	16.0	19.2	—	—	8.4	18.0	21.6	—	—	12.0	42.7	48.0	0.70	3.56	3.80	
7	15	24	—	—	46	Non-ducted	7.3	15.7	25.0	—	—	8.2	17.6	28.2	—	—	12.0	48.0	54.0	0.70	4.04	4.32	
7	18	18	—	—	43	Non-ducted	7.5	19.2	19.2	—	—	8.4	21.6	21.6	—	—	12.0	45.9	51.6	0.70	3.85	4.12	
7	18	24	—	—	49	Non-ducted	6.9	17.6	23.5	—	—	7.7	19.8	26.4	—	—	12.0	48.0	54.0	0.70	4.04	4.32	
9	9	18	—	—	36	Non-ducted	9.6	9.6	19.2	—	—	10.8	10.8	21.6	—	—	12.0	38.4	43.2	0.70	3.17	3.39	
9	9	24	—	—	42	Non-ducted	9.6	9.6	25.6	—	—	10.8	10.8	28.8	—	—	12.0	44.8	50.4	0.70	3.75	4.01	
9	12	15	—	—	36	Non-ducted	9.6	12.8	16.0	—	—	10.8	14.4	18.0	—	—	12.0	38.4	43.2	0.70	3.17	3.39	
9	12	18	—	—	39	Non-ducted	9.6	12.8	19.2	—	—	10.8	14.4	21.6	—	—	12.0	41.6	46.8	0.70	3.46	3.70	
9	12	24	—	—	45	Non-ducted	9.6	12.8	25.6	—	—	10.8	14.4	28.8	—	—	12.0	48.0	54.0	0.70	4.04	4.32	
9	15	15	—	—	39	Non-ducted	9.6	16.0	16.0	—	—	10.8	18.0	18.0	—	—	12.0	41.6	46.8	0.70	3.46	3.70	
9	15	18	—	—	42	Non-ducted	9.6	16.0	19.2	—	—	10.8	18.0	21.6	—	—	12.0	44.8	50.4	0.70	3.60	4.01	
9	15	24	—	—	48	Non-ducted	9.0	15.0	24.0	—	—	10.1	16.9	27.0	—	—	12.0	48.0	54.0	0.70	3.88	4.32	
9	18	18	—	—	45	Non-ducted	9.6	19.2	19.2	—	—	10.8	21.6	21.6	—	—	12.0	48.0	54.0	0.70	3.88	4.32	
9	18	24	—	—	51	Non-ducted	8.5	16.9	22.6	—	—	9.5	19.1	25.4	—	—	12.0	48.0	54.0	0.70	3.88	4.32	
12	12	12	—	—	36	Non-ducted	12.8	12.8	12.8	—	—	14.4	14.4	14.4	—	—	12.0	38.4	43.2	0.70	3.04	3.39	
12	12	15	—	—	39	Non-ducted	12.8	12.8	16.0	—	—	14.4	14.4	18.0	—	—	12.0	41.6	46.8	0.70	3.32	3.70	
12	12	18	—	—	42	Non-ducted	12.8	12.8	19.2	—	—	14.4	14.4	21.6	—	—	12.0	44.8	50.4	0.70	3.44	4.01	
12	12	24	—	—	48	Non-ducted	12.0	12.0	24.0	—	—	13.5	13.5	27.0	—	—	12.0	48.0	54.0	0.70	3.88	4.32	
12	15	15	—	—	42	Non-ducted	12.8	16.0	16.0	—	—	14.4	18.0	18.0	—	—	12.0	44.8	50.4	0.70	3.60	4.01	
12	15	18	—	—	45	Non-ducted	12.8	16.0	19.2	—	—	14.4	18.0	21.6	—	—	12.0	48.0	54.0	0.70	3.88	4.32	
12	15	24	—	—	51	Non-ducted	11.3	14.1	22.6	—	—	12.7	15.9	25.4	—	—	12.0	48.0	54.0	0.70	3.88	4.32	
12	18	18	—	—	48	Non-ducted	12.0	18.0	18.0	—	—	13.5	20.3	20.3	—	—	12.0	48.0	54.0	0.70	4.04	4.32	
12	18	24	—	—	54	Non-ducted	10.7	16.0	21.3	—	—	12.0	18.0	24.0	—	—	12.0	48.0	54.0	0.70	4.04	4.32	
15	15	15	—	—	45	Non-ducted	16.0	16.0	16.0	—	—	18.0	18.0	18.0	—	—	12.0	48.0	54.0	0.70	4.04	4.32	
15	15	18	—	—	48	Non-ducted	15.0	15.0	18.0	—	—	16.9	16.9	20.3	—	—	12.0	48.0	54.0	0.70	4.04	4.32	
15	15	24	—	—	54	Non-ducted	13.3	13.3	21.3	—	—	15.0	15.0	24.0	—	—	12.0	48.0	54.0	0.70	4.04	4.32	
15	18	18	—	—	51	Non-ducted	14.1	16.9	16.9	—	—	15.9	19.1	19.1	—	—	12.0	48.0	54.0	0.70	4.04	4.32	
18	18	—	—	—	54	Non-ducted	16.0	16.0	16.0	—	—	18.0	18.0	18.0	—	—	12.0	48.0	54.0	0.70	4.04	4.32	
7	7	7	15	—	36	Non-ducted	7.5	7.5	7.5	16.0	—	8.4	8.4	8.4	18.0	—	12.0	38.4	43.2	0.70	3.11	3.39	
7	7	7	18	—	39	Non-ducted	7.5	7.5	7.5	19.2	—	8.4	8.4	8.4	21.6	—	12.0	41.6	46.8	0.70	3.39	3.70	
7	7	7	24	—	45	Non-ducted	7.5	7.5	7.5	25.6	—	8.4	8.4	8.4	28.8	—	12.0	48.0	54.0	0.70	3.96	4.32	
7	7	9	12	—	35	Non-ducted	7.5	7.5	9.6	12.8	—	8.4	8.4	10.8	14.4	—	12.0	37.3	42.0	0.70	3.01	3.29	
7	7	9	15	—	38	Non-ducted	7.5	7.5	9.6	16.0	—	8.4	8.4	10.8	18.0	—	12.0	40.5	45.6	0.70	3.29	3.60	
7	7	9	18	—	41	Non-ducted	7.5	7.5	9.6	19.2	—	8.4	8.4	10.8	21.6	—	12.0	43.7	49.2	0.70	3.58	3.91	
7	7	9	24	—	47	Non-ducted	7.1	7.1	9.2	24.5	—	8.0	8.0	10.3	27.6	—	12.0	48.0	54.0	0.70	3.96	4.32	
7	7	12	12	—	38	Non-ducted	7.5	7.5	12.8	12.8	—	8.4	8.4	14.4	14.4	—	12.0	40.5	45.6	0.70	3.29	3.60	
7	7	12	15	—	41	Non-ducted	7.5	7.5	12.8	16.0	—	8.4	8.4	14.4	18.0	—	12.0	43.7	49.2	0.70	3.58	3.91	
7	7	12	18	—	44	Non-ducted	7.5	7.5	12.8	19.2	—	8.4	8.4	14.4	21.6	—	12.0	46.9	52.8	0.70	3.86	4.22	
7	7	12	24	—	50	Non-ducted	6.7	6.7	11.5	23.0	—	7.6	7.6	13.0	25.9	—	12.0	48.0	54.0	0.70	3.96	4.32	
7	7	15	15	—	44	Non-ducted	7.5	7.5	16.0	16.0	—	8.4	8.4	18.0	18.0	—	12.0	46.9	52.8	0.70	3.86	4.22	
7	7	15	18	—	47	Non-ducted	7.1	7.1	15.3	18.4	—	8.0	8.0	17.2	20.7	—	12.0	48.0	54.0	0.70	3.88	4.32	
7	7	18	18	—	50	Non-ducted	6.3	6.3	13.6	21.7	—	7.1	7.1	15.3	24.5	—	12.0	48.0	54.0	0.70	3.88	4.32	
7	9	9	9	—	34	Non-ducted	7.5	9.6	9.6	9.6	—	8.4	10.8	10.8	10.8	—	12.0	36.3	40.8	0.70	2.86		

Combination of indoor unit					Type of indoor unit	Rated capacity for each indoor unit [kBTu/h]					Maximum capacity for each indoor unit [kBTu/h]					Total capacity [kBTu/h]		Input power [kW]					
room						room					room					Min.	Rated	Max.	Min.	Rated	Max.		
1	2	3	4	5		1	2	3	4	5	1	2	3	4	5								
9	9	18	18	—	54	Non-ducted	8.0	8.0	16.0	16.0	—	9.0	9.0	18.0	18.0	—	12.0	48.0	54.0	0.70	3.88	4.32	
9	12	12	12	—	45	Non-ducted	9.6	12.8	12.8	12.8	—	10.8	14.4	14.4	14.4	—	12.0	48.0	54.0	0.70	3.88	4.32	
9	12	12	15	—	48	Non-ducted	9.0	12.0	12.0	15.0	—	10.1	13.5	13.5	16.9	—	12.0	48.0	54.0	0.70	3.88	4.32	
9	12	12	18	—	51	Non-ducted	8.5	11.3	11.3	16.9	—	9.5	12.7	12.7	19.1	—	12.0	48.0	54.0	0.70	3.88	4.32	
9	12	15	15	—	51	Non-ducted	8.5	11.3	14.1	14.1	—	9.5	12.7	15.9	15.9	—	12.0	48.0	54.0	0.70	3.68	4.32	
9	12	15	18	—	54	Non-ducted	8.0	10.7	13.3	16.0	—	9.0	12.0	15.0	18.0	—	12.0	48.0	54.0	0.70	3.88	4.32	
12	12	12	12	—	48	Non-ducted	12.0	12.0	12.0	12.0	—	13.5	13.5	13.5	13.5	—	12.0	48.0	54.0	0.70	3.88	4.32	
12	12	12	15	—	51	Non-ducted	11.3	11.3	11.3	14.1	—	12.7	12.7	12.7	15.9	—	12.0	48.0	54.0	0.70	3.88	4.32	
12	12	12	18	—	54	Non-ducted	10.7	10.7	10.7	16.0	—	12.0	12.0	12.0	18.0	—	12.0	48.0	54.0	0.70	3.88	4.32	
12	12	12	18	—	54	Non-ducted	10.7	10.7	10.7	16.0	—	12.0	12.0	12.0	18.0	—	12.0	48.0	54.0	0.70	3.96	4.32	
12	12	15	15	—	54	Non-ducted	10.7	10.7	13.3	13.3	—	12.0	12.0	15.0	15.0	—	12.0	48.0	54.0	0.70	3.96	4.32	
7	7	7	7	7	35	Non-ducted	7.5	7.5	7.5	7.5	7.5	8.4	8.4	8.4	8.4	8.4	12.0	39.5	44.4	0.70	2.95	3.29	
7	7	7	7	9	37	Non-ducted	7.5	7.5	7.5	7.5	9.6	8.4	8.4	8.4	8.4	10.8	12.0	39.5	44.4	0.70	3.14	3.49	
7	7	7	7	12	40	Non-ducted	7.5	7.5	7.5	7.5	12.8	8.4	8.4	8.4	8.4	14.4	12.0	42.7	48.0	50.4	0.70	3.42	3.80
7	7	7	7	15	43	Non-ducted	7.5	7.5	7.5	7.5	16.0	8.4	8.4	8.4	8.4	18.0	12.0	45.9	51.6	0.70	3.70	4.12	
7	7	7	7	18	46	Non-ducted	7.3	7.3	7.3	7.3	18.8	8.2	8.2	8.2	8.2	21.1	12.0	48.0	54.0	0.70	3.88	4.32	
7	7	7	7	24	52	Non-ducted	6.5	6.5	6.5	6.5	22.2	7.3	7.3	7.3	7.3	24.9	12.0	48.0	54.0	0.70	3.88	4.32	
7	7	7	9	9	39	Non-ducted	7.5	7.5	7.5	9.6	8.4	8.4	8.4	8.4	10.8	12.0	41.6	46.8	0.70	3.32	3.70		
7	7	7	9	12	42	Non-ducted	7.5	7.5	7.5	9.6	12.8	8.4	8.4	8.4	8.4	14.4	12.0	44.8	50.4	0.70	3.60	4.01	
7	7	7	9	15	45	Non-ducted	7.5	7.5	7.5	9.6	16.0	8.4	8.4	8.4	8.4	18.0	12.0	48.0	54.0	0.70	3.88	4.32	
7	7	7	9	18	48	Non-ducted	7.0	7.0	7.0	9.0	18.0	7.9	7.9	7.9	7.9	20.3	12.0	48.0	54.0	0.70	3.88	4.32	
7	7	7	9	24	54	Non-ducted	6.2	6.2	6.2	8.0	21.3	7.0	7.0	7.0	7.0	24.0	12.0	48.0	54.0	0.70	3.88	4.32	
7	7	7	12	12	45	Non-ducted	7.5	7.5	7.5	12.8	12.8	8.4	8.4	8.4	14.4	14.4	12.0	48.0	54.0	0.70	3.88	4.32	
7	7	7	12	15	48	Non-ducted	7.0	7.0	7.0	12.0	15.0	7.9	7.9	7.9	13.5	16.9	12.0	48.0	54.0	0.70	3.88	4.32	
7	7	7	12	18	51	Non-ducted	6.6	6.6	6.6	11.3	16.9	7.4	7.4	7.4	12.7	19.1	12.0	48.0	54.0	0.70	3.88	4.32	
7	7	7	15	15	51	Non-ducted	6.6	6.6	6.6	14.1	14.1	7.4	7.4	7.4	15.9	15.9	12.0	48.0	54.0	0.70	3.88	4.32	
7	7	7	15	18	54	Non-ducted	6.2	6.2	13.3	16.0	7.0	7.0	7.0	15.0	18.0	12.0	48.0	54.0	0.70	3.88	4.32		
7	7	9	9	9	41	Non-ducted	7.5	7.5	9.6	9.6	8.4	8.4	8.4	10.8	10.8	12.0	43.7	49.2	0.70	3.51	3.91		
7	7	9	9	12	44	Non-ducted	7.5	7.5	9.6	9.6	12.8	8.4	8.4	10.8	10.8	14.4	12.0	46.9	52.8	0.70	3.78	4.22	
7	7	9	9	15	47	Non-ducted	7.1	7.1	9.2	9.2	15.3	8.0	8.0	10.3	10.3	17.2	12.0	48.0	54.0	0.70	3.88	4.32	
7	7	9	9	18	50	Non-ducted	6.7	6.7	8.6	8.6	17.3	7.6	7.6	9.7	9.7	19.4	12.0	48.0	54.0	0.70	3.88	4.32	
7	7	9	12	12	47	Non-ducted	7.1	7.1	9.2	12.3	12.3	8.0	8.0	10.3	13.8	13.8	12.0	48.0	54.0	0.70	3.88	4.32	
7	7	9	12	15	50	Non-ducted	6.7	6.7	8.6	11.5	14.4	7.6	7.6	9.7	13.0	16.2	12.0	48.0	54.0	0.70	3.88	4.32	
7	7	9	12	18	53	Non-ducted	6.3	6.3	8.2	10.9	16.3	7.1	7.1	9.2	12.2	18.3	12.0	48.0	54.0	0.70	3.88	4.32	
7	7	9	15	15	53	Non-ducted	6.3	6.3	8.2	13.6	13.6	7.1	7.1	9.2	15.3	15.3	12.0	48.0	54.0	0.70	3.68	4.32	
7	7	12	12	12	50	Non-ducted	6.7	6.7	11.5	11.5	11.5	7.6	7.6	13.0	13.0	13.0	12.0	48.0	54.0	0.70	3.88	4.32	
7	7	12	12	15	53	Non-ducted	6.3	6.3	10.9	10.9	13.6	7.1	7.1	12.2	12.2	15.3	12.0	48.0	54.0	0.70	3.88	4.32	
7	9	9	9	9	43	Non-ducted	7.5	9.6	9.6	9.6	9.6	8.4	10.8	10.8	10.8	10.8	12.0	45.9	51.6	0.70	3.70	4.12	
7	9	9	9	12	46	Non-ducted	7.3	9.4	9.4	9.4	12.5	8.2	10.6	10.6	10.6	14.1	12.0	48.0	54.0	0.70	3.88	4.32	
7	9	9	9	15	49	Non-ducted	6.9	8.8	8.8	8.8	14.7	7.7	9.9	9.9	9.9	16.5	12.0	48.0	54.0	0.70	3.88	4.32	
7	9	9	9	18	52	Non-ducted	6.5	8.3	8.3	8.3	16.6	7.3	9.3	9.3	9.3	18.7	12.0	48.0	54.0	0.70	3.88	4.32	
7	9	9	12	12	49	Non-ducted	6.9	8.8	8.8	11.8	11.8	7.7	9.9	9.9	13.2	13.2	12.0	48.0	54.0	0.70	3.88	4.32	
7	9	9	12	15	52	Non-ducted	6.5	8.3	8.3	11.1	13.8	7.3	9.3	9.3	12.5	15.6	12.0	48.0	54.0	0.70	3.88	4.32	
7	9	9	12	18	52	Non-ducted	6.5	8.3	11.1	11.1	11.1	7.3	9.3	12.5	12.5	12.5	12.0	48.0	54.0	0.70	3.88	4.32	
9	9	9	9	9	45	Non-ducted	9.6	9.6	9.6	9.6	9.6	10.8	10.8	10.8	10.8	10.8	12.0	48.0	54.0	0.70	3.88	4.32	
9	9	9	9	12	48	Non-ducted	9.0	9.0	9.0	9.0	9.0	12.0	10.1	10.1	10.1	10.1	13.5	12.0	48.0	54.0	0.70	3.88	4.32
9	9	9	9	15	51	Non-ducted	8.5	8.5	8.5	8.5	14.1	9.5	9.5	9.5	9.5	15.9	12.0	48.0	54.0	0.70	3.88	4.32	
9	9	9	9	18	54	Non-ducted	8.0	8.0	8.0	8.0	16.0	9.0	9.0	9.0	9.0	18.0	12.0	48.0	54.0	0.70	3.88	4.32	
9	9	9	12	12	51	Non-ducted	8.5	8.5	8.5	11.3	11.3	9.5	9.5	9.5	12.7	12.7	12.0	48.0	54.0	0.70	3.88	4.32	
9	9	9	12	15	54	Non-ducted	8.0	8.0	8.0	10.7	13.3	9.0	9.0	9.0	12.0	15.0	12.0	48.0	54.0	0.70	3.88	4.32	
9	9	9	12	12	54	Non-ducted	8.0	8.0	10.7	10.7	10.7	9.0	9.0	12.0	12.0	12.0	12.0	48.0	54.0	0.70	3.88	4.32	
12	24	—	—	—	36	Ducted	12.3	24.5	—	—	—	14.4	28.8	—	—	—	12.0	36.8	43.2	0.70	3.26	3.48	
18	18	—	—	—	36	Ducted	18.4	18.4	—	—	—	21.6	21.6	—	—	—	12.0	36.					

Combination of indoor unit					Type of in-door unit	Rated capacity for each indoor unit [kBtu/h]					Maximum capacity for each in-door unit [kBtu/h]					Total capacity [kBtu/h]			Input power [kW]		
						room					room					Min.	Rated	Max.	Min.	Rated	Max.
1	2	3	4	5		1	2	3	4	5	1	2	3	4	5						
7	9	12	24	—	Ducted	6.2	8.0	10.6	21.2	—	7.3	9.3	12.5	24.9	—	12.0	46.0	54.0	0.70	3.83	4.41
7	9	18	18	—	Ducted	6.2	8.0	15.9	15.9	—	7.3	9.3	18.7	18.7	—	12.0	46.0	54.0	0.70	3.89	4.41
7	12	12	12	—	Ducted	7.2	12.3	12.3	12.3	—	8.4	14.4	14.4	14.4	—	12.0	44.0	51.6	0.70	3.79	4.21
7	12	12	18	—	Ducted	6.6	11.3	11.3	16.9	—	7.7	13.2	13.2	19.8	—	12.0	46.0	54.0	0.70	3.97	4.41
9	9	9	9	—	Ducted	9.2	9.2	9.2	9.2	—	10.8	10.8	10.8	10.8	—	12.0	36.8	43.2	0.70	3.13	3.48
9	9	9	12	—	Ducted	9.2	9.2	9.2	12.3	—	10.8	10.8	10.8	14.4	—	12.0	39.9	46.8	0.70	3.34	3.79
9	9	9	18	—	Ducted	9.2	9.2	9.2	18.4	—	10.8	10.8	10.8	21.6	—	12.0	46.0	54.0	0.70	3.89	4.41
9	9	9	24	—	Ducted	8.1	8.1	8.1	21.6	—	9.5	9.5	9.5	25.4	—	12.0	46.0	54.0	0.70	3.89	4.41
9	9	12	12	—	Ducted	9.2	9.2	12.3	12.3	—	10.8	10.8	14.4	14.4	—	12.0	42.9	50.4	0.70	3.61	4.10
9	9	12	18	—	Ducted	8.6	8.6	11.5	17.3	—	10.1	10.1	13.5	20.3	—	12.0	46.0	54.0	0.70	3.89	4.41
9	9	12	24	—	Ducted	7.7	7.7	10.2	20.4	—	9.0	9.0	12.0	24.0	—	12.0	46.0	54.0	0.70	3.89	4.41
9	9	18	18	—	Ducted	7.7	7.7	15.3	15.3	—	9.0	9.0	18.0	18.0	—	12.0	46.0	54.0	0.70	3.97	4.41
9	12	12	12	—	Ducted	9.2	12.3	12.3	12.3	—	10.8	14.4	14.4	14.4	—	12.0	46.0	54.0	0.70	3.97	4.41
9	12	12	18	—	Ducted	8.1	10.8	10.8	16.2	—	9.5	12.7	12.7	19.1	—	12.0	46.0	54.0	0.70	3.97	4.41
12	12	12	12	—	Ducted	11.5	11.5	11.5	11.5	—	13.5	13.5	13.5	13.5	—	12.0	46.0	54.0	0.70	3.89	4.41
12	12	12	18	—	Ducted	10.2	10.2	10.2	15.3	—	12.0	12.0	12.0	18.0	—	12.0	46.0	54.0	0.70	3.89	4.41
12	12	12	18	—	Ducted	10.2	10.2	10.2	15.3	—	12.0	12.0	12.0	18.0	—	12.0	46.0	54.0	0.70	3.89	4.41
7	7	7	7	7	Ducted	7.2	7.2	7.2	7.2	7.2	8.4	8.4	8.4	8.4	8.4	12.0	35.8	42.0	0.70	2.98	3.38
7	7	7	7	9	Ducted	7.2	7.2	7.2	7.2	9.2	8.4	8.4	8.4	8.4	8.4	12.0	37.8	44.4	0.70	3.16	3.58
7	7	7	7	12	Ducted	7.2	7.2	7.2	7.2	12.3	8.4	8.4	8.4	8.4	8.4	12.0	40.9	48.0	0.70	3.43	3.89
7	7	7	7	18	Ducted	7.0	7.0	7.0	7.0	18.0	8.2	8.2	8.2	8.2	21.1	12.0	46.0	54.0	0.70	3.89	4.41
7	7	7	7	24	Ducted	6.2	6.2	6.2	6.2	21.2	7.3	7.3	7.3	24.9	12.0	46.0	54.0	0.70	3.89	4.41	
7	7	7	9	9	Ducted	7.2	7.2	7.2	9.2	9.2	8.4	8.4	8.4	8.4	8.4	12.0	39.9	46.8	0.70	3.34	3.79
7	7	7	9	12	Ducted	7.2	7.2	7.2	7.2	12.3	8.4	8.4	8.4	8.4	8.4	12.0	42.9	50.4	0.70	3.61	4.10
7	7	7	9	18	Ducted	6.7	6.7	6.7	8.6	17.3	7.9	7.9	7.9	10.1	20.3	12.0	46.0	54.0	0.70	3.89	4.41
7	7	7	9	24	Ducted	6.0	6.0	6.0	7.7	20.4	7.0	7.0	7.0	9.0	24.0	12.0	46.0	54.0	0.70	3.89	4.41
7	7	7	12	12	Ducted	7.2	7.2	7.2	12.3	12.3	8.4	8.4	8.4	14.4	14.4	12.0	46.0	54.0	0.70	3.89	4.41
7	7	7	12	18	Ducted	6.3	6.3	6.3	10.8	16.2	7.4	7.4	7.4	12.7	19.1	12.0	46.0	54.0	0.70	3.89	4.41
7	7	9	9	9	Ducted	7.2	7.2	9.2	9.2	9.2	8.4	8.4	8.4	8.4	8.4	12.0	41.9	49.2	0.70	3.49	4.00
7	7	9	9	12	Ducted	7.2	7.2	9.2	9.2	12.3	8.4	8.4	8.4	10.8	10.8	12.0	45.0	52.8	0.70	3.80	4.31
7	7	9	9	18	Ducted	6.4	6.4	8.3	8.3	16.6	7.6	7.6	9.7	9.7	19.4	12.0	46.0	54.0	0.70	3.89	4.41
7	7	9	12	12	Ducted	6.9	6.9	8.8	11.7	11.7	8.0	8.0	10.3	13.8	13.8	12.0	46.0	54.0	0.70	3.89	4.41
7	7	9	12	18	Ducted	6.1	6.1	7.8	10.4	15.6	7.1	7.1	9.2	12.2	18.3	12.0	46.0	54.0	0.70	3.89	4.41
7	7	12	12	12	Ducted	6.4	6.4	11.0	11.0	11.0	7.6	7.6	13.0	13.0	13.0	12.0	46.0	54.0	0.70	3.89	4.41
7	9	9	9	9	Ducted	7.2	9.2	9.2	9.2	9.2	8.4	10.8	10.8	10.8	12.0	44.0	51.6	0.70	3.71	4.21	
7	9	9	9	12	Ducted	7.0	9.0	9.0	9.0	12.0	8.2	10.6	10.6	10.6	14.1	12.0	46.0	54.0	0.70	3.89	4.41
7	9	9	9	18	Ducted	6.2	8.0	8.0	8.0	15.9	7.3	9.3	9.3	9.3	18.7	12.0	46.0	54.0	0.70	3.89	4.41
7	9	9	12	12	Ducted	6.6	8.4	8.4	11.3	11.3	7.7	9.9	9.9	13.2	13.2	12.0	46.0	54.0	0.70	3.89	4.41
7	9	9	12	18	Ducted	6.2	8.0	10.6	10.6	10.6	7.3	9.3	12.5	12.5	12.0	46.0	54.0	0.70	3.83	4.41	
9	9	9	9	9	Ducted	9.2	9.2	9.2	9.2	10.8	10.8	10.8	10.8	10.8	12.0	46.0	54.0	0.70	3.89	4.41	
9	9	9	9	12	Ducted	8.6	8.6	8.6	8.6	11.5	10.1	10.1	10.1	10.1	13.5	12.0	46.0	54.0	0.70	3.89	4.41
9	9	9	9	18	Ducted	7.7	7.7	7.7	7.7	15.3	9.0	9.0	9.0	9.0	18.0	12.0	46.0	54.0	0.70	3.89	4.41
9	9	9	12	12	Ducted	8.1	8.1	8.1	10.8	10.8	9.5	9.5	9.5	12.7	12.7	12.0	46.0	54.0	0.70	3.89	4.41
9	9	12	12	12	Ducted	7.7	7.7	10.2	10.2	10.2	9.0	9.0	12.0	12.0	12.0	46.0	54.0	0.70	3.89	4.41	

**NOTES:**

- Specifications are based on the following conditions.
  - Power source of specifications: 230 V
  - 7: 7,000 Btu/h, 9: 9,000 Btu/h, 12: 12,000 Btu/h, 15: 14,000 Btu/h, 18: 18,000 Btu/h, 24: 24,000 Btu/h
  - 2 or more indoor units should be connected.
  - Heating: Indoor temperature of 70 °FDB (21.1 °CDB) / 60 °FWB (15.6 °CWB), and outdoor temperature of 47 °FDB (8.3 °CDB) / 43 °FWB (6.1 °CWB).
  - Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]
  - The total ability of connected a indoor unit is from 34,000 Btu up to 54,000 Btu.
  - Non-Ducted system combinations input are based on wall mount models. The input of combinations including cassette models may be a little higher.
  - Ducted system combinations capacities are based on slim duct units.
- Combination of 15+24 (14,000 Btu/h+24,000 Btu/h) of the indoor units is prohibited.

## 6-2. Cooling capacity

### ■ Model: AOU45RLXFZ

**NOTE:** Values mentioned in the table are calculated based on the maximum capacity.

#### ● Unit: kBtu/h, °F

TC: Total Capacity (kBtu/h), IP: Input Power (kW)

Indoor unit connecting capacity	Outdoor temperature	Indoor temperature											
		64 °FDB		70 °FDB		75 °FDB		80 °FDB		85 °FDB		90 °FDB	
		54 °FWB		60 °FWB		63 °FWB		67 °FWB		71 °FWB		73 °FWB	
kBtu/h	°FDB	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
54	14	37.6	1.71	42.5	1.74	44.8	1.76	48.0	1.78	51.3	1.80	52.9	1.81
	23	37.6	1.70	42.5	1.73	44.8	1.75	48.0	1.77	51.3	1.79	52.9	1.80
	32	37.6	1.69	42.5	1.72	44.8	1.74	48.0	1.76	51.3	1.78	52.9	1.79
	41	37.6	1.89	42.5	1.92	44.8	1.94	48.0	1.96	51.3	1.98	52.9	1.99
	50	37.6	2.08	42.5	2.12	44.8	2.13	48.0	2.16	51.3	2.18	52.9	2.19
	59	37.6	2.86	42.5	2.91	44.8	2.94	48.0	2.97	51.3	3.00	52.9	3.02
	67	37.6	3.65	42.5	3.71	44.8	3.74	48.0	3.78	51.3	3.82	52.9	3.85
	77	37.6	4.02	42.5	4.09	44.8	4.12	48.0	4.17	51.3	4.21	52.9	4.24
	87	37.6	4.39	42.5	4.46	44.8	4.50	48.0	4.55	51.3	4.60	52.9	4.63
	95	37.6	4.68	42.5	4.77	44.8	4.81	48.0	4.86	51.3	4.92	52.9	4.94
	104	32.7	4.35	37.0	4.43	39.0	4.46	41.8	4.51	44.6	4.56	46.0	4.59
	115	27.8	4.01	31.5	4.08	33.2	4.12	35.5	4.16	38.0	4.21	39.1	4.23
53	14	37.6	1.71	42.5	1.74	44.8	1.76	48.0	1.78	51.3	1.80	52.9	1.81
	23	37.6	1.70	42.5	1.73	44.8	1.75	48.0	1.77	51.3	1.79	52.9	1.80
	32	37.6	1.69	42.5	1.72	44.8	1.74	48.0	1.76	51.3	1.78	52.9	1.79
	41	37.6	1.89	42.5	1.92	44.8	1.94	48.0	1.96	51.3	1.98	52.9	1.99
	50	37.6	2.08	42.5	2.12	44.8	2.13	48.0	2.16	51.3	2.18	52.9	2.19
	59	37.6	2.86	42.5	2.91	44.8	2.94	48.0	2.97	51.3	3.00	52.9	3.02
	67	37.6	3.65	42.5	3.71	44.8	3.74	48.0	3.78	51.3	3.82	52.9	3.85
	77	37.6	4.02	42.5	4.09	44.8	4.12	48.0	4.17	51.3	4.21	52.9	4.24
	87	37.6	4.39	42.5	4.46	44.8	4.50	48.0	4.55	51.3	4.60	52.9	4.63
	95	37.6	4.68	42.5	4.77	44.8	4.81	48.0	4.86	51.3	4.92	52.9	4.94
	104	32.7	4.35	37.0	4.43	39.0	4.46	41.8	4.51	44.6	4.56	46.0	4.59
	115	27.8	4.01	31.5	4.08	33.2	4.12	35.5	4.16	38.0	4.21	39.1	4.23
52	14	37.6	1.71	42.5	1.74	44.8	1.76	48.0	1.78	51.3	1.80	52.9	1.81
	23	37.6	1.70	42.5	1.73	44.8	1.75	48.0	1.77	51.3	1.79	52.9	1.80
	32	37.6	1.69	42.5	1.72	44.8	1.74	48.0	1.76	51.3	1.78	52.9	1.79
	41	37.6	1.89	42.5	1.92	44.8	1.94	48.0	1.96	51.3	1.98	52.9	1.99
	50	37.6	2.08	42.5	2.12	44.8	2.13	48.0	2.16	51.3	2.18	52.9	2.19
	59	37.6	2.86	42.5	2.91	44.8	2.94	48.0	2.97	51.3	3.00	52.9	3.02
	67	37.6	3.65	42.5	3.71	44.8	3.74	48.0	3.78	51.3	3.82	52.9	3.85
	77	37.6	4.02	42.5	4.09	44.8	4.12	48.0	4.17	51.3	4.21	52.9	4.24
	87	37.6	4.39	42.5	4.46	44.8	4.50	48.0	4.55	51.3	4.60	52.9	4.63
	95	37.6	4.68	42.5	4.77	44.8	4.81	48.0	4.86	51.3	4.92	52.9	4.94
	104	32.7	4.35	37.0	4.43	39.0	4.46	41.8	4.51	44.6	4.56	46.0	4.59
	115	27.8	4.01	31.5	4.08	33.2	4.12	35.5	4.16	38.0	4.21	39.1	4.23
51	14	37.6	1.71	42.5	1.74	44.8	1.76	48.0	1.78	51.3	1.80	52.9	1.81
	23	37.6	1.70	42.5	1.73	44.8	1.75	48.0	1.77	51.3	1.79	52.9	1.80
	32	37.6	1.69	42.5	1.72	44.8	1.74	48.0	1.76	51.3	1.78	52.9	1.79
	41	37.6	1.89	42.5	1.92	44.8	1.94	48.0	1.96	51.3	1.98	52.9	1.99
	50	37.6	2.08	42.5	2.12	44.8	2.13	48.0	2.16	51.3	2.18	52.9	2.19
	59	37.6	2.86	42.5	2.91	44.8	2.94	48.0	2.97	51.3	3.00	52.9	3.02
	67	37.6	3.65	42.5	3.71	44.8	3.74	48.0	3.78	51.3	3.82	52.9	3.85
	77	37.6	4.02	42.5	4.09	44.8	4.12	48.0	4.17	51.3	4.21	52.9	4.24
	87	37.6	4.39	42.5	4.46	44.8	4.50	48.0	4.55	51.3	4.60	52.9	4.63
	95	37.6	4.68	42.5	4.77	44.8	4.81	48.0	4.86	51.3	4.92	52.9	4.94
	104	32.7	4.35	37.0	4.43	39.0	4.46	41.8	4.51	44.6	4.56	46.0	4.59
	115	27.8	4.01	31.5	4.08	33.2	4.12	35.5	4.16	38.0	4.21	39.1	4.23
50	14	37.6	1.71	42.5	1.74	44.8	1.76	48.0	1.78	51.3	1.80	52.9	1.81
	23	37.6	1.70	42.5	1.73	44.8	1.75	48.0	1.77	51.3	1.79	52.9	1.80
	32	37.6	1.69	42.5	1.72	44.8	1.74	48.0	1.76	51.3	1.78	52.9	1.79
	41	37.6	1.89	42.5	1.92	44.8	1.94	48.0	1.96	51.3	1.98	52.9	1.99
	50	37.6	2.08	42.5	2.12	44.8	2.13	48.0	2.16	51.3	2.18	52.9	2.19
	59	37.6	2.86	42.5	2.91	44.8	2.94	48.0	2.97	51.3	3.00	52.9	3.02
	67	37.6	3.65	42.5	3.71	44.8	3.74	48.0	3.78	51.3	3.82	52.9	3.85
	77	37.6	4.02	42.5	4.09	44.8	4.12	48.0	4.17	51.3	4.21	52.9	4.24
	87	37.6	4.39	42.5	4.46	44.8	4.50	48.0	4.55	51.3	4.60	52.9	4.63
	95	37.6	4.68	42.5	4.77	44.8	4.81	48.0	4.86	51.3	4.92	52.9	4.94
	104	32.7	4.35	37.0	4.43	39.0	4.46	41.8	4.51	44.6	4.56	46.0	4.59
	115	27.8	4.01	31.5	4.08	33.2	4.12	35.5	4.16	38.0	4.21	39.1	4.23
49	14	37.6	1.71	42.5	1.74	44.8	1.76	48.0	1.78	51.3	1.80	52.9	1.81
	23	37.6	1.70	42.5	1.73	44.8	1.75	48.0	1.77	51.3	1.79	52.9	1.80
	32	37.6	1.69	42.5	1.72	44.8	1.74	48.0	1.76	51.3	1.78	52.9	1.79
	41	37.6	1.89	42.5	1.92	44.8	1.94	48.0	1.96	51.3	1.98	52.9	1.99
	50	37.6	2.08	42.5	2.12	44.8	2.13	48.0	2.16	51.3	2.18	52.9	2.19
	59	37.6	2.86	42.5	2.91	44.8	2.94	48.0	2.97	51.3	3.00	52.9	3.02
	67	37.6	3.65	42.5	3.71	44.8	3.74	48.0	3.78	51.3	3.82	52.9	3.85
	77	37.6	4.02	42.5	4.09	44.8	4.12	48.0	4.17	51.3	4.21	52.9	4.24
	87	37.6	4.39	42.5	4.46	44.8	4.50	48.0	4.55	51.3	4.60	52.9	4.63
	95	37.6	4.68	42.5	4.77	44.8	4.81	48.0	4.86	51.3	4.92	52.9	4.94
	104	32.7	4.35	37.0	4.43	39.0	4.46	41.8	4.51	44.6	4.56	46.0	4.59
	115	27.8	4.01	31.5	4.08	33.2	4.12	35.5	4.16	38.0	4.21	39.1	4.23

Indoor unit connect-ing capacity	Outdoor temperature	Indoor temperature											
		64 °FDB		70 °FDB		75 °FDB		80 °FDB		85 °FDB		90 °FDB	
		54 °FWB		60 °FWB		63 °FWB		67 °FWB		71 °FWB		73 °FWB	
kBtu/h	°FDB	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
48	14	37.6	1.71	42.5	1.74	44.8	1.76	48.0	1.78	51.3	1.80	52.9	1.81
	23	37.6	1.70	42.5	1.73	44.8	1.75	48.0	1.77	51.3	1.79	52.9	1.80
	32	37.6	1.69	42.5	1.72	44.8	1.74	48.0	1.76	51.3	1.78	52.9	1.79
	41	37.6	1.89	42.5	1.92	44.8	1.94	48.0	1.96	51.3	1.98	52.9	1.99
	50	37.6	2.08	42.5	2.12	44.8	2.13	48.0	2.16	51.3	2.18	52.9	2.19
	59	37.6	2.86	42.5	2.91	44.8	2.94	48.0	2.97	51.3	3.00	52.9	3.02
	67	37.6	3.65	42.5	3.71	44.8	3.74	48.0	3.78	51.3	3.82	52.9	3.85
	77	37.6	4.02	42.5	4.09	44.8	4.12	48.0	4.17	51.3	4.21	52.9	4.24
	87	37.6	4.39	42.5	4.46	44.8	4.50	48.0	4.55	51.3	4.60	52.9	4.63
	95	37.6	4.68	42.5	4.77	44.8	4.81	48.0	4.86	51.3	4.92	52.9	4.94
	104	32.7	4.35	37.0	4.43	39.0	4.46	41.8	4.51	44.6	4.56	46.0	4.59
	115	27.8	4.01	31.5	4.08	33.2	4.12	35.5	4.16	38.0	4.21	39.1	4.23
47	14	37.6	1.71	42.5	1.74	44.8	1.76	48.0	1.78	51.3	1.80	52.9	1.81
	23	37.6	1.70	42.5	1.73	44.8	1.75	48.0	1.77	51.3	1.79	52.9	1.80
	32	37.6	1.69	42.5	1.72	44.8	1.74	48.0	1.76	51.3	1.78	52.9	1.79
	41	37.6	1.89	42.5	1.92	44.8	1.94	48.0	1.96	51.3	1.98	52.9	1.99
	50	37.6	2.08	42.5	2.12	44.8	2.13	48.0	2.16	51.3	2.18	52.9	2.19
	59	37.6	2.86	42.5	2.91	44.8	2.94	48.0	2.97	51.3	3.00	52.9	3.02
	67	37.6	3.65	42.5	3.71	44.8	3.74	48.0	3.78	51.3	3.82	52.9	3.85
	77	37.6	4.02	42.5	4.09	44.8	4.12	48.0	4.17	51.3	4.21	52.9	4.24
	87	37.6	4.39	42.5	4.46	44.8	4.50	48.0	4.55	51.3	4.60	52.9	4.63
	95	37.6	4.68	42.5	4.77	44.8	4.81	48.0	4.86	51.3	4.92	52.9	4.94
	104	32.7	4.35	37.0	4.43	39.0	4.46	41.8	4.51	44.6	4.56	46.0	4.59
	115	27.8	4.01	31.5	4.08	33.2	4.12	35.5	4.16	38.0	4.21	39.1	4.23
46	14	37.6	1.71	42.5	1.74	44.8	1.76	48.0	1.78	51.3	1.80	52.9	1.81
	23	37.6	1.70	42.5	1.73	44.8	1.75	48.0	1.77	51.3	1.79	52.9	1.80
	32	37.6	1.69	42.5	1.72	44.8	1.74	48.0	1.76	51.3	1.78	52.9	1.79
	41	37.6	1.89	42.5	1.92	44.8	1.94	48.0	1.96	51.3	1.98	52.9	1.99
	50	37.6	2.08	42.5	2.12	44.8	2.13	48.0	2.16	51.3	2.18	52.9	2.19
	59	37.6	2.86	42.5	2.91	44.8	2.94	48.0	2.97	51.3	3.00	52.9	3.02
	67	37.6	3.65	42.5	3.71	44.8	3.74	48.0	3.78	51.3	3.82	52.9	3.85
	77	37.6	4.02	42.5	4.09	44.8	4.12	48.0	4.17	51.3	4.21	52.9	4.24
	87	37.6	4.39	42.5	4.46	44.8	4.50	48.0	4.55	51.3	4.60	52.9	4.63
	95	37.6	4.68	42.5	4.77	44.8	4.81	48.0	4.86	51.3	4.92	52.9	4.94
	104	32.7	4.35	37.0	4.43	39.0	4.46	41.8	4.51	44.6	4.56	46.0	4.59
	115	27.8	4.01	31.5	4.08	33.2	4.12	35.5	4.16	38.0	4.21	39.1	4.23
45	14	37.6	1.71	42.5	1.74	44.8	1.76	48.0	1.78	51.3	1.80	52.9	1.81
	23	37.6	1.70	42.5	1.73	44.8	1.75	48.0	1.77	51.3	1.79	52.9	1.80
	32	37.6	1.69	42.5	1.72	44.8	1.74	48.0	1.76	51.3	1.78	52.9	1.79
	41	37.6	1.89	42.5	1.92	44.8	1.94	48.0	1.96	51.3	1.98	52.9	1.99
	50	37.6	2.08	42.5	2.12	44.8	2.13	48.0	2.16	51.3	2.18	52.9	2.19
	59	37.6	2.86	42.5	2.91	44.8	2.94	48.0	2.97	51.3	3.00	52.9	3.02
	67	37.6	3.65	42.5	3.71	44.8	3.74	48.0	3.78	51.3	3.82	52.9	3.85
	77	37.6	4.02	42.5	4.09	44.8	4.12	48.0	4.17	51.3	4.21	52.9	4.24
	87	37.6	4.39	42.5	4.46	44.8	4.50	48.0	4.55	51.3	4.60	52.9	4.63
	95	37.6	4.68	42.5	4.77	44.8	4.81	48.0	4.86	51.3	4.92	52.9	4.94
	104	32.7	4.35	37.0	4.43	39.0	4.46	41.8	4.51	44.6	4.56	46.0	4.59
	115	27.8	4.01	31.5	4.08	33.2	4.12	35.5	4.16	38.0	4.21	39.1	4.23
44	14	36.8	1.68	41.6	1.71	43.8	1.72	46.9	1.74	50.2	1.76	51.7	1.77
	23	36.8	1.67	41.6	1.70	43.8	1.71	46.9	1.73	50.2	1.75	51.7	1.76
	32	36.8	1.66	41.6	1.69	43.8	1.70	46.9	1.72	50.2	1.74	51.7	1.75
	41	36.8	1.85	41.6	1.88	43.8	1.90	46.9	1.92	50.2	1.94	51.7	1.95
	50	36.8	2.04	41.6	2.07	43.8	2.09	46.9	2.11	50.2	2.14	51.7	2.15
	59	36.8	2.81	41.6	2.85	43.8	2.88	46.9	2.91	50.2	2.94	51.7	2.96
	67	36.8	3.57	41.6	3.64	43.8	3.67	46.9	3.71	50.2	3.75	51.7	3.77
	77	36.8	3.94	41.6	4.01	43.8	4.04	46.9	4.08	50.2	4.13	51.7	4.15
	87	36.8	4.30	41.6	4.38	43.8	4.41	46.9	4.46	50.2	4.51	51.7	4.54
	95	36.8	4.59	41.6	4.67	43.8	4.71	46.9	4.76	50.2	4.82	51.7	4.84
	104	32.0	4.26	36.2	4.34	38.1	4.37	40.8	4.42	43.6	4.47	45.0	4.50
	115	27.2	3.93	30.8	4.00	32.4	4.04	34.7	4.08	37.1	4.13	38.3	4.15
43	14	36.0	1.62	40.6	1.65	42.8	1.66	45.9	1.68	49.0	1.70	50.5	1.71
	23	36.0	1.61	40.6	1.64	42.8	1.65	45.9	1.67	49.0	1.69	50.5	1.70
	32	36.0	1.60	40.6	1.63	42.8	1.64	45.9	1.66	49.0	1.68	50.5	1.69
	41	36.0	1.79	40.6	1.82	42.8	1.83	45.9	1.85	49.0	1.87	50.5	1.88
	50	36.0	1.97	40.6	2.00	42.8	2.02	45.9	2.04	49.0	2.07	50.5	2.08
	59	36.0	2.71	40.6	2.76	42.8	2.78	45.9	2.81	49.0	2.84	50.5	2.86
	67	36.0	3.45	40.6	3.51	42.8	3.54	45.9	3.58	49.0	3.62	50.5	3.64
	77	36.0	3.80	40.6	3.87	42.8	3.90	45.9	3.95	49.0	3.99	50.5	4.01
	87	36.0	4.15	40.6	4.23	42.8	4.26	45.9	4.31	49.0	4.36	50.5	4.38
	95	36.0	4.44	40.6	4.51	42.8	4.55	45.9	4.60	49.0	4.65	50.5	4.68
	104	31.3	4.12	35.3	4.19	37.3	4.23	39.9	4.27	42.7	4.32	44.0	4.34
	115	26.6	3.80	30.1	3.87	31.7	3.90	33.9	3.94	36.3	3.99	37.4	4.01
42	14	35.1	1.56	39.7	1.59	41.8	1.60	44.8	1.62	47.9	1.64	49.4	1.65
	23	35.1	1.56	39.7	1.58	41.8	1.60	44.8	1.61	47.9	1.63	49.4	1.64
	32	35.1	1.55	39.7	1.57	41.8	1.59	44.8	1.60	47.9	1.62	49.4	1.63
	41	35.1	1.72	39.7	1.75	41.8	1.77	44.8	1.79	47.9	1.81	49.4	1.82
	50	35.1	1.90	39.7	1.93	41.8	1.95	44.8	1.97	47.9	1.99	49.4	2.01
	59	35.1	2.62	39.7	2.66	41.8	2.68	44.8	2.71	47.9	2.74	49.4	2.76
	67	35.1											

Indoor unit connect-ing capacity	Outdoor temperature	Indoor temperature											
		64 °FDB		70 °FDB		75 °FDB		80 °FDB		85 °FDB		90 °FDB	
		54 °FWB		60 °FWB		63 °FWB		67 °FWB		71 °FWB		73 °FWB	
kBtu/h	°FDB	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
41	14	34.3	1.51	38.7	1.53	40.8	1.55	43.7	1.56	46.8	1.58	48.2	1.59
	23	34.3	1.50	38.7	1.53	40.8	1.54	43.7	1.56	46.8	1.57	48.2	1.58
	32	34.3	1.49	38.7	1.52	40.8	1.53	43.7	1.55	46.8	1.56	48.2	1.57
	41	34.3	1.66	38.7	1.69	40.8	1.70	43.7	1.72	46.8	1.74	48.2	1.75
	50	34.3	1.83	38.7	1.86	40.8	1.88	43.7	1.90	46.8	1.92	48.2	1.93
	59	34.3	2.52	38.7	2.57	40.8	2.59	43.7	2.62	46.8	2.65	48.2	2.66
	67	34.3	3.21	38.7	3.27	40.8	3.29	43.7	3.33	46.8	3.37	48.2	3.39
	77	34.3	3.54	38.7	3.60	40.8	3.63	43.7	3.67	46.8	3.71	48.2	3.73
	87	34.3	3.86	38.7	3.93	40.8	3.96	43.7	4.01	46.8	4.05	48.2	4.08
	95	34.3	4.13	38.7	4.20	40.8	4.23	43.7	4.28	46.8	4.33	48.2	4.35
	104	29.8	3.83	33.7	3.90	35.5	3.93	38.0	3.97	40.7	4.02	41.9	4.04
	115	25.4	3.54	28.7	3.60	30.2	3.63	32.4	3.67	34.6	3.71	35.7	3.73
40	14	33.5	1.45	37.8	1.48	39.9	1.49	42.7	1.50	45.6	1.52	47.0	1.53
	23	33.5	1.44	37.8	1.47	39.9	1.48	42.7	1.50	45.6	1.51	47.0	1.52
	32	33.5	1.44	37.8	1.46	39.9	1.47	42.7	1.49	45.6	1.51	47.0	1.51
	41	33.5	1.60	37.8	1.63	39.9	1.64	42.7	1.66	45.6	1.68	47.0	1.69
	50	33.5	1.76	37.8	1.79	39.9	1.81	42.7	1.83	45.6	1.85	47.0	1.86
	59	33.5	2.43	37.8	2.47	39.9	2.49	42.7	2.52	45.6	2.55	47.0	2.56
	67	33.5	3.09	37.8	3.14	39.9	3.17	42.7	3.21	45.6	3.24	47.0	3.26
	77	33.5	3.40	37.8	3.46	39.9	3.49	42.7	3.53	45.6	3.57	47.0	3.59
	87	33.5	3.72	37.8	3.78	39.9	3.82	42.7	3.86	45.6	3.90	47.0	3.92
	95	33.5	3.97	37.8	4.04	39.9	4.07	42.7	4.12	45.6	4.17	47.0	4.19
	104	29.1	3.69	32.9	3.75	34.7	3.78	37.1	3.82	39.7	3.87	40.9	3.89
	115	24.7	3.40	28.0	3.46	29.5	3.49	31.6	3.53	33.7	3.57	34.8	3.59
39	14	32.6	1.39	36.9	1.42	38.9	1.43	41.6	1.45	44.5	1.46	45.8	1.47
	23	32.6	1.39	36.9	1.41	38.9	1.42	41.6	1.44	44.5	1.45	45.8	1.46
	32	32.6	1.38	36.9	1.40	38.9	1.41	41.6	1.43	44.5	1.45	45.8	1.45
	41	32.6	1.54	36.9	1.56	38.9	1.58	41.6	1.59	44.5	1.61	45.8	1.62
	50	32.6	1.69	36.9	1.72	38.9	1.74	41.6	1.76	44.5	1.78	45.8	1.79
	59	32.6	2.33	36.9	2.37	38.9	2.39	41.6	2.42	44.5	2.45	45.8	2.46
	67	32.6	2.97	36.9	3.02	38.9	3.05	41.6	3.08	44.5	3.12	45.8	3.13
	77	32.6	3.27	36.9	3.33	38.9	3.36	41.6	3.39	44.5	3.43	45.8	3.45
	87	32.6	3.57	36.9	3.64	38.9	3.67	41.6	3.71	44.5	3.75	45.8	3.77
	95	32.6	3.82	36.9	3.88	38.9	3.91	41.6	3.96	44.5	4.00	45.8	4.03
	104	28.4	3.54	32.1	3.61	33.8	3.63	36.2	3.67	38.7	3.72	39.9	3.74
	115	24.1	3.27	27.3	3.33	28.7	3.35	30.8	3.39	32.9	3.43	33.9	3.45
38	14	31.8	1.34	35.9	1.36	37.9	1.37	40.5	1.39	43.3	1.40	44.7	1.41
	23	31.8	1.33	35.9	1.35	37.9	1.36	40.5	1.38	43.3	1.40	44.7	1.40
	32	31.8	1.32	35.9	1.35	37.9	1.36	40.5	1.37	43.3	1.39	44.7	1.40
	41	31.8	1.47	35.9	1.50	37.9	1.51	40.5	1.53	43.3	1.55	44.7	1.56
	50	31.8	1.63	35.9	1.65	37.9	1.67	40.5	1.69	43.3	1.71	44.7	1.71
	59	31.8	2.24	35.9	2.28	37.9	2.30	40.5	2.32	43.3	2.35	44.7	2.36
	67	31.8	2.85	35.9	2.90	37.9	2.92	40.5	2.96	43.3	2.99	44.7	3.01
	77	31.8	3.14	35.9	3.19	37.9	3.22	40.5	3.26	43.3	3.29	44.7	3.31
	87	31.8	3.43	35.9	3.49	37.9	3.52	40.5	3.56	43.3	3.60	44.7	3.62
	95	31.8	3.66	35.9	3.73	37.9	3.76	40.5	3.80	43.3	3.84	44.7	3.86
	104	27.6	3.40	31.2	3.46	32.9	3.49	35.3	3.53	37.7	3.57	38.9	3.59
37	14	30.9	1.28	35.0	1.30	36.9	1.31	39.5	1.33	42.2	1.34	43.5	1.35
	23	30.9	1.27	35.0	1.29	36.9	1.30	39.5	1.32	42.2	1.34	43.5	1.34
	32	30.9	1.27	35.0	1.29	36.9	1.30	39.5	1.31	42.2	1.33	43.5	1.34
	41	30.9	1.47	35.0	1.50	36.9	1.51	39.5	1.53	42.2	1.55	44.7	1.56
	50	30.9	1.63	35.0	1.65	37.9	1.67	40.5	1.69	43.3	1.71	44.7	1.71
	59	30.9	2.14	35.0	2.18	36.9	2.20	39.5	2.22	42.2	2.25	43.5	2.26
	67	30.9	2.73	35.0	2.78	36.9	2.80	39.5	2.83	42.2	2.86	43.5	2.88
	77	30.9	3.01	35.0	3.06	36.9	3.08	39.5	3.12	42.2	3.15	43.5	3.17
	87	30.9	3.28	35.0	3.34	36.9	3.37	39.5	3.41	42.2	3.45	43.5	3.46
	95	30.9	3.51	35.0	3.57	36.9	3.60	39.5	3.64	42.2	3.68	43.5	3.70
	104	26.9	3.25	30.4	3.31	32.1	3.34	34.3	3.38	36.7	3.42	37.8	3.43
	115	22.9	3.00	25.9	3.06	27.3	3.08	29.2	3.12	31.2	3.15	32.2	3.17
36	14	30.1	1.22	34.0	1.25	35.9	1.26	38.4	1.27	41.0	1.28	42.3	1.29
	23	30.1	1.22	34.0	1.24	35.9	1.25	38.4	1.26	41.0	1.28	42.3	1.28
	32	30.1	1.21	34.0	1.23	35.9	1.24	38.4	1.26	41.0	1.27	42.3	1.28
	41	30.1	1.35	34.0	1.37	35.9	1.38	38.4	1.40	41.0	1.42	42.3	1.42
	50	30.1	1.49	34.0	1.51	35.9	1.53	38.4	1.54	41.0	1.56	42.3	1.57
	59	30.1	2.05	34.0	2.08	35.9	2.10	38.4	2.12	41.0	2.15	42.3	2.16
	67	30.1	2.61	34.0	2.65	35.9	2.68	38.4	2.70	41.0	2.74	42.3	2.75
	77	30.1	2.87	34.0	2.92	35.9	2.95	38.4	2.98	41.0	3.01	42.3	3.03
	87	30.1	3.14	34.0	3.19	35.9	3.22	38.4	3.26	41.0	3.29	42.3	3.31
	95	30.1	3.35	34.0	3.41	35.9	3.44	38.4	3.48	41.0	3.52	42.3	3.54
	104	26.2	3.11	29.6	3.17	31.2	3.19	33.4	3.23	35.7	3.26	36.8	3.28
	115	22.3	2.87	25.2	2.92	26.5	2.95	28.4	2.98	30.4	3.01	31.3	3.03
35	14	29.3	1.17	33.1	1.19	34.9	1.20	37.3	1.21	39.9	1.23	41.1	1.23
	23	29.3	1.16	33.1	1.18	34.9	1.19	37.3	1.20	39.9	1.22	41.1	1.23
	32	29.3	1.15	33.1	1.18	34.9	1.18	37.3	1.20	39.9	1.21	41.1	1.22
	41	29.3	1.29	33.1	1.31	34.9	1.32	37.3	1.34	39.9	1.35	41.1	1.36
	50	29.3	1.42	33.1	1.44	34.9	1.46	37.3	1.47	39.9	1.49	41.1	1.50
	59	29.3	1.95	33.1	1.99	34.9	2.00	37.3	2.03	39.9	2.05	41.1	2.06
	67	29.3	2.49	33.1	2.53	34.9	2.55	37.3	2.58	39.9	2.61	41.1	2.62
	77	29.3</											

Indoor unit connect-ing capacity	Outdoor temperature	Indoor temperature											
		64 °FDB		70 °FDB		75 °FDB		80 °FDB		85 °FDB		90 °FDB	
		54 °FWB		60 °FWB		63 °FWB		67 °FWB		71 °FWB		73 °FWB	
kBtu/h	°FDB	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
34	14	28.4	1.11	32.1	1.13	33.9	1.14	36.3	1.15	38.8	1.17	40.0	1.17
	23	28.4	1.10	32.1	1.12	33.9	1.13	36.3	1.15	38.8	1.16	40.0	1.17
	32	28.4	1.10	32.1	1.12	33.9	1.13	36.3	1.14	38.8	1.15	40.0	1.16
	41	28.4	1.22	32.1	1.25	33.9	1.26	36.3	1.27	38.8	1.28	40.0	1.29
	50	28.4	1.35	32.1	1.37	33.9	1.39	36.3	1.40	38.8	1.42	40.0	1.42
	59	28.4	1.86	32.1	1.89	33.9	1.91	36.3	1.93	38.8	1.95	40.0	1.96
	67	28.4	2.37	32.1	2.41	33.9	2.43	36.3	2.45	38.8	2.48	40.0	2.50
	77	28.4	2.61	32.1	2.65	33.9	2.67	36.3	2.70	38.8	2.74	40.0	2.75
	87	28.4	2.85	32.1	2.90	33.9	2.92	36.3	2.95	38.8	2.99	40.0	3.00
	95	28.4	3.04	32.1	3.09	33.9	3.12	36.3	3.15	38.8	3.19	40.0	3.21
	104	24.7	2.82	28.0	2.87	29.5	2.90	31.5	2.93	33.7	2.96	34.8	2.98
	115	21.0	2.61	23.8	2.65	25.1	2.67	26.8	2.70	28.7	2.73	29.6	2.75

**NOTE:** Specifications are based on the following conditions.

- Power source of specifications: 230 V
- 2 or more indoor units should be connected.
- Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]
- The total ability of connected a indoor unit is from 34,000 Btu up to 54,000 Btu.
- Input in the table are calculated based on the maximum indoor unit input combinations.

**● Unit: kW, °C**

TC: Total Capacity (kW), IP: Input Power (kW)

**OUTDOOR UNIT**  
AOU45RLXFZ

**OUTDOOR UNIT**  
AOU45RLXFZ

Indoor unit connecting capacity	Outdoor temperature	Indoor temperature											
		17.8 °CDB		21.1 °CDB		23.9 °CDB		26.7 °CDB		29.4 °CDB		32.2 °CDB	
		12.2 °CWB		15.6 °CWB		17.2 °CWB		19.4 °CWB		21.7 °CWB		22.8 °CWB	
kBtu/h	°CDB	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
54	-10.0	11.02	1.71	12.46	1.74	13.13	1.76	14.00	1.78	15.03	1.80	15.50	1.81
	-5.0	11.02	1.70	12.46	1.73	13.13	1.75	14.00	1.77	15.03	1.79	15.50	1.80
	0.0	11.02	1.69	12.46	1.72	13.13	1.74	14.00	1.76	15.03	1.78	15.50	1.79
	5.0	11.02	1.89	12.46	1.92	13.13	1.94	14.00	1.96	15.03	1.98	15.50	1.99
	10.0	11.02	2.08	12.46	2.12	13.13	2.13	14.00	2.16	15.03	2.18	15.50	2.19
	15.0	11.02	2.86	12.46	2.91	13.13	2.94	14.00	2.97	15.03	3.00	15.50	3.02
	20.0	11.02	3.65	12.46	3.71	13.13	3.74	14.00	3.78	15.03	3.82	15.50	3.85
	25.0	11.02	4.02	12.46	4.09	13.13	4.12	14.00	4.17	15.03	4.21	15.50	4.24
	30.0	11.02	4.39	12.46	4.46	13.13	4.50	14.00	4.55	15.03	4.60	15.50	4.63
	35.0	11.02	4.68	12.46	4.77	13.13	4.81	14.00	4.86	15.03	4.92	15.50	4.94
	40.0	9.59	4.35	10.84	4.43	11.42	4.46	12.20	4.51	13.08	4.56	13.48	4.59
	46.1	8.15	4.01	9.22	4.08	9.71	4.12	10.40	4.16	11.12	4.21	11.46	4.23
53	-10.0	11.02	1.71	12.46	1.74	13.13	1.76	14.00	1.78	15.03	1.80	15.50	1.81
	-5.0	11.02	1.70	12.46	1.73	13.13	1.75	14.00	1.77	15.03	1.79	15.50	1.80
	0.0	11.02	1.69	12.46	1.72	13.13	1.74	14.00	1.76	15.03	1.78	15.50	1.79
	5.0	11.02	1.89	12.46	1.92	13.13	1.94	14.00	1.96	15.03	1.98	15.50	1.99
	10.0	11.02	2.08	12.46	2.12	13.13	2.13	14.00	2.16	15.03	2.18	15.50	2.19
	15.0	11.02	2.86	12.46	2.91	13.13	2.94	14.00	2.97	15.03	3.00	15.50	3.02
	20.0	11.02	3.65	12.46	3.71	13.13	3.74	14.00	3.78	15.03	3.82	15.50	3.85
	25.0	11.02	4.02	12.46	4.09	13.13	4.12	14.00	4.17	15.03	4.21	15.50	4.24
	30.0	11.02	4.39	12.46	4.46	13.13	4.50	14.00	4.55	15.03	4.60	15.50	4.63
	35.0	11.02	4.68	12.46	4.77	13.13	4.81	14.00	4.86	15.03	4.92	15.50	4.94
	40.0	9.59	4.35	10.84	4.43	11.42	4.46	12.20	4.51	13.08	4.56	13.48	4.59
	46.1	8.15	4.01	9.22	4.08	9.71	4.12	10.40	4.16	11.12	4.21	11.46	4.23
52	-10.0	11.02	1.71	12.46	1.74	13.13	1.76	14.00	1.78	15.03	1.80	15.50	1.81
	-5.0	11.02	1.70	12.46	1.73	13.13	1.75	14.00	1.77	15.03	1.79	15.50	1.80
	0.0	11.02	1.69	12.46	1.72	13.13	1.74	14.00	1.76	15.03	1.78	15.50	1.79
	5.0	11.02	1.89	12.46	1.92	13.13	1.94	14.00	1.96	15.03	1.98	15.50	1.99
	10.0	11.02	2.08	12.46	2.12	13.13	2.13	14.00	2.16	15.03	2.18	15.50	2.19
	15.0	11.02	2.86	12.46	2.91	13.13	2.94	14.00	2.97	15.03	3.00	15.50	3.02
	20.0	11.02	3.65	12.46	3.71	13.13	3.74	14.00	3.78	15.03	3.82	15.50	3.85
	25.0	11.02	4.02	12.46	4.09	13.13	4.12	14.00	4.17	15.03	4.21	15.50	4.24
	30.0	11.02	4.39	12.46	4.46	13.13	4.50	14.00	4.55	15.03	4.60	15.50	4.63
	35.0	11.02	4.68	12.46	4.77	13.13	4.81	14.00	4.86	15.03	4.92	15.50	4.94
	40.0	9.59	4.35	10.84	4.43	11.42	4.46	12.20	4.51	13.08	4.56	13.48	4.59
	46.1	8.15	4.01	9.22	4.08	9.71	4.12	10.40	4.16	11.12	4.21	11.46	4.23
51	-10.0	11.02	1.71	12.46	1.74	13.13	1.76	14.00	1.78	15.03	1.80	15.50	1.81
	-5.0	11.02	1.70	12.46	1.73	13.13	1.75	14.00	1.77	15.03	1.79	15.50	1.80
	0.0	11.02	1.69	12.46	1.72	13.13	1.74	14.00	1.76	15.03	1.78	15.50	1.79
	5.0	11.02	1.89	12.46	1.92	13.13	1.94	14.00	1.96	15.03	1.98	15.50	1.99
	10.0	11.02	2.08	12.46	2.12	13.13	2.13	14.00	2.16	15.03	2.18	15.50	2.19
	15.0	11.02	2.86	12.46	2.91	13.13	2.94	14.00	2.97	15.03	3.00	15.50	3.02
	20.0	11.02	3.65	12.46	3.71	13.13	3.74	14.00	3.78	15.03	3.82	15.50	3.85
	25.0	11.02	4.02	12.46	4.09	13.13	4.12	14.00	4.17	15.03	4.21	15.50	4.24
	30.0	11.02	4.39	12.46	4.46	13.13	4.50	14.00	4.55	15.03	4.60	15.50	4.63
	35.0	11.02	4.68	12.46	4.77	13.13	4.81	14.00	4.86	15.03	4.92	15.50	4.94
	40.0	9.59	4.35	10.84	4.43	11.42	4.46	12.20	4.51	13.08	4.56	13.48	4.59
	46.1	8.15	4.01	9.22	4.08	9.71	4.12	10.40	4.16	11.12	4.21	11.46	4.23
50	-10.0	11.02	1.71	12.46	1.74	13.13	1.76	14.00	1.78	15.03	1.80	15.50	1.81
	-5.0	11.02	1.70	12.46	1.73	13.13	1.75	14.00	1.77	15.03	1.79	15.50	1.80
	0.0	11.02	1.69	12.46	1.72	13.13	1.74	14.00	1.76	15.03	1.78	15.50	1.79
	5.0	11.02	1.89	12.46	1.92	13.13	1.94	14.00	1.96	15.03	1.98	15.50	1.99
	10.0	11.02	2.08	12.46	2.12	13.13	2.13	14.00	2.16	15.03	2.18	15.50	2.19
	15.0	11.02	2.86	12.46	2.91	13.13	2.94	14.00	2.97	15.03	3.00	15.50	3.02
	20.0	11.02	3.65	12.46	3.71	13.13	3.74	14.00	3.78	15.03	3.82	15.50	3.85
	25.0	11.02	4.02	12.46	4.09	13.13	4.12	14.00	4.17	15.03	4.21	15.50	4.24
	30.0	11.02	4.39	12.46	4.46	13.13	4.50	14.00	4.55	15.03	4.60	15.50	4.63
	35.0	11.02	4.68	12.46	4.77	13.13	4.81	14.00	4.86	15.03	4.92	15.50	4.94
	40.0	9.59	4.35	10.84	4.43	11.42	4.46	12.20	4.51	13.08	4.56	13.48	4.59
	46.1	8.15	4.01	9.22	4.08	9.71	4.12	10.40	4.16	11.12	4.21	11.46	4.23
49	-10.0	11.02	1.71	12.46	1.74	13.13	1.76	14.00	1.78	15.03	1.80	15.50	1.81
	-5.0	11.02	1.70	12.46	1.73	13.13	1.75	14.00	1.77	15.03	1.79	15.50	1.80
	0.0	11.02	1.69	12.46	1.72	13.13	1.74	14.00	1.76	15.03	1.78	15.50	1.79
	5.0	11.02	1.89	12.46	1.92	13.13	1.94	14.00	1.96	15.03	1.98	15.50	1.99
	10.0	11.02	2.08	12.46	2.12	13.13	2.13	14.00	2.16	15.03	2.18	15.50	2.19
	15.0	11.02	2.86	12.46	2.91	13.13	2.94	14.00	2.97	15.03	3.00	15.50	3.02
	20.0	11.02	3.65	12.46	3.71	13.13	3.74	14.00	3.78	15.03	3.82	15.50	3.85
	25.0	11.02	4.02	12.46	4.09	13.13	4.12	14.00	4.17	15.03	4.21	15.50	4.24
	30.0	11.02	4.39	12.46	4.46	13.13	4.50	14.00	4.55	15.03	4.60	15.50	4.63
	35.0	11.02	4.68	12.46	4.77	13.13	4.81	14.00	4.86	15.03	4.92	15.50	4.94
	40.0	9.59	4.35	10.84	4.43	11.42	4.46	12.20	4.51	13.08	4.56	13.48	4.59
	46.1	8.15	4.01	9.22	4.08	9.71	4.12	10.40	4.16	11.12	4.21	11.46	4.23

OUTDOOR UNIT  
AOU45RLXFZOUTDOOR UNIT  
AOU45RLXFZ

Indoor unit connecting capacity	Outdoor temperature	Indoor temperature											
		17.8 °CDB		21.1 °CDB		23.9 °CDB		26.7 °CDB		29.4 °CDB		32.2 °CDB	
		12.2 °CWB		15.6 °CWB		17.2 °CWB		19.4 °CWB		21.7 °CWB		22.8 °CWB	
kBtu/h	°CDB	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
48	-10.0	11.02	1.71	12.46	1.74	13.13	1.76	14.00	1.78	15.03	1.80	15.50	1.81
	-5.0	11.02	1.70	12.46	1.73	13.13	1.75	14.00	1.77	15.03	1.79	15.50	1.80
	0.0	11.02	1.69	12.46	1.72	13.13	1.74	14.00	1.76	15.03	1.78	15.50	1.79
	5.0	11.02	1.89	12.46	1.92	13.13	1.94	14.00	1.96	15.03	1.98	15.50	1.99
	10.0	11.02	2.08	12.46	2.12	13.13	2.13	14.00	2.16	15.03	2.18	15.50	2.19
	15.0	11.02	2.86	12.46	2.91	13.13	2.94	14.00	2.97	15.03	3.00	15.50	3.02
	20.0	11.02	3.65	12.46	3.71	13.13	3.74	14.00	3.78	15.03	3.82	15.50	3.85
	25.0	11.02	4.02	12.46	4.09	13.13	4.12	14.00	4.17	15.03	4.21	15.50	4.24
	30.0	11.02	4.39	12.46	4.46	13.13	4.50	14.00	4.55	15.03	4.60	15.50	4.63
	35.0	11.02	4.68	12.46	4.77	13.13	4.81	14.00	4.86	15.03	4.92	15.50	4.94
	40.0	9.59	4.35	10.84	4.43	11.42	4.46	12.20	4.51	13.08	4.56	13.48	4.59
	46.1	8.15	4.01	9.22	4.08	9.71	4.12	10.40	4.16	11.12	4.21	11.46	4.23
47	-10.0	11.02	1.71	12.46	1.74	13.13	1.76	14.00	1.78	15.03	1.80	15.50	1.81
	-5.0	11.02	1.70	12.46	1.73	13.13	1.75	14.00	1.77	15.03	1.79	15.50	1.80
	0.0	11.02	1.69	12.46	1.72	13.13	1.74	14.00	1.76	15.03	1.78	15.50	1.79
	5.0	11.02	1.89	12.46	1.92	13.13	1.94	14.00	1.96	15.03	1.98	15.50	1.99
	10.0	11.02	2.08	12.46	2.12	13.13	2.13	14.00	2.16	15.03	2.18	15.50	2.19
	15.0	11.02	2.86	12.46	2.91	13.13	2.94	14.00	2.97	15.03	3.00	15.50	3.02
	20.0	11.02	3.65	12.46	3.71	13.13	3.74	14.00	3.78	15.03	3.82	15.50	3.85
	25.0	11.02	4.02	12.46	4.09	13.13	4.12	14.00	4.17	15.03	4.21	15.50	4.24
	30.0	11.02	4.39	12.46	4.46	13.13	4.50	14.00	4.55	15.03	4.60	15.50	4.63
	35.0	11.02	4.68	12.46	4.77	13.13	4.81	14.00	4.86	15.03	4.92	15.50	4.94
	40.0	9.59	4.35	10.84	4.43	11.42	4.46	12.20	4.51	13.08	4.56	13.48	4.59
	46.1	8.15	4.01	9.22	4.08	9.71	4.12	10.40	4.16	11.12	4.21	11.46	4.23
46	-10.0	11.02	1.71	12.46	1.74	13.13	1.76	14.00	1.78	15.03	1.80	15.50	1.81
	-5.0	11.02	1.70	12.46	1.73	13.13	1.75	14.00	1.77	15.03	1.79	15.50	1.80
	0.0	11.02	1.69	12.46	1.72	13.13	1.74	14.00	1.76	15.03	1.78	15.50	1.79
	5.0	11.02	1.89	12.46	1.92	13.13	1.94	14.00	1.96	15.03	1.98	15.50	1.99
	10.0	11.02	2.08	12.46	2.12	13.13	2.13	14.00	2.16	15.03	2.18	15.50	2.19
	15.0	11.02	2.86	12.46	2.91	13.13	2.94	14.00	2.97	15.03	3.00	15.50	3.02
	20.0	11.02	3.65	12.46	3.71	13.13	3.74	14.00	3.78	15.03	3.82	15.50	3.85
	25.0	11.02	4.02	12.46	4.09	13.13	4.12	14.00	4.17	15.03	4.21	15.50	4.24
	30.0	11.02	4.39	12.46	4.46	13.13	4.50	14.00	4.55	15.03	4.60	15.50	4.63
	35.0	11.02	4.68	12.46	4.77	13.13	4.81	14.00	4.86	15.03	4.92	15.50	4.94
	40.0	9.59	4.35	10.84	4.43	11.42	4.46	12.20	4.51	13.08	4.56	13.48	4.59
	46.1	8.15	4.01	9.22	4.08	9.71	4.12	10.40	4.16	11.12	4.21	11.46	4.23
45	-10.0	11.02	1.71	12.46	1.74	13.13	1.76	14.00	1.78	15.03	1.80	15.50	1.81
	-5.0	11.02	1.70	12.46	1.73	13.13	1.75	14.00	1.77	15.03	1.79	15.50	1.80
	0.0	11.02	1.69	12.46	1.72	13.13	1.74	14.00	1.76	15.03	1.78	15.50	1.79
	5.0	11.02	1.89	12.46	1.92	13.13	1.94	14.00	1.96	15.03	1.98	15.50	1.99
	10.0	11.02	2.08	12.46	2.12	13.13	2.13	14.00	2.16	15.03	2.18	15.50	2.19
	15.0	11.02	2.86	12.46	2.91	13.13	2.94	14.00	2.97	15.03	3.00	15.50	3.02
	20.0	11.02	3.65	12.46	3.71	13.13	3.74	14.00	3.78	15.03	3.82	15.50	3.85
	25.0	11.02	4.02	12.46	4.09	13.13	4.12	14.00	4.17	15.03	4.21	15.50	4.24
	30.0	11.02	4.39	12.46	4.46	13.13	4.50	14.00	4.55	15.03	4.60	15.50	4.63
	35.0	11.02	4.68	12.46	4.77	13.13	4.81	14.00	4.86	15.03	4.92	15.50	4.94
	40.0	9.59	4.35	10.84	4.43	11.42	4.46	12.20	4.51	13.08	4.56	13.48	4.59
	46.1	8.15	4.01	9.22	4.08	9.71	4.12	10.40	4.16	11.12	4.21	11.46	4.23
44	-10.0	10.78	1.68	12.18	1.71	12.84	1.72	13.70	1.74	14.70	1.76	15.15	1.77
	-5.0	10.78	1.67	12.18	1.70	12.84	1.71	13.70	1.73	14.70	1.75	15.15	1.76
	0.0	10.78	1.66	12.18	1.69	12.84	1.70	13.70	1.72	14.70	1.74	15.15	1.75
	5.0	10.78	1.85	12.18	1.88	12.84	1.90	13.70	1.92	14.70	1.94	15.15	1.95
	10.0	10.78	2.04	12.18	2.07	12.84	2.09	13.70	2.11	14.70	2.14	15.15	2.15
	15.0	10.78	2.81	12.18	2.85	12.84	2.88	13.70	2.91	14.70	2.94	15.15	2.96
	20.0	10.78	3.57	12.18	3.64	12.84	3.67	13.70	3.71	14.70	3.75	15.15	3.77
	25.0	10.78	3.94	12.18	4.01	12.84	4.04	13.70	4.08	14.70	4.13	15.15	4.15
	30.0	10.78	4.30	12.18	4.38	12.84	4.41	13.70	4.46	14.70	4.51	15.15	4.54
	35.0	10.78	4.59	12.18	4.67	12.84	4.71	13.70	4.76	14.70	4.82	15.15	4.84
	40.0	9.38	4.26	10.60	4.34	11.17	4.37	11.90	4.42	12.79	4.47	13.18	4.50
	46.1	7.97	3.93	9.01	4.00	9.50	4.04	10.10	4.08	10.87	4.13	11.21	4.15
43	-10.0	10.53	1.62	11.91	1.65	12.55	1.66	13.40	1.68	14.37	1.70	14.81	1.71
	-5.0	10.53	1.61	11.91	1.64	12.55	1.65	13.40	1.67	14.37	1.69	14.81	1.70
	0.0	10.53	1.60	11.91	1.63	12.55	1.64	13.40	1.66	14.37	1.68	14.81	1.69
	5.0	10.53	1.79	11.91	1.82	12.55	1.83	13.40	1.85	14.37	1.87	14.81	1.88
	10.0	10.53	1.97	11.91	2.00	12.55	2.02	13.40	2.04	14.37	2.07	14.81	2.08
	15.0	10.53	2.71	11.91	2.76	12.55	2.78	13.40	2.81	14.37	2.84	14.81	2.86
	20.0	10.53	3.45	11.91	3.51	12.55	3.54	13.40	3.58	14.37	3.62	14.81	3.64
	25.0	10.53	3.80	11.91	3.87	12.55	3.90	13.40	3.95	14.37	3.99	14.81	4.01
	30.0	10.53	4.15	11.91	4.23	12.55	4.26	13.40	4.31	14.37	4.36	14.81	4.38
	35.0	10.53	4.44	11.91	4.51	12.55	4.55	13.40	4.60	14.37	4.65	14.81	4.68
	40.0	9.16	4.12	10.36	4.19	10.92	4.23	11.60	4.27	12.50	4.32	12.88	4.34
	46.1	7.79	3.80	8.81	3.87	9.28	3.90	9.90	3.94	10.63	3.99	10.95	4.01
42	-10.0	10.29	1.56	11.63	1.59	12.26	1.60	13.10	1.62	14.03	1.64	14.46	1.65
	-5.0	10.29	1.56	11.63	1.58	12.26	1.60	13.10	1				

OUTDOOR UNIT  
AOU45RLXFZOUTDOOR UNIT  
AOU45RLXFZ

Indoor unit connect-ing capacity	Outdoor temperature	Indoor temperature											
		17.8 °CDB		21.1 °CDB		23.9 °CDB		26.7 °CDB		29.4 °CDB		32.2 °CDB	
		12.2 °CWB		15.6 °CWB		17.2 °CWB		19.4 °CWB		21.7 °CWB		22.8 °CWB	
kBtu/h	°CDB	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
41	-10.0	10.04	1.51	11.35	1.53	11.97	1.55	12.80	1.56	13.70	1.58	14.12	1.59
	-5.0	10.04	1.50	11.35	1.53	11.97	1.54	12.80	1.56	13.70	1.57	14.12	1.58
	0.0	10.04	1.49	11.35	1.52	11.97	1.53	12.80	1.55	13.70	1.56	14.12	1.57
	5.0	10.04	1.66	11.35	1.69	11.97	1.70	12.80	1.72	13.70	1.74	14.12	1.75
	10.0	10.04	1.83	11.35	1.86	11.97	1.88	12.80	1.90	13.70	1.92	14.12	1.93
	15.0	10.04	2.52	11.35	2.57	11.97	2.59	12.80	2.62	13.70	2.65	14.12	2.66
	20.0	10.04	3.21	11.35	3.27	11.97	3.29	12.80	3.33	13.70	3.37	14.12	3.39
	25.0	10.04	3.54	11.35	3.60	11.97	3.63	12.80	3.67	13.70	3.71	14.12	3.73
	30.0	10.04	3.86	11.35	3.93	11.97	3.96	12.80	4.01	13.70	4.05	14.12	4.08
	35.0	10.04	4.13	11.35	4.20	11.97	4.23	12.80	4.28	13.70	4.33	14.12	4.35
	40.0	8.74	3.83	9.87	3.90	10.41	3.93	11.10	3.97	11.91	4.02	12.28	4.04
	46.1	7.43	3.54	8.40	3.60	8.85	3.63	9.40	3.67	10.13	3.71	10.44	3.73
40	-10.0	9.80	1.45	11.07	1.48	11.67	1.49	12.50	1.50	13.36	1.52	13.78	1.53
	-5.0	9.80	1.44	11.07	1.47	11.67	1.48	12.50	1.50	13.36	1.51	13.78	1.52
	0.0	9.80	1.44	11.07	1.46	11.67	1.47	12.50	1.49	13.36	1.51	13.78	1.51
	5.0	9.80	1.60	11.07	1.63	11.67	1.64	12.50	1.66	13.36	1.68	13.78	1.69
	10.0	9.80	1.76	11.07	1.79	11.67	1.81	12.50	1.83	13.36	1.85	13.78	1.86
	15.0	9.80	2.43	11.07	2.47	11.67	2.49	12.50	2.52	13.36	2.55	13.78	2.56
	20.0	9.80	3.09	11.07	3.14	11.67	3.17	12.50	3.21	13.36	3.24	13.78	3.26
	25.0	9.80	3.40	11.07	3.46	11.67	3.49	12.50	3.53	13.36	3.57	13.78	3.59
	30.0	9.80	3.72	11.07	3.78	11.67	3.82	12.50	3.86	13.36	3.90	13.78	3.92
	35.0	9.80	3.97	11.07	4.04	11.67	4.07	12.50	4.12	13.36	4.17	13.78	4.19
	40.0	8.52	3.69	9.63	3.75	10.15	3.78	10.80	3.82	11.62	3.87	11.98	3.89
	46.1	7.25	3.40	8.19	3.46	8.63	3.49	9.20	3.53	9.88	3.57	10.19	3.59
39	-10.0	9.55	1.39	10.80	1.42	11.38	1.43	12.10	1.45	13.03	1.46	13.43	1.47
	-5.0	9.55	1.39	10.80	1.41	11.38	1.42	12.10	1.44	13.03	1.45	13.43	1.46
	0.0	9.55	1.38	10.80	1.40	11.38	1.41	12.10	1.43	13.03	1.45	13.43	1.45
	5.0	9.55	1.54	10.80	1.56	11.38	1.58	12.10	1.59	13.03	1.61	13.43	1.62
	10.0	9.55	1.69	10.80	1.72	11.38	1.74	12.10	1.76	13.03	1.78	13.43	1.79
	15.0	9.55	2.33	10.80	2.37	11.38	2.39	12.10	2.42	13.03	2.45	13.43	2.46
	20.0	9.55	2.97	10.80	3.02	11.38	3.05	12.10	3.08	13.03	3.12	13.43	3.13
	25.0	9.55	3.27	10.80	3.33	11.38	3.36	12.10	3.39	13.03	3.43	13.43	3.45
	30.0	9.55	3.57	10.80	3.64	11.38	3.67	12.10	3.71	13.03	3.75	13.43	3.77
	35.0	9.55	3.82	10.80	3.88	11.38	3.91	12.10	3.96	13.03	4.00	13.43	4.03
	40.0	8.31	3.54	9.39	3.61	9.90	3.63	10.60	3.67	11.33	3.72	11.68	3.74
	46.1	7.07	3.27	7.99	3.33	8.42	3.35	9.00	3.39	9.64	3.43	9.93	3.45
38	-10.0	9.31	1.34	10.52	1.36	11.09	1.37	11.80	1.39	12.69	1.40	13.09	1.41
	-5.0	9.31	1.33	10.52	1.35	11.09	1.36	11.80	1.38	12.69	1.40	13.09	1.40
	0.0	9.31	1.32	10.52	1.35	11.09	1.36	11.80	1.37	12.69	1.39	13.09	1.40
	5.0	9.31	1.47	10.52	1.50	11.09	1.51	11.80	1.53	12.69	1.55	13.09	1.56
	10.0	9.31	1.63	10.52	1.65	11.09	1.67	11.80	1.69	12.69	1.71	13.09	1.71
	15.0	9.31	2.24	10.52	2.28	11.09	2.30	11.80	2.32	12.69	2.35	13.09	2.36
	20.0	9.31	2.85	10.52	2.90	11.09	2.92	11.80	2.96	12.69	2.99	13.09	3.01
	25.0	9.31	3.14	10.52	3.19	11.09	3.22	11.80	3.26	12.69	3.29	13.09	3.31
	30.0	9.31	3.43	10.52	3.49	11.09	3.52	11.80	3.56	12.69	3.60	13.09	3.62
	35.0	9.31	3.66	10.52	3.73	11.09	3.76	11.80	3.80	12.69	3.84	13.09	3.86
	40.0	8.10	3.40	9.15	3.46	9.65	3.49	10.30	3.53	11.04	3.57	11.38	3.59
	46.1	6.88	3.14	7.78	3.19	8.20	3.22	8.70	3.25	9.39	3.29	9.68	3.31
37	-10.0	9.06	1.28	10.24	1.30	10.80	1.31	11.50	1.33	12.36	1.34	12.74	1.35
	-5.0	9.06	1.27	10.24	1.30	10.80	1.31	11.50	1.32	12.36	1.34	12.74	1.34
	0.0	9.06	1.27	10.24	1.29	10.80	1.30	11.50	1.31	12.36	1.33	12.74	1.34
	5.0	9.06	1.41	10.24	1.44	10.80	1.45	11.50	1.46	12.36	1.48	12.74	1.49
	10.0	9.06	1.56	10.24	1.58	10.80	1.60	11.50	1.61	12.36	1.63	12.74	1.64
	15.0	9.06	2.14	10.24	2.18	10.80	2.20	11.50	2.22	12.36	2.25	12.74	2.26
	20.0	9.06	2.73	10.24	2.78	10.80	2.80	11.50	2.83	12.36	2.86	12.74	2.88
	25.0	9.06	3.01	10.24	3.06	10.80	3.08	11.50	3.12	12.36	3.15	12.74	3.17
	30.0	9.06	3.28	10.24	3.34	10.80	3.37	11.50	3.41	12.36	3.45	12.74	3.46
	35.0	9.06	3.51	10.24	3.57	10.80	3.60	11.50	3.64	12.36	3.68	12.74	3.70
	40.0	7.88	3.25	8.91	3.31	9.39	3.34	10.00	3.38	10.75	3.42	11.08	3.43
	46.1	6.70	3.00	7.58	3.06	7.99	3.08	8.50	3.12	9.14	3.15	9.42	3.17
36	-10.0	8.82	1.22	9.97	1.25	10.51	1.26	11.20	1.27	12.03	1.28	12.40	1.29
	-5.0	8.82	1.22	9.97	1.24	10.51	1.25	11.20	1.26	12.03	1.28	12.40	1.28
	0.0	8.82	1.21	9.97	1.23	10.51	1.24	11.20	1.26	12.03	1.27	12.40	1.28
	5.0	8.82	1.35	9.97	1.37	10.51	1.38	11.20	1.40	12.03	1.42	12.40	1.42
	10.0	8.82	1.49	9.97	1.51	10.51	1.53	11.20	1.54	12.03	1.56	12.40	1.57
	15.0	8.82	2.05	9.97	2.08	10.51	2.10	11.20	2.12	12.03	2.15	12.40	2.16
	20.0	8.82	2.61	9.97	2.65	10.51	2.68	11.20	2.70	12.03	2.74	12.40	2.75
	25.0	8.82	2.87	9.97	2.92	10.51	2.95	11.20	2.98	12.03	3.01	12.40	3.03
	30.0	8.82	3.14	9.97	3.19	10.51	3.22	11.20	3.26	12.03	3.29	12.40	3.31
	35.0	8.82	3.35	9.97	3.41	10.51	3.44	11.20	3.48	12.03	3.52	12.40	3.54
	40.0	7.67	3.11	8.67	3.17	9.14	3.19	9.70	3.23	10.46	3.26	10.78	3.28
	46.1	6.52	2.87	7.37	2.92	7.77	2.95	8.30	2.98	8.89	3.01	9.17	3.03
35	-10.0	8.57	1.17	9.69	1.19	10.21	1.20	10.90	1.21	11.69	1.23	12.05	1.23
	-5.0	8.57	1.16	9.69	1.18	10.21	1.19	10.90	1.20	11.69	1.22	12.05	1.23
	0.0	8.57	1.15	9.									

Indoor unit connect-ing capacity	Outdoor temperature	Indoor temperature											
		17.8 °CDB		21.1 °CDB		23.9 °CDB		26.7 °CDB		29.4 °CDB		32.2 °CDB	
		12.2 °CWB		15.6 °CWB		17.2 °CWB		19.4 °CWB		21.7 °CWB		22.8 °CWB	
kBtu/h	°CDB	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
34	-10.0	8.33	1.11	9.41	1.13	9.92	1.14	10.60	1.15	11.36	1.17	11.71	1.17
	-5.0	8.33	1.10	9.41	1.12	9.92	1.13	10.60	1.15	11.36	1.16	11.71	1.17
	0.0	8.33	1.10	9.41	1.12	9.92	1.13	10.60	1.14	11.36	1.15	11.71	1.16
	5.0	8.33	1.22	9.41	1.25	9.92	1.26	10.60	1.27	11.36	1.28	11.71	1.29
	10.0	8.33	1.35	9.41	1.37	9.92	1.39	10.60	1.40	11.36	1.42	11.71	1.42
	15.0	8.33	1.86	9.41	1.89	9.92	1.91	10.60	1.93	11.36	1.95	11.71	1.96
	20.0	8.33	2.37	9.41	2.41	9.92	2.43	10.60	2.45	11.36	2.48	11.71	2.50
	25.0	8.33	2.61	9.41	2.65	9.92	2.67	10.60	2.70	11.36	2.74	11.71	2.75
	30.0	8.33	2.85	9.41	2.90	9.92	2.92	10.60	2.95	11.36	2.99	11.71	3.00
	35.0	8.33	3.04	9.41	3.09	9.92	3.12	10.60	3.15	11.36	3.19	11.71	3.21
	40.0	7.24	2.82	8.19	2.87	8.63	2.90	9.20	2.93	9.88	2.96	10.18	2.98
	46.1	6.16	2.61	6.96	2.65	7.34	2.67	7.80	2.70	8.40	2.73	8.66	2.75

**NOTE:** Specifications are based on the following conditions.

- Power source of specifications: 230 V
- 2 or more indoor units should be connected.
- Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]
- The total ability of connected a indoor unit is from 34,000 Btu up to 54,000 Btu.
- Input in the table are calculated based on the maximum indoor unit input combinations.

## ■ Compact cassette type

### ● Unit: kBtu/h, °F

- TC: Total Capacity (kBtu/h), SHC: Sensible Heat Capacity (kBtu/h).
- The data is based on the following conditions:  
Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]

#### MODEL: AUU7RLF

Outdoor temperature (°FDB)	Indoor temperature (°FDB / °FWB)											
	64.0 / 54.0		70.0 / 60.0		75.0 / 63.0		80.0 / 67.0		85.0 / 71.0		90.0 / 73.0	
	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
14.0	5.88	3.97	6.65	4.52	7.01	5.21	7.50	5.85	8.02	6.40	8.27	7.33
23.0	5.88	3.97	6.65	4.52	7.01	5.21	7.50	5.85	8.02	6.40	8.27	7.33
32.0	5.88	3.97	6.65	4.52	7.01	5.21	7.50	5.85	8.02	6.40	8.27	7.33
41.0	5.88	3.97	6.65	4.52	7.01	5.21	7.50	5.85	8.02	6.40	8.27	7.33
50.0	5.88	3.97	6.65	4.52	7.01	5.21	7.50	5.85	8.02	6.40	8.27	7.33
59.0	5.88	3.97	6.65	4.52	7.01	5.21	7.50	5.85	8.02	6.40	8.27	7.33
67.0	5.88	3.97	6.65	4.52	7.01	5.21	7.50	5.85	8.02	6.40	8.27	7.33
77.0	5.88	3.97	6.65	4.52	7.01	5.21	7.50	5.85	8.02	6.40	8.27	7.33
87.0	5.88	3.97	6.65	4.52	7.01	5.21	7.50	5.85	8.02	6.40	8.27	7.33
95.0	5.88	3.97	6.65	4.52	7.01	5.21	7.50	5.85	8.02	6.40	8.27	7.33
104.0	5.56	3.55	6.29	4.05	6.63	4.66	7.10	5.24	7.59	5.73	7.82	6.56
115.0	5.25	3.16	5.93	3.60	6.25	4.15	6.69	4.66	7.15	5.10	7.38	5.84

#### MODEL: AUU9RLF

Outdoor temperature (°FDB)	Indoor temperature (°FDB / °FWB)											
	64.0 / 54.0		70.0 / 60.0		75.0 / 63.0		80.0 / 67.0		85.0 / 71.0		90.0 / 73.0	
	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
14.0	7.53	5.01	8.51	5.71	8.97	6.58	9.60	7.39	10.26	8.08	10.58	9.26
23.0	7.53	5.01	8.51	5.71	8.97	6.58	9.60	7.39	10.26	8.08	10.58	9.26
32.0	7.53	5.01	8.51	5.71	8.97	6.58	9.60	7.39	10.26	8.08	10.58	9.26
41.0	7.53	5.01	8.51	5.71	8.97	6.58	9.60	7.39	10.26	8.08	10.58	9.26
50.0	7.53	5.01	8.51	5.71	8.97	6.58	9.60	7.39	10.26	8.08	10.58	9.26
59.0	7.53	5.01	8.51	5.71	8.97	6.58	9.60	7.39	10.26	8.08	10.58	9.26
67.0	7.53	5.01	8.51	5.71	8.97	6.58	9.60	7.39	10.26	8.08	10.58	9.26
77.0	7.53	5.01	8.51	5.71	8.97	6.58	9.60	7.39	10.26	8.08	10.58	9.26
87.0	7.53	5.01	8.51	5.71	8.97	6.58	9.60	7.39	10.26	8.08	10.58	9.26
95.0	7.53	5.01	8.51	5.71	8.97	6.58	9.60	7.39	10.26	8.08	10.58	9.26
104.0	7.12	4.49	8.05	5.12	8.48	5.89	9.08	6.62	9.71	7.24	10.01	8.29
115.0	6.72	3.99	7.59	4.55	8.00	5.24	8.57	5.89	9.16	6.44	9.44	7.38

#### MODEL: AUU12RLF

Outdoor temperature (°FDB)	Indoor temperature (°FDB / °FWB)											
	64.0 / 54.0		70.0 / 60.0		75.0 / 63.0		80.0 / 67.0		85.0 / 71.0		90.0 / 73.0	
	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
14.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
23.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
32.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
41.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
50.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
59.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
67.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
77.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
87.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
95.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
104.0	9.50	5.91	10.73	6.73	11.31	7.75	12.11	8.71	12.95	9.53	13.35	10.91
115.0	8.96	5.25	10.12	5.99	10.67	6.90	11.42	7.75	12.21	8.47	12.59	9.71

## MODEL: AUU18RLF

Outdoor temperature (°FDB)	Indoor temperature (°FDB / °FWB)											
	64.0 / 54.0		70.0 / 60.0		75.0 / 63.0		80.0 / 67.0		85.0 / 71.0		90.0 / 73.0	
TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC
14.0	15.05	9.11	17.01	10.39	17.93	11.96	19.20	13.44	20.52	14.70	21.16	16.84
23.0	15.05	9.11	17.01	10.39	17.93	11.96	19.20	13.44	20.52	14.70	21.16	16.84
32.0	15.05	9.11	17.01	10.39	17.93	11.96	19.20	13.44	20.52	14.70	21.16	16.84
41.0	15.05	9.11	17.01	10.39	17.93	11.96	19.20	13.44	20.52	14.70	21.16	16.84
50.0	15.05	9.11	17.01	10.39	17.93	11.96	19.20	13.44	20.52	14.70	21.16	16.84
59.0	15.05	9.11	17.01	10.39	17.93	11.96	19.20	13.44	20.52	14.70	21.16	16.84
67.0	15.05	9.11	17.01	10.39	17.93	11.96	19.20	13.44	20.52	14.70	21.16	16.84
77.0	15.05	9.11	17.01	10.39	17.93	11.96	19.20	13.44	20.52	14.70	21.16	16.84
87.0	15.05	9.11	17.01	10.39	17.93	11.96	19.20	13.44	20.52	14.70	21.16	16.84
95.0	15.05	9.11	17.01	10.39	17.93	11.96	19.20	13.44	20.52	14.70	21.16	16.84
104.0	14.24	8.16	16.10	9.30	16.97	10.71	18.17	12.03	19.42	13.16	20.02	15.08
115.0	13.43	7.26	15.18	8.27	16.00	9.53	17.13	10.70	18.32	11.71	18.88	13.41

OUTDOOR UNIT  
AOU45RLXFZOUTDOOR UNIT  
AOU45RLXFZ

## ● Unit: kW, °C

- TC: Total Capacity (kW), SHC: Sensible Heat Capacity (kW).
- The data is based on the following conditions:  
Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]

### MODEL: AUU7RLF

Outdoor temperature	Indoor temperature (°CDB / °CWB)											
	17.8 / 12.2		21.1 / 15.6		23.9 / 17.2		26.7 / 19.4		29.4 / 21.7		32.2 / 22.8	
(°CDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
-10.0	1.72	1.16	1.95	1.33	2.05	1.53	2.20	1.71	2.35	1.88	2.42	2.15
-5.0	1.72	1.16	1.95	1.33	2.05	1.53	2.20	1.71	2.35	1.88	2.42	2.15
0.0	1.72	1.16	1.95	1.33	2.05	1.53	2.20	1.71	2.35	1.88	2.42	2.15
5.0	1.72	1.16	1.95	1.33	2.05	1.53	2.20	1.71	2.35	1.88	2.42	2.15
10.0	1.72	1.16	1.95	1.33	2.05	1.53	2.20	1.71	2.35	1.88	2.42	2.15
15.0	1.72	1.16	1.95	1.33	2.05	1.53	2.20	1.71	2.35	1.88	2.42	2.15
20.0	1.72	1.16	1.95	1.33	2.05	1.53	2.20	1.71	2.35	1.88	2.42	2.15
25.0	1.72	1.16	1.95	1.33	2.05	1.53	2.20	1.71	2.35	1.88	2.42	2.15
30.0	1.72	1.16	1.95	1.33	2.05	1.53	2.20	1.71	2.35	1.88	2.42	2.15
35.0	1.72	1.16	1.95	1.33	2.05	1.53	2.20	1.71	2.35	1.88	2.42	2.15
40.0	1.63	1.04	1.84	1.19	1.94	1.37	2.08	1.53	2.22	1.68	2.29	1.92
46.1	1.54	0.93	1.74	1.06	1.83	1.22	1.96	1.37	2.10	1.49	2.16	1.71

### MODEL: AUU9RLF

Outdoor temperature	Indoor temperature (°CDB / °CWB)											
	17.8 / 12.2		21.1 / 15.6		23.9 / 17.2		26.7 / 19.4		29.4 / 21.7		32.2 / 22.8	
(°CDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
-10.0	2.21	1.47	2.49	1.67	2.63	1.93	2.81	2.17	3.01	2.37	3.10	2.71
-5.0	2.21	1.47	2.49	1.67	2.63	1.93	2.81	2.17	3.01	2.37	3.10	2.71
0.0	2.21	1.47	2.49	1.67	2.63	1.93	2.81	2.17	3.01	2.37	3.10	2.71
5.0	2.21	1.47	2.49	1.67	2.63	1.93	2.81	2.17	3.01	2.37	3.10	2.71
10.0	2.21	1.47	2.49	1.67	2.63	1.93	2.81	2.17	3.01	2.37	3.10	2.71
15.0	2.21	1.47	2.49	1.67	2.63	1.93	2.81	2.17	3.01	2.37	3.10	2.71
20.0	2.21	1.47	2.49	1.67	2.63	1.93	2.81	2.17	3.01	2.37	3.10	2.71
25.0	2.21	1.47	2.49	1.67	2.63	1.93	2.81	2.17	3.01	2.37	3.10	2.71
30.0	2.21	1.47	2.49	1.67	2.63	1.93	2.81	2.17	3.01	2.37	3.10	2.71
35.0	2.21	1.47	2.49	1.67	2.63	1.93	2.81	2.17	3.01	2.37	3.10	2.71
40.0	2.09	1.32	2.36	1.50	2.49	1.73	2.66	1.94	2.85	2.12	2.93	2.43
46.1	1.97	1.17	2.22	1.33	2.35	1.54	2.51	1.73	2.68	1.89	2.77	2.16

### MODEL: AUU12RLF

Outdoor temperature	Indoor temperature (°CDB / °CWB)											
	17.8 / 12.2		21.1 / 15.6		23.9 / 17.2		26.7 / 19.4		29.4 / 21.7		32.2 / 22.8	
(°CDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
-10.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
-5.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
0.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
5.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
10.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
15.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
20.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
25.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
30.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
35.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
40.0	2.78	1.73	3.14	1.97	3.32	2.27	3.55	2.55	3.79	2.79	3.91	3.20
46.1	2.62	1.54	2.97	1.76	3.13	2.02	3.35	2.27	3.58	2.48	3.69	2.85

## MODEL: AUU18RLF

Outdoor temperature (°CDB)	Indoor temperature (°CDB / °CWB)											
	17.8 / 12.2		21.1 / 15.6		23.9 / 17.2		26.7 / 19.4		29.4 / 21.7		32.2 / 22.8	
TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC
-10.0	4.41	2.67	4.99	3.05	5.26	3.51	5.63	3.94	6.02	4.31	6.20	4.94
-5.0	4.41	2.67	4.99	3.05	5.26	3.51	5.63	3.94	6.02	4.31	6.20	4.94
0.0	4.41	2.67	4.99	3.05	5.26	3.51	5.63	3.94	6.02	4.31	6.20	4.94
5.0	4.41	2.67	4.99	3.05	5.26	3.51	5.63	3.94	6.02	4.31	6.20	4.94
10.0	4.41	2.67	4.99	3.05	5.26	3.51	5.63	3.94	6.02	4.31	6.20	4.94
15.0	4.41	2.67	4.99	3.05	5.26	3.51	5.63	3.94	6.02	4.31	6.20	4.94
20.0	4.41	2.67	4.99	3.05	5.26	3.51	5.63	3.94	6.02	4.31	6.20	4.94
25.0	4.41	2.67	4.99	3.05	5.26	3.51	5.63	3.94	6.02	4.31	6.20	4.94
30.0	4.41	2.67	4.99	3.05	5.26	3.51	5.63	3.94	6.02	4.31	6.20	4.94
35.0	4.41	2.67	4.99	3.05	5.26	3.51	5.63	3.94	6.02	4.31	6.20	4.94
40.0	4.17	2.39	4.72	2.73	4.97	3.14	5.32	3.53	5.69	3.86	5.87	4.42
46.1	3.94	2.13	4.45	2.42	4.69	2.79	5.02	3.14	5.37	3.43	5.53	3.93

OUTDOOR UNIT  
AOU45RLXFZOUTDOOR UNIT  
AOU45RLXFZ

## ■ Slim duct type

### ● Unit: kBtu/h, °F

- TC: Total Capacity (kBtu/h), SHC: Sensible Heat Capacity (kBtu/h).
- The data is based on the following conditions.
- Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]

### MODEL: ARU7RLF

Outdoor temperature	Indoor temperature (°FDB / °FWB)											
	64.0 / 54.0		70.0 / 60.0		75.0 / 63.0		80.0 / 67.0		85.0 / 71.0		90.0 / 73.0	
(°FDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
14.0	5.88	4.07	6.65	4.64	7.01	5.34	7.50	6.00	8.02	6.56	8.27	7.52
23.0	5.88	4.07	6.65	4.64	7.01	5.34	7.50	6.00	8.02	6.56	8.27	7.52
32.0	5.88	4.07	6.65	4.64	7.01	5.34	7.50	6.00	8.02	6.56	8.27	7.52
41.0	5.88	4.07	6.65	4.64	7.01	5.34	7.50	6.00	8.02	6.56	8.27	7.52
50.0	5.88	4.07	6.65	4.64	7.01	5.34	7.50	6.00	8.02	6.56	8.27	7.52
59.0	5.88	4.07	6.65	4.64	7.01	5.34	7.50	6.00	8.02	6.56	8.27	7.52
67.0	5.88	4.07	6.65	4.64	7.01	5.34	7.50	6.00	8.02	6.56	8.27	7.52
77.0	5.88	4.07	6.65	4.64	7.01	5.34	7.50	6.00	8.02	6.56	8.27	7.52
87.0	5.88	4.07	6.65	4.64	7.01	5.34	7.50	6.00	8.02	6.56	8.27	7.52
95.0	5.88	4.07	6.65	4.64	7.01	5.34	7.50	6.00	8.02	6.56	8.27	7.52
104.0	5.56	3.64	6.29	4.15	6.63	4.78	7.10	5.37	7.59	5.88	7.82	6.73
115.0	5.25	3.24	5.93	3.69	6.25	4.25	6.69	4.78	7.15	5.23	7.38	5.99

### MODEL: ARU9RLF

Outdoor temperature	Indoor temperature (°FDB / °FWB)											
	64.0 / 54.0		70.0 / 60.0		75.0 / 63.0		80.0 / 67.0		85.0 / 71.0		90.0 / 73.0	
(°FDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
14.0	7.53	4.82	8.51	5.49	8.97	6.32	9.60	7.10	10.26	7.77	10.58	8.90
23.0	7.53	4.82	8.51	5.49	8.97	6.32	9.60	7.10	10.26	7.77	10.58	8.90
32.0	7.53	4.82	8.51	5.49	8.97	6.32	9.60	7.10	10.26	7.77	10.58	8.90
41.0	7.53	4.82	8.51	5.49	8.97	6.32	9.60	7.10	10.26	7.77	10.58	8.90
50.0	7.53	4.82	8.51	5.49	8.97	6.32	9.60	7.10	10.26	7.77	10.58	8.90
59.0	7.53	4.82	8.51	5.49	8.97	6.32	9.60	7.10	10.26	7.77	10.58	8.90
67.0	7.53	4.82	8.51	5.49	8.97	6.32	9.60	7.10	10.26	7.77	10.58	8.90
77.0	7.53	4.82	8.51	5.49	8.97	6.32	9.60	7.10	10.26	7.77	10.58	8.90
87.0	7.53	4.82	8.51	5.49	8.97	6.32	9.60	7.10	10.26	7.77	10.58	8.90
95.0	7.53	4.82	8.51	5.49	8.97	6.32	9.60	7.10	10.26	7.77	10.58	8.90
104.0	7.12	4.31	8.05	4.92	8.48	5.66	9.08	6.36	9.71	6.96	10.01	7.97
115.0	6.72	3.84	7.59	4.37	8.00	5.04	8.57	5.66	9.16	6.19	9.44	7.09

### MODEL: ARU12RLF

Outdoor temperature	Indoor temperature (°FDB / °FWB)											
	64.0 / 54.0		70.0 / 60.0		75.0 / 63.0		80.0 / 67.0		85.0 / 71.0		90.0 / 73.0	
(°FDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
14.0	9.88	6.32	11.16	7.21	11.77	8.30	12.60	9.32	13.47	10.20	13.89	11.68
23.0	9.88	6.32	11.16	7.21	11.77	8.30	12.60	9.32	13.47	10.20	13.89	11.68
32.0	9.88	6.32	11.16	7.21	11.77	8.30	12.60	9.32	13.47	10.20	13.89	11.68
41.0	9.88	6.32	11.16	7.21	11.77	8.30	12.60	9.32	13.47	10.20	13.89	11.68
50.0	9.88	6.32	11.16	7.21	11.77	8.30	12.60	9.32	13.47	10.20	13.89	11.68
59.0	9.88	6.32	11.16	7.21	11.77	8.30	12.60	9.32	13.47	10.20	13.89	11.68
67.0	9.88	6.32	11.16	7.21	11.77	8.30	12.60	9.32	13.47	10.20	13.89	11.68
77.0	9.88	6.32	11.16	7.21	11.77	8.30	12.60	9.32	13.47	10.20	13.89	11.68
87.0	9.88	6.32	11.16	7.21	11.77	8.30	12.60	9.32	13.47	10.20	13.89	11.68
95.0	9.88	6.32	11.16	7.21	11.77	8.30	12.60	9.32	13.47	10.20	13.89	11.68
104.0	9.35	5.66	10.56	6.45	11.14	7.43	11.92	8.35	12.74	9.13	13.14	10.46
115.0	8.82	5.04	9.96	5.74	10.50	6.61	11.24	7.42	12.02	8.12	12.39	9.30

**MODEL: ARU18RLF**

Outdoor temperature	Indoor temperature (°FDB / °FWB)											
	64.0 / 54.0		70.0 / 60.0		75.0 / 63.0		80.0 / 67.0		85.0 / 71.0		90.0 / 73.0	
(°FDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
14.0	15.05	9.37	17.01	10.69	17.93	12.30	19.20	13.82	20.52	15.12	21.16	17.32
23.0	15.05	9.37	17.01	10.69	17.93	12.30	19.20	13.82	20.52	15.12	21.16	17.32
32.0	15.05	9.37	17.01	10.69	17.93	12.30	19.20	13.82	20.52	15.12	21.16	17.32
41.0	15.05	9.37	17.01	10.69	17.93	12.30	19.20	13.82	20.52	15.12	21.16	17.32
50.0	15.05	9.37	17.01	10.69	17.93	12.30	19.20	13.82	20.52	15.12	21.16	17.32
59.0	15.05	9.37	17.01	10.69	17.93	12.30	19.20	13.82	20.52	15.12	21.16	17.32
67.0	15.05	9.37	17.01	10.69	17.93	12.30	19.20	13.82	20.52	15.12	21.16	17.32
77.0	15.05	9.37	17.01	10.69	17.93	12.30	19.20	13.82	20.52	15.12	21.16	17.32
87.0	15.05	9.37	17.01	10.69	17.93	12.30	19.20	13.82	20.52	15.12	21.16	17.32
95.0	15.05	9.37	17.01	10.69	17.93	12.30	19.20	13.82	20.52	15.12	21.16	17.32
104.0	14.24	8.39	16.10	9.57	16.97	11.02	18.17	12.38	19.42	13.54	20.02	15.51
115.0	13.43	7.47	15.18	8.51	16.00	9.80	17.13	11.01	18.32	12.04	18.88	13.79

**MODEL: ARU24RLF**

Outdoor temperature	Indoor temperature (°FDB / °FWB)											
	64.0 / 54.0		70.0 / 60.0		75.0 / 63.0		80.0 / 67.0		85.0 / 71.0		90.0 / 73.0	
(°FDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
14.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
23.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
32.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
41.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
50.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
59.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
67.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
77.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
87.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
95.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
104.0	18.99	10.88	21.46	12.40	22.62	14.28	24.22	16.04	25.89	17.55	26.69	20.10
115.0	17.91	9.68	20.24	11.03	21.34	12.70	22.84	14.27	24.42	15.61	25.17	17.88

## ● Unit: kW, °C

- TC: Total Capacity (kW), SHC: Sensible Heat Capacity (kW).
- The data is based on the following conditions:  
Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]

### MODEL: ARU7RLF

Outdoor temperature	Indoor temperature (°CDB / °CWB)											
	17.8 / 12.2		21.1 / 15.6		23.9 / 17.2		26.7 / 19.4		29.4 / 21.7		32.2 / 22.8	
(°CDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
-10.0	1.72	1.19	1.95	1.36	2.05	1.57	2.20	1.76	2.35	1.92	2.42	2.20
-5.0	1.72	1.19	1.95	1.36	2.05	1.57	2.20	1.76	2.35	1.92	2.42	2.20
0.0	1.72	1.19	1.95	1.36	2.05	1.57	2.20	1.76	2.35	1.92	2.42	2.20
5.0	1.72	1.19	1.95	1.36	2.05	1.57	2.20	1.76	2.35	1.92	2.42	2.20
10.0	1.72	1.19	1.95	1.36	2.05	1.57	2.20	1.76	2.35	1.92	2.42	2.20
15.0	1.72	1.19	1.95	1.36	2.05	1.57	2.20	1.76	2.35	1.92	2.42	2.20
20.0	1.72	1.19	1.95	1.36	2.05	1.57	2.20	1.76	2.35	1.92	2.42	2.20
25.0	1.72	1.19	1.95	1.36	2.05	1.57	2.20	1.76	2.35	1.92	2.42	2.20
30.0	1.72	1.19	1.95	1.36	2.05	1.57	2.20	1.76	2.35	1.92	2.42	2.20
35.0	1.72	1.19	1.95	1.36	2.05	1.57	2.20	1.76	2.35	1.92	2.42	2.20
40.0	1.63	1.07	1.84	1.22	1.94	1.40	2.08	1.57	2.22	1.72	2.29	1.97
46.1	1.54	0.95	1.74	1.08	1.83	1.25	1.96	1.40	2.10	1.53	2.16	1.75

### MODEL: ARU9RLF

Outdoor temperature	Indoor temperature (°CDB / °CWB)											
	17.8 / 12.2		21.1 / 15.6		23.9 / 17.2		26.7 / 19.4		29.4 / 21.7		32.2 / 22.8	
(°CDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
-10.0	2.21	1.41	2.49	1.61	2.63	1.85	2.81	2.08	3.01	2.28	3.10	2.61
-5.0	2.21	1.41	2.49	1.61	2.63	1.85	2.81	2.08	3.01	2.28	3.10	2.61
0.0	2.21	1.41	2.49	1.61	2.63	1.85	2.81	2.08	3.01	2.28	3.10	2.61
5.0	2.21	1.41	2.49	1.61	2.63	1.85	2.81	2.08	3.01	2.28	3.10	2.61
10.0	2.21	1.41	2.49	1.61	2.63	1.85	2.81	2.08	3.01	2.28	3.10	2.61
15.0	2.21	1.41	2.49	1.61	2.63	1.85	2.81	2.08	3.01	2.28	3.10	2.61
20.0	2.21	1.41	2.49	1.61	2.63	1.85	2.81	2.08	3.01	2.28	3.10	2.61
25.0	2.21	1.41	2.49	1.61	2.63	1.85	2.81	2.08	3.01	2.28	3.10	2.61
30.0	2.21	1.41	2.49	1.61	2.63	1.85	2.81	2.08	3.01	2.28	3.10	2.61
35.0	2.21	1.41	2.49	1.61	2.63	1.85	2.81	2.08	3.01	2.28	3.10	2.61
40.0	2.09	1.26	2.36	1.44	2.49	1.66	2.66	1.86	2.85	2.04	2.93	2.34
46.1	1.97	1.12	2.22	1.28	2.35	1.48	2.51	1.66	2.68	1.81	2.77	2.08

### MODEL: ARU12RLF

Outdoor temperature	Indoor temperature (°CDB / °CWB)											
	17.8 / 12.2		21.1 / 15.6		23.9 / 17.2		26.7 / 19.4		29.4 / 21.7		32.2 / 22.8	
(°CDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
-10.0	2.90	1.85	3.27	2.11	3.45	2.43	3.69	2.73	3.95	2.99	4.07	3.42
-5.0	2.90	1.85	3.27	2.11	3.45	2.43	3.69	2.73	3.95	2.99	4.07	3.42
0.0	2.90	1.85	3.27	2.11	3.45	2.43	3.69	2.73	3.95	2.99	4.07	3.42
5.0	2.90	1.85	3.27	2.11	3.45	2.43	3.69	2.73	3.95	2.99	4.07	3.42
10.0	2.90	1.85	3.27	2.11	3.45	2.43	3.69	2.73	3.95	2.99	4.07	3.42
15.0	2.90	1.85	3.27	2.11	3.45	2.43	3.69	2.73	3.95	2.99	4.07	3.42
20.0	2.90	1.85	3.27	2.11	3.45	2.43	3.69	2.73	3.95	2.99	4.07	3.42
25.0	2.90	1.85	3.27	2.11	3.45	2.43	3.69	2.73	3.95	2.99	4.07	3.42
30.0	2.90	1.85	3.27	2.11	3.45	2.43	3.69	2.73	3.95	2.99	4.07	3.42
35.0	2.90	1.85	3.27	2.11	3.45	2.43	3.69	2.73	3.95	2.99	4.07	3.42
40.0	2.74	1.66	3.10	1.89	3.26	2.18	3.49	2.45	3.74	2.68	3.85	3.07
46.1	2.58	1.48	2.92	1.68	3.08	1.94	3.30	2.18	3.52	2.38	3.63	2.73

**MODEL: ARU18RLF**

Outdoor temperature (°CDB)	Indoor temperature (°CDB / °CWB)											
	17.8 / 12.2		21.1 / 15.6		23.9 / 17.2		26.7 / 19.4		29.4 / 21.7		32.2 / 22.8	
TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	
-10.0	4.41	2.75	4.99	3.13	5.26	3.61	5.63	4.05	6.02	4.43	6.20	5.08
-5.0	4.41	2.75	4.99	3.13	5.26	3.61	5.63	4.05	6.02	4.43	6.20	5.08
0.0	4.41	2.75	4.99	3.13	5.26	3.61	5.63	4.05	6.02	4.43	6.20	5.08
5.0	4.41	2.75	4.99	3.13	5.26	3.61	5.63	4.05	6.02	4.43	6.20	5.08
10.0	4.41	2.75	4.99	3.13	5.26	3.61	5.63	4.05	6.02	4.43	6.20	5.08
15.0	4.41	2.75	4.99	3.13	5.26	3.61	5.63	4.05	6.02	4.43	6.20	5.08
20.0	4.41	2.75	4.99	3.13	5.26	3.61	5.63	4.05	6.02	4.43	6.20	5.08
25.0	4.41	2.75	4.99	3.13	5.26	3.61	5.63	4.05	6.02	4.43	6.20	5.08
30.0	4.41	2.75	4.99	3.13	5.26	3.61	5.63	4.05	6.02	4.43	6.20	5.08
35.0	4.41	2.75	4.99	3.13	5.26	3.61	5.63	4.05	6.02	4.43	6.20	5.08
40.0	4.17	2.46	4.72	2.80	4.97	3.23	5.32	3.63	5.69	3.97	5.87	4.55
46.1	3.94	2.19	4.45	2.49	4.69	2.87	5.02	3.23	5.37	3.53	5.53	4.04

**MODEL: ARU24RLF**

Outdoor temperature (°CDB)	Indoor temperature (°CDB / °CWB)											
	17.8 / 12.2		21.1 / 15.6		23.9 / 17.2		26.7 / 19.4		29.4 / 21.7		32.2 / 22.8	
TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	
-10.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
-5.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
0.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
5.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
10.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
15.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
20.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
25.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
30.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
35.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
40.0	5.57	3.19	6.29	3.63	6.63	4.19	7.10	4.70	7.59	5.14	7.82	5.89
46.1	5.25	2.84	5.93	3.23	6.25	3.72	6.70	4.18	7.16	4.57	7.38	5.24

## ■ Wall mounted type

### ● Unit: kBtu/h, °F

- TC: Total Capacity (kBtu/h), SHC: Sensible Heat Capacity (kBtu/h).
- The data is based on the following conditions.
- Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]

### MODEL: ASU7RLF1

Outdoor temperature (°FDB)	Indoor temperature (°FDB / °FWB)											
	64.0 / 54.0		70.0 / 60.0		75.0 / 63.0		80.0 / 67.0		85.0 / 71.0		90.0 / 73.0	
	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
14.0	5.88	4.12	6.65	4.70	7.01	5.41	7.50	6.08	8.02	6.64	8.27	7.61
23.0	5.88	4.12	6.65	4.70	7.01	5.41	7.50	6.08	8.02	6.64	8.27	7.61
32.0	5.88	4.12	6.65	4.70	7.01	5.41	7.50	6.08	8.02	6.64	8.27	7.61
41.0	5.88	4.12	6.65	4.70	7.01	5.41	7.50	6.08	8.02	6.64	8.27	7.61
50.0	5.88	4.12	6.65	4.70	7.01	5.41	7.50	6.08	8.02	6.64	8.27	7.61
59.0	5.88	4.12	6.65	4.70	7.01	5.41	7.50	6.08	8.02	6.64	8.27	7.61
67.0	5.88	4.12	6.65	4.70	7.01	5.41	7.50	6.08	8.02	6.64	8.27	7.61
77.0	5.88	4.12	6.65	4.70	7.01	5.41	7.50	6.08	8.02	6.64	8.27	7.61
87.0	5.88	4.12	6.65	4.70	7.01	5.41	7.50	6.08	8.02	6.64	8.27	7.61
95.0	5.88	4.12	6.65	4.70	7.01	5.41	7.50	6.08	8.02	6.64	8.27	7.61
104.0	5.11	3.12	5.78	3.55	6.09	4.09	6.52	4.60	6.97	5.03	7.19	5.76
115.0	4.35	2.25	4.92	2.57	5.18	2.96	5.55	3.32	5.93	3.64	6.11	4.17

### MODEL: ASU9RLF1

Outdoor temperature (°FDB)	Indoor temperature (°FDB / °FWB)											
	64.0 / 54.0		70.0 / 60.0		75.0 / 63.0		80.0 / 67.0		85.0 / 71.0		90.0 / 73.0	
	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
14.0	7.53	5.27	8.51	6.01	8.97	6.92	9.60	7.78	10.26	8.50	10.58	9.74
23.0	7.53	5.27	8.51	6.01	8.97	6.92	9.60	7.78	10.26	8.50	10.58	9.74
32.0	7.53	5.27	8.51	6.01	8.97	6.92	9.60	7.78	10.26	8.50	10.58	9.74
41.0	7.53	5.27	8.51	6.01	8.97	6.92	9.60	7.78	10.26	8.50	10.58	9.74
50.0	7.53	5.27	8.51	6.01	8.97	6.92	9.60	7.78	10.26	8.50	10.58	9.74
59.0	7.53	5.27	8.51	6.01	8.97	6.92	9.60	7.78	10.26	8.50	10.58	9.74
67.0	7.53	5.27	8.51	6.01	8.97	6.92	9.60	7.78	10.26	8.50	10.58	9.74
77.0	7.53	5.27	8.51	6.01	8.97	6.92	9.60	7.78	10.26	8.50	10.58	9.74
87.0	7.53	5.27	8.51	6.01	8.97	6.92	9.60	7.78	10.26	8.50	10.58	9.74
95.0	7.53	5.27	8.51	6.01	8.97	6.92	9.60	7.78	10.26	8.50	10.58	9.74
104.0	6.55	3.99	7.40	4.55	7.80	5.24	8.35	5.88	8.93	6.44	9.20	7.37
115.0	5.57	2.89	6.29	3.29	6.63	3.79	7.10	4.26	7.59	4.65	7.83	5.33

### MODEL: ASU12RLF1

Outdoor temperature (°FDB)	Indoor temperature (°FDB / °FWB)											
	64.0 / 54.0		70.0 / 60.0		75.0 / 63.0		80.0 / 67.0		85.0 / 71.0		90.0 / 73.0	
	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
14.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
23.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
32.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
41.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
50.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
59.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
67.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
77.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
87.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
95.0	10.04	6.60	11.34	7.52	11.96	8.66	12.80	9.73	13.68	10.64	14.11	12.19
104.0	8.73	4.99	9.87	5.69	10.40	6.55	11.13	7.36	11.90	8.05	12.27	9.22
115.0	7.42	3.61	8.39	4.12	8.84	4.74	9.47	5.32	10.12	5.82	10.43	6.67

**MODEL: ASU15RLF1**

Outdoor temperature	Indoor temperature (°FDB / °FWB)											
	64.0 / 54.0		70.0 / 60.0		75.0 / 63.0		80.0 / 67.0		85.0 / 71.0		90.0 / 73.0	
(°FDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
14.0	12.54	8.14	14.18	9.28	14.94	10.68	16.00	12.00	17.10	13.12	17.63	15.04
23.0	12.54	8.14	14.18	9.28	14.94	10.68	16.00	12.00	17.10	13.12	17.63	15.04
32.0	12.54	8.14	14.18	9.28	14.94	10.68	16.00	12.00	17.10	13.12	17.63	15.04
41.0	12.54	8.14	14.18	9.28	14.94	10.68	16.00	12.00	17.10	13.12	17.63	15.04
50.0	12.54	8.14	14.18	9.28	14.94	10.68	16.00	12.00	17.10	13.12	17.63	15.04
59.0	12.54	8.14	14.18	9.28	14.94	10.68	16.00	12.00	17.10	13.12	17.63	15.04
67.0	12.54	8.14	14.18	9.28	14.94	10.68	16.00	12.00	17.10	13.12	17.63	15.04
77.0	12.54	8.14	14.18	9.28	14.94	10.68	16.00	12.00	17.10	13.12	17.63	15.04
87.0	12.54	8.14	14.18	9.28	14.94	10.68	16.00	12.00	17.10	13.12	17.63	15.04
95.0	12.54	8.14	14.18	9.28	14.94	10.68	16.00	12.00	17.10	13.12	17.63	15.04
104.0	10.91	6.16	12.33	7.02	13.00	8.08	13.92	9.08	14.88	9.93	15.34	11.38
115.0	9.28	4.45	10.49	5.08	11.05	5.84	11.84	6.57	12.65	7.18	13.04	8.23

**MODEL: ASU18RLF**

Outdoor temperature	Indoor temperature (°FDB / °FWB)											
	64.0 / 54.0		70.0 / 60.0		75.0 / 63.0		80.0 / 67.0		85.0 / 71.0		90.0 / 73.0	
(°FDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
14.0	15.05	10.03	17.01	11.43	17.93	13.16	19.20	14.78	20.52	16.17	21.16	18.53
23.0	15.05	10.03	17.01	11.43	17.93	13.16	19.20	14.78	20.52	16.17	21.16	18.53
32.0	15.05	10.03	17.01	11.43	17.93	13.16	19.20	14.78	20.52	16.17	21.16	18.53
41.0	15.05	10.03	17.01	11.43	17.93	13.16	19.20	14.78	20.52	16.17	21.16	18.53
50.0	15.05	10.03	17.01	11.43	17.93	13.16	19.20	14.78	20.52	16.17	21.16	18.53
59.0	15.05	10.03	17.01	11.43	17.93	13.16	19.20	14.78	20.52	16.17	21.16	18.53
67.0	15.05	10.03	17.01	11.43	17.93	13.16	19.20	14.78	20.52	16.17	21.16	18.53
77.0	15.05	10.03	17.01	11.43	17.93	13.16	19.20	14.78	20.52	16.17	21.16	18.53
87.0	15.05	10.03	17.01	11.43	17.93	13.16	19.20	14.78	20.52	16.17	21.16	18.53
95.0	15.05	10.03	17.01	11.43	17.93	13.16	19.20	14.78	20.52	16.17	21.16	18.53
104.0	13.09	7.59	14.80	8.65	15.60	9.96	16.70	11.19	17.85	12.24	18.41	14.02
115.0	11.14	5.49	12.58	6.25	13.27	7.20	14.20	8.09	15.18	8.85	15.65	10.14

**MODEL: ASU24RLF**

Outdoor temperature	Indoor temperature (°FDB / °FWB)											
	64.0 / 54.0		70.0 / 60.0		75.0 / 63.0		80.0 / 67.0		85.0 / 71.0		90.0 / 73.0	
(°FDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
14.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
23.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
32.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
41.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
50.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
59.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
67.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
77.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
87.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
95.0	20.07	12.15	22.68	13.85	23.91	15.95	25.60	17.92	27.37	19.60	28.21	22.46
104.0	17.46	9.20	19.73	10.48	20.80	12.07	22.27	13.56	23.81	14.83	24.54	16.99
115.0	14.85	6.65	16.78	7.58	17.69	8.73	18.94	9.81	20.24	10.73	20.87	12.29

## ● Unit: kW, °C

- TC: Total Capacity (kW), SHC: Sensible Heat Capacity (kW).
- The data is based on the following conditions:  
Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]

### MODEL: ASU7RLF1

Outdoor temperature	Indoor temperature (°CDB / °CWB)											
	17.8 / 12.2		21.1 / 15.6		23.9 / 17.2		26.7 / 19.4		29.4 / 21.7		32.2 / 22.8	
(°CDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
-10.0	1.72	1.21	1.95	1.38	2.05	1.58	2.20	1.78	2.35	1.95	2.42	2.23
-5.0	1.72	1.21	1.95	1.38	2.05	1.58	2.20	1.78	2.35	1.95	2.42	2.23
0.0	1.72	1.21	1.95	1.38	2.05	1.58	2.20	1.78	2.35	1.95	2.42	2.23
5.0	1.72	1.21	1.95	1.38	2.05	1.58	2.20	1.78	2.35	1.95	2.42	2.23
10.0	1.72	1.21	1.95	1.38	2.05	1.58	2.20	1.78	2.35	1.95	2.42	2.23
15.0	1.72	1.21	1.95	1.38	2.05	1.58	2.20	1.78	2.35	1.95	2.42	2.23
20.0	1.72	1.21	1.95	1.38	2.05	1.58	2.20	1.78	2.35	1.95	2.42	2.23
25.0	1.72	1.21	1.95	1.38	2.05	1.58	2.20	1.78	2.35	1.95	2.42	2.23
30.0	1.72	1.21	1.95	1.38	2.05	1.58	2.20	1.78	2.35	1.95	2.42	2.23
35.0	1.72	1.21	1.95	1.38	2.05	1.58	2.20	1.78	2.35	1.95	2.42	2.23
40.0	1.50	0.91	1.69	1.04	1.79	1.20	1.91	1.35	2.04	1.47	2.11	1.69
46.1	1.27	0.66	1.44	0.75	1.52	0.87	1.63	0.97	1.74	1.07	1.79	1.22

### MODEL: ASU9RLF1

Outdoor temperature	Indoor temperature (°CDB / °CWB)											
	17.8 / 12.2		21.1 / 15.6		23.9 / 17.2		26.7 / 19.4		29.4 / 21.7		32.2 / 22.8	
(°CDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
-10.0	2.21	1.55	2.49	1.76	2.63	2.03	2.81	2.28	3.01	2.49	3.10	2.86
-5.0	2.21	1.55	2.49	1.76	2.63	2.03	2.81	2.28	3.01	2.49	3.10	2.86
0.0	2.21	1.55	2.49	1.76	2.63	2.03	2.81	2.28	3.01	2.49	3.10	2.86
5.0	2.21	1.55	2.49	1.76	2.63	2.03	2.81	2.28	3.01	2.49	3.10	2.86
10.0	2.21	1.55	2.49	1.76	2.63	2.03	2.81	2.28	3.01	2.49	3.10	2.86
15.0	2.21	1.55	2.49	1.76	2.63	2.03	2.81	2.28	3.01	2.49	3.10	2.86
20.0	2.21	1.55	2.49	1.76	2.63	2.03	2.81	2.28	3.01	2.49	3.10	2.86
25.0	2.21	1.55	2.49	1.76	2.63	2.03	2.81	2.28	3.01	2.49	3.10	2.86
30.0	2.21	1.55	2.49	1.76	2.63	2.03	2.81	2.28	3.01	2.49	3.10	2.86
35.0	2.21	1.55	2.49	1.76	2.63	2.03	2.81	2.28	3.01	2.49	3.10	2.86
40.0	1.92	1.17	2.17	1.33	2.29	1.53	2.45	1.72	2.62	1.89	2.70	2.16
46.1	1.63	0.85	1.84	0.96	1.94	1.11	2.08	1.25	2.22	1.36	2.29	1.56

### MODEL: ASU12RLF1

Outdoor temperature	Indoor temperature (°CDB / °CWB)											
	17.8 / 12.2		21.1 / 15.6		23.9 / 17.2		26.7 / 19.4		29.4 / 21.7		32.2 / 22.8	
(°CDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
-10.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
-5.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
0.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
5.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
10.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
15.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
20.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
25.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
30.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
35.0	2.94	1.93	3.32	2.20	3.50	2.54	3.75	2.85	4.01	3.12	4.13	3.57
40.0	2.56	1.46	2.89	1.67	3.05	1.92	3.26	2.16	3.49	2.36	3.60	2.70
46.1	2.18	1.06	2.46	1.21	2.59	1.39	2.78	1.56	2.97	1.71	3.06	1.96

**MODEL: ASU15RLF**

Outdoor temperature (°CDB)	Indoor temperature (°CDB / °CWB)											
	17.8 / 12.2		21.1 / 15.6		23.9 / 17.2		26.7 / 19.4		29.4 / 21.7		32.2 / 22.8	
TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	
-10.0	3.68	2.39	4.15	2.72	4.38	3.13	4.69	3.52	5.01	3.85	5.17	4.41
-5.0	3.68	2.39	4.15	2.72	4.38	3.13	4.69	3.52	5.01	3.85	5.17	4.41
0.0	3.68	2.39	4.15	2.72	4.38	3.13	4.69	3.52	5.01	3.85	5.17	4.41
5.0	3.68	2.39	4.15	2.72	4.38	3.13	4.69	3.52	5.01	3.85	5.17	4.41
10.0	3.68	2.39	4.15	2.72	4.38	3.13	4.69	3.52	5.01	3.85	5.17	4.41
15.0	3.68	2.39	4.15	2.72	4.38	3.13	4.69	3.52	5.01	3.85	5.17	4.41
20.0	3.68	2.39	4.15	2.72	4.38	3.13	4.69	3.52	5.01	3.85	5.17	4.41
25.0	3.68	2.39	4.15	2.72	4.38	3.13	4.69	3.52	5.01	3.85	5.17	4.41
30.0	3.68	2.39	4.15	2.72	4.38	3.13	4.69	3.52	5.01	3.85	5.17	4.41
35.0	3.68	2.39	4.15	2.72	4.38	3.13	4.69	3.52	5.01	3.85	5.17	4.41
40.0	3.20	1.80	3.61	2.06	3.81	2.37	4.08	2.66	4.36	2.91	4.50	3.33
46.1	2.72	1.31	3.07	1.49	3.24	1.71	3.47	1.92	3.71	2.10	3.82	2.41

**MODEL: ASU18RLF**

Outdoor temperature (°CDB)	Indoor temperature (°CDB / °CWB)											
	17.8 / 12.2		21.1 / 15.6		23.9 / 17.2		26.7 / 19.4		29.4 / 21.7		32.2 / 22.8	
TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	
-10.0	4.41	2.94	4.99	3.35	5.26	3.86	5.63	4.33	6.02	4.74	6.20	5.43
-5.0	4.41	2.94	4.99	3.35	5.26	3.86	5.63	4.33	6.02	4.74	6.20	5.43
0.0	4.41	2.94	4.99	3.35	5.26	3.86	5.63	4.33	6.02	4.74	6.20	5.43
5.0	4.41	2.94	4.99	3.35	5.26	3.86	5.63	4.33	6.02	4.74	6.20	5.43
10.0	4.41	2.94	4.99	3.35	5.26	3.86	5.63	4.33	6.02	4.74	6.20	5.43
15.0	4.41	2.94	4.99	3.35	5.26	3.86	5.63	4.33	6.02	4.74	6.20	5.43
20.0	4.41	2.94	4.99	3.35	5.26	3.86	5.63	4.33	6.02	4.74	6.20	5.43
25.0	4.41	2.94	4.99	3.35	5.26	3.86	5.63	4.33	6.02	4.74	6.20	5.43
30.0	4.41	2.94	4.99	3.35	5.26	3.86	5.63	4.33	6.02	4.74	6.20	5.43
35.0	4.41	2.94	4.99	3.35	5.26	3.86	5.63	4.33	6.02	4.74	6.20	5.43
40.0	3.84	2.22	4.34	2.53	4.57	2.92	4.89	3.28	5.23	3.59	5.39	4.11
46.1	3.26	1.61	3.69	1.83	3.89	2.11	4.16	2.37	4.45	2.59	4.59	2.97

**MODEL: ASU24RLF**

Outdoor temperature (°CDB)	Indoor temperature (°CDB / °CWB)											
	17.8 / 12.2		21.1 / 15.6		23.9 / 17.2		26.7 / 19.4		29.4 / 21.7		32.2 / 22.8	
TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	
-10.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
-5.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
0.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
5.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
10.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
15.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
20.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
25.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
30.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
35.0	5.88	3.56	6.65	4.06	7.01	4.67	7.50	5.25	8.02	5.74	8.27	6.58
40.0	5.12	2.70	5.78	3.07	6.10	3.54	6.53	3.97	6.98	4.35	7.19	4.98
46.1	4.35	1.95	4.92	2.22	5.18	2.56	5.55	2.87	5.93	3.14	6.12	3.60

## ■ Floor type

### ● Unit: kBtu/h, °F

- TC: Total Capacity (kBtu/h), SHC: Sensible Heat Capacity (kBtu/h).
- The data is based on the following conditions:  
Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]

#### MODEL: AGU9RLF

Outdoor temperature (°FDB)	Indoor temperature (°FDB / °FWB)											
	64.0 / 54.0		70.0 / 60.0		75.0 / 63.0		80.0 / 67.0		85.0 / 71.0		90.0 / 73.0	
TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	
14.0	7.53	5.14	8.51	5.86	8.97	6.75	9.60	7.58	10.26	8.29	10.58	9.50
23.0	7.53	5.14	8.51	5.86	8.97	6.75	9.60	7.58	10.26	8.29	10.58	9.50
32.0	7.53	5.14	8.51	5.86	8.97	6.75	9.60	7.58	10.26	8.29	10.58	9.50
41.0	7.53	5.14	8.51	5.86	8.97	6.75	9.60	7.58	10.26	8.29	10.58	9.50
50.0	7.53	5.14	8.51	5.86	8.97	6.75	9.60	7.58	10.26	8.29	10.58	9.50
59.0	7.53	5.14	8.51	5.86	8.97	6.75	9.60	7.58	10.26	8.29	10.58	9.50
67.0	7.53	5.14	8.51	5.86	8.97	6.75	9.60	7.58	10.26	8.29	10.58	9.50
77.0	7.53	5.14	8.51	5.86	8.97	6.75	9.60	7.58	10.26	8.29	10.58	9.50
87.0	7.53	5.14	8.51	5.86	8.97	6.75	9.60	7.58	10.26	8.29	10.58	9.50
95.0	7.53	5.14	8.51	5.86	8.97	6.75	9.60	7.58	10.26	8.29	10.58	9.50
104.0	7.12	4.60	8.05	5.25	8.48	6.04	9.08	6.79	9.71	7.43	10.01	8.51
115.0	6.72	4.10	7.59	4.67	8.00	5.38	8.57	6.04	9.16	6.61	9.44	7.57

#### MODEL: AGU12RLF

Outdoor temperature (°FDB)	Indoor temperature (°FDB / °FWB)											
	64.0 / 54.0		70.0 / 60.0		75.0 / 63.0		80.0 / 67.0		85.0 / 71.0		90.0 / 73.0	
TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	
14.0	10.04	6.42	11.34	7.32	11.96	8.43	12.80	9.47	13.68	10.36	14.11	11.87
23.0	10.04	6.42	11.34	7.32	11.96	8.43	12.80	9.47	13.68	10.36	14.11	11.87
32.0	10.04	6.42	11.34	7.32	11.96	8.43	12.80	9.47	13.68	10.36	14.11	11.87
41.0	10.04	6.42	11.34	7.32	11.96	8.43	12.80	9.47	13.68	10.36	14.11	11.87
50.0	10.04	6.42	11.34	7.32	11.96	8.43	12.80	9.47	13.68	10.36	14.11	11.87
59.0	10.04	6.42	11.34	7.32	11.96	8.43	12.80	9.47	13.68	10.36	14.11	11.87
67.0	10.04	6.42	11.34	7.32	11.96	8.43	12.80	9.47	13.68	10.36	14.11	11.87
77.0	10.04	6.42	11.34	7.32	11.96	8.43	12.80	9.47	13.68	10.36	14.11	11.87
87.0	10.04	6.42	11.34	7.32	11.96	8.43	12.80	9.47	13.68	10.36	14.11	11.87
95.0	10.04	6.42	11.34	7.32	11.96	8.43	12.80	9.47	13.68	10.36	14.11	11.87
104.0	9.50	5.75	10.73	6.56	11.31	7.55	12.11	8.48	12.95	9.27	13.35	10.63
115.0	8.96	5.12	10.12	5.83	10.67	6.71	11.42	7.54	12.21	8.25	12.59	9.45

#### MODEL: AGU15RLF

Outdoor temperature (°FDB)	Indoor temperature (°FDB / °FWB)											
	64.0 / 54.0		70.0 / 60.0		75.0 / 63.0		80.0 / 67.0		85.0 / 71.0		90.0 / 73.0	
TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	
14.0	12.54	7.81	14.18	8.91	14.94	10.25	16.00	11.52	17.10	12.60	17.63	14.44
23.0	12.54	7.81	14.18	8.91	14.94	10.25	16.00	11.52	17.10	12.60	17.63	14.44
32.0	12.54	7.81	14.18	8.91	14.94	10.25	16.00	11.52	17.10	12.60	17.63	14.44
41.0	12.54	7.81	14.18	8.91	14.94	10.25	16.00	11.52	17.10	12.60	17.63	14.44
50.0	12.54	7.81	14.18	8.91	14.94	10.25	16.00	11.52	17.10	12.60	17.63	14.44
59.0	12.54	7.81	14.18	8.91	14.94	10.25	16.00	11.52	17.10	12.60	17.63	14.44
67.0	12.54	7.81	14.18	8.91	14.94	10.25	16.00	11.52	17.10	12.60	17.63	14.44
77.0	12.54	7.81	14.18	8.91	14.94	10.25	16.00	11.52	17.10	12.60	17.63	14.44
87.0	12.54	7.81	14.18	8.91	14.94	10.25	16.00	11.52	17.10	12.60	17.63	14.44
95.0	12.54	7.81	14.18	8.91	14.94	10.25	16.00	11.52	17.10	12.60	17.63	14.44
104.0	11.87	6.99	13.41	7.97	14.14	9.18	15.14	10.31	16.18	11.28	16.68	12.92
115.0	11.19	6.22	12.65	7.09	13.34	8.17	14.28	9.17	15.26	10.03	15.73	11.50

## ● Unit: kW, °C

- TC: Total Capacity (kW), SHC: Sensible Heat Capacity (kW).
- The data is based on the following conditions:  
Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]

OUTDOOR UNIT  
AOU45RLXFZOUTDOOR UNIT  
AOU45RLXFZ

### MODEL: AGU9RLF

Outdoor temperature	Indoor temperature (°CDB / °CWB)											
	17.8 / 12.2		21.1 / 15.6		23.9 / 17.2		26.7 / 19.4		29.4 / 21.7		32.2 / 22.8	
(°CDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
-10.0	2.21	1.51	2.49	1.72	2.63	1.98	2.81	2.22	3.01	2.43	3.10	2.79
-5.0	2.21	1.51	2.49	1.72	2.63	1.98	2.81	2.22	3.01	2.43	3.10	2.79
0.0	2.21	1.51	2.49	1.72	2.63	1.98	2.81	2.22	3.01	2.43	3.10	2.79
5.0	2.21	1.51	2.49	1.72	2.63	1.98	2.81	2.22	3.01	2.43	3.10	2.79
10.0	2.21	1.51	2.49	1.72	2.63	1.98	2.81	2.22	3.01	2.43	3.10	2.79
15.0	2.21	1.51	2.49	1.72	2.63	1.98	2.81	2.22	3.01	2.43	3.10	2.79
20.0	2.21	1.51	2.49	1.72	2.63	1.98	2.81	2.22	3.01	2.43	3.10	2.79
25.0	2.21	1.51	2.49	1.72	2.63	1.98	2.81	2.22	3.01	2.43	3.10	2.79
30.0	2.21	1.51	2.49	1.72	2.63	1.98	2.81	2.22	3.01	2.43	3.10	2.79
35.0	2.21	1.51	2.49	1.72	2.63	1.98	2.81	2.22	3.01	2.43	3.10	2.79
40.0	2.09	1.35	2.36	1.54	2.49	1.77	2.66	1.99	2.85	2.18	2.93	2.49
46.1	1.97	1.20	2.22	1.37	2.35	1.58	2.51	1.77	2.68	1.94	2.77	2.22

### MODEL: AGU12RLF

Outdoor temperature	Indoor temperature (°CDB / °CWB)											
	17.8 / 12.2		21.1 / 15.6		23.9 / 17.2		26.7 / 19.4		29.4 / 21.7		32.2 / 22.8	
(°CDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
-10.0	2.94	1.88	3.32	2.15	3.50	2.47	3.75	2.78	4.01	3.04	4.13	3.48
-5.0	2.94	1.88	3.32	2.15	3.50	2.47	3.75	2.78	4.01	3.04	4.13	3.48
0.0	2.94	1.88	3.32	2.15	3.50	2.47	3.75	2.78	4.01	3.04	4.13	3.48
5.0	2.94	1.88	3.32	2.15	3.50	2.47	3.75	2.78	4.01	3.04	4.13	3.48
10.0	2.94	1.88	3.32	2.15	3.50	2.47	3.75	2.78	4.01	3.04	4.13	3.48
15.0	2.94	1.88	3.32	2.15	3.50	2.47	3.75	2.78	4.01	3.04	4.13	3.48
20.0	2.94	1.88	3.32	2.15	3.50	2.47	3.75	2.78	4.01	3.04	4.13	3.48
25.0	2.94	1.88	3.32	2.15	3.50	2.47	3.75	2.78	4.01	3.04	4.13	3.48
30.0	2.94	1.88	3.32	2.15	3.50	2.47	3.75	2.78	4.01	3.04	4.13	3.48
35.0	2.94	1.88	3.32	2.15	3.50	2.47	3.75	2.78	4.01	3.04	4.13	3.48
40.0	2.78	1.69	3.14	1.92	3.32	2.21	3.55	2.49	3.79	2.72	3.91	3.11
46.1	2.62	1.50	2.97	1.71	3.13	1.97	3.35	2.21	3.58	2.42	3.69	2.77

### MODEL: AGU15RLF

Outdoor temperature	Indoor temperature (°CDB / °CWB)											
	17.8 / 12.2		21.1 / 15.6		23.9 / 17.2		26.7 / 19.4		29.4 / 21.7		32.2 / 22.8	
(°CDB)	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC	TC	SHC
-10.0	3.68	2.29	4.15	2.61	4.38	3.01	4.69	3.38	5.01	3.69	5.17	4.23
-5.0	3.68	2.29	4.15	2.61	4.38	3.01	4.69	3.38	5.01	3.69	5.17	4.23
0.0	3.68	2.29	4.15	2.61	4.38	3.01	4.69	3.38	5.01	3.69	5.17	4.23
5.0	3.68	2.29	4.15	2.61	4.38	3.01	4.69	3.38	5.01	3.69	5.17	4.23
10.0	3.68	2.29	4.15	2.61	4.38	3.01	4.69	3.38	5.01	3.69	5.17	4.23
15.0	3.68	2.29	4.15	2.61	4.38	3.01	4.69	3.38	5.01	3.69	5.17	4.23
20.0	3.68	2.29	4.15	2.61	4.38	3.01	4.69	3.38	5.01	3.69	5.17	4.23
25.0	3.68	2.29	4.15	2.61	4.38	3.01	4.69	3.38	5.01	3.69	5.17	4.23
30.0	3.68	2.29	4.15	2.61	4.38	3.01	4.69	3.38	5.01	3.69	5.17	4.23
35.0	3.68	2.29	4.15	2.61	4.38	3.01	4.69	3.38	5.01	3.69	5.17	4.23
40.0	3.48	2.05	3.93	2.34	4.14	2.69	4.44	3.02	4.74	3.31	4.89	3.79
46.1	3.28	1.82	3.71	2.08	3.91	2.39	4.18	2.69	4.47	2.94	4.61	3.37

## 6-3. Heating capacity

### ■ Model: AOU45RLXFZ

**NOTE:** Values mentioned in the table are calculated based on the maximum capacity.

#### ● Unit: kBtu/h, °F

TC: Total Capacity (kBtu/h), IP: Input Power (kW)

Indoor unit connecting capacity	Outdoor temperature		Indoor temperature											
			60 °FDB		65 °FDB		70 °FDB		75 °FDB		78 °FDB			
kBtu/h	°FDB	°FWB	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP		
54	5	3	33.1	4.70	32.3	4.80	31.5	4.90	30.8	5.00	30.0	5.10		
	14	12	37.3	4.70	36.5	4.80	35.6	4.90	34.7	5.00	33.8	5.10		
	23	19	41.6	4.70	40.6	4.80	39.6	4.90	38.6	5.00	37.6	5.10		
	32	28	48.4	4.70	47.3	4.80	46.1	4.90	45.0	5.00	43.8	5.10		
	41	37	55.3	4.70	54.0	4.80	52.7	4.90	51.3	5.00	50.0	5.10		
	47	43	56.7	4.24	55.4	4.32	54.0	4.41	52.7	4.50	51.3	4.59		
	50	47	56.7	4.24	55.4	4.32	54.0	4.41	52.7	4.50	51.3	4.59		
	59	50	56.7	3.95	55.4	4.03	54.0	4.11	52.7	4.19	51.3	4.27		
	68	59	54.1	3.42	52.8	3.49	51.5	3.56	50.2	3.63	49.0	3.70		
53	75	65	51.6	3.12	50.3	3.19	49.1	3.25	47.9	3.32	46.7	3.38		
	5	3	33.1	4.70	32.3	4.80	31.5	4.90	30.8	5.00	30.0	5.10		
	14	12	37.3	4.70	36.5	4.80	35.6	4.90	34.7	5.00	33.8	5.10		
	23	19	41.6	4.70	40.6	4.80	39.6	4.90	38.6	5.00	37.6	5.10		
	32	28	48.4	4.70	47.3	4.80	46.1	4.90	45.0	5.00	43.8	5.10		
	41	37	55.3	4.70	54.0	4.80	52.7	4.90	51.3	5.00	50.0	5.10		
	47	43	56.7	4.24	55.4	4.32	54.0	4.41	52.7	4.50	51.3	4.59		
	50	47	56.7	4.24	55.4	4.32	54.0	4.41	52.7	4.50	51.3	4.59		
	59	50	56.7	3.95	55.4	4.03	54.0	4.11	52.7	4.19	51.3	4.27		
52	68	59	54.1	3.42	52.8	3.49	51.5	3.56	50.2	3.63	49.0	3.70		
	75	65	51.6	3.12	50.3	3.19	49.1	3.25	47.9	3.32	46.7	3.38		
	5	3	33.1	4.70	32.3	4.80	31.5	4.90	30.8	5.00	30.0	5.10		
	14	12	37.3	4.70	36.5	4.80	35.6	4.90	34.7	5.00	33.8	5.10		
	23	19	41.6	4.70	40.6	4.80	39.6	4.90	38.6	5.00	37.6	5.10		
	32	28	48.4	4.70	47.3	4.80	46.1	4.90	45.0	5.00	43.8	5.10		
	41	37	55.3	4.70	54.0	4.80	52.7	4.90	51.3	5.00	50.0	5.10		
	47	43	56.7	4.24	55.4	4.32	54.0	4.41	52.7	4.50	51.3	4.59		
	50	47	56.7	4.24	55.4	4.32	54.0	4.41	52.7	4.50	51.3	4.59		
51	59	50	56.7	3.95	55.4	4.03	54.0	4.11	52.7	4.19	51.3	4.27		
	68	59	54.1	3.42	52.8	3.49	51.5	3.56	50.2	3.63	49.0	3.70		
	75	65	51.6	3.12	50.3	3.19	49.1	3.25	47.9	3.32	46.7	3.38		
	5	3	33.1	4.70	32.3	4.80	31.5	4.90	30.8	5.00	30.0	5.10		
	14	12	37.3	4.70	36.5	4.80	35.6	4.90	34.7	5.00	33.8	5.10		
	23	19	41.6	4.70	40.6	4.80	39.6	4.90	38.6	5.00	37.6	5.10		
	32	28	48.4	4.70	47.3	4.80	46.1	4.90	45.0	5.00	43.8	5.10		
	41	37	55.3	4.70	54.0	4.80	52.7	4.90	51.3	5.00	50.0	5.10		
	47	43	56.7	4.24	55.4	4.32	54.0	4.41	52.7	4.50	51.3	4.59		
50	50	47	56.7	4.24	55.4	4.32	54.0	4.41	52.7	4.50	51.3	4.59		
	59	50	56.7	3.95	55.4	4.03	54.0	4.11	52.7	4.19	51.3	4.27		
	68	59	54.1	3.42	52.8	3.49	51.5	3.56	50.2	3.63	49.0	3.70		
	75	65	51.6	3.12	50.3	3.19	49.1	3.25	47.9	3.32	46.7	3.38		
	5	3	33.1	4.70	32.3	4.80	31.5	4.90	30.8	5.00	30.0	5.10		
	14	12	37.3	4.70	36.5	4.80	35.6	4.90	34.7	5.00	33.8	5.10		
	23	19	41.6	4.70	40.6	4.80	39.6	4.90	38.6	5.00	37.6	5.10		
	32	28	48.4	4.70	47.3	4.80	46.1	4.90	45.0	5.00	43.8	5.10		
	41	37	55.3	4.70	54.0	4.80	52.7	4.90	51.3	5.00	50.0	5.10		
49	47	43	56.7	4.24	55.4	4.32	54.0	4.41	52.7	4.50	51.3	4.59		
	50	47	56.7	4.24	55.4	4.32	54.0	4.41	52.7	4.50	51.3	4.59		
	59	50	56.7	3.95	55.4	4.03	54.0	4.11	52.7	4.19	51.3	4.27		
	68	59	54.1	3.42	52.8	3.49	51.5	3.56	50.2	3.63	49.0	3.70		
	75	65	51.6	3.12	50.3	3.19	49.1	3.25	47.9	3.32	46.7	3.38		
	5	3	33.1	4.70	32.3	4.80	31.5	4.90	30.8	5.00	30.0	5.10		
	14	12	37.3	4.70	36.5	4.80	35.6	4.90	34.7	5.00	33.8	5.10		
	23	19	41.6	4.70	40.6	4.80	39.6	4.90	38.6	5.00	37.6	5.10		
	32	28	48.4	4.70	47.3	4.80	46.1	4.90	45.0	5.00	43.8	5.10		
48	41	37	55.3	4.70	54.0	4.80	52.7	4.90	51.3	5.00	50.0	5.10		
	47	43	56.7	4.24	55.4	4.32	54.0	4.41	52.7	4.50	51.3	4.59		
	50	47	56.7	4.24	55.4	4.32	54.0	4.41	52.7	4.50	51.3	4.59		
	59	50	56.7	3.95	55.4	4.03	54.0	4.11	52.7	4.19	51.3	4.27		
	68	59	54.1	3.42	52.8	3.49	51.5	3.56	50.2	3.63	49.0	3.70		
	75	65	51.6	3.12	50.3	3.19	49.1	3.25	47.9	3.32	46.7	3.38		



Indoor unit connecting capacity	Outdoor temperature		Indoor temperature									
			60 °FDB		65 °FDB		70 °FDB		75 °FDB		78 °FDB	
kBtu/h	°FDB	°FWB	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
38	5	3	28.0	3.93	27.3	4.01	26.6	4.10	26.0	4.18	25.3	4.26
	14	12	31.5	3.93	30.8	4.01	30.0	4.10	29.3	4.18	28.5	4.26
	23	19	35.1	3.93	34.3	4.01	33.4	4.10	32.6	4.18	31.8	4.26
	32	28	40.9	3.93	39.9	4.01	38.9	4.10	38.0	4.18	37.0	4.26
	41	37	46.7	3.93	45.6	4.01	44.5	4.10	43.4	4.18	42.2	4.26
	47	43	47.9	3.54	46.7	3.61	45.6	3.69	44.5	3.76	43.3	3.84
	50	47	47.9	3.54	46.7	3.61	45.6	3.69	44.5	3.76	43.3	3.84
	59	50	47.9	3.30	46.7	3.37	45.6	3.44	44.5	3.50	43.3	3.57
	68	59	45.7	2.86	44.6	2.92	43.5	2.97	42.4	3.03	41.3	3.09
37	75	65	43.6	2.61	42.5	2.66	41.5	2.72	40.4	2.77	39.4	2.83
	5	3	27.2	3.83	26.6	3.91	25.9	3.99	25.3	4.07	24.6	4.15
	14	12	30.7	3.83	30.0	3.91	29.2	3.99	28.5	4.07	27.8	4.15
	23	19	34.2	3.83	33.4	3.91	32.6	3.99	31.7	4.07	30.9	4.15
	32	28	39.8	3.83	38.9	3.91	37.9	3.99	37.0	4.07	36.0	4.15
	41	37	45.5	3.83	44.4	3.91	43.3	3.99	42.2	4.07	41.1	4.15
	47	43	46.6	3.44	45.5	3.51	44.4	3.58	43.3	3.66	42.2	3.73
	50	47	46.6	3.44	45.5	3.51	44.4	3.58	43.3	3.66	42.2	3.73
	59	50	46.6	3.21	45.5	3.27	44.4	3.34	43.3	3.41	42.2	3.47
36	68	59	44.5	2.78	43.4	2.83	42.4	2.89	41.3	2.95	40.3	3.01
	75	65	42.4	2.54	41.4	2.59	40.4	2.64	39.4	2.70	38.4	2.75
	5	3	26.5	3.72	25.9	3.79	25.2	3.87	24.6	3.95	24.0	4.02
	14	12	29.9	3.72	29.2	3.79	28.5	3.87	27.7	3.95	27.0	4.02
	23	19	33.3	3.72	32.5	3.79	31.7	3.87	30.9	3.95	30.1	4.02
	32	28	38.7	3.72	37.8	3.79	36.9	3.87	36.0	3.95	35.1	4.02
	41	37	44.2	3.72	43.2	3.79	42.1	3.87	41.1	3.95	40.0	4.02
	47	43	45.4	3.34	44.3	3.41	43.2	3.48	42.1	3.55	41.0	3.62
	50	47	45.4	3.34	44.3	3.41	43.2	3.48	42.1	3.55	41.0	3.62
35	59	50	45.4	3.11	44.3	3.18	43.2	3.24	42.1	3.31	41.0	3.37
	68	59	43.3	2.70	42.3	2.75	41.2	2.81	40.2	2.86	39.2	2.92
	75	65	41.3	2.46	40.3	2.52	39.3	2.57	38.3	2.62	37.3	2.67
	5	3	25.8	3.60	25.1	3.68	24.5	3.75	23.9	3.83	23.3	3.90
	14	12	29.0	3.60	28.4	3.68	27.7	3.75	27.0	3.83	26.3	3.90
	23	19	32.3	3.60	31.6	3.68	30.8	3.75	30.0	3.83	29.3	3.90
	32	28	37.7	3.60	36.8	3.68	35.9	3.75	35.0	3.83	34.1	3.90
	41	37	43.0	3.60	42.0	3.68	41.0	3.75	39.9	3.83	38.9	3.90
	47	43	44.1	3.24	43.1	3.31	42.0	3.38	41.0	3.44	39.9	3.51
34	50	47	44.1	3.24	43.1	3.31	42.0	3.38	41.0	3.44	39.9	3.51
	59	50	44.1	3.02	43.1	3.08	42.0	3.15	41.0	3.21	39.9	3.27
	68	59	42.1	2.62	41.1	2.67	40.1	2.72	39.1	2.78	38.1	2.83
	75	65	40.1	2.39	39.2	2.44	38.2	2.49	37.3	2.54	36.3	2.59
	5	3	25.0	3.49	24.4	3.57	23.8	3.64	23.2	3.71	22.6	3.79
	14	12	28.2	3.49	27.5	3.57	26.9	3.64	26.2	3.71	25.5	3.79
	23	19	31.4	3.49	30.7	3.57	29.9	3.64	29.2	3.71	28.4	3.79
	32	28	36.6	3.49	35.7	3.57	34.8	3.64	34.0	3.71	33.1	3.79
	41	37	41.8	3.49	40.8	3.57	39.8	3.64	38.8	3.71	37.8	3.79

**NOTE:** Specifications are based on the following conditions.

- Power source of specifications: 230 V
- 2 or more indoor units should be connected.
- Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]
- The total ability of connected a indoor unit is from 34,000 Btu up to 54,000 Btu.
- Input in the table are calculated based on the maximum indoor unit input combinations.

## ● Unit: kW, °C

TC: Total Capacity (kW), IP: Input Power (kW)

Indoor unit connecting capacity	Outdoor temperature		Indoor temperature									
			15.6 °CDB		18.3 °CDB		21.1 °CDB		23.9 °CDB		25.6 °CDB	
kBtu/h	°CDB	°CWB	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
46	-15.0	-16.1	9.70	4.70	9.47	4.80	9.20	4.90	9.01	5.00	8.78	5.10
	-10.0	-11.1	10.94	4.70	10.68	4.80	10.40	4.90	10.16	5.00	9.90	5.10
	-5.0	-7.2	12.18	4.70	11.89	4.80	11.60	4.90	11.31	5.00	11.02	5.10
	0.0	-2.2	14.19	4.70	13.85	4.80	13.50	4.90	13.18	5.00	12.84	5.10
	5.0	2.8	16.20	4.70	15.81	4.80	15.40	4.90	15.04	5.00	14.66	5.10
	8.3	6.1	16.61	4.24	16.22	4.32	15.80	4.41	15.43	4.50	15.03	4.59
	10.0	8.3	16.61	4.24	16.22	4.32	15.80	4.41	15.43	4.50	15.03	4.59
	15.0	10.0	16.61	3.95	16.22	4.03	15.80	4.11	15.43	4.19	15.03	4.27
	20.0	15.0	15.85	3.42	15.48	3.49	15.10	3.56	14.72	3.63	14.34	3.70
	23.9	18.3	15.11	3.12	14.75	3.19	14.30	3.25	14.03	3.32	13.67	3.38
45	-15.0	-16.1	9.70	4.70	9.47	4.80	9.20	4.90	9.01	5.00	8.78	5.10
	-10.0	-11.1	10.94	4.70	10.68	4.80	10.40	4.90	10.16	5.00	9.90	5.10
	-5.0	-7.2	12.18	4.70	11.89	4.80	11.60	4.90	11.31	5.00	11.02	5.10
	0.0	-2.2	14.19	4.70	13.85	4.80	13.50	4.90	13.18	5.00	12.84	5.10
	5.0	2.8	16.20	4.70	15.81	4.80	15.40	4.90	15.04	5.00	14.66	5.10
	8.3	6.1	16.61	4.24	16.22	4.32	15.80	4.41	15.43	4.50	15.03	4.59
	10.0	8.3	16.61	4.24	16.22	4.32	15.80	4.41	15.43	4.50	15.03	4.59
	15.0	10.0	16.61	3.95	16.22	4.03	15.80	4.11	15.43	4.19	15.03	4.27
	20.0	15.0	15.85	3.42	15.48	3.49	15.10	3.56	14.72	3.63	14.34	3.70
	23.9	18.3	15.11	3.12	14.75	3.19	14.30	3.25	14.03	3.32	13.67	3.38
44	-15.0	-16.1	9.49	4.60	9.26	4.69	9.00	4.79	8.81	4.89	8.58	4.98
	-10.0	-11.1	10.70	4.60	10.44	4.69	10.10	4.79	9.93	4.89	9.68	4.98
	-5.0	-7.2	11.91	4.60	11.62	4.69	11.30	4.79	11.06	4.89	10.77	4.98
	0.0	-2.2	13.87	4.60	13.54	4.69	13.20	4.79	12.88	4.89	12.55	4.98
	5.0	2.8	15.84	4.60	15.46	4.69	15.00	4.79	14.71	4.89	14.33	4.98
	8.3	6.1	16.24	4.14	15.86	4.22	15.40	4.31	15.08	4.39	14.70	4.48
	10.0	8.3	16.24	4.14	15.86	4.22	15.40	4.31	15.08	4.39	14.70	4.48
	15.0	10.0	16.24	3.85	15.86	3.93	15.40	4.01	15.08	4.09	14.70	4.17
	20.0	15.0	15.50	3.34	15.13	3.41	14.70	3.48	14.39	3.55	14.02	3.61
	23.9	18.3	14.78	3.05	14.42	3.11	14.00	3.18	13.72	3.24	13.37	3.30
43	-15.0	-16.1	9.27	4.48	9.05	4.58	8.80	4.67	8.61	4.76	8.39	4.86
	-10.0	-11.1	10.45	4.48	10.20	4.58	9.90	4.67	9.71	4.76	9.46	4.86
	-5.0	-7.2	11.64	4.48	11.36	4.58	11.00	4.67	10.81	4.76	10.53	4.86
	0.0	-2.2	13.56	4.48	13.24	4.58	12.90	4.67	12.59	4.76	12.27	4.86
	5.0	2.8	15.48	4.48	15.11	4.58	14.70	4.67	14.37	4.76	14.01	4.86
	8.3	6.1	15.87	4.04	15.50	4.12	15.10	4.21	14.74	4.29	14.36	4.37
	10.0	8.3	15.87	4.04	15.50	4.12	15.10	4.21	14.74	4.29	14.36	4.37
	15.0	10.0	15.87	3.76	15.14	3.74	14.70	3.82	14.40	3.90	14.03	3.97
	20.0	15.0	15.15	3.26	14.79	3.32	14.00	3.31	13.74	3.37	13.39	3.44
	23.9	18.3	14.44	2.98	14.10	3.04	13.70	3.10	13.41	3.16	13.06	3.22
42	-15.0	-16.1	9.05	4.38	8.84	4.47	8.60	4.56	8.41	4.65	8.19	4.74
	-10.0	-11.1	10.21	4.38	9.97	4.47	9.70	4.56	9.48	4.65	9.24	4.74
	-5.0	-7.2	11.37	4.38	11.10	4.47	10.80	4.56	10.55	4.65	10.28	4.74
	0.0	-2.2	13.24	4.38	12.93	4.47	12.60	4.56	12.30	4.65	11.98	4.74
	5.0	2.8	15.12	4.38	14.76	4.47	14.40	4.56	14.04	4.65	13.68	4.74
	8.3	6.1	15.50	3.94	15.14	4.02	14.70	4.10	14.40	4.18	14.03	4.27
	10.0	8.3	15.50	3.94	15.14	4.02	14.70	4.10	14.40	4.18	14.03	4.27
	15.0	10.0	15.50	3.67	15.14	3.74	14.70	3.82	14.40	3.90	14.03	3.97
	20.0	15.0	14.80	3.18	14.44	3.24	14.00	3.31	13.74	3.37	13.39	3.44
	23.9	18.3	14.10	2.90	13.77	2.96	13.40	3.02	13.10	3.08	12.76	3.15
41	-15.0	-16.1	8.84	4.26	8.63	4.35	8.40	4.44	8.21	4.53	8.00	4.62
	-10.0	-11.1	9.97	4.26	9.73	4.35	9.40	4.44	9.25	4.53	9.02	4.62
	-5.0	-7.2	11.10	4.26	10.83	4.35	10.50	4.44	10.30	4.53	10.04	4.62
	0.0	-2.2	12.93	4.26	12.62	4.35	12.30	4.44	12.00	4.53	11.70	4.62
	5.0	2.8	14.76	4.26	14.41	4.35	14.00	4.44	13.71	4.53	13.35	4.62
	8.3	6.1	15.14	3.84	14.78	3.92	14.40	4.00	14.05	4.08	13.69	4.16
	10.0	8.3	15.14	3.84	14.78	3.92	14.40	4.00	14.05	4.08	13.69	4.16
	15.0	10.0	15.14	3.58	14.78	3.65	14.40	3.72	14.05	3.80	13.69	3.87
	20.0	15.0	14.44	3.10	14.10	3.16	13.70	3.23	13.41	3.29	13.07	3.35
	23.9	18.3	13.77	2.83	13.44	2.89	13.10	2.95	12.78	3.01	12.46	3.07
40	-15.0	-16.1	8.62	4.16	8.42	4.24	8.20	4.33	8.01	4.42	7.80	4.50
	-10.0	-11.1	9.72	4.16	9.49	4.24	9.20	4.33	9.03	4.42	8.80	4.50
	-5.0	-7.2	10.82	4.16	10.57	4.24	10.30	4.33	10.05	4.42	9.79	4.50
	0.0	-2.2	12.61	4.16	12.31	4.24	12.00	4.33	11.71	4.42	11.41	4.50
	5.0	2.8	14.40	4.16	14.06	4.24	13.70	4.33	13.37	4.42	13.03	4.50
	8.3	6.1	14.77	3.74	14.41	3.82	14.00	3.89	13.71	3.97	13.36	4.05
	10.0	8.3	14.77	3.74	14.41	3.82	14.00	3.89	13.71	3.97	13.36	4.05
	15.0	10.0	14.77	3.48	14.41	3.56	14.00	3.63	13.71	3.70	13.36	3.77
	20.0	15.0	14.09	3.02	13.76	3.08	13.40	3.14	13.09	3.20	12.75	3.27
	23.9	18.3	13.43	2.76	13.11	2.81	12.70	2.87	12.47	2.93	12.15	2.99
39	-15.0	-16.1	8.41	4.05	8.21	4.14	8.00	4.22	7.81	4.30	7.61	4.39
	-10.0	-11.1	9.48	4.05	9.25	4.14	9.00	4.22	8.80	4.30	8.58	4.39
	-5.0	-7.2	10.55	4.05	10.30	4.14	10.00	4.22	9.80	4.30	9.55	4.39
	0.0	-2.2	12.30	4.05	12.00	4.14	11.70	4.22	11.42	4.30	11.12	4.39
	5.0	2.8	14.04	4.05	13.71	4.14	13.30	4.22	13.04	4.30	12.70	4.39
	8.3	6.1	14.40	3.64	14.05	3.72	13.70	3.79	13.37	3.87	13.03	3.94
	10.0	8.3	14.40	3.64	14.05	3.72	13.70	3.79	13.37	3.87	13.03	3.94
	15.0	10.0	14.40	3.39	14.05	3.46	13.70	3.53	13.37	3.60	13.03	3.67
	20.0	15.0	13.74	2.94	13.41	3.00	13.00	3.06	12.76	3.12	12.43	3.18
	23.9	18.3	13.10	2.68	12.78	2.74	12.40	2.80	12.16	2.85	11.85	2.91
38	-15.0	-16.1	8.19	3.93	8.00	4.01	7.80	4.10	7.61	4.18	7.41	4.26
	-10.0	-11.1	9.24	3.93	9.02	4.01	8.80	4.10	8.58	4.18	8.36	4.26

Indoor unit connecting capacity	Outdoor temperature		Indoor temperature									
			15.6 °CDB		18.3 °CDB		21.1 °CDB		23.9 °CDB		25.6 °CDB	
kBtu/h	°CDB	°CWB	TC	IP	TC	IP	TC	IP	TC	IP	TC	IP
37	-15.0	-16.1	7.98	3.83	7.79	3.91	7.60	3.99	7.41	4.07	7.22	4.15
	-10.0	-11.1	8.99	3.83	8.78	3.91	8.50	3.99	8.35	4.07	8.14	4.15
	-5.0	-7.2	10.01	3.83	9.77	3.91	9.50	3.99	9.30	4.07	9.06	4.15
	0.0	-2.2	11.67	3.83	11.39	3.91	11.10	3.99	10.83	4.07	10.55	4.15
	5.0	2.8	13.32	3.83	13.00	3.91	12.60	3.99	12.37	4.07	12.05	4.15
	8.3	6.1	13.66	3.44	13.33	3.51	13.00	3.58	12.68	3.66	12.36	3.73
	10.0	8.3	13.66	3.44	13.33	3.51	13.00	3.58	12.68	3.66	12.36	3.73
	15.0	10.0	13.66	3.21	13.33	3.27	13.00	3.34	12.68	3.41	12.36	3.47
	20.0	15.0	13.03	2.78	12.72	2.83	12.40	2.89	12.10	2.95	11.79	3.01
	23.9	18.3	12.42	2.54	12.13	2.59	11.80	2.64	11.54	2.70	11.24	2.75
36	-15.0	-16.1	7.76	3.72	7.58	3.79	7.30	3.87	7.21	3.95	7.02	4.02
	-10.0	-11.1	8.75	3.72	8.54	3.79	8.30	3.87	8.13	3.95	7.92	4.02
	-5.0	-7.2	9.74	3.72	9.51	3.79	9.20	3.87	9.05	3.95	8.81	4.02
	0.0	-2.2	11.35	3.72	11.08	3.79	10.80	3.87	10.54	3.95	10.27	4.02
	5.0	2.8	12.96	3.72	12.65	3.79	12.30	3.87	12.03	3.95	11.72	4.02
	8.3	6.1	13.29	3.34	12.97	3.41	12.60	3.48	12.34	3.55	12.02	3.62
	10.0	8.3	13.29	3.34	12.97	3.41	12.60	3.48	12.34	3.55	12.02	3.62
	15.0	10.0	13.29	3.11	12.97	3.18	12.60	3.24	12.34	3.31	12.02	3.37
	20.0	15.0	12.68	2.70	12.38	2.75	12.00	2.81	11.78	2.86	11.47	2.92
	23.9	18.3	12.09	2.46	11.80	2.52	11.50	2.57	11.22	2.62	10.94	2.67
35	-15.0	-16.1	7.54	3.60	7.36	3.68	7.10	3.75	7.01	3.83	6.83	3.90
	-10.0	-11.1	8.51	3.60	8.30	3.68	8.10	3.75	7.90	3.83	7.70	3.90
	-5.0	-7.2	9.47	3.60	9.25	3.68	9.00	3.75	8.79	3.83	8.57	3.90
	0.0	-2.2	11.03	3.60	10.77	3.68	10.50	3.75	10.25	3.83	9.98	3.90
	5.0	2.8	12.60	3.60	12.30	3.68	12.00	3.75	11.70	3.83	11.40	3.90
	8.3	6.1	12.92	3.24	12.61	3.31	12.30	3.38	12.00	3.44	11.69	3.51
	10.0	8.3	12.92	3.24	12.61	3.31	12.30	3.38	12.00	3.44	11.69	3.51
	15.0	10.0	12.92	3.02	12.61	3.08	12.30	3.15	12.00	3.21	11.69	3.27
	20.0	15.0	12.33	2.62	12.04	2.67	11.70	2.72	11.45	2.78	11.16	2.83
	23.9	18.3	11.75	2.39	11.47	2.44	11.10	2.49	10.91	2.54	10.63	2.59
34	-15.0	-16.1	7.33	3.49	7.15	3.57	6.90	3.64	6.80	3.71	6.63	3.79
	-10.0	-11.1	8.26	3.49	8.07	3.57	7.80	3.64	7.67	3.71	7.48	3.79
	-5.0	-7.2	9.20	3.49	8.98	3.57	8.70	3.64	8.54	3.71	8.32	3.79
	0.0	-2.2	10.72	3.49	10.46	3.57	10.20	3.64	9.95	3.71	9.70	3.79
	5.0	2.8	12.24	3.49	11.95	3.57	11.60	3.64	11.36	3.71	11.07	3.79
	8.3	6.1	12.55	3.15	12.25	3.21	11.90	3.28	11.65	3.34	11.35	3.41
	10.0	8.3	12.55	3.15	12.25	3.21	11.90	3.28	11.65	3.34	11.35	3.41
	15.0	10.0	12.55	2.93	12.25	2.99	11.90	3.05	11.65	3.11	11.35	3.17
	20.0	15.0	11.98	2.54	11.69	2.59	11.40	2.64	11.12	2.70	10.84	2.75
	23.9	18.3	11.42	2.32	11.14	2.37	10.80	2.42	10.60	2.46	10.33	2.51

**NOTE:** Specifications are based on the following conditions.

- Power source of specifications: 230 V
- 2 or more indoor units should be connected.
- Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]
- The total ability of connected a indoor unit is from 34,000 Btu up to 54,000 Btu.
- Input in the table are calculated based on the maximum indoor unit input combinations.

## ■ Compact cassette type

### ● Unit: kBtu/h, °F

- TC: Total Capacity (kBtu/h).
- The data is based on the following conditions:  
Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]

### MODEL: AUU7RLF

Outdoor temperature		Indoor temperature (°FDB)				
		60.0	65.0	70.0	75.0	78.0
(°FDB)	(°FWB)	TC	TC	TC	TC	TC
5.0	3.0	5.15	5.03	4.91	4.78	4.66
14.0	12.0	5.81	5.67	5.53	5.39	5.26
23.0	19.0	6.47	6.31	6.16	6.00	5.85
32.0	28.0	7.53	7.35	7.17	7.00	6.82
41.0	37.0	8.60	8.40	8.19	7.99	7.78
47.0	43.0	8.82	8.61	8.40	8.19	7.98
50.0	47.0	8.82	8.61	8.40	8.19	7.98
59.0	50.0	8.82	8.61	8.40	8.19	7.98
68.0	59.0	8.42	8.22	8.02	7.82	7.62
75.0	65.0	8.02	7.83	7.64	7.45	7.26

### MODEL: AUU9RLF

Outdoor temperature		Indoor temperature (°FDB)				
		60.0	65.0	70.0	75.0	78.0
(°FDB)	(°FWB)	TC	TC	TC	TC	TC
5.0	3.0	6.62	6.47	6.31	6.15	5.99
14.0	12.0	7.47	7.29	7.11	6.94	6.76
23.0	19.0	8.31	8.12	7.92	7.72	7.52
32.0	28.0	9.69	9.46	9.22	8.99	8.76
41.0	37.0	11.06	10.80	10.53	10.27	10.01
47.0	43.0	11.34	11.07	10.80	10.53	10.26
50.0	47.0	11.34	11.07	10.80	10.53	10.26
59.0	50.0	11.34	11.07	10.80	10.53	10.26
68.0	59.0	10.82	10.56	10.31	10.05	9.79
75.0	65.0	10.32	10.07	9.82	9.58	9.33

### MODEL: AUU12RLF

Outdoor temperature		Indoor temperature (°FDB)				
		60.0	65.0	70.0	75.0	78.0
(°FDB)	(°FWB)	TC	TC	TC	TC	TC
5.0	3.0	8.83	8.62	8.41	8.20	7.99
14.0	12.0	9.96	9.72	9.48	9.25	9.01
23.0	19.0	11.08	10.82	10.56	10.29	10.03
32.0	28.0	12.91	12.61	12.30	11.99	11.68
41.0	37.0	14.74	14.39	14.04	13.69	13.34
47.0	43.0	15.12	14.76	14.40	14.04	13.68
50.0	47.0	15.12	14.76	14.40	14.04	13.68
59.0	50.0	15.12	14.76	14.40	14.04	13.68
68.0	59.0	14.43	14.09	13.74	13.40	13.06
75.0	65.0	13.75	13.43	13.10	12.77	12.44

### MODEL: AUU18RLF

Outdoor temperature		Indoor temperature (°FDB)				
		60.0	65.0	70.0	75.0	78.0
(°FDB)	(°FWB)	TC	TC	TC	TC	TC
5.0	3.0	13.25	12.93	12.62	12.30	11.99
14.0	12.0	14.94	14.58	14.23	13.87	13.51
23.0	19.0	16.63	16.23	15.84	15.44	15.04
32.0	28.0	19.37	18.91	18.45	17.99	17.53
41.0	37.0	22.12	21.59	21.06	20.54	20.01
47.0	43.0	22.68	22.14	21.60	21.06	20.52
50.0	47.0	22.68	22.14	21.60	21.06	20.52
59.0	50.0	22.68	22.14	21.60	21.06	20.52
68.0	59.0	21.64	21.13	20.61	20.10	19.58
75.0	65.0	20.63	20.14	19.65	19.16	18.67

## ● Unit: kW, °C

- TC: Total Capacity (kW).
- The data is based on the following conditions:  
Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]

### MODEL: AUU7RLF

Outdoor temperature		Indoor temperature (°CDB)				
		15.6	18.3	21.1	23.9	25.6
(°CDB)	(°CWB)	TC	TC	TC	TC	TC
-15.0	-16.1	1.51	1.47	1.44	1.40	1.37
-10.0	-11.1	1.70	1.66	1.62	1.58	1.54
-5.0	-7.2	1.90	1.85	1.80	1.76	1.71
0.0	-2.2	2.21	2.16	2.10	2.05	2.00
5.0	2.8	2.52	2.46	2.40	2.34	2.28
8.3	6.1	2.58	2.52	2.46	2.40	2.34
10.0	8.3	2.58	2.52	2.46	2.40	2.34
15.0	10.0	2.58	2.52	2.46	2.40	2.34
20.0	15.0	2.47	2.41	2.35	2.29	2.23
23.9	18.3	2.35	2.30	2.24	2.18	2.13

### MODEL: AUU9RLF

Outdoor temperature		Indoor temperature (°CDB)				
		15.6	18.3	21.1	23.9	25.6
(°CDB)	(°CWB)	TC	TC	TC	TC	TC
-15.0	-16.1	1.94	1.90	1.85	1.80	1.76
-10.0	-11.1	2.19	2.14	2.08	2.03	1.98
-5.0	-7.2	2.44	2.38	2.32	2.26	2.20
0.0	-2.2	2.84	2.77	2.70	2.64	2.57
5.0	2.8	3.24	3.16	3.09	3.01	2.93
8.3	6.1	3.32	3.24	3.17	3.09	3.01
10.0	8.3	3.32	3.24	3.17	3.09	3.01
15.0	10.0	3.32	3.24	3.17	3.09	3.01
20.0	15.0	3.17	3.10	3.02	2.95	2.87
23.9	18.3	3.02	2.95	2.88	2.81	2.74

### MODEL: AUU12RLF

Outdoor temperature		Indoor temperature (°CDB)				
		15.6	18.3	21.1	23.9	25.6
(°CDB)	(°CWB)	TC	TC	TC	TC	TC
-15.0	-16.1	2.59	2.53	2.47	2.40	2.34
-10.0	-11.1	2.92	2.85	2.78	2.71	2.64
-5.0	-7.2	3.25	3.17	3.09	3.02	2.94
0.0	-2.2	3.79	3.69	3.60	3.51	3.42
5.0	2.8	4.32	4.22	4.12	4.01	3.91
8.3	6.1	4.43	4.33	4.22	4.11	4.01
10.0	8.3	4.43	4.33	4.22	4.11	4.01
15.0	10.0	4.43	4.33	4.22	4.11	4.01
20.0	15.0	4.23	4.13	4.03	3.93	3.83
23.9	18.3	4.03	3.94	3.84	3.74	3.65

### MODEL: AUU18RLF

Outdoor temperature		Indoor temperature (°CDB)				
		15.6	18.3	21.1	23.9	25.6
(°CDB)	(°CWB)	TC	TC	TC	TC	TC
-15.0	-16.1	3.88	3.79	3.70	3.61	3.51
-10.0	-11.1	4.38	4.27	4.17	4.07	3.96
-5.0	-7.2	4.87	4.76	4.64	4.53	4.41
0.0	-2.2	5.68	5.54	5.41	5.27	5.14
5.0	2.8	6.48	6.33	6.17	6.02	5.86
8.3	6.1	6.65	6.49	6.33	6.17	6.01
10.0	8.3	6.65	6.49	6.33	6.17	6.01
15.0	10.0	6.65	6.49	6.33	6.17	6.01
20.0	15.0	6.34	6.19	6.04	5.89	5.74
23.9	18.3	6.05	5.90	5.76	5.61	5.47

## ■ Slim duct type

### ● Unit: kBtu/h, °F

- TC: Total Capacity (kBtu/h).
- The data is based on the following conditions:  
Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]

### MODEL: ARU7RLF

Outdoor temperature		Indoor temperature (°FDB)				
		60.0	65.0	70.0	75.0	78.0
(°FDB)	(°FWB)	TC	TC	TC	TC	TC
5.0	3.0	5.15	5.03	4.91	4.78	4.66
14.0	12.0	5.81	5.67	5.53	5.39	5.26
23.0	19.0	6.47	6.31	6.16	6.00	5.85
32.0	28.0	7.53	7.35	7.17	7.00	6.82
41.0	37.0	8.60	8.40	8.19	7.99	7.78
47.0	43.0	8.82	8.61	8.40	8.19	7.98
50.0	47.0	8.82	8.61	8.40	8.19	7.98
59.0	50.0	8.82	8.61	8.40	8.19	7.98
68.0	59.0	8.42	8.22	8.02	7.82	7.62
75.0	65.0	8.02	7.83	7.64	7.45	7.26

### MODEL: ARU9RLF

Outdoor temperature		Indoor temperature (°FDB)				
		60.0	65.0	70.0	75.0	78.0
(°FDB)	(°FWB)	TC	TC	TC	TC	TC
5.0	3.0	6.62	6.47	6.31	6.15	5.99
14.0	12.0	7.47	7.29	7.11	6.94	6.76
23.0	19.0	8.31	8.12	7.92	7.72	7.52
32.0	28.0	9.69	9.46	9.22	8.99	8.76
41.0	37.0	11.06	10.80	10.53	10.27	10.01
47.0	43.0	11.34	11.07	10.80	10.53	10.26
50.0	47.0	11.34	11.07	10.80	10.53	10.26
59.0	50.0	11.34	11.07	10.80	10.53	10.26
68.0	59.0	10.82	10.56	10.31	10.05	9.79
75.0	65.0	10.32	10.07	9.82	9.58	9.33

### MODEL: ARU12RLF

Outdoor temperature		Indoor temperature (°FDB)				
		60.0	65.0	70.0	75.0	78.0
(°FDB)	(°FWB)	TC	TC	TC	TC	TC
5.0	3.0	8.83	8.62	8.41	8.20	7.99
14.0	12.0	9.96	9.72	9.48	9.25	9.01
23.0	19.0	11.08	10.82	10.56	10.29	10.03
32.0	28.0	12.91	12.61	12.30	11.99	11.68
41.0	37.0	14.74	14.39	14.04	13.69	13.34
47.0	43.0	15.12	14.76	14.40	14.04	13.68
50.0	47.0	15.12	14.76	14.40	14.04	13.68
59.0	50.0	15.12	14.76	14.40	14.04	13.68
68.0	59.0	14.43	14.09	13.74	13.40	13.06
75.0	65.0	13.75	13.43	13.10	12.77	12.44

### MODEL: ARU18RLF

Outdoor temperature		Indoor temperature (°FDB)				
		60.0	65.0	70.0	75.0	78.0
(°FDB)	(°FWB)	TC	TC	TC	TC	TC
5.0	3.0	13.25	12.93	12.62	12.30	11.99
14.0	12.0	14.94	14.58	14.23	13.87	13.51
23.0	19.0	16.63	16.23	15.84	15.44	15.04
32.0	28.0	19.37	18.91	18.45	17.99	17.53
41.0	37.0	22.12	21.59	21.06	20.54	20.01
47.0	43.0	22.68	22.14	21.60	21.06	20.52
50.0	47.0	22.68	22.14	21.60	21.06	20.52
59.0	50.0	22.68	22.14	21.60	21.06	20.52
68.0	59.0	21.64	21.13	20.61	20.10	19.58
75.0	65.0	20.63	20.14	19.65	19.16	18.67

**MODEL: ARU24RLF**

Outdoor temperature		Indoor temperature (°FDB)				
		60.0	65.0	70.0	75.0	78.0
(°FDB)	(°FWB)	TC	TC	TC	TC	TC
5.0	3.0	17.66	17.24	16.82	16.40	15.98
14.0	12.0	19.92	19.44	18.97	18.49	18.02
23.0	19.0	22.17	21.64	21.11	20.59	20.06
32.0	28.0	25.83	25.21	24.60	23.98	23.37
41.0	37.0	29.49	28.79	28.08	27.38	26.68
47.0	43.0	30.24	29.52	28.80	28.08	27.36
50.0	47.0	30.24	29.52	28.80	28.08	27.36
59.0	50.0	30.24	29.52	28.80	28.08	27.36
68.0	59.0	28.86	28.17	27.49	26.80	26.11
75.0	65.0	27.51	26.85	26.20	25.54	24.89

OUTDOOR UNIT  
AOU45RLXFZOUTDOOR UNIT  
AOU45RLXFZ

## ● Unit: kW, °C

- TC: Total Capacity (kW).
- The data is based on the following conditions:  
Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]

### MODEL: ARU7RLF

Outdoor temperature		Indoor temperature (°CDB)				
		15.6	18.3	21.1	23.9	25.6
(°CDB)	(°CWB)	TC	TC	TC	TC	TC
-15.0	-16.1	1.51	1.47	1.44	1.40	1.37
-10.0	-11.1	1.70	1.66	1.62	1.58	1.54
-5.0	-7.2	1.90	1.85	1.80	1.76	1.71
0.0	-2.2	2.21	2.16	2.10	2.05	2.00
5.0	2.8	2.52	2.46	2.40	2.34	2.28
8.3	6.1	2.58	2.52	2.46	2.40	2.34
10.0	8.3	2.58	2.52	2.46	2.40	2.34
15.0	10.0	2.58	2.52	2.46	2.40	2.34
20.0	15.0	2.47	2.41	2.35	2.29	2.23
23.9	18.3	2.35	2.30	2.24	2.18	2.13

### MODEL: ARU9RLF

Outdoor temperature		Indoor temperature (°CDB)				
		15.6	18.3	21.1	23.9	25.6
(°CDB)	(°CWB)	TC	TC	TC	TC	TC
-15.0	-16.1	1.94	1.90	1.85	1.80	1.76
-10.0	-11.1	2.19	2.14	2.08	2.03	1.98
-5.0	-7.2	2.44	2.38	2.32	2.26	2.20
0.0	-2.2	2.84	2.77	2.70	2.64	2.57
5.0	2.8	3.24	3.16	3.09	3.01	2.93
8.3	6.1	3.32	3.24	3.17	3.09	3.01
10.0	8.3	3.32	3.24	3.17	3.09	3.01
15.0	10.0	3.32	3.24	3.17	3.09	3.01
20.0	15.0	3.17	3.10	3.02	2.95	2.87
23.9	18.3	3.02	2.95	2.88	2.81	2.74

### MODEL: ARU12RLF

Outdoor temperature		Indoor temperature (°CDB)				
		15.6	18.3	21.1	23.9	25.6
(°CDB)	(°CWB)	TC	TC	TC	TC	TC
-15.0	-16.1	2.59	2.53	2.47	2.40	2.34
-10.0	-11.1	2.92	2.85	2.78	2.71	2.64
-5.0	-7.2	3.25	3.17	3.09	3.02	2.94
0.0	-2.2	3.79	3.69	3.60	3.51	3.42
5.0	2.8	4.32	4.22	4.12	4.01	3.91
8.3	6.1	4.43	4.33	4.22	4.11	4.01
10.0	8.3	4.43	4.33	4.22	4.11	4.01
15.0	10.0	4.43	4.33	4.22	4.11	4.01
20.0	15.0	4.23	4.13	4.03	3.93	3.83
23.9	18.3	4.03	3.94	3.84	3.74	3.65

### MODEL: ARU18RLF

Outdoor temperature		Indoor temperature (°CDB)				
		15.6	18.3	21.1	23.9	25.6
(°CDB)	(°CWB)	TC	TC	TC	TC	TC
-15.0	-16.1	3.88	3.79	3.70	3.61	3.51
-10.0	-11.1	4.38	4.27	4.17	4.07	3.96
-5.0	-7.2	4.87	4.76	4.64	4.53	4.41
0.0	-2.2	5.68	5.54	5.41	5.27	5.14
5.0	2.8	6.48	6.33	6.17	6.02	5.86
8.3	6.1	6.65	6.49	6.33	6.17	6.01
10.0	8.3	6.65	6.49	6.33	6.17	6.01
15.0	10.0	6.65	6.49	6.33	6.17	6.01
20.0	15.0	6.34	6.19	6.04	5.89	5.74
23.9	18.3	6.05	5.90	5.76	5.61	5.47

**MODEL: ARU24RLF**

Outdoor temperature		Indoor temperature (°CDB)				
		15.6	18.3	21.1	23.9	25.6
(°CDB)	(°CWB)	TC	TC	TC	TC	TC
-15.0	-16.1	5.18	5.05	4.93	4.81	4.68
-10.0	-11.1	5.84	5.70	5.56	5.42	5.28
-5.0	-7.2	6.50	6.34	6.19	6.03	5.88
0.0	-2.2	7.57	7.39	7.21	7.03	6.85
5.0	2.8	8.64	8.44	8.23	8.03	7.82
8.3	6.1	8.86	8.65	8.44	8.23	8.02
10.0	8.3	8.86	8.65	8.44	8.23	8.02
15.0	10.0	8.86	8.65	8.44	8.23	8.02
20.0	15.0	8.46	8.26	8.06	7.85	7.65
23.9	18.3	8.06	7.87	7.68	7.49	7.29

OUTDOOR UNIT  
AOU45RLXFZOUTDOOR UNIT  
AOU45RLXFZ

## ■ Wall mounted type

### ● Unit: kBtu/h, °F

- TC: Total Capacity (kBtu/h).
- The data is based on the following conditions:  
Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]

#### MODEL: ASU7RLF1

Outdoor temperature		Indoor temperature (°FDB)				
		60.0	65.0	70.0	75.0	78.0
(°FDB)	(°FWB)	TC	TC	TC	TC	TC
5.0	3.0	5.15	5.03	4.91	4.78	4.66
14.0	12.0	5.81	5.67	5.53	5.39	5.26
23.0	19.0	6.47	6.31	6.16	6.00	5.85
32.0	28.0	7.53	7.35	7.17	7.00	6.82
41.0	37.0	8.60	8.40	8.19	7.99	7.78
47.0	43.0	8.82	8.61	8.40	8.19	7.98
50.0	47.0	8.82	8.61	8.40	8.19	7.98
59.0	50.0	8.82	8.61	8.40	8.19	7.98
68.0	59.0	8.42	8.22	8.02	7.82	7.62
75.0	65.0	8.02	7.83	7.64	7.45	7.26

#### MODEL: ASU9RLF1

Outdoor temperature		Indoor temperature (°FDB)				
		60.0	65.0	70.0	75.0	78.0
(°FDB)	(°FWB)	TC	TC	TC	TC	TC
5.0	3.0	6.62	6.47	6.31	6.15	5.99
14.0	12.0	7.47	7.29	7.11	6.94	6.76
23.0	19.0	8.31	8.12	7.92	7.72	7.52
32.0	28.0	9.69	9.46	9.22	8.99	8.76
41.0	37.0	11.06	10.80	10.53	10.27	10.01
47.0	43.0	11.34	11.07	10.80	10.53	10.26
50.0	47.0	11.34	11.07	10.80	10.53	10.26
59.0	50.0	11.34	11.07	10.80	10.53	10.26
68.0	59.0	10.82	10.56	10.31	10.05	9.79
75.0	65.0	10.32	10.07	9.82	9.58	9.33

#### MODEL: ASU12RLF1

Outdoor temperature		Indoor temperature (°FDB)				
		60.0	65.0	70.0	75.0	78.0
(°FDB)	(°FWB)	TC	TC	TC	TC	TC
5.0	3.0	8.83	8.62	8.41	8.20	7.99
14.0	12.0	9.96	9.72	9.48	9.25	9.01
23.0	19.0	11.08	10.82	10.56	10.29	10.03
32.0	28.0	12.91	12.61	12.30	11.99	11.68
41.0	37.0	14.74	14.39	14.04	13.69	13.34
47.0	43.0	15.12	14.76	14.40	14.04	13.68
50.0	47.0	15.12	14.76	14.40	14.04	13.68
59.0	50.0	15.12	14.76	14.40	14.04	13.68
68.0	59.0	14.43	14.09	13.74	13.40	13.06
75.0	65.0	13.75	13.43	13.10	12.77	12.44

**MODEL: ASU15RLF1**

Outdoor temperature		Indoor temperature (°FDB)				
		60.0	65.0	70.0	75.0	78.0
(°FDB)	(°FWB)	TC	TC	TC	TC	TC
5.0	3.0	11.04	10.78	10.51	10.25	9.99
14.0	12.0	12.45	12.15	11.85	11.56	11.26
23.0	19.0	13.86	13.53	13.20	12.87	12.54
32.0	28.0	16.14	15.76	15.37	14.99	14.61
41.0	37.0	18.43	17.99	17.55	17.11	16.68
47.0	43.0	18.90	18.45	18.00	17.55	17.10
50.0	47.0	18.90	18.45	18.00	17.55	17.10
59.0	50.0	18.90	18.45	18.00	17.55	17.10
68.0	59.0	18.04	17.61	17.18	16.75	16.32
75.0	65.0	17.19	16.78	16.37	15.96	15.55

**MODEL: ASU18RLF**

Outdoor temperature		Indoor temperature (°FDB)				
		60.0	65.0	70.0	75.0	78.0
(°FDB)	(°FWB)	TC	TC	TC	TC	TC
5.0	3.0	13.25	12.93	12.62	12.30	11.99
14.0	12.0	14.94	14.58	14.23	13.87	13.51
23.0	19.0	16.63	16.23	15.84	15.44	15.04
32.0	28.0	19.37	18.91	18.45	17.99	17.53
41.0	37.0	22.12	21.59	21.06	20.54	20.01
47.0	43.0	22.68	22.14	21.60	21.06	20.52
50.0	47.0	22.68	22.14	21.60	21.06	20.52
59.0	50.0	22.68	22.14	21.60	21.06	20.52
68.0	59.0	21.64	21.13	20.61	20.10	19.58
75.0	65.0	20.63	20.14	19.65	19.16	18.67

**MODEL: ASU24RLF**

Outdoor temperature		Indoor temperature (°FDB)				
		60.0	65.0	70.0	75.0	78.0
(°FDB)	(°FWB)	TC	TC	TC	TC	TC
5.0	3.0	17.66	17.24	16.82	16.40	15.98
14.0	12.0	19.92	19.44	18.97	18.49	18.02
23.0	19.0	22.17	21.64	21.11	20.59	20.06
32.0	28.0	25.83	25.21	24.60	23.98	23.37
41.0	37.0	29.49	28.79	28.08	27.38	26.68
47.0	43.0	30.24	29.52	28.80	28.08	27.36
50.0	47.0	30.24	29.52	28.80	28.08	27.36
59.0	50.0	30.24	29.52	28.80	28.08	27.36
68.0	59.0	28.86	28.17	27.49	26.80	26.11
75.0	65.0	27.51	26.85	26.20	25.54	24.89

OUTDOOR UNIT  
AOU45RLXFZOUTDOOR UNIT  
AOU45RLXFZ

## ● Unit: kW, °C

- TC: Total Capacity (kW).
- The data is based on the following conditions:  
Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]

### MODEL: ASU7RLF1

Outdoor temperature		Indoor temperature (°CDB)				
		15.6	18.3	21.1	23.9	25.6
(°CDB)	(°CWB)	TC	TC	TC	TC	TC
-15.0	-16.1	1.51	1.47	1.44	1.40	1.37
-10.0	-11.1	1.70	1.66	1.62	1.58	1.54
-5.0	-7.2	1.90	1.85	1.80	1.76	1.71
0.0	-2.2	2.21	2.16	2.10	2.05	2.00
5.0	2.8	2.52	2.46	2.40	2.34	2.28
8.3	6.1	2.58	2.52	2.46	2.40	2.34
10.0	8.3	2.58	2.52	2.46	2.40	2.34
15.0	10.0	2.58	2.52	2.46	2.40	2.34
20.0	15.0	2.47	2.41	2.35	2.29	2.23
23.9	18.3	2.35	2.30	2.24	2.18	2.13

### MODEL: ASU9RLF1

Outdoor temperature		Indoor temperature (°CDB)				
		15.6	18.3	21.1	23.9	25.6
(°CDB)	(°CWB)	TC	TC	TC	TC	TC
-15.0	-16.1	1.94	1.90	1.85	1.80	1.76
-10.0	-11.1	2.19	2.14	2.08	2.03	1.98
-5.0	-7.2	2.44	2.38	2.32	2.26	2.20
0.0	-2.2	2.84	2.77	2.70	2.64	2.57
5.0	2.8	3.24	3.16	3.09	3.01	2.93
8.3	6.1	3.32	3.24	3.17	3.09	3.01
10.0	8.3	3.32	3.24	3.17	3.09	3.01
15.0	10.0	3.32	3.24	3.17	3.09	3.01
20.0	15.0	3.17	3.10	3.02	2.95	2.87
23.9	18.3	3.02	2.95	2.88	2.81	2.74

### MODEL: ASU12RLF1

Outdoor temperature		Indoor temperature (°CDB)				
		15.6	18.3	21.1	23.9	25.6
(°CDB)	(°CWB)	TC	TC	TC	TC	TC
-15.0	-16.1	2.59	2.53	2.47	2.40	2.34
-10.0	-11.1	2.92	2.85	2.78	2.71	2.64
-5.0	-7.2	3.25	3.17	3.09	3.02	2.94
0.0	-2.2	3.79	3.69	3.60	3.51	3.42
5.0	2.8	4.32	4.22	4.12	4.01	3.91
8.3	6.1	4.43	4.33	4.22	4.11	4.01
10.0	8.3	4.43	4.33	4.22	4.11	4.01
15.0	10.0	4.43	4.33	4.22	4.11	4.01
20.0	15.0	4.23	4.13	4.03	3.93	3.83
23.9	18.3	4.03	3.94	3.84	3.74	3.65

**MODEL: ASU15RLF1**

Outdoor temperature		Indoor temperature (°CDB)				
		15.6	18.3	21.1	23.9	25.6
(°CDB)	(°CWB)	TC	TC	TC	TC	TC
-15.0	-16.1	3.24	3.16	3.08	3.00	2.93
-10.0	-11.1	3.65	3.56	3.47	3.39	3.30
-5.0	-7.2	4.06	3.96	3.87	3.77	3.67
0.0	-2.2	4.73	4.62	4.51	4.39	4.28
5.0	2.8	5.40	5.27	5.14	5.02	4.89
8.3	6.1	5.54	5.41	5.28	5.14	5.01
10.0	8.3	5.54	5.41	5.28	5.14	5.01
15.0	10.0	5.54	5.41	5.28	5.14	5.01
20.0	15.0	5.29	5.16	5.03	4.91	4.78
23.9	18.3	5.04	4.92	4.80	4.68	4.56

**MODEL: ASU18RLF**

Outdoor temperature		Indoor temperature (°CDB)				
		15.6	18.3	21.1	23.9	25.6
(°CDB)	(°CWB)	TC	TC	TC	TC	TC
-15.0	-16.1	3.88	3.79	3.70	3.61	3.51
-10.0	-11.1	4.38	4.27	4.17	4.07	3.96
-5.0	-7.2	4.87	4.76	4.64	4.53	4.41
0.0	-2.2	5.68	5.54	5.41	5.27	5.14
5.0	2.8	6.48	6.33	6.17	6.02	5.86
8.3	6.1	6.65	6.49	6.33	6.17	6.01
10.0	8.3	6.65	6.49	6.33	6.17	6.01
15.0	10.0	6.65	6.49	6.33	6.17	6.01
20.0	15.0	6.34	6.19	6.04	5.89	5.74
23.9	18.3	6.05	5.90	5.76	5.61	5.47

**MODEL: ASU24RLF**

Outdoor temperature		Indoor temperature (°CDB)				
		15.6	18.3	21.1	23.9	25.6
(°CDB)	(°CWB)	TC	TC	TC	TC	TC
-15.0	-16.1	5.18	5.05	4.93	4.81	4.68
-10.0	-11.1	5.84	5.70	5.56	5.42	5.28
-5.0	-7.2	6.50	6.34	6.19	6.03	5.88
0.0	-2.2	7.57	7.39	7.21	7.03	6.85
5.0	2.8	8.64	8.44	8.23	8.03	7.82
8.3	6.1	8.86	8.65	8.44	8.23	8.02
10.0	8.3	8.86	8.65	8.44	8.23	8.02
15.0	10.0	8.86	8.65	8.44	8.23	8.02
20.0	15.0	8.46	8.26	8.06	7.85	7.65
23.9	18.3	8.06	7.87	7.68	7.49	7.29

## ■ Floor type

### ● Unit: kBtu/h, °F

- TC: Total Capacity (kBtu/h).
- The data is based on the following conditions:  
Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]

#### MODEL: AGU9RLF

Outdoor temperature		Indoor temperature (°FDB)				
		60.0	65.0	70.0	75.0	78.0
(°FDB)	(°FWB)	TC	TC	TC	TC	TC
5.0	3.0	6.62	6.47	6.31	6.15	5.99
14.0	12.0	7.47	7.29	7.11	6.94	6.76
23.0	19.0	8.31	8.12	7.92	7.72	7.52
32.0	28.0	9.69	9.46	9.22	8.99	8.76
41.0	37.0	11.06	10.80	10.53	10.27	10.01
47.0	43.0	11.34	11.07	10.80	10.53	10.26
50.0	47.0	11.34	11.07	10.80	10.53	10.26
59.0	50.0	11.34	11.07	10.80	10.53	10.26
68.0	59.0	10.82	10.56	10.31	10.05	9.79
75.0	65.0	10.32	10.07	9.82	9.58	9.33

#### MODEL: AGU12RLF

Outdoor temperature		Indoor temperature (°FDB)				
		60.0	65.0	70.0	75.0	78.0
(°FDB)	(°FWB)	TC	TC	TC	TC	TC
5.0	3.0	8.83	8.62	8.41	8.20	7.99
14.0	12.0	9.96	9.72	9.48	9.25	9.01
23.0	19.0	11.08	10.82	10.56	10.29	10.03
32.0	28.0	12.91	12.61	12.30	11.99	11.68
41.0	37.0	14.74	14.39	14.04	13.69	13.34
47.0	43.0	15.12	14.76	14.40	14.04	13.68
50.0	47.0	15.12	14.76	14.40	14.04	13.68
59.0	50.0	15.12	14.76	14.40	14.04	13.68
68.0	59.0	14.43	14.09	13.74	13.40	13.06
75.0	65.0	13.75	13.43	13.10	12.77	12.44

#### MODEL: AGU15RLF

Outdoor temperature		Indoor temperature (°FDB)				
		60.0	65.0	70.0	75.0	78.0
(°FDB)	(°FWB)	TC	TC	TC	TC	TC
5.0	3.0	11.04	10.78	10.51	10.25	9.99
14.0	12.0	12.45	12.15	11.85	11.56	11.26
23.0	19.0	13.86	13.53	13.20	12.87	12.54
32.0	28.0	16.14	15.76	15.37	14.99	14.61
41.0	37.0	18.43	17.99	17.55	17.11	16.68
47.0	43.0	18.90	18.45	18.00	17.55	17.10
50.0	47.0	18.90	18.45	18.00	17.55	17.10
59.0	50.0	18.90	18.45	18.00	17.55	17.10
68.0	59.0	18.04	17.61	17.18	16.75	16.32
75.0	65.0	17.19	16.78	16.37	15.96	15.55

## ● Unit: kW, °C

- TC: Total Capacity (kW).
- The data is based on the following conditions:  
Pipe length: 24.6 ft (7.5 m), Height difference: 0 ft (0 m) [Outdoor unit - Indoor unit]

### MODEL: AGU9RLF

Outdoor temperature		Indoor temperature (°CDB)				
		15.6	18.3	21.1	23.9	25.6
(°CDB)	(°CWB)	TC	TC	TC	TC	TC
-15.0	-16.1	1.94	1.90	1.85	1.80	1.76
-10.0	-11.1	2.19	2.14	2.08	2.03	1.98
-5.0	-7.2	2.44	2.38	2.32	2.26	2.20
0.0	-2.2	2.84	2.77	2.70	2.64	2.57
5.0	2.8	3.24	3.16	3.09	3.01	2.93
8.3	6.1	3.32	3.24	3.17	3.09	3.01
10.0	8.3	3.32	3.24	3.17	3.09	3.01
15.0	10.0	3.32	3.24	3.17	3.09	3.01
20.0	15.0	3.17	3.10	3.02	2.95	2.87
23.9	18.3	3.02	2.95	2.88	2.81	2.74


### MODEL: AGU12RLF

Outdoor temperature		Indoor temperature (°CDB)				
		15.6	18.3	21.1	23.9	25.6
(°CDB)	(°CWB)	TC	TC	TC	TC	TC
-15.0	-16.1	2.59	2.53	2.47	2.40	2.34
-10.0	-11.1	2.92	2.85	2.78	2.71	2.64
-5.0	-7.2	3.25	3.17	3.09	3.02	2.94
0.0	-2.2	3.79	3.69	3.60	3.51	3.42
5.0	2.8	4.32	4.22	4.12	4.01	3.91
8.3	6.1	4.43	4.33	4.22	4.11	4.01
10.0	8.3	4.43	4.33	4.22	4.11	4.01
15.0	10.0	4.43	4.33	4.22	4.11	4.01
20.0	15.0	4.23	4.13	4.03	3.93	3.83
23.9	18.3	4.03	3.94	3.84	3.74	3.65

### MODEL: AGU15RLF

Outdoor temperature		Indoor temperature (°CDB)				
		15.6	18.3	21.1	23.9	25.6
(°CDB)	(°CWB)	TC	TC	TC	TC	TC
-15.0	-16.1	3.24	3.16	3.08	3.00	2.93
-10.0	-11.1	3.65	3.56	3.47	3.39	3.30
-5.0	-7.2	4.06	3.96	3.87	3.77	3.67
0.0	-2.2	4.73	4.62	4.51	4.39	4.28
5.0	2.8	5.40	5.27	5.14	5.02	4.89
8.3	6.1	5.54	5.41	5.28	5.14	5.01
10.0	8.3	5.54	5.41	5.28	5.14	5.01
15.0	10.0	5.54	5.41	5.28	5.14	5.01
20.0	15.0	5.29	5.16	5.03	4.91	4.78
23.9	18.3	5.04	4.92	4.80	4.68	4.56

## 7. Capacity compensation rate for pipe length and height difference

OUTDOOR UNIT  
AOU45RLXFZOUTDOOR UNIT  
AOU45RLXFZ

### 7-1. Model: AOU45RLXFZ

**NOTE:** Values mentioned in the table are calculated based on the maximum capacity.

#### ■ Indoor unit: 7,000 Btu

COOLING		Pipe length							
			m	5	7.5	10	15	20	25
		m	ft	16	25	33	49	66	82
Height difference H (m)	Indoor unit is higher than outdoor unit * <sup>1</sup>	15	49	—	—	—	0.955	0.941	0.927
		10	33	—	—	0.976	0.962	0.949	0.935
		7.5	25	—	0.988	0.980	0.966	0.952	0.939
		5	16	0.995	0.992	0.984	0.970	0.956	0.942
	Indoor unit is lower than outdoor unit * <sup>2</sup>	0	0	1.003	1.000	0.992	0.978	0.964	0.950
		-5	-16	1.003	1.000	0.992	0.978	0.964	0.950
		-7.5	-25	—	1.000	0.992	0.978	0.964	0.950
		-10	-33	—	—	0.992	0.978	0.964	0.950
		-15	-49	—	—	—	0.978	0.964	0.950

HEATING		Pipe length							
			m	5	7.5	10	15	20	25
		m	ft	16	25	33	49	66	82
Height difference H (m)	Indoor unit is higher than outdoor unit * <sup>1</sup>	15	49	—	—	—	0.976	0.957	0.938
		10	33	—	—	0.991	0.976	0.957	0.938
		7.5	25	—	1.000	0.991	0.976	0.957	0.938
		5	16	0.990	1.000	0.991	0.976	0.957	0.938
	Indoor unit is lower than outdoor unit * <sup>2</sup>	0	0	0.990	1.000	0.991	0.976	0.957	0.938
		-5	-16	0.985	0.995	0.986	0.971	0.952	0.933
		-7.5	-25	—	0.993	0.984	0.969	0.950	0.931
		-10	-33	—	—	0.981	0.966	0.947	0.929
		-15	-49	—	—	—	0.961	0.943	0.924

## ■ Indoor unit: 9,000 Btu

OUTDOOR UNIT  
AOU45RLXFZOUTDOOR UNIT  
AOU45RLXFZ

COOLING		Pipe length							
			m	5	7.5	10	15	20	25
		m	ft	16	25	33	49	66	82
Height difference H (m)	Indoor unit is higher than outdoor unit *1	15	49	—	—	—	0.956	0.942	0.928
		10	33	—	—	0.977	0.963	0.950	0.936
		7.5	25	—	0.988	0.981	0.967	0.954	0.940
		5	16	0.999	0.992	0.985	0.971	0.957	0.943
Height difference H (m)	Indoor unit is lower than outdoor unit *2	0	0	1.007	1.000	0.993	0.979	0.965	0.951
		-5	-16	1.007	1.000	0.993	0.979	0.965	0.951
		-7.5	-25	—	1.000	0.993	0.979	0.965	0.951
		-10	-33	—	—	0.993	0.979	0.965	0.951
		-15	-49	—	—	—	0.979	0.965	0.951

HEATING		Pipe length							
			m	5	7.5	10	15	20	25
		m	ft	16	25	33	49	66	82
Height difference H (m)	Indoor unit is higher than outdoor unit *1	15	49	—	—	—	0.977	0.958	0.939
		10	33	—	—	0.993	0.977	0.958	0.939
		7.5	25	—	1.000	0.993	0.977	0.958	0.939
		5	16	0.993	1.000	0.993	0.977	0.958	0.939
Height difference H (m)	Indoor unit is lower than outdoor unit *2	0	0	0.993	1.000	0.993	0.977	0.958	0.939
		-5	-16	0.988	0.995	0.988	0.972	0.954	0.934
		-7.5	-25	—	0.993	0.986	0.970	0.952	0.932
		-10	-33	—	—	0.983	0.967	0.949	0.930
		-15	-49	—	—	—	0.962	0.944	0.925

## ■ Indoor unit: 12,000 Btu

COOLING		Pipe length							
			m	5	7.5	10	15	20	25
		m	ft	16	25	33	49	66	82
Height difference H (m)	Indoor unit is higher than outdoor unit *1	15	49	—	—	—	0.937	0.912	0.888
		10	33	—	—	0.970	0.944	0.919	0.896
		7.5	25	—	0.988	0.974	0.948	0.923	0.899
		5	16	1.006	0.992	0.978	0.952	0.927	0.903
Height difference H (m)	Indoor unit is lower than outdoor unit *2	0	0	1.014	1.000	0.986	0.960	0.934	0.910
		-5	-16	1.014	1.000	0.986	0.960	0.934	0.910
		-7.5	-25	—	1.000	0.986	0.960	0.934	0.910
		-10	-33	—	—	0.986	0.960	0.934	0.910
		-15	-49	—	—	—	0.960	0.934	0.910

HEATING		Pipe length							
			m	5	7.5	10	15	20	25
		m	ft	16	25	33	49	66	82
Height difference H (m)	Indoor unit is higher than outdoor unit *1	15	49	—	—	—	0.977	0.958	0.938
		10	33	—	—	0.993	0.977	0.958	0.938
		7.5	25	—	1.000	0.993	0.977	0.958	0.938
		5	16	0.995	1.000	0.993	0.977	0.958	0.938
Height difference H (m)	Indoor unit is lower than outdoor unit *2	0	0	0.995	1.000	0.993	0.977	0.958	0.938
		-5	-16	0.990	0.995	0.988	0.972	0.953	0.933
		-7.5	-25	—	0.993	0.986	0.970	0.952	0.932
		-10	-33	—	—	0.983	0.967	0.949	0.929
		-15	-49	—	—	—	0.962	0.944	0.924

## ■ Indoor unit: 14,000 Btu

OUTDOOR UNIT  
AOU45RLXFZOUTDOOR UNIT  
AOU45RLXFZ

COOLING		Pipe length							
			m	5	7.5	10	15	20	25
		m	ft	16	25	33	49	66	82
Height difference H (m)	Indoor unit is higher than outdoor unit *1	15	49	—	—	—	0.955	0.937	0.922
		10	33	—	—	0.974	0.962	0.945	0.930
		7.5	25	—	0.988	0.978	0.966	0.948	0.934
		5	16	0.997	0.992	0.982	0.970	0.952	0.937
Height difference H (m)	Indoor unit is lower than outdoor unit *2	0	0	1.005	1.000	0.990	0.978	0.960	0.945
		-5	-16	1.005	1.000	0.990	0.978	0.960	0.945
		-7.5	-25	—	1.000	0.990	0.978	0.960	0.945
		-10	-33	—	—	0.990	0.978	0.960	0.945
		-15	-49	—	—	—	0.978	0.960	0.945

HEATING		Pipe length							
			m	5	7.5	10	15	20	25
		m	ft	16	25	33	49	66	82
Height difference H (m)	Indoor unit is higher than outdoor unit *1	15	49	—	—	—	0.972	0.945	0.919
		10	33	—	—	0.992	0.972	0.945	0.919
		7.5	25	—	1.000	0.992	0.972	0.945	0.919
		5	16	1.000	1.000	0.992	0.972	0.945	0.919
Height difference H (m)	Indoor unit is lower than outdoor unit *2	0	0	1.000	1.000	0.992	0.972	0.945	0.919
		-5	-16	0.995	0.995	0.987	0.967	0.940	0.914
		-7.5	-25	—	0.993	0.985	0.965	0.938	0.912
		-10	-33	—	—	0.982	0.962	0.935	0.910
		-15	-49	—	—	—	0.957	0.930	0.905

## ■ Indoor unit: 18,000 Btu

COOLING		Pipe length							
			m	5	7.5	10	15	20	25
		m	ft	16	25	33	49	66	82
Height difference H (m)	Indoor unit is higher than outdoor unit *1	15	49	—	—	—	0.968	0.961	0.954
		10	33	—	—	0.982	0.976	0.969	0.962
		7.5	25	—	0.988	0.986	0.980	0.973	0.966
		5	16	0.994	0.992	0.990	0.984	0.977	0.970
Height difference H (m)	Indoor unit is lower than outdoor unit *2	0	0	1.002	1.000	0.998	0.992	0.985	0.978
		-5	-16	1.002	1.000	0.998	0.992	0.985	0.978
		-7.5	-25	—	1.000	0.998	0.992	0.985	0.978
		-10	-33	—	—	0.998	0.992	0.985	0.978
		-15	-49	—	—	—	0.992	0.985	0.978

HEATING		Pipe length							
			m	5	7.5	10	15	20	25
		m	ft	16	25	33	49	66	82
Height difference H (m)	Indoor unit is higher than outdoor unit *1	15	49	—	—	—	0.967	0.943	0.917
		10	33	—	—	0.990	0.967	0.943	0.917
		7.5	25	—	1.000	0.990	0.967	0.943	0.917
		5	16	1.010	1.000	0.990	0.967	0.943	0.917
Height difference H (m)	Indoor unit is lower than outdoor unit *2	0	0	1.010	1.000	0.990	0.967	0.943	0.917
		-5	-16	1.005	0.995	0.985	0.962	0.938	0.912
		-7.5	-25	—	0.993	0.983	0.960	0.936	0.910
		-10	-33	—	—	0.980	0.958	0.933	0.908
		-15	-49	—	—	—	0.953	0.929	0.903

## ■ Indoor unit: 24,000 Btu

OUTDOOR UNIT  
AOU45RLXFZOUTDOOR UNIT  
AOU45RLXFZ

COOLING		Pipe length							
			m	5	7.5	10	15	20	25
		m	ft	16	25	33	49	66	82
Height difference H (m)	Indoor unit is higher than outdoor unit *1	15	49	—	—	—	0.978	0.969	0.953
		10	33	—	—	0.986	0.986	0.977	0.961
		7.5	25	—	0.988	0.990	0.990	0.981	0.965
		5	16	0.989	0.992	0.994	0.994	0.984	0.968
Height difference H (m)	Indoor unit is lower than outdoor unit *2	0	0	0.997	1.000	1.002	1.002	0.992	0.976
		-5	-16	0.997	1.000	1.002	1.002	0.992	0.976
		-7.5	-25	—	1.000	1.002	1.002	0.992	0.976
		-10	-33	—	—	1.002	1.002	0.992	0.976
		-15	-49	—	—	—	1.002	0.992	0.976

HEATING		Pipe length							
			m	5	7.5	10	15	20	25
		m	ft	16	25	33	49	66	82
Height difference H (m)	Indoor unit is higher than outdoor unit *1	15	49	—	—	—	0.964	0.939	0.913
		10	33	—	—	0.988	0.964	0.939	0.913
		7.5	25	—	1.000	0.988	0.964	0.939	0.913
		5	16	1.008	1.000	0.988	0.964	0.939	0.913
Height difference H (m)	Indoor unit is lower than outdoor unit *2	0	0	1.008	1.000	0.988	0.964	0.939	0.913
		-5	-16	1.003	0.995	0.983	0.959	0.934	0.909
		-7.5	-25	—	0.993	0.981	0.957	0.932	0.907
		-10	-33	—	—	0.978	0.954	0.929	0.904
		-15	-49	—	—	—	0.949	0.925	0.899

## 8. Additional charge calculation

### 8-1. Model: AOU45RLXFZ

Refrigerant type	R410A		
Refrigerant amount	lb oz	8 lb 13 oz	
	g	4,000	

#### ■ Refrigerant charge

Total pipe length	ft (m)	164 (50) or less	197 (60)	230 (70)	262 (80) (Max.)	0.22 oz/ft (20 g/m)
Additional charge	lb oz (g)	0	7.1 oz (200)	14.1 oz (400)	21.2 oz (600)	

## 9. Airflow

### 9-1. Model: AOU45RLXFZ

#### ● Cooling

m <sup>3</sup> /h	4,200
l/s	1,167
CFM	2,472

#### ● Heating


m <sup>3</sup> /h	4,200
l/s	1,167
CFM	2,472

## 10. Operation noise (sound pressure)


### 10-1. Noise level curve

#### ■ Model: AOU45RLXFZ


##### ● Cooling



##### ● Heating



### 10-2. Sound level check point



**NOTE:** Detailed shape of the actual outdoor unit might be slightly different from the one illustrated above.

## 11. Electrical characteristics

Model name			AOU45RLXFZ
Power supply	Voltage	V	208/230 ~
	Frequency	Hz	60
MCA		A	28.9
Starting current		A	20.1
Wiring spec. *	CKT. BKR	A	30
	Power cable	AWG	10

\*: Selected sample based on Japan Electrotechnical Standards and Codes Committee E0005. As the regulations of wire size and circuit breaker differ in each country or region, select appropriate devices complied to the regional standard.

MCA: Minimum Circuit Ampacity (Calculation based on UL1995)

CKT. BKR: Circuit Breaker

## 12. Safety devices

Type of protection	Protection form	Model	
		AOU45RLXFZ	
Circuit protection	Current fuse (PCB)	250 V, 10 A 250 V, 5 A 400 V, 5 A 250 V, 3.15 A	
	Protector (PCB)	500 V, 45 A	
Fan motor protection	Thermal protection program	Activate	239±27 °F (115±15 °C) Fan motor stop
		Reset	158 °F (70 °C) Fan motor restart
Compressor protection	Thermal protection program (Compressor temp.)	Activate	226 °F (108 °C) Compressor stop
		Reset	176 °F (80 °C) Compressor restart
	Thermal protection program (Discharge temp.)	Activate	230 °F (110 °C) Compressor stop
		Reset	After 3 minutes and 230 °F (110 °C) less than Compressor restart

## 13. Function settings

### 13-1. Setting methods


#### **⚠ WARNING**

Never touch electrical components such as the terminal blocks or reactor except the switch on the display board. It may cause a serious accident such as electric shock.

#### **⚠ CAUTION**


- Once refrigerant charging is completed, be sure to open the valve prior to performing the local settings. Otherwise, the compressor may fail.
- Discharge any static electricity from your body before touching the push switches. Never touch any terminal or pattern of any parts on the control board.

The positions of the switches on the outdoor unit control board are shown in the figure below.



## ■ Setting method

1. Be sure to disconnect the power supply or turn off the breaker.
2. Change the DIP switch setting according to the required setting.
  - Various settings can be adjusted by changing DIP switches and push switches on the board of the outdoor unit.
  - The printed characters for the LED display are shown below.



## ■ Description of display

LED display lamp			Function or operation method
(1) POWER/MODE		Green	<ul style="list-style-type: none"> <li>Turns on when the power supply is ON (Including when error occurs).</li> <li>Indicate the MODE by the number of flashes when the installation function is active.</li> </ul>
(2) ERROR		Red	Flashes at high-speed when there is an error.
(3) MONITOR	A	Red	<ul style="list-style-type: none"> <li>Displays the location and contents of errors when there is an error. (Refer to Chapter 14-3. "Error code" on page 232 for details.)</li> <li>Displays when check run is activated. (Refer to Chapter 14-1. "Check run" on page 224 for details.)</li> </ul>
	B	Red	
	C	Red	
	D	Red	
	E	Red	
	F	Red	

Switch		Function or operation method	Factory setting
SW1	Push	<ul style="list-style-type: none"> <li>For the test run start and stop.</li> <li>For the pump down start and stop.</li> </ul>	—
SW2	Push	<ul style="list-style-type: none"> <li>For when check run function is activated.</li> <li>For displaying the check run.</li> <li>For resetting the Automatic wiring correction memory.</li> </ul>	—
SET1-1	DIP	For selecting cooling or heating during test operation.	OFF
SET1-2	DIP	For switching SW1 operation.	OFF
SET1-3	DIP	(Prohibited)	OFF (Do not change)
SET1-4	DIP	(Prohibited)	OFF (Do not change)
SET2-1	DIP	<ul style="list-style-type: none"> <li>For selecting outdoor unit low noise operation function.</li> <li>To use this function, the Central remote controller (option) is necessary.</li> </ul>	OFF
SET2-2	DIP	(Prohibited)	OFF (Do not change)
SET2-3	DIP	(Prohibited)	OFF (Do not change)
SET2-4	DIP	(Prohibited)	OFF (Do not change)
SET3-1	DIP	(Prohibited)	OFF (Do not change)
SET3-2	DIP	(Prohibited)	OFF (Do not change)
SET3-3	DIP	(Prohibited)	OFF (Do not change)
SET3-4	DIP	(Prohibited)	OFF (Do not change)

Be sure to disconnect the power supply or turn off the breaker before changing the DIP switch setting.

## 13-2. Outdoor unit low noise operation function (option)

Change the outdoor unit low noise operation by using this setting. Optional Central remote controller is necessary to use this function.

SET2-1	Setting	Factory setting
ON	Lower	
OFF	Low	◆

### ⚠ CAUTION

- When the low noise operation function is working, cooling and heating capacity will decrease.
- When changing the settings, explain to the customer beforehand that the capacity decreases.

## 14. Check and test

### 14-1. Check run

- The check run is a function to screen and detect any wiring errors.
- After carrying out the check run, you can use the automatic wiring correction function to correct the wiring.
- Normal operation is possible without using the check run. In this case, use the test run or forced cooling function of the indoor unit to confirm any wiring errors.

#### ■ Things to confirm before starting the check run

To ensure safety, check that the following work, inspections and operations have been completed.

Check item		Check column
1	Check that all work on the piping connecting the outdoor unit, indoor units has been completed.	
2	Check that all work on the wiring connecting the outdoor unit, indoor units has been completed.	
3	Is there a gas leakage? (At pipe connections [flange connections and brazed areas])	
4	Is the system charged with the specified volume of refrigerant?	
5	Is a breaker installed at the power supply cable of outdoor unit?	
6	Are the wires connected to the terminals without looseness, and in accordance with the specifications?	
7	Is the 3-way valve of the outdoor unit open? (Gas pipe and liquid pipe)	
8	Is the power supply connected for more than 12 hours?	

#### ■ Restrictions applicable when performing the check run

- When the check run starts, all indoor units connected to the outdoor unit will start to run automatically. During the check run, you cannot check the operation of the indoor units separately. After the check run, check the operation of the indoor units separately in normal operation.
- The check run can be used when the temperature is within the operable temperature of the air conditioner.
- In the check run, the air conditioner will automatically switch between cooling and heating depending on the external temperature and internal temperature.
- The check run can be completed in about 30 minutes (cooling) or about 1 hour (heating), but may take more depending on the external and internal temperature conditions etc.
- Do not conduct the check run with all the windows in the room closed. Otherwise the room temperature could get too low or too high.
- Depending on the difference of the room temperature of each room, a judgment may be impossible.
- Check run is a special operation so there may be a noise louder than the normal refrigerant noise or a creaking noise.


## ■ Operating procedure for check run

### ⚠ CAUTION

Initiate check run after more than 12 hours after the power supply is connected.

**NOTE:** Be sure that the indoor unit and outdoor unit are not operating before starting the check run.

1. Press the "CHECK" switch for 3 seconds or more.




2. The number of indoor units (and the places) connected through the communication lines is displayed.

- If the displayed number of units (places) and the installed number of units (places) is the same, proceed to step 3.
- If the displayed number of units (places) and the installed number of units (places) is not the same, shut off the power and check whether the indoor and outdoor communication lines are properly connected.
- If there is no operation for 1 minute, the LED will return to the original display. (POWER/MODE LED: ON)

**Example: When 4 indoor units (A to D) are connected**

POWER / MODE	ERROR	MONITOR					
		A	B	C	D	E	F



(2-blink)


3. Press the "CHECK" switch for 3 seconds or more again. Check run is initiated.

- When check run is initiated, all LEDs from A to F will flash. (Preliminary operation)
- The LED for each indoor unit will switch off in order as check for each unit is completed.

**NOTE:** To interrupt the check run, press the "CHECK" switch.

**Example: When 4 indoor units (A to D) are connected**

POWER / MODE	ERROR	MONITOR					
		A	B	C	D	E	F




4. After the check run is completed, results will be displayed. Fill the displayed results in the result table accordingly.

- If the connection is correct (Example: When 4 indoor units are connected)**

After the number of connected units are displayed, the LED for each unit will light up in order from A to D.


POWER /MODE	ERROR	MONITOR					
		A	B	C	D	E	F



- If the connection is incorrect (Example: When connection of B and C of the 4 units are reversed)**

After the number of connected units are displayed, B and C will light up in reverse.

POWER /MODE	ERROR	MONITOR					
		A	B	C	D	E	F



#### NOTES:

- Automatic wiring correction will not be completed if the power supply is disconnected while displaying the results. To confirm the automatic wiring correction, be sure to carry out step 5.
- If frost is formed on the outdoor unit while displaying the results, automatic defrost function will be operated. Proceed to step 5 after the defrost function is finished.

**[How to record the contents]**


- Fill the displayed results according to the following example.

Example: When piping A to D is connected but the wires for B and C are connected in reverse.

<Displayed results>

The LEDs will light up in 7 second intervals in the following order.

POWER /MODE	ERROR	MONITOR					
		A	B	C	D	E	F



<Example of result table>

- Please write a ● where the LEDs light up in the order that they light up.

	A	B	C	D	E	F
1	●	●	●	●	○	○
2	●	○	○	○	○	○
3	○	○	●	○	○	○
4	○	●	○	○	○	○
5	○	○	○	●	○	○
6	○	○	○	○	○	○
7	○	○	○	○	○	○

- Based on the results of step (a), please record as follows.

- Trace the dotted circle with a pen if multiple places light up.

A	B	C	D	E	F
○	○	○	○	○	○

- Write the order from A to D in which the LEDs lit up inside the circle.

A	B	C	D	E	F
(A)	(C)	(B)	(D)	(E)	(F)

- Select the correction method.

→ Correct the wiring manually.\*2  
Proceed to step 6.

Use the Automatic wiring correction function.\*1  
Proceed to step 5.

Write down the same results in the label on the reverse side of the service panel.

The results recorded are needed at the time of servicing.

**NOTES:**

- \*1: By using this function, the wiring is automatically corrected according to the piping.
- \*2: When correcting the wiring manually, please disconnect the power supply or turn off the breaker during results display, and then change the wiring manually according to the obtained test results.

For example, in Example 1, the wirings connected to the terminals B and C is to be exchanged manually.

**<Result Table>**


	A	B	C	D	E	F
1	○	○	○	○	○	○
2	○	○	○	○	○	○
3	○	○	○	○	○	○
4	○	○	○	○	○	○
5	○	○	○	○	○	○
6	○	○	○	○	○	○
7	○	○	○	○	○	○

A	B	C	D	E	F
○	○	○	○	○	○

5. During results display, press the "CHECK" switch for 3 seconds or more.

After LEDs A to F have lit in turn, all LEDs will light up indicating that the automatic wiring correction is completed.



6. Disconnect the power supply or turn off the breaker and wait 10 minutes then turn the power back on and perform test run.

**NOTE:** If you do not disconnect the power supply or turn off the breaker, normal operation is not possible.


**Notices:**

- If an error occurs during check run it will be suspended. Correct the error and start check run again.
- After the check run, if automatic wiring correction is carried out, the indoor unit's position will be modified to match the piping. (Note that the display of the optional remote controller changes.)
- If you start check run again after the automatic wiring correction is finished, the modification will be reset.


## ■ Check run judgment failure display

If check run cannot be performed, the following is displayed. In this case, the check run will stop. Please check by using the cooling test run of the indoor unit.

### ● Temperature out of range judgment



### ● Wiring/piping number difference



## ■ Re-display check run results

- If you wish to check the automatic wiring correction contents, by briefly pressing the "CHECK" switch, the check run results is displayed. Check the check run results by referring to the result table in step (4) of "Chapter 14-1-3. [Operating procedure for check run](#)" on page 225".
- If the automatic wiring correction contents has not been done, the POWER/MODE LED will blink twice and the MONITOR LED will turn off.

## ■ Automatic wiring correction memory reset

### ⚠ CAUTION

When relocating the unit, reset the memory beforehand, or the unit may not function normally.

1. Press the "CHECK" switch.  
The LED will light as shown in "[Re-display check run results](#)" on page 229".
2. Press the "CHECK" switch for more than 3 seconds when the LED is on.
3. The LEDs from A to F will light in sequence, and then all LEDs will light to indicate the completion of the Automatic wiring correction memory reset.
4. Disconnect the power supply or turn off the breaker.

## 14-2. Test run

### ⚠ CAUTION


Always connect the power supply 12 hours prior to the start of the operation in order to protect the compressor.

1. Indoor unit
  - a. Is the drain normal?
  - b. Is there any abnormal noise and vibration during operation?
2. Outdoor unit
  - a. Is there any abnormal noise and vibration during operation?
  - b. Will noise, wind, or drain water from the unit disturb the neighbors?
  - c. Is there any gas leakage?
  - Do not operate the air conditioner in the test running state for a long time.
  - For the operation method of the test run for indoor unit and central remote controller, refer to the operating manual and perform operation check.


### ■ Test run method

Be sure to temporarily disconnect the power supply or turn off the breaker before changing the DIP switch settings.

1. Check the 3-way valves (both at the liquid side and gas side) are opened. Confirm that the DIP switch SET1-2 is switched off.
2. Set the operation mode to "COOL" or "HEAT". When switching the DIP switch SET1-1 between HEAT and COOL, disconnect the power supply or turn off the circuit breaker beforehand.



- In the first test run, be sure to set the operation mode to "COOL".
  - The operation mode cannot be switched between "COOL" and "HEAT" during the test run. To switch the operation mode between "COOL" and "HEAT", stop the test run, switch the operation mode, and then start the test run again.
3. Press "TEST RUN" switch for more than 3 seconds.  
The POWER / MODE LED flashes once.



4. Confirm operating status.

5. Press "TEST RUN" switch for more than 3 seconds.

POWER /MODE	ERROR	MONITOR					
		A	B	C	D	E	F
		●	○	○	○	○	○


POWER/MODE LED will turn on, and test run stops.

## 14-3. Error code

If an error occurs, the LED will light up to display the error location and the error code.

### ■ In the event of an error


The error LED blink quickly.



### ■ Error location display

LEDs A to F of MONITOR light up and display the error location. In the case of an overall error, LEDs A to F of MONITOR do not light up.


**Example:** Coil error in indoor unit B



## ■ Error code display

While the error is occurring, briefly press SW1. The error code is displayed.

**Example: Coil error (Error cord = 9A.1)**



Display mode

LED on: ●

LED off: ○

Blink: (0.5s Light on / 0.5s Light off)

Number of blinking: ( )

For MONITOR (A and B)

A: 10-Blink

C: 11-Blink

F: 12-Blink

J: 13-Blink

P: 14-Blink

U: 15-Blink

C	D	E	F	→ 1
○	○	○	●	→ 1
○	○	●	○	→ 2
○	○	●	●	→ 3
○	●	○	○	→ 4
○	●	●	●	→ 5
○	●	●	○	→ 6
●	○	○	●	→ 7
●	○	○	●	→ 8
●	○	○	●	→ 9
●	○	●	●	→ A
●	○	●	●	→ C
●	●	○	●	→ F
●	●	○	●	→ J
●	●	●	○	→ P
●	●	●	●	→ U

Error code	Error type
11.3	Serial communication error
11.4	Serial communication error during operation
16.5	Communication error between controller and outdoor unit
22.1	Indoor unit capacity error
5U.1	Indoor unit error
62.1	PCB model information error
62.3	EEPROM access error
62.8	EEPROM data corruption error
63.1	Inverter error
65.3	IPM error (Trip terminal L error)
71.1	Discharge temp. sensor error
72.1	Compressor temp. sensor error
73.2	Heat exchanger middle temp. sensor error
73.3	Heat exchanger liquid temp. sensor error
74.1	Outdoor temp. sensor error
75.1	Suction gas temp. sensor error
76.1	Valve sensor error
76.2	
77.1	Heat sink temp. sensor error
84.1	Current sensor 1 error (stoppage permanently)
86.1	Discharge pressure sensor error
94.1	Trip detection
95.1	Compressor motor control error (stoppage permanently)
97.3	Fan motor 1 error (Duty error)
98.3	Fan motor 2 error (Duty error)
99.1	4-way valve error
9A.1	Coil 1 (expansion valve 1) error
A1.1	Discharge temperature 1 error (stoppage permanently)
A3.1	Compressor 1 temperature error

## 14-4. Pump down


### **⚠ WARNING**

During the pump down operation, make sure that compressor is off before you remove the refrigerant piping. Do not remove the connection pipe while the compressor is in operation with valve open. This may cause abnormal pressure in the refrigeration cycle that leads to breakage and even injury.

### ■ Pump down operation


When moving or discarding the air conditioner, in order to consider the environment and avoid the discharge of refrigerant to the atmosphere, pump down according to the following procedure.

1. Connect the pressure gauge to the charging port.
2. Change the DIP switch on the board (SET1-2) to On\*1  
\*Be sure the power supply is disconnected on the breaker is turned off when changing the DIP switch.




\*1: DIP switch  
(SET1-2)

3. To start operation, press the [PUMP DOWN] switch\*2 for 3 seconds or press after the power has been on for 3 min.




During pump down, the LED (POWER/MODE) will flash 3 times consecutively.




**NOTE:** If the [PUMP DOWN] switch is pressed during compressor operation, the compressor will stop, and the operation will start after about 3 min.

4. Close the liquid pipe valve.
5. When the value between 7.3 psi and 0 psi (0.05 Mpa to 0 Mpa) is shown, close the gas pipe valve.
6. Stop pump down by pressing the [PUMP DOWN] switch for 3 seconds.  
The LED will light as follows.



## 7. Disconnect the power supply or turn off the breaker.

**NOTE:** If the pump down is not stopped by pressing the switch as in step 6, it will stop automatically after 15 minutes and the LED will light as follows. If the pump down is complete, disconnect the power supply or turn off the breaker. If not completed open the liquid pipe valve, and then start again from step 3.



- In order to interrupt the pump down operation, press the [PUMP DOWN] switch again. The LED will return to the original display before starting pump down.  
(POWER/MODE LED: On)
- The pump down may stop before completion due to error. To complete the pump down, correct the error, open the liquid pipe valve and then start from step 1 again.  
Otherwise, the refrigerant can be recovered from the service port.

## 15. Accessories

OUTDOOR UNIT  
AOU45RLXFZOUTDOOR UNIT  
AOU45RLXFZ

Part name	Exterior	Q'ty	Part name	Exterior	Q'ty
Installation manual		1	Drain cap		7
Drain pipe		1	Adapter K 1/2 in (12.70 mm) 3/8 in (9.52 mm)		2 set
Cable tie with clip (Large)		2	Adapter L 1/2 in (12.70 mm) 5/8 in (15.88 mm)		2 set
Cable tie with clip (Small)		2	Adapter H 3/8 in (9.52 mm) 1/2 in (12.70 mm)		1 set
Cable tie		1			

## 16. Optional parts

Exterior	Part name	Model name	Summary
	Central remote controller	UTY-DMMUM	<p>Set temperatures on timers to best meet individuals' needs. Includes a large backlit LCD and 4-way navigation pad.</p> <p>Remote controller cable: 22AWG (0.33 mm<sup>2</sup>)</p> <p><b>NOTE:</b> The remote controller cable supplied with this controller is for indoor use. If you require cables for outdoor use, purchase locally. Material is not specified. However, it should be selected considering the installing environment (temperature, humidity), and regional regulations (RoHS Directive, etc.).</p>

## 17. Outdoor unit installation precautions

**NOTE:** The information listed below are general precautions.

Some models also include items that do not apply.

### 17-1. Places where prohibited for use

- Places where there is a danger of combustible gas leakage.
- Places where sulfur gas, chlorine gas, acid, alkali, or other matter which effects equipment is generated.
- Places not affected by heat radiation from other heat sources.
- Places where the air is not stagnant.
- Places where machinery which generates high frequencies is used.
- Ocean beaches and other areas where there is a lot of salt.
- Inside of vehicles, ships, and other conveyances.
- Places where voltage fluctuations are product.

### 17-2. Points to remember when installing

- The product shall be installed at a place which can withstand the weight and vibration of the outdoor unit.
- To allow maintenance after refrigerant piping, drain piping, and electric wiring connection and installation, provide an installation service space.  
\*Installation service space is shown in "[Installation space](#)" on page 160.
- Be careful when installing the set at the following places.

Condition	Contents	Countermeasures (Reference)
When installed near adjacent houses.	Perform installation work so that operating sound does not disturb the neighbors.	<ol style="list-style-type: none"> <li>Install a soundproof barrier.</li> <li>Change the installation site.</li> </ol>
When there is the possibility of strong wind.	<ul style="list-style-type: none"> <li>If the outdoor unit is exposed to strong wind, capacity may drop, frost may form during heating, and operation may be stopped by high pressure rise. In addition, when a very strong wind blows, the fan may be damaged.</li> <li>When a very strong wind blows, there is the possibility of the outdoor unit being toppled over if held only by foundation bolts.</li> </ul>	<ol style="list-style-type: none"> <li>Install the outdoor unit with keeping a sufficient distance between the outlet side of the unit and a facing wall or fence.</li> <li>Make the outlet direction and wind direction perpendicular.</li> <li>Fasten the outdoor unit using toppling prevention hardware (purchased locally).</li> </ol>
When snow accumulates.	If the outdoor unit is covered by accumulated snow, it may not be able to operate.	<ol style="list-style-type: none"> <li>Make the foundation as high as possible.</li> <li>Perform snow prevention work.</li> </ol>
When installing the inverter type.	It may generate noise in TV sets, stereos and PCs.	The inverter type should be installed at a sufficient distance from these equipments.