

Job Name:	
Tag#	



Submittal Data Sheet	FTXR09TVJUW(S)
.75-Ton Wall Mounted Indoor Unit	



Indoor Specifications				
	Cooling		Heating	
	H	M	H	M
Airflow Rate (cfm)	272	208	346	258
	L	SL	L	SL
	162	134	201	117
Sound (dBA) H / M / L / SL	38 / 32 / 25 / 19		41 / 34 / 28 / 19	
Dimensions (H x W x D) (in)	11-15/16 x 39-5/16 x 8-3/8			
Weight (Lbs)	27			
Nominal Capacity (Btu/hr)	9,000			

*See Outdoor Unit for Rated Capacities

Complete warranty details available from your local dealer or at www.daikincomfort.com. To receive the 12-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec. *If product is installed in a commercial application, limited warranty period is 5 years.*

Electrical	*208/230V	
	Cooling	Heating
Running Current (Rated) (A)	.07/.07*	.13/.12*
Power Consumption (Rated) (W)	13/13*	26/26*

Piping	
Liquid (in)	1/4
Gas (in)	3/8
Drain (in)	11/16


Color Selection

White _____ Silver _____

Optional Accessories	
-----------------------------	--

Included	Part Number	Description
	BRP072A43	Wireless Interface Adapter (S21 Adapter Included)
	BRC944B2-A08	Wired Remote Controller Kit (Includes BRC944B2 & BRCW901A08)
	BRCW901A03	Wired Remote Controller Cable - 10 ft (For BRC944B2)
	BRCW901A08	Wired Remote Controller Cable - 25 ft (For BRC944B2)
	KRP928BB2S	Interface adaptor for DIII-NET
	DACA-CP1-1	Inline Condensate Pump (Fits inside all Daikin wall & floor mount units)
	DACA-CP4-1	External Condensate Pump
	KAF970A46	Air-purifying filter with photocatalytic deodorizing function (without frame)

FTXR09TVJUW(S) Dimensional Data



Daikin North America LLC 5151 San Felipe, Suite 500 Houston, TX 77056

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications and information in this data sheet without notice and without incurring any obligations)