

SUBMITTAL DATA: UTY-TTRX

Third Party Thermostat Convertor

Job Name: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Engineer: \_\_\_\_\_  
 Submitted to: \_\_\_\_\_  
 Submitted by: \_\_\_\_\_  
 Reference: \_\_\_\_\_

Date: \_\_\_\_\_  
 Approval: \_\_\_\_\_  
 Construction: \_\_\_\_\_  
 Unit #: \_\_\_\_\_  
 Drawing #: \_\_\_\_\_



**GENERAL FEATURES**

The UTY-TTRX Thermostat Adapter allows a Fujitsu ductless system to be connected to a third-party thermostat such as Honeywell, Nest, etc.

**FEATURES**

- UP to 16 indoor units may be controlled with a single thermostat controller.
- Multiple indoor units connected to convertor operate by the same operating setting.

**COMPATIBLE INDOOR UNITS**

ASU7RLF	ARU7RLF	ASU9RLS3
ASU9RLF	ARU9RLF	ASU12RLS3
ASU12RLF	ARU12RLF	ASU15RLS3
ASU7RLF1	ARU18RLF	ASU9RLS2
ASU9RLF1	ARU24RLF	ASU12RLS2
ASU12RLF1	AGU9RLF	ASU15RLS2
ASU15RLF1	AGU12RLF	AUU7RLF
ASU18RLF	AGU15RLF	AUU9RLF
ASU24RLF	ASU9RLS3Y*	AUU12RLF
ASU30RLE	ASU12RLS3Y*	AUU18RLF
	ASU15RLS3Y*	

\* Before using UTY-TTRX with RLS3Y Series, please unplug the built-in WIFI adapter (CN12)

Please note field supplied 24V transformer required

**ELECTRICAL**

Power Supply DC (V) ..... 12  
 Max Power Consumption (W)..... 0.6  
 Wire Type ..... Polar 2 core sheathed PVC cable

**TEMPERATURE**

Operating Temperature Range °F (°C) .....32-114 (0~46)  
 Storage Temperature Range °F (°C) ..... 14-140 (-10~60)  
 Humidity Range (%) .....0-95 (no condensation)

**WEIGHT AND DIMENSIONS**


Weight oz. (g).....4 (100)  
 Dim.Net (HxWxD) in (mm).....1-1/16 x 3-7/16 x 3-7/16  
 (27 x 86.7 x 86.7)

# SUBMITTAL

## DIMENSIONS


This product is comprised of a body and cover.

Unit : in (mm)



Set the bottom side to a flat place.

### Maximum Wire Lengths for 2-Wire Controls



### Maximum Wire Lengths for 3-Wire Controls

