

New Product Release

New Product Release

-	0
I	
l	
l	
l	
I	
l	
	IIIIII IIIIIII IIIIIII
	EC02S Temperature Sensor EC02S Remot



LPW ECO2S 2-Stage Electronic Heater w/ Remote Temperature Sensing

Selectable Wattages Up To 4500W For Large Spaces

Meet the ECO2S Temperature Sensor.

With the ECO2S Temperature Sensor, your heater knows exactly where the room's cold spot is and works smarter to keep the entire room comfortable. Just place it on a wall or shelf and get the right temperature, right where you want it.





EC02S Temperature Sensor

EC02S Remote

LPW ECO2S 2-Stage Electronic Smart Heater w/ Remote

Smart Energy-Saving Design ECO2S Electronic Controller For Temperature Accuracy

2-Stage Heating: Automatically Uses Lowest Wattage Needed

Infrared Remote Control Included

Dual Pic-A-Watt® Elements: Multiple Wattage Options, Tailors Heater To Specific Heating Requirements

Patented Smart Limit Protection®

Built-In Fan Delay To Dissipate Heat

Long Life Unit Bearing Motor

5-Blade Aluminum Fan

Timer and Summer Fan Only Modes

Available in New Designer Finishes White Dove, Almondine, Satin Nickel or Oiled Bronze

WARRANTY 5-Year Limited Warranty

Almondine

Satin Nickel

Oiled Bronze





Meet the ECO2S Temperature Sensor.

With the ECO2S your heater knows exactly where the room's cold spot is and works smarter to keep the entire room comfortable. Just place it on a wall or shelf. Get the right temperature, right where you want it.



 $\label{eq:modern} \begin{array}{l} \textbf{Modern} \ \textbf{Curved} \ \textbf{Grill} - \textbf{Simultaneously} \ \textbf{makes} \ \textbf{a} \ \textbf{bold} \ \textbf{statement} \ \textbf{and} \ \textbf{blends} \ \textbf{in} \ \textbf{with} \ \textbf{any} \ \textbf{decor} \end{array}$

Built-In Fan Delay – Dissipates heat from the high-mass steel fin elements increasing energy efficiency

Selectable Wattage – Tailor the heater to an area's specific heating requirements.

ECO2S Electronic Control – Automatically Uses Lowest Wattage Needed – To Heat The Room

Infrared Remote Control Included

Timer and Summer Fan Only Modes

ECO2S Remote Temperature Sensor – Temperature Sensing At The Coldest Spot In The Room For Balanced Heating



With U.S. & Global Materials

(Shown in White Dove)

Ordering Information *Add suffix -AD-R for optional Almondine color -SN-R for optional Satin Nickel color -OB-R for optional Oiled Bronze color

0

MODEL	VOLTS	WATTS	AMPS	WT. (lbs.)	
LPW1227-ECO-WD-R	120	1500•1750•2000•2250•2500•2750	10.4-22.9	19	<u> </u>
LPW2045-ECO-WD-R	208	2500•3000•3500•4000•4500	10.8-21.6	19	
LPW2445-ECO-WD-R	240/208*	2500•3000•3500•4000•4500	9.4-18.8	19	

*Dual rated heaters will draw 13% less amps and 25% less wattage when operated at 208V.

For Distributors: Products can be sold with custom color grills separately. Contact sales managers for details.